DIMETHOXYMETHANE IN DIESEL FUEL:

Chemical Characterization of Toxicologically Relevant Compounds from Diesel Emissions

INTERIM REPORT
TFLRF No. 358

by
Douglas M. Yost
Janet Buckingham
Edwin A. Frame
U.S. Army TARDEC Fuels and Lubricants Research Facility (SwRI)
Southwest Research Institute
San Antonio, TX 78238

Under Contract to

U.S. Army TARDEC
Petroleum and Water Business Area
Warren, MI 48397-5000

for
U. S. Department of Energy
Office of Transportation Technologies
1000 Independence Avenue, SW
Washington, D. C. 20585

and
Coordinating Research Council, Inc.
3650 Mansell Road, Ste. 140
Alpharetta, GA 30022-3068

April 2001

Disclaimers

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

Trade names cited in this report do not constitute an official endorsement or approval of the use of such commercial hardware or software.

DTIC Availability Notice

Qualified requestors may obtain copies of this report from the Defense Technical Information Center, Attn: DTIC-OCC, 8725 John J. Kingman Road, Suite 0944, Fort Belvoir, Virginia 22060-6218.

Disposition Instructions

Destroy this report when no longer needed. Do not return it to the originator.

DIMETHOXYMETHANE IN DIESEL FUEL:
Chemical Characterization of Toxicologically Relevant Compounds from Diesel Emissions

INTERIM REPORT
TFLRF No. 358

by
Douglas M. Yost
Janet Buckingham
Edwin A. Frame
U.S. Army TARDEC Fuels and Lubricants Research Facility (SwRI)
Southwest Research Institute
San Antonio, TX 78228

Under Contract to
U.S. Army TARDEC
Petroleum and Water Business Area
Warren, MI 48397-5000

for
U. S. Department of Energy
Office of Transportation Technologies
1000 Independence Avenue, SW
Washington, D. C. 20585

and
Coordinating Research Council, Inc.
3650 Mansell Road, Ste. 140
Alpharetta, Ga. 30022-3068

TARDEC Contract Nos. DAAE-07-99-C-L053 (WD03 of SwRI Project No. 03-3227)
DAAK-70-92-C-0059 (WD69 of SwRI Project No. 03-5137)
CRC No. CIDI-1 (SwRI Project No. 03-03143)

Approved by: **April 2001**

Edwin C. Owens, Director
U.S. Army TARDEC Fuels and Lubricants
      Research Facility (SwRI)

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

1. AGENCY USE	2. REPORT DATE April 2001	3. REPORT TYPE AND DATES COVERED Interim, October 1999 - August 2000

4. TITLE AND SUBTITLE DIMETHOXYMETHANE IN DIESEL FUEL: Chemical Characterization of Toxicologically Relevant Compounds from Diesel Emissions	5. FUNDING NUMBERS WD69 DAAK-70-92-C-0059
6. AUTHOR(S) Yost, D. M. , Buckingham, J., and Frame, Edwin A.	WD03 DAAE07-99-C-L053

7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army TARDEC Fuels and Lubricants Research Facility (SwRI) Southwest Research Institute P.O. Drawer 28510 San Antonio, Texas 78228-0510	8. PERFORMING ORGANIZATION REPORT NUMBER IR TFLRF No. 358

9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army TACOM U.S. Army TARDEC Petroleum and Water Business Area Warren, MI 48397-5000	10. SPONSORING/ MONITORING AGENCY REPORT NUMBER

11. SUPPLEMENTARY NOTES

12a. DISTRIBUTION/AVAILABILITY approved for public release; distribution unlimited	12b. DISTRIBUTION CODE

13. ABSTRACT (Maximum 200 words)

The objective of this study was to quantify engine-out emissions of potentially toxic compounds from a modern diesel engine operated with different fuels. Five diesel fuels were examined: a low-sulfur, low-aromatic hydrocracked fuel, the same low sulfur fuel containing 15% v/v dimethoxy methane, a Fischer-Tropsch fuel, a California reformulated fuel, and a EPA number 2 certification fuel. A DaimlerChrysler OM611 CIDI engine was controlled with a SwRI Rapid Prototyping Electronic Control system. The engine was operated over 5 speed-load modes. Each operating mode and fuel combination was run in triplicate. Thirty-three potentially toxic compounds were measured for each fuel and mode. An analysis of variance of the fuels showed that, in general, the 15% v/v dimethoxy methane fuel and the Fisher-Tropsch fuels had significantly lower emissions of measured compounds compared to the remaining fuels and were statistically indistinguishable from each other. The effect of pilot fuel injection on engine-out emissions was also determined. The pilot fuel injection was either turned off or turned on with engine control by either Location of Peak Pressure (LPP) of combustion or the original equipment manufacturer (OEM) calibration strategy. These three control strategies were compared over 2 speed-load modes run in triplicate. Thirty-three potentially toxic compounds were measured. In general, either pilot fuel injection strategy (LPP or OEM) produced higher emissions than with pilot injection turned off.

14. SUBJECT TERMS PAH Diesel Emissions CIDI engine Pilot Injection Toxic Compounds Clean Air Act	15. NUMBER OF PAGES 176
	16. PRICE CODE

17. SECURITY CLASSIFICATION OF REPORT	18. SECURITY CLASSIFICATION OF THIS PAGE	19. SECURITY CLASSIFICATION OF ABSTRACT	20. LIMITATION OF ABSTRACT

EXECUTIVE SUMMARY

Objectives:
- Investigate the role of dimethoxy methane as an oxygenated diesel fuel additive on the engine-out exhaust emissions of potentially toxicologically relevant compounds.
- Determine the polycyclic aromatic hydrocarbon (PAH) content of organic solvent extracts of exhaust particulate matter; gaseous exhaust PAH; other toxic air pollutants collected from a diesel engine using various fuel compositions and engine operating conditions.

Approach:
- A DaimlerChrysler OM611 CIDI engine was used to determine the effect of diesel fuel type on toxicologically relevant compounds from engine-out exhaust emissions.
- The engine was controlled by a SwRI Rapid Prototyping Electronic Control System (RPECS).
- The test matrix included 5 fuels (including one oxygenate blend) operated over 5 speed/load points.
- Each speed/load point was devised to hold Location of Peak Pressure (LPP) at 7°ATDC, while maintaining cylinder balance within 5 % of the Indicated Mean Effective Pressure (IMEP), with pilot fuel injection disabled.
- Two of the speed/load points were operated at two different pilot fuel injection strategies. One pilot strategy used the stock controller, while the other was to include pilot fuel injection while maintaining the Location of Peak Pressure at a constant.
- Four toxic air pollutant exhaust emissions were measured.
- Eleven gaseous PAH compounds were measured.
- Seventeen PAH compounds were determined from the soluble organic fraction of the exhaust particulate matter.

Accomplishments:
- All fuel tests were completed in triplicate for five modes, pilot injections off, LPP operation. Evaluation of pilot fuel injection effects for all fuels were completed in triplicate for two modes and two pilot fuel injection strategies.
- Statistically significant fuel effects on exhaust emissions were identified.
- Oxygenate-containing fuel and Fischer-Tropsch fuel produced the lowest overall toxic air pollutant and PAH exhaust emissions.

Future Directions:
In a follow-on phase, similar investigations will be conducted using an engine with exhaust emission control devices.

FOREWORD/ACKNOWLEDGMENTS

TABLE OF CONTENTS

TABLE OF CONTENTS (contd)

APPENDICES

LIST OF TABLES

LIST OF ILLUSTRATIONS

LIST OF ILLUSTRATIONS (contd)

LIST OF ILLUSTRATIONS (contd)

xiv

SYMBOLS AND ABBREVIATIONS

ADMM15	Blend of 15%v DMM in ALS fuel
ALS	Alternative Low Sulfur
ANOVA	Analysis of Variance
ASTM	American Society for Testing and Materials
ATDC	After Top Dead Center
bhp	Brake Horse Power
BMEP	Brake Mean Effective Pressure
BSFC	Brake Specific Fuel Consumption
CARB	California Reference Fuel
CIDI	Compression Ignition, Direct Injection
CO	Carbon Monoxide
CO_2	Carbon Dioxide
COTR	Contracting Officer's Technical Representative
DF-2	EPA Certification Grade Diesel Fuel
DMM	Dimethoxymethane
DNPH	Dinitrophenylhydrazine
DOE	Department of Energy
DPF	Diesel Particulate Filter
EGR	Exhaust Gas Recirculation
FT-100	Neat Fischer-Tropsch Fuel
HC	Hydrocarbon
IMEP	Indicated Mean Effective Pressure
LPP	Location of Peak Pressure
NOx	Nitrogen Oxides
PAH	Polycyclic aromatic hydrocarbon
PM	Particulate Matter
PNGV	Partnership for a New Generation of Vehicles
RPECS	SwRI Rapid Prototyping Electronic Control System
RPM	Revolutions per Minute
SOF	Soluble Organic Fraction
SwRI	Southwest Research Institute
TARDEC	Tank-Automotive Research Development and Engineering Center
TFLRF	U.S. Army TARDEC Fuels and Lubricants Research Facility

1.0   INTRODUCTION

1.1   Background

This project exists as follow-on work to Phase I and Phase II emissions research utilizing a DaimlerChrysler OM611 diesel engine. The Phase I testing was designed to evaluate the potential benefits of several alternative diesel fuels without making any adjustments to the engine control system[1]. The objective of the second phase of work was to optimize the OM611 engine for a subset of the seven fuels that were tested in Phase I, as well as the fuels recommended by the Auto/Energy Ad Hoc Diesel Fuels committee[2].

Optimization was necessary to obtain a detailed comparison of alternative fuels. Because the fuels under consideration have differing physical and chemical properties, a portion of any change in exhaust emissions measured in Phase I may be due to the response of the engine injection system to differences in the fuel physical properties. The optimization phase of this work involved recalibration of the engine operating parameters that influence engine emissions and fuel economy. These operating parameters include boost level, exhaust gas recirculation (EGR), fuel-injection timing, and pressure in the common rail injection system.

This program is part of an overall study that examines the effect of one oxygenated compound (dimethoxymethane) in diesel fuel on the emissions of particulate matter, oxides of nitrogen, and fuel economy. This program will focus on the chemical characterization of emissions of compounds with known or suspected toxicological properties. A body of work exists[3-10] that suggests fuel property variations can influence the emissions of toxic compounds from diesel engine combustion. In a follow-on phase, the emissions of these compounds using an after-treatment device will be compared to the engine-out emissions to better understand the effects of after-treatment devices. Future research will examine other oxygenated compounds as possible alternatives to dimethoxymethane.

2.0   OBJECTIVE

The overall objective of this project is to better understand the role of fuels on the exhaust emissions of a subset of potentially toxicologically relevant compounds. The three objectives of

this program are to measure the following pollutants collected from diesel engines under a matrix of engine and fuel conditions:

1. polycyclic aromatic hydrocarbon (PAH) content of organic solvent extracts of particulate matter
2. gas phase polycyclic aromatic hydrocarbons
3. other gaseous compounds such as formaldehyde, acetaldehyde, benzene and 1,3-butadiene

These measurements were made on engine out emissions. In future tests other potentially hazardous compounds may have to be measured depending on the technology used in after-treatment devices. For example, if urea were used as a reductant to lower NO_x levels, then compounds relevant to the use of this chemical would need to be measured including, but not limited to urea, ammonia, biuret, and cyanic acid.

3.0   TECHNICAL APPROACH

3.1   Test Engine

The engine used in this investigation was a DaimlerChrysler OM611. The OM611 engine is a 2.2L, direct-injection, compression-ignition, with a Bosch, high-pressure, common-rail, fuel-injection system. The OM611 engine is turbocharged with wastegate control and utilizes an intercooler. The engine design closely matches the specifications of the partnership for a new generation vehicle (PNGV) target compression-ignition direct-injection (CIDI) engine. Characteristics of the OM611 engine are presented in Table 1.

Table 1. OM611 Engine Performance Characteristics	
Displacement	2151 cm^3
Maximum Power	92 kW at 4200 RPM
Maximum Torque	300 N-m at 1800 - 2600 RPM
Maximum BMEP	17.5 bar
Compression Ratio	19:1
Minimum Specific Fuel Consumption	203 g/kW-hr

Besides the electronically controlled common rail fuel injection system, the OM611 engine has several other unique features that affect combustion. The engine has two intake ports, one helical for swirl, and one high flow port. The high flow port also contains an Intake Runner Valve (IRV), which is used to shut the port off at low speeds and light loads. This allows for variable swirl in the engine for improving light load exhaust emissions.

The OM611 engine also utilizes variable Exhaust Gas Recirculation (EGR). The EGR is controlled with pulse width modulation of an EGR valve and intake damper, and is referenced to the engine mass air-flow sensor. The high EGR region is from idle to approximately 50% speed and 50 % load. The hot EGR passes through a cooling passage integral with the cylinder head, then on to the intake manifold via he EGR valve.

A feature of the OM611 engine used for controlling both exhaust and noise emissions is the employment of pilot fuel injection. The pilot fuel injection results in a slower start of combustion, which reduces noise levels and may reduce Oxides of Nitrogen emissions. Pilot fuel injection is disabled when the engine is operating above 3000 RPM and 50 % load.

3.2   Engine Setup

3.2.1   Test Cell

The OM611 engine was installed in test cell supplied with conditioned air and attached to an eddy current absorption dynamometer. The engine load was monitored with an electronic load cell. The engine speed was monitored using a 60-tooth gear and a frequency to voltage converter. The fuel system included a constant level day tank, and a Micro-Motion mass flow sensor. Intake air mass flow was measured according to SAE J244 using a Merriam Laminar Flow Element.

The engine was fitted with a gaseous exhaust sample probe and a heated sample line to the emission bench. An exhaust particulate sampling probe was inserted into the exhaust and connected to a 203-mm diameter dilution tunnel. Exhaust dilution ratio was monitored using carbon dioxide tracer. Dilution tunnel sample zone temperature was maintained below 125°F by splitting the engine exhaust.

3.2.2 Electronic Engine Control

The stock engine control unit (ECU) was replaced with the SwRI developed Rapid Prototyping Electronic Control System (RPECS). The RPECS system is a PC-based tool (both hardware and software) that is used for real-time embedded powertrain control system development. The procedure for installing the RPECS hardware involved intercepting and mapping the signals from the stock engine controller. The engine calibration tables and control signals are then duplicated with the RPECS hardware/software in order to control the engine. The operating parameters of interest will be adjusted through changes to the calibration tables in RPECS.

The RPECS has been configured to allow control of the common rail fuel injection system, and intake manifold conditions. The items controllable by RPECS as presently configured are shown in Table 2.

Table 2. RPECS Controlled Engine Parameters				
Common Rail Fuel Injection				
Fuel Injection	**Cylinder 1**	**Cylinder 2**	**Cylinder 3**	**Cylinder 4**
Timing	Individual	Individual	Individual	Individual
Duration	Individual	Individual	Individual	Individual
ON/OFF	Individual	Individual	Individual	Individual
Pilot ON/OFF	Global			
Pilot-to-Main Timing	Global			
Pilot Duration	Individual	Individual	Individual	Individual
Pilot/Main Duration Ratio	Individual	Individual	Individual	Individual
Rail Pressure	Global			
Intake Manifold				
Boost - PWM Variable				
Intake Runner Valve - ON/OFF				
EGR - PWM Variable, Intake Mass Air Flow feedback, measured by intake/exhaust CO_2				

The RPECS uses pulse width modulation (PWM) for closed-loop control of EGR, manifold pressure, and the common rail fuel injection pressure. The feedback for the EGR control loop is the engine mass air flow sensor. The manifold pressure sensor provides feedback for RPECS, with the turbocharger wastegate utilized as the control element. The common rail fuel pressure is controlled with a PWM fuel pressure vent, with feedback from a 1500 bar rail pressure sensor.

The RPECS has an eight-channel timer board that synchronizes with the engine crankshaft and camshaft pulses for activation of the fuel injectors. Each cylinder of the engine utilizes two timer

channels, one for the pilot fuel injection event and one for the main fuel injection event. The fuel injectors are powered by peak-and-hold drivers, which allow variation of timing and duration of both pilot and main fuel injection. Additional fuel injection control features include individual cylinder control of pilot and main fuel injection events and pilot/main fuel injection ratio control.

One-dimensional tables, one for speed and one for load, were programmed into RPECS so engine operating conditions could be consistently repeated. The RPECS has the ability to operate in either closed-loop torque or closed-loop speed control. In closed-loop torque control RPECS adjusts fuel injection quantity to attain the set point torque value from the dynamometer electronic load cell feedback. In closed-loop torque mode the engine speed is controlled by an eddy-current dynamometer controller. Closed-loop torque control was used for four of the five operating conditions in this program.

In closed-loop speed control mode, RPECS calculated fuel quantity to maintain a steady engine speed using the crankshaft signal. In this program closed-loop speed control was used at the idle condition. At idle the torque was maintained by controlling dynamometer windage with the dynamometer cooling water flow.

3.2.3   Cylinder Pressure Transducers

Program modifications were made to the RPECS to allow individual cylinder fuel injection timing and quantity control. Pressure transducer adapters were machined to fit in the cylinder head via the glow-plug passages. Kistler 6052A transducers were mounted in the adapters. All cylinder pressure transducers were calibrated, and connected to a DSP Technologies high-speed data acquisition system for combustion analysis and cylinder balance. The DSP was clocked with a 720-pulse/revolution shaft encoder.

3.3   Exhaust Emissions Measurement

The OM611 engine was instrumented for the exhaust species shown in Table 3 and as diagramed in Figure 1. The gaseous emissions were drawn from the raw exhaust, with a sample probe located approximately three pipe diameters downstream of the turbocharger outlet. The gaseous exhaust sampling probe was located upstream of the back pressure regulating butterfly. The backpressure regulating butterfly was locked in the position that produced 11-in-Hg backpressure at rated speed and load. The gaseous emissions sampling was performed in accordance with the

guidelines outlined in 40 CFR Part 86, Subpart D. The OM611 engine exhaust was coupled to the house exhaust system and a Constant Volume Sampling (CVS) system. The CVS system consists of a 203-mm dilution tunnel, with a Variable speed Roots type blower. In order to attain a 125°F filter face temperature with the CVS system, the engine exhaust was split between the house exhaust and the dilution tunnel. The dilution tunnel sample zone temperatures were verified at each of the test modes. The blower speed setting was adjusted to maintain 120°F in the sample zone at Mode 5, the highest speed and load condition.

Table 3. Analytical Instrumentation	
Constituent	**Analysis Method**
Total Hydrocarbon	Heated Flame Ionization Detector
Carbon Monoxide	Non-Dispersive Infrared Analysis
Carbon Dioxide	Non-Dispersive Infrared Analysis
Oxides of Nitrogen	Chemiluminescent Analysis
Particulate Matter	Gravimetric, CVS, CO_2 tracer
Soluble Organic Fraction of PM	Gravimetric, Soxhlet Extraction Toluene/Ethanol
Benzene	Gas Chromatography
1,3-Butadiene	Gas Chromatography
Formaldehyde	DNPH Adsorbent/High Pressure Liquid Chromatography
Acetaldehyde	DNPH Adsorbent/High Pressure Liquid Chromatography
Polycyclic Aromatic Hydrocarbons	Gas Chromatography/Mass Spectroscopy/Selected Ion Monitoring

Figure 1. Dilution Tunnel for Particulate and Air Toxin Sampling

A carbon dioxide tracer technique was utilized to determine the dilution ratio in the CVS system. The particulate matter sampling procedures were performed in accordance with the guidelines established in 40 CFR Part 86, Subpart N. A polyurethane foam and XAD-2 resin trap were utilized for sampling gas phase PAH compounds. Soluble phase PAH compounds were extracted from 90 mm filters. Benzene and 1,3-butadiene were collected in a sample bag from the dilution tunnel sample zone. Formaldehyde and acetaldehyde were trapped on a DNPH adsorbent cartridge from the dilution tunnel sample zone.

3.3.1 Gaseous Emissions Analyses

The following three groups of gaseous engine out exhaust emissions were determined for each test point, i.e. engine mode and fuel combination.

3.3.1.1 Typical Exhaust Gases

The following species concentrations were measured utilizing the instrumentation shown in Table3:

- hydrocarbons (HC)
- carbon monoxide (CO)
- carbon dioxide (CO_2)
- oxides of nitrogen (NO_x)
- oxygen (O_2)

3.3.1.2 Toxic Air Pollutants Cited in the Clean Air Act

A sample cart, as seen in Figures 2 and 3, was configured and placed in the test cell near the engine and exhaust dilution tunnel. This cart was arranged so that one technician could effectively collect bag samples and cartridge samples simultaneously. The cart was utilized for sampling the following four Clean Air Act toxic air pollutants:

- benzene
- 1,3-butadiene
- formaldehyde
- acetaldehyde

The front of the cart was used to control and monitor the cartridge sampling for formaldehyde and acetaldehyde while the back of the cart supported the pumps and metering valves for collecting the bag samples for benzene and 1,3-butadiene analyses.

Figure 2. Gas Sampling Cart – Front

Figure 3. Gas Sampling Cart Rear

3.3.1.2.1 Benzene and 1,3-Butadiene

Exhaust samples for benzene and 1,3-butadiene determination were taken in Tedlar7 bags via a diaphragm vacuum pump from a dilution tunnel through an unheated 1/4" Teflon tube. A corresponding background air sample was taken from the ambient air. The collected samples were transported to the SwRI Department of Emissions Research (DER) for analysis. These two toxic air pollutant compounds were analyzed using two different gas chromatographs (GC) as described in Table 4. The two GCs were configured and operated according to the CRC Auto-Oil Phase II Air Quality Improvement Research Program guidelines.[1] These instruments were calibrated with CRC/NIST gas mixtures according to DER Standard Operating Procedures. Detection limits for the GCs are on the order of 10 parts per billion.

Table 4. Gas Chromatographic Analysis Parameters		
	1,3-Butadiene	**Benzene**
Gas Chromatograph	Hewlett- Packard 5890-II	Hewlett- Packard 6890
Injector	10 port gas sampling valve w/ 5 mL sample loop	10 port gas sampling valve w/ 5 ml sample loop
Detector	hydrogen flame ionization	hydrogen flame ionization
Column/s	DB-Wax, 15 meter x 0.53mm, 1.0 film, J&W Scientific, Alumina PLOT/KCL, 50meter x 0.53mm, 10 µm film, Chrompack, International	pre-column: 2 meter of 0.25 mm I.D. deactivated fused silica Analytical column:30 m x 0.25 mm DB-5, 0.25　m film thickness

3.3.1.2.2 Formaldehyde and Acetaldehyde

To collect the aldehydes, a metered volume of the dilute exhaust was transferred with a diaphragm vacuum pump from the dilution tunnel through a heated sample transfer line and heated particulate filter, both maintained at 375°F and finally through a cartridge containing silica impregnated with 2,4-dinitrophenylhydrazine (DNPH), Figure 4. A metered volume of the background air was pulled through another cartridge. A Hastings model HFC-202D mass flow meter was used to measure the volume of gases sampled. Air temperature and barometric pressure were recorded by the engine control computer. Any aldehyde or ketone present in the sampled gas reacted quickly with the DNPH to form a stable derivative (R-CHO phenylhydrozone). These derivatives were extracted from the trap with ultra-pure acetonitrile. Analysis of the extracted samples and backgrounds were performed using a high performance liquid chromatograph (HPLC), pumping a ternary solvent gradient of water, methanol, and acetonitrile through an ultra-violet (UV) spectroscopic detector. The instrument was calibrated using purified aldehyde derivatives according to the DER Standard Operating Procedures. The detection limit for this instrument is on the order of 0.005-ppm aldehyde in dilute exhaust.

Figure 4. Sample Cartridges

The collection of optimum sample volumes during the engine test modes required precise timing of starting and stopping pumps and opening and closing valves by the cart operator. Appendix A describes the sequence of these events. Revision to the first sequence was determined necessary when HPLC analyses indicated overloading or breakthrough of the DNPH aldehyde cartridges. Background cartridge samples were a composite of one entire day of sampling.

3.3.1.3 Gaseous PAH compounds

The gaseous phase (PUF/XAD-2 trap) samples are Soxhlet extracted with methylene chloride for 18 hours. At the beginning of the extraction, a PAH surrogate spiking solution containing three deuterated PAH [benzo(b)fluoranthene-d12, benzo(a)anthracene-d12, and dibenz(a,h)anthracene-d14 at 100 nanograms each] is spiked into the sample. Sample extracts are then concentrated and solvent exchanged into hexane. A cleanup procedure that consists of an acid wash and liquid chromatography is then applied. The acid used is a diluted sulfuric acid. The chromatography is performed on a silica gel column that would separate fuel and oil from the PAHs. The sample extracts were in hexane, transferred onto the Si column, the column flushed with hexane (to remove the fuel and oil), and the PAHs were then eluted out of the column by using a DCM/pentane solvent system. The sample extracts, after the cleanup, were blown down to a final volume of 100 microliters (uL). An internal standard mixture containing deuterated PAH is added to these extracts prior to GC/MS/SIM (selected ion monitoring) analysis. Two or three characteristic ions of each PAH are monitored. A PAH calibration curve consisted of at least 5 points is obtained prior to the sample analysis. A solvent or lab blank is analyzed immediately after the last calibration standard analysis to ensure no significant carryover occurs on the instrument. The PAH are analyzed in the positive ion electron impact (PI/EI) mode. Separate GC/MS/SIM analyses are necessary to acquire the PAH data.

The estimated detection limits (DLs) are 1.0 nanogram (total) per PAH per sample. This is based on the lowest calibration standard of 0.01 ng/uL/PAH with a 100 uL final volume. Note, different target compounds behave differently on the instrument and, therefore, exert different final DLs. The DLs given here should be considered as estimated values. There are other factors such as massive interference, and/or split samples for other analyses that will inevitably increase the DLs. A PUF/XAD-2 filter blank was extracted with each set of engine PUF/XAD-2 filters. The PUF/XAD-2 blank was analyzed to determine the PAH background from the media. Additionally three PUF/XAD-2 tunnel blanks were analyzed to determine the PAH background from the test cell, dilution tunnel, and sample system. The tunnel blanks were drawn for one

hour; the background values that are reported in Table 5 have been adjusted to represent the 30-minute sample time that was used during engine testing. Included in Table 5 is the reported detection limits for each gaseous phase PAH compound. The gaseous phase PAH compounds were analyzed using a high-resolution gas chromatograph with a 1.0 atomic mass unit (AMU) low-resolution mass spectrographic detector. There was not any non-detects for gaseous phase PAH compounds during testing.

Table 5. Gaseous Phase PAH Backgrounds and Detection Limits			
COMPOUND	Average PUF/XAD-2 Filter Blank	Average PUF/XAD-2 Tunnel Blank	PUF/XAD-2 Extract HRGC/LRMS(1 AMU) Detection Limit
	ng/sample	ng/sample	ng/sample
naphthalene	369	2227	10
2-methylnaphthalene	181	945	10
1-methylnaphthalene	132	572	10
2,6-dimethylnaphthalene	105	618	10
acenaphthylene	102	113	10
acenaphthene	105	114	10
fluorene	113	192	10
phenanthrene	128	597	10
anthracene	112	22	10
fluoranthene	104	22	10
pyrene	101	22	10

3.3.2   Exhaust Particulate Matter Analyses

The soluble organic fraction of diesel exhaust particulate collected on 90 mm Pallflex filters was removed from the particulate using a Soxhlet extraction system. The extraction solvent was 30 percent toluene/ 70 percent ethanol by volume. One hundred microliters of a PAH surrogate spiking solution, containing three deuterated PAH (benzo(b)fluoranthene-d12, benzo(a)anthracene-d12, and dibenzo(a,h)anthracene-d14, at 100 nanograms each) was syringed onto each filter prior to solvent extraction to determine the PAH extraction efficiency. This Soxhlet extraction method is similar to washing the filter with approximately five gallons of solvent. The percent mass extracted from the diesel particulate on the filter is determined by weight loss, usually in milligram quantities, after solvent extraction and drying.

The exhaust particulate were analyzed for Soluble Organic Fractions (SOF) and specific PAH compounds following EPA Protocol 8100. The particulate (filter) samples are analyzed the same way as described above for the PUF/XAD-2 samples except the solvent used for the PM filter extraction is ethanol/toluene (30/70; v/v).

Three 90-mm Pallflex filter blanks were extracted and analyzed to determine the PAH background from the media. Additionally, three 90-mm Pallflex tunnel blanks were analyzed to determine the PAH background from the test cell, dilution tunnel, and sample system. The tunnel blanks were drawn for one hour; the background values that are reported in Table 6 have been adjusted to reflect the 30-minute sample time that was used during engine testing. Included in Table 6 is the reported detection limits for each gaseous phase PAH compound for two analytical instruments. Due to low levels of contamination, the filter and tunnel blanks had lower detection limits than the SOF extracts. The particulate matter PAH compounds were initially analyzed using a high-resolution gas chromatograph with a 1.0 atomic mass unit (AMU) low-resolution mass spectrographic detector. Depending on the engine-operating mode and test fuel utilized, there were non-detect values for several key PAH compounds. Primarily, the non-detects were reported due to interference from other organic compounds around the molecular weight of the compound of interest. For the higher molecular weight PAH compound shown in Table 6, a high-resolution gas chromatograph with a 0.01 atomic mass unit (AMU) high-resolution mass spectrographic detector was used for selected test runs.

Table 6. Particulate Matter PAH Backgrounds and Detection Limits						
COMPOUND	Average Pallflex 90mm Filter Blank		Average Pallflex 90mm Tunnel Blank		SOF Extract HRGC/LRMS(1AMU) Average Detection Limit	SOF Extract HRGC/HRMS(0.01AMU) Average Detection Limit
	ng/sample	DL	ng/sample	DL	ng/sample	ng/sample
Naphthalene	543	3	245	4	10	
Acenaphthylene	9	3	8	4	10	
Acenaphthene	74	3	37	4	10	
Fluorene	120	3	62	4	10	
Phenanthrene	665	3	370	4	10	
Anthracene	63	3	16	4	10	
Fluoranthene	89	3	85	4	10	
Pyrene	41	3	67	4	10	
Benzo[a]anthracene	1	3	2	4	10	
Chrysene	3	3	5	4	10	
Benzo[b]fluoranthene	1	3	6	4	10	
Benzo[k]fluoranthene	1	3	4	4	10	
Benzo[e]pyrene	1	3	3	4	10	
Benzo[a]pyrene	0.6	3	1	4	10	0.1
Indeno(1,2,3-cd)pyrene	ND	3	2	4	10	0.1
Dibenzo[a,h]anthracene	ND	3	1	4	10	0.25
Benzo[ghi]perylene	0.9	3	3	4	10	0.1

3.4 Measured Quantities and Accuracy

Table 7 shows the estimated accuracy of the engine and emission measurements.

Table 7. Measured Quantities			
Quantity	**Description**	**Unit**	**Accuracy**
Engine Speed		rpm	+/- 4.2
Engine Load		ft-lb	+/- 2.3
Fuel Flow		lb/hr	+/- 5 %
Temp. Coolant In		°F	+/- 4
Temp. Coolant Out		°F	+/- 4
Temp. Oil		°F	+/- 4
Temp. Intake Air		°F	+/- 4
Temp. Fuel		°F	+/- 4
Temp. Exhaust		°F	+/- 25
Temp. Intercooler In		°F	+/- 4
Temp. Intercooler Out		°F	+/- 4
Temp. Air Dewpoint		°F	+/- 4
Pres. Ambient		"Hg	+/- 1%
Pres. Exh. Restriction		"Hg	+/- 1%
Pres. Boost Pre-Intercooler		"Hg	+/- 1%
Pres. Boost Post-Intercooler		"Hg	+/- 1%
Carbon Monoxide	CO	g/kW-hr	+/- 15 %
Hydrocarbon	HC	g/kW-hr	+/- 20 %
Nitric Oxides	NO_x	g/kW-hr	+/- 10 %
Carbon Dioxide	CO_2	g/kW-hr	+/- 10 %
Particulate (Total)	PM	g/kW-hr	+/- 20 %

3.5 Fuels

Five fuels were evaluated in this program and are described in Table 8.

Table 8. Fuels Descriptions		
Test Fuel	**Fuel Code**	**Fuel Description**
1	CA	California Reference Diesel
2	ADMM15	Blend: 15% Dimethoxymethane (DMM) with 85% ALS Diesel
3	FT-100	Neat Fischer-Tropsch Diesel
4	ALS	Low Sulfur Diesel, Low Aromatics
5	DF-2	EPA Certification Grade Diesel

Fuel analyses are provided in Appendix B from previous work. Fuel properties of interest are shown in Table 9.

Table 9. Fuel Property Summary						
Fuel (Code)	H,wt%	C,wt%	O,wt%	Cetane Number	Sulfur, ppm	Aromatics, wt%
California Reference Diesel Fuel (CA)	13.4	86.4	0.2	45	176	18.9
Low Sulfur Diesel Fuel (ALS)	14.4	85.6	0.0	63	1	9.0
Fischer-Tropsch Diesel (FT-100)	15.1	84.8	0.1	84	1	0.2
Oxygenate Blend: 15% Dimethoxymethane in ALS (ADMM15)	13.7	81.6	4.7	59	1	8.2
EPA 2D Certification Fuel (DF-2)	13.0	86.7	0.3	44	337	30.3

3.6   Engine Lubricant

A synthetic lubricant, SAE 5W30 viscosity grade, was used in this project. A synthetic oil will have less volatile fractions than a petroleum-based lubricant, which will minimize oil contribution to exhaust particulates. Frequent oil changes were made to minimize the engine oil contaminant contribution to exhaust particulates.

4.0   DESIGN OF EXPERIMENT

4.1   Steady-State Operating Conditions

The engine was installed in a steady-state test cell. The engine was supplied with conditioned intake air, controlled to EPA intake conditions. EPA intake air conditions are shown in Table 10.

Table 10. EPA Intake Air Conditions		
Parameter	Set Point	Tolerance
Intake Pressure	100 kPa	±1 kPa
Intake Temperature	25 °C	±2 °C
Intake Dew Point	15 °C	±1 °C

4.1.1   Modes

Five modes of steady-state operation (speed/load points) were included in these investigations. Table 11 shows the engine steady-state test points while Figure 5 shows these five points in relation to the baseline torque curve.

Table 11. Steady-State Test Points			
Mode	BMEP, bar	RPM	MB Equiv. Torque, ft-lb$_f$
M12	0.10	900	1-2
M11	2.62	1500	33.1
M10	2.00	2000	25.3
M6	4.20	2300	53.0
M5	8.80	2600	111

Figure 5. Speed/Load Points for Auto/Energy Fuels

4.1.2 Location of Peak Pressure (LPP)

The OM611 engine utilizes pilot injection. The pilot injection was turned off for the LPP phase of the toxicology study. The OM611 engine was operated at each of the test modes with EGR levels as prescribed by the Auto/Energy CIDI Ad Hoc fuels committee. The Location of Peak Pressure (LPP) was held as constant as feasible for each test mode and test fuel. The IMEP in each cylinder was matched within 5%. The engine was operated with the DaimlerChrysler calibrations for fuel injection rail pressure, boost, and intake runner valve position.

The LPP was established for the OM611 engine by determining MBT timing at a fixed rail pressure and fixed injection duration utilizing CARB fuel for each test mode. The procedure for each test mode was as follows:

1. Check motoring trace on each cylinder, find encoder offset.
2. Turn OFF pilot injection.
3. Establish proper IRV position.
4. Set fuel injection rail pressure.
5. Set EGR level.

6. Fix injection duration that meets BMEP target.

7. Determine IMEP for cylinder balance; adjust individual cylinder injection duration.

8. Establish MBT, starting at 7°ATDC LPP, advance and retard timing.

9. Determine LPP at MBT, and determine base injection duration offsets for IMEP balance.

10. Update Controller tables for fuel injection timing and duration.

4.1.3   Cylinder Balance

The DaimlerChrysler OM611 engine will have a Kistler 6052A piezoelectric pressure transducer installed in each of the four cylinders via a glow plug adapter. The cylinder pressures were monitored with a DSP high-speed data acquisition system clocked at 0.5° crankshaft intervals. The DSP data system will be set up to monitor Location of Peak Pressure (LPP) and Indicated Mean Effective Pressure (IMEP) for each cylinder. The DSP was also used to calculate engine average IMEP and LPP for 50 consecutive combustion cycles. During testing, the RPECS control system was able to maintain IMEP within 5% cylinder-to-cylinder, and hold LPP within 2 crankangle degrees cylinder-to-cylinder for all modes.

During testing, the OM611 engine was operated at the conditions that follow in Table 12 with the pilot fuel injection turned off:

Table 12. Engine Operating Conditions								
Mode	RPM	BMEP, bar	EGR, %	Rail Pressure, bar	Boost, bar g	LPP Timing, °ATDC	IMEP, cyl. To cyl. %	IRV Status
12	900	0.2	40	Stock	Stock	7	±5	Closed
11	1500	2.62	30	Stock	Stock	7	±5	Closed
10	2000	2.0	30	Stock	Stock	7	±5	Closed
6	2300	4.2	15	Stock	Stock	7	±5	Open
5	2600	8.8	5	Stock	Stock	7	±5	Open

The cylinder balance procedure was as follows:

1. Set Test Mode, RPECS will do closed loop torque control by dithering injection duration.

2. Set EGR level.

3. Make individual cylinder timing changes to meet LPP for MBT.

4. Average IMEP for all four cylinders.

5. Adjust individual injection duration offsets to set cylinder IMEP within ±5% of the average IMEP.

6. Iterate between timing changes and IMEP adjustments.
7. Update Controller tables for timing and duration offsets.
8. Stabilize engine at balanced IMEP and LPP.
9. Initiate particulate and gaseous emission sampling.
10. Spot Check IMEP and LPP during particulate sampling.

4.1.4   Pilot Fuel Injection

A brief pilot fuel injection evaluation was performed to determine if differences in exhaust emissions existed between modes operated with and without pilot fuel injection. The approach was to operate the engine at each of five test modes, utilizing three differing control strategies, and using CARB fuel. The control approaches consisted of locating peak pressure (LPP) without pilot injection, LPP with pilot injection (Pilot A), and the calibrated (Pilot B) engine strategy, which also uses pilot injection. The LPP and Pilot A strategies were performed using an RPECS controller. Under RPECS control, each cylinder was balanced within 5% of the engine average IMEP. The Pilot B strategy was performed with the OEM controller. The LPP was determined by fixing injection rail pressure, specified EGR, and setting the injector pulse width that meets the BMEP setting for the mode. The main start of injection timing was swept, and the LPP that produced the best torque was noted. When the location of peak pressure during Pilot A operation was determined, the pilot-to-main, injection-pulse-width ratio and the pilot-to-main timing gap remained as the calibrated settings for the mode.

The basic findings during the brief evaluation concerned the PM and Soluble Organic Fraction of the PM. The PM emissions increased when pilot injection was utilized. However, pilot injection results in a higher exhaust temperature that reduces the SOF level of the particulate.

The conclusions from the study were that the pilot fuel injection operation does affect emissions, noise, and BSFC. The heat release traces show early combustion, which could lead to variations in exhaust compounds. For the non-idle modes, pilot injection reduces noise and NOx, increases PM and BSFC, and reduces the SOF of the PM. Combustion heat release analysis reveals reactions that occur BTDC, with long in-cylinder residence time of the pilot injected fuel. Differences in combustion and emissions warrant investigation of pilot injection. For the idle mode, the results were variable. The higher EGR at idle, using the Pilot B (OEM) strategy, probably had more effect on emissions than the actual pilot injection event. Detailed results from the pilot fuel injection study are available in Appendix C.

The following recommendations were presented to DOE and the Auto/Energy CIDI Ad Hoc fuels committee following the brief pilot fuel injection evaluation:

- Complete tests as planned without pilot injection for all five fuels.
- Perform tests with pilot injection using LPP with addition of pilot fuel injection and using the OEM ECM strategies.
- Use OEM calibrated pilot-to-main gap of 1.8 ms.
- Use OEM calibrated pilot-to-main, pulse-width ratio for BMEP, for each fuel.
- Evaluate all five fuels using pilot fuel injection.
- Evaluate at two modes weighted highly by Ad Hoc fuels study:
    - mode 11: 1500 rpm/ 2.62 bar BMEP
    - mode 10: 2000 rpm/ 2.0 bar BMEP
- Perform experiments in triplicate.

4.1.5 Intake Runner Valve

The engine has an Intake Runner Valve (IRV) for increasing swirl at low-speeds, light-loads. The IRV works by closing off one of the two intake ports, forcing the entire intake charge down the other intake tract. The status of the IRV under Bosch ECM control is as shown in Table 13 for the five test modes.

Table 13. Modal Intake Runner Valve Positions			
Mode	RPM	BMEP, bar	IRV Status
12	900	0.2	Closed
11	1500	2.62	Closed
10	2000	2.0	Closed
6	2300	4.2	Open
5	2600	8.8	Open

For the toxicology study, the IRV was utilized as calibrated by DaimlerChrysler. Changing the in-cylinder charge air motion by varying IRV status could alter combustion and impact the results for the OM611 engine.

4.2   Test Plan

4.2.1   LPP Tests

Best torque injection timing sweeps were performed at all modes to determine the LPP at the specified EGR. The engine was controlled with pilot injection off, specified EGR, and at the fixed injection pulse width to maintain the brake mean effective pressure operating target. The IMEP was monitored on each cylinder, along with LPP, to be maintained within the criteria discussed previously. Injection timing was swept until a change in brake torque was noted. For all modes, a LPP of 7°ATDC corresponded with the best torque timing.

The cylinder pressures were monitored and Location of Peak Pressure (LPP) and Indicated Mean Effective Pressure (IMEP) control were verified for each cylinder. The RPECS system was able to maintain IMEP within 5% cylinder-to-cylinder, and hold LPP within 2 crank angle degrees cylinder-to-cylinder for all modes.

All control parameters for the RPECS were verified for maintaining cylinder balance, constant LPP, and specified EGR. A tunnel blank was performed to evaluate sample system toxic air pollutants and PAH concentrations.

4.2.2   Pilot Fuel Injection Tests

To determine if pilot fuel injection on a direct-injected diesel engine with a Common-Rail fuel system exhibits impacts on engine gaseous, PM, toxic air pollutant, and PAH exhaust emissions, evaluations were performed at two modes (10 and11) with three control strategies.

The control approaches consisted of Location of Peak Pressure (LPP) without pilot injection, LPP with Pilot Injection (Pilot A), and the calibrated OEM (Pilot B) engine strategy which also uses pilot injection. When Pilot A control was utilized, the pilot-to-main injection pulse width ratio, and the Pilot-to-Main timing gap was kept the same as the Pilot B settings for the mode.

The timings for the differing control strategies are outlined in Table 14 for each of the test modes. Note the LPP for the Pilot B strategy shown is for the CA fuel, the other test fuels would likely result in a different LPP using the OEM controller. With the OEM controller there was not any timing adjustments available to control LPP with each test fuel. Also note the higher EGR with the Pilot B strategy.

Table 14. Timing Parameters for Pilot Fuel Injection Study –CA Fuel							
Mode	**Speed**	**BMEP, bar**	**Pilot A**				
			LPP	**PSOI†**	**MSOI**	**EGR, %**	
11	1500	2.62	7	24	8	30	
10	2000	2	7	31	10	30	
LPP			**Pilot B**				
LPP*	**MSOI‡**	**EGR, %**	**LPP**	**PSOI**	**MSOI**	**EGR, %**	
7	9	30	12	18	2	36	
7	12	30	15	23	2	35	

*LPP - Location of Peak Pressure, dATDC
‡MSOI - Main Start of Injection, dBTDC
†PSOI – Pilot Start of Injection, dBTDC

4.3   Statistical Analysis Methodology

The goal of this study was to provide information on the PAH content of exhaust gas and exhaust particulates, some of which have been shown to cause tumors in animals. In addition to investigating PAH content, toxic air pollutants and mass emissions were also studied. The engine test results were used to compare the PAH levels of four modified diesel fuels and a baseline fuel to determine the effect of fuel modifications on the total emissions of these toxicologically important compounds. Additionally, the mode (speed and load) of engine operation and the pilot condition settings were also controlled to assess their effects on the PAH or emissions response.

Analysis of variance (ANOVA) statistical techniques[11] were used to investigate the factor effects of fuel, mode, and pilot condition using models on four different data segments. These four data segments included engine test results from the following scenarios:

(1)   LPP only condition for modes 5, 6, 10, and 11;
(2)   LPP only condition for mode 12;
(3)   LPP and pilot on conditions for modes 10 and 11; and
(4)   LPP only condition for weighted modes 5, 6, 10, and 11.

Each of these four data segments included independent ANOVA models on the 38 measured responses which included: five typical gaseous emissions, four toxic air pollutant emissions, 11 gaseous PAH emissions, 17 specific PAH from SOF, and one SOF. Each fuel, mode, and pilot condition combination was run in triplicate. The ANOVA identified which factors were statistically significant with respect to the average response. For example, the ANOVA tested whether the average response of the five fuels was statistically different. It also determined if significant differences existed across the modes, and whether an interaction between the fuel and mode was significant. If significant differences existed, a Tukey's HSD post-hoc multiple comparison procedure[12] was conducted to discriminate between the response averages across the levels of the significant factor. All comparison tests were made at the 5% level of significance.

No mathematical transformations were made on any of the response variables (PAH content, toxic air pollutants and mass emissions). All analyses were conducted in the original response variable units. The units used for the PM and SOF emissions were g/kW-hr, toxic air pollutant emissions were mg/kW-hr, soluble PAH were micro-grams/kW-hr, and the gaseous PAH were micro-grams/kW-hr.

The ANOVA models used for each of the four data segments are described below.

> LPP only condition for modes 5, 6, 10, and 11 - Using only the pilot off condition data, an ANOVA was performed using the 5 fuels and 4 modes (5, 6, 10, and 11). This ANOVA model contained a FUEL and MODE effect along with a FUEL by MODE interaction.

> LPP only condition for mode 12 - Using only the pilot off condition data, an ANOVA was performed using the 5 fuels and only Mode 12. Thus, there was not a MODE effect in the ANOVA but only a FUEL effect.

> LPP and pilot on conditions for modes 10 and 11 - In comparing the responses across the 3 different pilot conditions, only modes 10 and 11 were used. Data from the 5 fuels, 2 modes and 3 pilot conditions were used in an ANOVA model that included the FUEL, MODE, and PILOT effects along with all 2-way interactions and a 3-way interaction.

LPP only condition for weighted modes 5, 6, 10, and 11 - The final analysis included a composite response that was computed by weighting 4 modes (5, 6, 10, and 11) according to the Ad Hoc Diesel Fuels Panel weighting criteria. The composite was computed as:

$$(25/1200)*response@Mode\ 5 + (200/1200)*response@Mode\ 6 +$$
$$(375/1200)*response@Mode\ 10 + (600/1200)*response@Mode\ 11$$

A composite response was computed for each test mode set run with each fuel. Since each fuel, mode, and pilot condition combination was run in triplicate, a composite response was determined from the test results for modes 5, 6, 10, and 11 that were run nearest to one another. This usually occurred on the same test day. Therefore, three composite responses were computed for each PAH, toxic air pollutants and mass emissions. However, there were four soluble PAH responses that resulted in non-detects in one or two modes in the ALS, CA or DF-2 fuels. These responses were acenaphthylene, fluorene, benzo[b]fluoranthene, and benzo[e]pyrene. In each of these soluble PAH cases only one composite response could be computed. Therefore, the remaining two composite responses were calculated based on imputed values for the non-detects. The missing PAH values were replaced with either the lowest actual measurement for that mode and fuel or the lower detection limit for that mode and fuel. In situations where two of the three composite responses were computed, no imputed values were used to replace the one missing composite response.

Using only the pilot off condition data and the composite responses, an ANOVA was performed using the 5 fuels. Thus, there was not a MODE effect in the ANOVA - only a FUEL effect.

5.0   FUEL IMPACT ON EMISSIONS – WEIGHTED LPP RESULTS

Fuel comparisons utilizing the Ad Hoc Fuels Group Mode Weighting Factors shown in Table 15 were made for brake specific exhaust emissions with the engine operated under LPP control with pilot fuel injection turned off. Mode 12 was not included in the weighting scheme due to the combination of variability of the mode 12 data and the large mode 12 weight which masked the fuel effects on emissions. The ANOVA tables for the weighted averages can be found in Appendix C.

Table 15. Weighting Factors for Engine Out Emissions	
Mode	**Mode Weights, seconds**
Mode 11	600
Mode 10	375
Mode 6	200
Mode 5	25
Total	1200

5.1   Fuel Impact on Regulated Brake Specific Mass Emissions

Several statistically significant trends, at 95% confidence, were apparent from an ANOVA of the weighted average brake specific emissions data. Table 16 summarizes the general rank order for the regulated weighted average mass emissions during LPP engine operation with pilot fuel injection turned off. The table displays the fuels rank from highest response to lowest response for the Least-Square means of the weighted analysis. Statistically significant similar fuel groupings are also shown for each emission response in Table 16.

The discussions to follow are summaries of the ANOVA performed for each emission response for the weighted averages, and refer to the results in Table 16. The ANOVA tables for the weighted averages can be found in Appendix C.

5.1.1   Fuel Impact on Particulate

ANOVA revealed statistically significant differences in the average weighted particulate among the test fuels. The statistical groupings and relative levels of particulate matter emissions are shown in Figure 6 for the test fuels. Average particulate at fuels FT-100 and ADMM15 are not significantly different from one another, but are different than the other three fuels. The average particulate at Fuel ALS is significantly different than Fuel DF-2. The CA fuel is not significantly different than either the ALS or DF-2 fuel for particulate.

5.1.2 Fuel Impact on NOx

The ANOVA revealed statistically significant differences in the average weighted brake specific NO_X among the fuels. From Figure 7 the highest NOx emitter was DF-2, followed jointly by ADMM15, FT-100, and CA, with ALS being the lowest NOx emitting fuel. The average weighted $BSNO_X$ for the DF-2 fuel is significantly different from the remaining four fuels. Another significant finding is the average weighted $BSNO_X$ for the ADMM15 fuel blend is significantly different than the ALS fuel. ALS was the base fuel for the ADMM15 blend.

Table 16. Weighted Mass Emissions (g/kWh) ANOVA Summary for LPP Only Conditions			
	LPP Only – Weighted Modes 5,6,10,11		
Response	Fuel	LS Means[1]	Significant Fuel Groups[2]
BSPM	DF-2	0.2888	A
	CA	0.2627	AB
	ALS	0.2249	B
	ADMM15	0.1431	C
	FT-100	0.1337	C
$BSNO_X$	DF-2	4.331	A
	ADMM15	3.719	B
	FT-100	3.441	BC
	CA	3.431	BC
	ALS	3.145	C
BSHC	DF-2	1.428	A
	CA	1.221	A
	ALS	0.7848	B
	ADMM15	0.6766	B
	FT-100	0.3935	C
BSCO	DF-2	5.063	A
	CA	4.931	A
	ALS	3.236	B
	ADMM15	3.095	B
	FT-100	1.830	C
$BSCO_2$	ADMM15	959.4	A
	DF-2	948.0	AB
	CA	911.9	BC
	ALS	910.9	BC
	FT-100	874.2	C
BSSOF	DF-2	0.2279	A
	CA	0.2207	A
	ALS	0.1608	B
	ADMM15	0.1237	C
	FT-100	0.0723	D
[1]Fuels listed from highest to lowest least squares mean			
[2]Letters designate groups of fuel means within which there are no statistically significant differences			
NS = no statistically significant differences in the mean response at the 5% level of significance			

Particulate Matter Emissions

Figure 6. Test Fuel Weighted Average Particulate Matter Mass Emissions (g/kWh)

NOx Emissions

Figure 7. Test Fuel Weighted Average NOx Mass Emissions (g/kWh)

5.1.3   Fuel Impact on HC

A statistically significant difference in the average weighted BSHC among the test fuels was seen from the ANOVA. Figure 8 shows the relative levels of test fuel hydrocarbon emissions, with statistically similar groupings shown with horizontal bars. The average weighted BSHC for the FT-100 fuel is significantly different from the remaining four fuels. The other fuels can be divided into two distinct fuel groupings. The ADMM15 and ALS fuels are not significantly different from one another, but are different from the CA and DF-2 fuels. The CA and DF-2 fuels are not significantly different from one another.

5.1.4   Fuel Impact on CO

Figure 9 shows the ANOVA statistically significant differences in the average weighted BSCO among the fuels. The average weighted BSCO for the FT-100 fuel is significantly different from the remaining four fuels. The other fuels can be divided into two distinct fuel groupings. The ADMM15 and the ALS fuels are not significantly different from one another, but are different from the CA and DF-2 fuels. The CA and DF-2 fuels are not significantly different from one another. The CO and HC results show the same statistical trends, which is not unexpected considering both species are measures of combustion inefficiency.

5.1.5   Fuel Impact on CO_2

The ANOVA results for $BSCO_2$ reveal statistically significant differences in the average weighted response among the fuels. Figure 10 shows the statistical groupings for CO_2. The average weighted $BSCO_2$ for the ADMM15 fuel is significantly different than the ALS, CA, and FT-100 fuels. Also, the average weighted $BSCO_2$ for the FT-100 fuel is significantly different than the DF-2 fuel. CO_2 emissions are a measure of energy consumption, and in the case of the test fuels reflects the fuels heating value. ADMM15 has the lowest net heat of combustion of the test fuels, which results in the highest CO_2 emissions. FT-100 has the highest heating value, and correspondingly lowest CO_2 emissions.

5.1.6   Fuel Impact on SOF of PM

From the ANOVA statistically significant differences in the average weighted BSSOF among the fuels exists.   The relative SOF levels of the particulate matter and their statistical groups are

represented in Figure 11. There are four distinct fuel groupings with respect to the average weighted BSSOF. The FT-100, ADMM15, and ALS fuels are significantly different from one another and the remaining two fuels. The CA and DF-2 fuels are not significantly different from one another, but are significantly different from the other three fuels.

The SOF represents the portion of the total particulate that includes unburned fuel, unburned lube oil, and byproducts of combustion of fuel and lube oil. Although ADMM15 and FT-100 have statistically similar total PM response, the SOF for the two fuels is statistically different. The oxygenated fuel, ADMM15, has a significantly higher soluble organic fraction than FT-100. Whilst FT-100 has a larger portion of insoluble particulate matter. Symkowicz[3] saw a higher fraction of "dry" particulate with FT-100 as part of the Ad Hoc Diesel Fuels Group core program. The ratio of SOF to total particulate may be of interest for determining engine aftertreatment strategies, Figure 12. ADMM15 also has a greater ratio of SOF/PM than both FT-100 and its parent fuel ALS.

Figure 8. Test Fuel Weighted Average Hydrocarbon Mass Emissions (g/kWh)

Carbon Monoxide Emissions

Figure 9. Test Fuel Weighted Average Carbon Monoxide Mass Emissions (g/kWh)

Carbon Dioxide Emissions

Figure 10. Test Fuel Weighted Average Carbon Dioxide Mass Emissions (g/kWh)

Soluble Organic Fraction of Particulate Emissions

Figure 11. Test Fuel Weighted Average Soluble Organic Fraction of Particulate Mass Emissions (g/kWh)

Relationship of SOF/PM for Weighted Average Results

Figure 12. Ratio of SOF to Total PM of Weighted Average Results for Test Fuels

5.2   Fuel Impact on Four Clean Air Act Toxic Air Pollutants

Table 17 is the ranking of the test fuels from the ANOVA for the four EPA Clean Air Act toxic air pollutant compounds. For the EPA toxic air pollutants, ADMM15 and FT-100 were statistically similar emitting fuels, and always in the lowest grouping for the weighted average for LPP operation with pilot fuel injection turned off.

The discussions to follow are summaries of the ANOVA performed for each emission response for the weighted averages, and refer to the results in Table 17.   The ANOVA tables for the weighted averages can be found in Appendix C.

Table 17. Clean Air Act Toxic Air Pollutant Compounds Weighted Mass Emissions (mg/kWh) ANOVA Summary for LPP Operation			
	LPP Only - Weighted Modes 5,6,10,11		
Response	Fuel	LS Means[1]	Significant Fuel Groups[2]
Benzene	CA	7.297	A
	DF-2	6.360	AB
	ALS	5.017	B
	FT-100	2.504	C
	ADMM15	2.075	C
1,3-Butadiene	CA	6.108	A
	DF-2	5.778	A
	ALS	4.817	AB
	ADMM15	3.921	BC
	FT-100	2.650	C
Formaldehyde	DF-2	484.2	A
	ALS	366.8	AB
	CA	332.4	AB
	ADMM15	267.1	B
	FT-100	206.8	B
Acetaldehyde	DF-2	177.0	A
	ALS	148.8	AB
	CA	126.0	ABC
	ADMM15	92.39	BC
	FT-100	75.01	C
[1]Fuels listed from highest to lowest least squares mean			
[2]Letters designate groups of fuel means within which there are no statistically significant differences			
NS = no statistically significant differences in the mean response at the 5% level of significance			

5.2.1   Benzene

The ANOVA for the toxic air pollutant emission benzene revealed statistically significant differences in the average weighted benzene among the fuels. Figure 13 shows the ranking and statistically significant similar groupings (horizontal bars) for benzene emissions. Average weighted benzene at fuels ADMM15 and FT-100 are not significantly different from one another, but are different than the other three fuels. The average weighted benzene at fuel ALS is significantly different than fuel CA. The DF-2 fuel is not significantly different than either the ALS or CA fuel.

5.2.2 1,3-Butadiene

An ANOVA for 1,3-butadiene indicated statistically significant differences exist in the average weighted response among the fuels. For 1,3-butadiene the lowest emitting fuels were FT-100 and ADMM15, then ALS, with the highest emitting fuels being DF-2 and CA; the statistical groupings are shown in Figure 14. The average weighted 1,3-butadiene for the CA and DF-2 fuels are not significantly different from one another, but are significantly different than the ADMM15 and FT-100 fuels. The ADMM15 and FT-100 fuels are not significantly different from one another. Also, the average weighted 1,3-butadiene for the ALS fuel is significantly different than the FT-100 fuel.

5.2.3   Formaldehyde

Statistically significant differences exist in the average weighted formaldehyde emission among the test fuels based on the ANOVA. Figure 15 shows the relative levels and statistical groupings for Formaldehyde emissions.   The average weighted formaldehyde for the DF-2 fuel is significantly different than the FT-100 and the ADMM15 fuels.

5.2.4   Acetaldehyde

From ANOVA, statistically significant differences in the average weighted acetaldehyde among the fuels exist. Corresponding groupings for acetaldehyde are shown in Figure 16.   The average weighted acetaldehyde for the DF-2 fuel is significantly different than the FT-100 or ADMM15 fuels. The FT-100 and ADMM15 fuels are not significantly different from one another. Also, the average weighted acetaldehyde for the FT-100 fuel is significantly different than the ALS fuel.

Benzene Emissions

Figure 13. Test Fuel Weighted Average Benzene Mass Emissions (mg/kWh)

1,3-Butadiene Emissions

Figure 14. Test Fuel Weighted Average 1,3-Butadiene Mass Emissions (mg/kWh)

Figure 15. Test Fuel Weighted Average Formaldehyde Mass Emissions (mg/kWh)

Figure 16. Test Fuel Weighted Average Acetaldehyde Mass Emissions (mg/kWh)

5.3 Fuel Impact on Particulate Soluble Extract PAH Species

The fuel rankings for 13 of the particulate bound soluble phase PAH compounds are shown in Table 18. Due to non-detects, four PAH compounds are being analyzed again with a higher resolution instrument. The four compounds reanalyzed were benzo[a]pyrene, indeno(123-cd)pyrene, dibenzo(a,h)anthracene, and benzo(ghi)perylene. For the majority of PAH compounds DF-2 fuel was statistically different from the other test fuels. The ADMM15 and FT-100 fuels were in the statistically equivalent (95% confidence) lowest grouping for particulate bound PAH compounds.

The discussions to follow are summaries of the ANOVA performed for each emission response for the weighted averages, and refer to the results in Table 18. The ANOVA tables for the weighted averages weighted averages can be found in Appendix C.

Table 18. Weighted Soluble PAH ANOVA Summary for LPP Only Conditions			
Response	**LPP Only - Weighted Modes 5,6,10,11**		
	Fuel	**LS Means[1]**	**Significant Fuel Groups[2]**
Naphthalene	DF-2	48.71	A
	CA	46.18	A
	FT-100	39.38	AB
	ADMM15	28.43	AB
	ALS	23.45	B
Acenaphthylene[3]	CA	0.9966	A
	DF-2	0.8074	AB
	FT-100	0.6035	AB
	ADMM15	0.4807	B
	ALS	0.4780	B
Acenaphthene	DF-2	6.564	NS
	CA	5.323	
	FT-100	4.471	
	ADMM15	4.333	
	ALS	2.314	
Fluorene[3]	DF-2	12.49	A
	CA	9.226	AB
	ADMM15	7.173	B
	FT-100	6.208	B
	ALS	4.214	B
Phenanthrene	DF-2	103.0	A
	CA	72.85	AB
	FT-100	43.01	B
	ALS	36.00	B
	ADMM15	29.81	B
Anthracene	DF-2	4.197	A
	CA	4.161	A
	FT-100	2.920	AB
	ADMM15	2.287	BC
	ALS	0.7376	C

Table 18. Weighted Soluble PAH ANOVA Summary for LPP Only Conditions (contd)			
Response	**LPP Only - Weighted Modes 5,6,10,11**		
	Fuel	**LS Means[1]**	**Significant Fuel Groups[2]**
Fluoranthene	DF-2	51.19	A
	ALS	19.54	B
	CA	17.78	B
	FT-100	15.48	B
	ADMM15	9.829	B
Pyrene	DF-2	83.53	A
	ALS	21.30	B
	CA	13.67	B
	FT-100	12.71	B
	ADMM15	9.984	B
Benzo[a]anthracene	DF-2	2.455	A
	CA	1.063	B
	ALS	0.7125	BC
	FT-100	0.2531	BC
	ADMM15	0.1550	C
Chrysene	DF-2	7.735	A
	CA	2.391	B
	ALS	1.936	B
	FT-100	0.7735	B
	ADMM15	0.5860	B
Benzo[b]fluoranthene[3]	DF-2	1.538	A
	ALS	1.253	A
	CA	1.190	A
	ADMM15	0.3893	B
	FT-100	0.3046	B
Benzo[k]fluoranthene	DF-2	2.291	A
	CA	1.189	B
	ALS	0.6576	B
	ADMM15	0.4236	B
	FT-100	0.3539	B
Benzo[e]pyrene[3]	DF-2	1.059	A
	CA	0.6799	AB
	ALS	0.6206	AB
	FT-100	0.2671	B
	ADMM15	0.2101	B
Benzo[a]pyrene	ALS	0.4346	A
	CA	0.3467	AB
	DF-2	0.2002	BC
	FT-100	0.0684	C
	ADMM15	0.0548	C
Indeno(1,2,3-cd)pyrene	DF-2	0.3978	A
	ADMM15	0.0731	B
	FT-100	0.0613	B
Benzo[ghi]perylene	CA	0.7062	A
	DF-2	0.6439	A
	ADMM15	0.2085	B
	FT-100	0.1541	B

[1]Fuels listed from highest to lowest least squares mean
[2]Letters designate groups of fuel means within which there are no statistically significant differences
[3]Some fuel data were imputed in the calculation of the weighted response because of non-detects
NS = no statistically significant differences in the mean response at the 5% level of significance

5.3.1   Naphthalene

The ANOVA revealed statistically significant differences in the average naphthalene among the fuels. Figure 17 shows the statistical groupings for the PAH naphthalene bound to the particulate matter. The average weighted naphthalene for the ALS fuel is significantly different from the CA and DF-2 fuels.

5.3.2   Acenaphthylene

The ANOVA for acenaphthylene revealed statistically significant differences in the average weighted acenaphthylene among the fuels. Some fuel data were imputed in the calculation of the weighted response because of non-detects for various modes and fuels. The data was imputed utilizing the detection limits. The weighted average acenaphthylene response, and the statistical groups are shown in Figure 18. The average weighted acenaphthylene for the CA fuel is significantly different from the ADMM15 and ALS fuels.

5.3.3   Acenaphthene

The weighted average acenaphthene response is shown in Figure 19. From ANOVA statistically significant differences did not exist in the average acenaphthene among the test fuels.

5.3.4 Fluorene

The ANOVA showed statistically significant differences in the average weighted fluorene among the fuels. Some ALS fuel data was imputed for repeat runs because of non-detects in modes 5 and 11.   The average weighted fluorene for the DF-2 fuel is significantly different from the ADMM15, FT-100, and ALS fuels. Figure 20 shows the weighted average fluorene and the statistical groups.

5.3.5   Phenanthrene

A statistically significant difference in the average weighted phenanthrene response exists among the test fuels.   The phenanthrene response is shown in Figure 21.   The average weighted phenanthrene for the DF-2 fuel is significantly different than the ADMM15, ALS, and FT-100 fuels. The average weighted phenanthrene for the ADMM15, ALS, FT-100, and CA fuels are not significantly different from one another.

Particulate Naphthalene Emissions

Figure 17. Test Fuel Weighted Average Particulate Phase Naphthalene Mass Emissions (µg/kWh)

Particulate Acenaphthylene Emissions

Figure 18.Test Fuel Weighted Average Particulate Phase Acenaphthylene Mass Emissions (µg/kWh)

Particulate Acenaphthene Emissions

Weighted Mass Emission, μg/kWh

Fuel	Value
DF-2	6.56
CA	5.32
FT-100	4.47
ADMM15	4.33
ALS	2.31

Statistical Grouping

Figure 19. Test Fuel Weighted Average Particulate Phase Acenaphthene Mass Emissions (μg/kWh)

Particulate Fluorene Emissions

Weighted Mass Emission, μg/kWh

Fuel	Value
DF-2	12.5
CA	9.23
ADMM15	7.17
FT-100	6.21
ALS	4.21

Statistical Grouping

Figure 20. Test Fuel Weighted Average Particulate Phase Fluorene Mass Emissions (μg/kWh)

Particulate Phenanthrene Emissions

Figure 21. Test Fuel Weighted Average Particulate Phase Phenanthrene Mass Emissions (µg/kWh)

5.3.6 Anthracene

From ANOVA a statistically significant difference in the average weighted anthracene is revealed among the fuels. The weighted average results for anthracene are shown in Figure 22. The average weighted anthracene for the ALS fuel is significantly different from the CA, DF-2, and FT-100 fuels. Also, the ADMM15 fuel has a significantly different weighted anthracene than the CA and DF-2 fuels.

5.3.7 Fluoranthene

Statistically significant differences exist in the average weighted fluoranthene response among the fuels. The average weighted fluoranthene for the DF-2 fuel is significantly different from the remaining four fuels. The ADMM15, FT-100, CA, and ALS fuels are not significantly different from one another with respect to the average weighted fluoranthene, Figure 23.

Particulate Anthracene Emissions

Figure 22. Test Fuel Weighted Average Particulate Phase Anthracene Mass Emissions (µg/kWh)

Particulate Fluoranthene Emissions

Figure 23. Test Fuel Weighted Average Particulate Phase Fluoranthene Mass Emissions (µg/kWh)

5.3.8   Pyrene

The average weighted pyrene for the DF-2 fuel is significantly different than the remaining four fuels. The pyrene results are shown in Figure 24. The ADMM15, FT-100, CA, and ALS fuels are not significantly different from one another with respect to the average weighted pyrene.

5.3.9   Benzo[a]anthracene

The ANOVA for benzo[a]anthracene, levels shown in Figure 25, indicated there were statistically significant differences in the average weighted benzo[a]anthracene among the fuels. The average weighted benzo[a]anthracene for the DF-2 fuel is significantly different than the remaining four fuels. Also, the average weighted benzo[a]anthracene for the CA fuel is significantly different than the ADMM15 fuel.

5.3.10   Chrysene

There were statistically significant differences in the average weighted chrysene for the test fuels. Figure 26 is the statistical groupings for the particulate phase PAH chrysene.   The average weighted chrysene for the DF-2 fuel is significantly different than the remaining four fuels. The ADMM15, FT-100, ALS, and CA fuels are not significantly different from one another with respect to the average weighted chrysene.

5.3.11   Benzo[b]fluoranthene

The ANOVA for the PAH benzo[b]fluoranthene has shown statistically significant differences in the average weighted benzo[b]fluoranthene among the fuels. Some of the CA fuel data was imputed for the analysis due to non-detects in modes 5 and 11. The results are depicted in Figure 27.   There   are   two   distinct   fuel   groupings   with   respect   to   the   average   weighted benzo[b]fluoranthene. The ADMM15 and FT-100 fuels are not significantly different from one another, but are different from the remaining three fuels. The ALS, CA, and DF-2 fuels are not significantly different from one another.

Particulate Pyrene Emissions

Figure 24. Test Fuel Weighted Average Particulate Phase Pyrene Mass Emissions (µg/kWh)

Particulate Benzo[a]anthracene Emissions

Figure 25. Test Fuel Weighted Average Particulate Phase Benzo[a]anthracene Mass Emissions (µg/kWh)

Particulate Chrysene Emissions

Figure 26. Test Fuel Weighted Average Particulate Chrysene Mass Emissions

Particulate Benzo[b]fluoranthene Emissions

Figure 27. Test Fuel Weighted Average Particulate Phase
Benzo[b]fluoranthene Mass Emissions (µg/kWh)

5.3.12   Benzo[k]fluoranthene

Average weighted benzo[k]fluoranthene response had statistically significant differences among the fuels. The least-square means and groups are shown in Figure 28 for benzo[k]fluoranthene. The average weighted benzo[k]fluoranthene for the DF-2 fuel is significantly different than the remaining four fuels. The FT-100, ADMM15, ALS, and CA fuels are not significantly different from one another with respect to the average weighted benzo[k]fluoranthene.

5.3.13   Benzo[e]pyrene

For the ANOVA for benzo[e]pyrene, statistically significant differences were seen in the average weighted benzo[e]pyrene among the fuels. Some DF-2 data was imputed for repeat runs because of non-detects in modes 5 and 6. The emissions of particulate bound PAH benzo[e]pyrene is shown in Figure 29, along with the statistical groupings. The average weighted benzo[e]pyrene for the DF-2 fuel is significantly different than the ADMM15 and FT-100 fuels.

5.3.14   Benzo[a]pyrene

Due to non-detects for benzo[a]pyrene using high-resolution GC/ low-resolution MS, the extracts were reanalyzed utilizing a high-resolution MS detector. The selection criteria for reanalysis was any non-idle modal LPP experiment that did not have a benzo[a]pyrene result with the low-resolution instrument. The ANOVA for benzo[a]pyrene revealed statistically significant differences in the average benzo[a]pyrene response among the fuels. The emissions of particulate bound PAH benzo[e]pyrene are shown in Figure 30, along with the statistical groupings. The average weighted benzo[a]pyrene for the ADMM15 and FT-100 fuels is significantly different than the CA and ALS fuels.   Also, ALS fuel has a significantly different weighted benzo[a]pyrene than the DF-2 fuel.

5.3.15   Indeno(1,2,3-cd)pyrene

High-resolution analysis of the extracts were also performed for the PAH indeno(1,2,3-cd)pyrene. Statistically significant differences were seen in the average weighted indeno(1,2,3-cd)pyrene among the fuels, and the results are shown in Figure 31. Figure 31 does not have results for ALS or CA fuels due to the number of non-detects that made analysis meaningless. The average indeno(1,2,3-cd)pyrene for the ADMM15 and FT-100 fuels are not significantly different from one another, but both are significantly different from the DF-2 fuel.

Figure 28. Test Fuel Weighted Average Particulate Phase Benzo[k]fluoranthene Mass Emissions (µg/kWh)

Figure 29. Test Fuel Weighted Average Particulate Phase Benzo(e)pyrene Mass Emissions (µg/kWh)

Figure 30. Test Fuel Weighted Average Particulate Phase Benzo[a]pyrene Mass Emissions (μg/kWh)

Figure 31. Test Fuel Weighted Average Particulate Phase Indeno(1,2,3-cd)pyrene Mass Emissions (μg/kWh)

5.3.16   Dibenzo[a,h]anthracene

Although high-resolution analysis was attempted on this PAH species, sufficient non-detects existed such that the weighted averaging could not be performed in a meaningful manner.

5.3.17   Benzo[ghi]perylene

High-resolution analysis of the extracts were also performed for the PAH benzo[ghi]perylene. Statistically significant differences were seen in the average weighted benzo[ghi]perylene among the fuels, and the results are shown in Figure 32.   The average benzo[ghi]perylene for the FT-100 and ADMM15 fuels are significantly different from the DF-2 and CA fuels, but not significantly different from one another.   Also, the DF-2 and CA fuels are not significantly different from one another.

Particulate Benzo[ghi]perylene Emissions

Figure 32. Test Fuel Weighted Average Particulate Phase Benzo[ghi]perylene Mass Emissions (µg/kWh)

5.4   Fuel Impact on Gaseous PAH Species

The gas phase PAH emissions rank the test fuels in the general order shown in Table 19. Included in Table 19 are the least-square means from the ANOVA, along with the statistically significant groupings for the weighted average mass emissions. The general trends were for DF-2 to have the highest gas phase PAH emissions, while ADMM15 and FT-100 always had the statistically lowest PAH emissions. The ANOVA for gas phase PAH species indicated the oxygenated diesel fuel, ADMM15, was statistically equivalent to FT-100.

The discussions to follow are summaries of the ANOVA performed for each emission response for the weighted averages, and refer to the results in Table 19. The ANOVA tables for the weighted averages can be found in Appendix C.

Table 19. Weighted Gaseous PAH ANOVA Summary for LPP Only Conditions			
	LPP Only - Weighted Modes 5,6,10,11		
Response	Fuel	LS Means[1]	Significant Fuel Groups[2]
Naphthalene	CA	5436	A
	DF-2	3226	B
	ALS	1127	C
	ADMM15	467.1	C
	FT-100	252.5	C
2-Methylnaphthalene	DF-2	4750	A
	CA	3065	B
	ALS	737.3	C
	ADMM15	238.8	C
	FT-100	113.9	C
1-Methylnaphthalene	DF-2	3268	A
	CA	1713	B
	ALS	409.9	C
	ADMM15	111.1	C
	FT-100	65.72	C
2,6-Dimethylnaphthalene	DF-2	3462	A
	CA	722.3	B
	ALS	242.3	B
	ADMM15	48.81	B
	FT-100	44.71	B
Acenaphthylene	DF-2	324.8	A
	ALS	122.2	B
	CA	102.2	B
	ADMM15	46.44	B
	FT-100	45.21	B
Acenaphthene	DF-2	517.5	A
	CA	75.37	B
	ALS	37.61	B
	ADMM15	19.14	B
	FT-100	8.501	B

Table 19. Weighted Gaseous PAH ANOVA Summary for LPP Only Conditions (contd)			
	LPP Only - Weighted Modes 5,6,10,11		
Response	Fuel	LS Means[1]	Significant Fuel Groups[2]
Fluorene	DF-2	931.9	A
	CA	108.6	B
	ALS	45.82	B
	FT-100	15.91	B
	ADMM15	15.54	B
Phenanthrene	DF-2	1586	A
	CA	199.5	B
	ALS	120.1	B
	FT-100	40.99	B
	ADMM15	35.57	B
Anthracene	DF-2	51.59	A
	CA	9.235	B
	ALS	5.364	B
	ADMM15	1.954	B
	FT-100	1.676	B
Fluoranthene	DF-2	13.22	A
	CA	3.921	B
	ALS	3.295	B
	FT-100	1.870	B
	ADMM15	1.454	B
Pyrene	DF-2	17.54	A
	CA	3.137	B
	ALS	2.838	B
	FT-100	1.406	B
	ADMM15	1.142	B
[1]Fuels listed from highest to lowest least squares mean			
[2]Letters designate groups of fuel means within which there are no statistically significant differences			
NS = no statistically significant differences in the mean response at the 5% level of significance			

5.4.1   Naphthalene

Statistically significant differences were noted in the average weighted gas phase naphthalene among the fuels. The gas phase PAH naphthalene mass emissions are shown in Figure 33 along with the statistical groupings. There are three distinct fuel groupings with respect to the average weighted naphthalene. FT-100, ADMM15, and ALS fuels are not significantly different from one another, but they are significantly different from the other two fuels. The DF-2 and CA fuels are significantly different from one another and the remaining three fuels.

Figure 33. Test Fuel Weighted Average Gaseous Phase Naphthalene Mass Emissions (μg/kWh)

5.4.2   2-Methylnaphthalene

Statistically significant differences in the average weighted 2-methylnaphthalene among the fuels are shown in Figure 34. There are three distinct fuel groupings with respect to the average weighted 2-methylnaphthalene. FT-100, ADMM15, and ALS fuels are not significantly different from one another, but they are significantly different from the other two fuels. The DF-2 and CA fuels are significantly different from one another and the remaining three fuels.

5.4.3   1-Methylnaphthalene

The ANOVA for 1-methylnaphthalene showed statistically significant differences in the average weighted 1-methylnapthalene among the fuels. There are three distinct fuel groupings with respect to the average weighted 1-methylnaphthalene as shown in Figure 35. FT-100, ADMM15, and ALS fuels are not significantly different from one another, but they are significantly different from the other two fuels. The DF-2 and CA fuels are significantly different from one another and the remaining three fuels.

Gaseous 2-Methylnaphthalene Emissions

Figure 34. Test Fuel Weighted Average Gaseous Phase 2-Methylnaphthalene Mass Emissions (µg/kWh)

Gaseous 1-Methylnaphthalene Emissions

Figure 35. Test Fuel Weighted Average Gaseous Phase 1-Methylnaphthalene Mass Emissions (µg/kWh)

5.4.4   2,6-Dimethylnaphthalene

Statistically significant differences in the average weighted 2,6-dimethylnaphthalene are shown in Figure 36. The average weighted 2,6-dimethylnaphthalene for the DF-2 fuel is significantly different than the other four fuels. The average weighted 2,6-dimethylnaphthalene among the FT-100, ADMM15, ALS, and CA fuels are not significantly different from one another.

5.4.5   Acenaphthylene

Figure 37 shows the average weighted acenaphthylene for the DF-2 fuel is significantly different than the other four fuels. The average weighted acenaphthylene among the FT-100, ADMM15, CA, and ALS fuels are not significantly different from one another.

5.4.6   Acenaphthene

The average weighted acenaphthene for the DF-2 fuel is significantly different than the other four fuels. The average weighted acenaphthene among the FT-100, ADMM15, ALS, and CA fuels are not significantly different from one another. The relative response is shown in Figure 38 for the gas phase PAH acenaphthene.

5.4.7   Fluorene

The statistically significant differences in the average weighted fluorene among the fuels is shown in Figure 39. The average weighted fluorene for the DF-2 fuel is significantly different than the other four fuels. The average weighted fluorene among the ADMM15, FT-100, ALS, and CA fuels are not significantly different from one another.

5.4.8   Phenanthrene

Shown in Figure 40, the average weighted phenanthrene for the DF-2 fuel is significantly different than the other four fuels. The average weighted phenanthrene among the ADMM15, FT-100, ALS, and CA fuels are not significantly different from one another.

Gaseous 2,6-Dimethylnaphthalene Emissions

Figure 36. Test Fuel Weighted Average Gaseous Phase 2,6-Dimethylnaphthalene Mass Emissions (µg/kWh)

Gaseous Acenaphthylene Emissions

Figure 37. Test Fuel Weighted Average Gaseous Phase Acenaphthylene Mass Emissions (µg/kWh)

Gaseous Acenaphthene Emissions

Figure 38. Test Fuel Weighted Average Gaseous Phase Acenaphthene Mass Emissions (µg/kWh)

Gaseous Fluorene Emissions

Figure 39. Test Fuel Weighted Average Gaseous Phase Fluorene Mass Emissions (µg/kWh)

Figure 40. Test Fuel Weighted Average Gaseous Phase Phenanthrene Mass Emissions (µg/kWh)

5.4.9   Anthracene

The average weighted anthracene for the DF-2 fuel is significantly different than the other four fuels, Figure 41. The average weighted anthracene among the FT-100, ADMM15, ALS, and CA fuels are not significantly different from one another.

5.4.10   Fluoranthene

From Figure 42 the average weighted fluoranthene for the DF-2 fuel is seen to be significantly different than the other four fuels. The average weighted fluoranthene among the ADMM15, FT-100, ALS, and CA fuels are not significantly different from one another.

5.4.11   Pyrene

The average weighted pyrene for the DF-2 fuel is significantly different than the other four fuels. As seen in Figure 43, the average weighted pyrene for the ADMM15, FT-100, ALS, and CA fuels are not significantly different from one another.

Gaseous Anthracene Emissions

Figure 41. Test Fuel Weighted Average Gaseous Phase Anthracene Mass Emissions (μg/kWh)

Gaseous Fluoranthene Emissions

Figure 42. Test Fuel Weighted Average Gaseous Phase Fluoranthene Mass Emissions (μg/kWh)

Figure 43. Test Fuel Weighted Average Gaseous Phase Pyrene Mass Emissions (µg/kWh)

6.0 FUEL IMPACT ON EMISSIONS-MODAL LPP TESTS

Fuel comparisons were made for the modal brake specific exhaust emissions with the engine operated under LPP control with the pilot fuel injection turned off. The multifactor ANOVA included fuel effects, mode effects, and fuel/mode interaction effects. The ANOVA tables for the modal LPP Operation (modes 5,6,10,11) can be found in Appendix E.

6.1 Fuel Impact on Regulated Brake Specific Mass Emissions

Several statistically significant trends, at 95% confidence, were apparent from an ANOVA of the modal brake specific emissions data. Table 20 summarizes the general rank order for the regulated modal mass emissions during LPP engine operation with pilot fuel injection turned off. The table displays the fuels rank from highest response to lowest response for the least-square means of the modal analysis. Statistically significant similar fuel groupings are also shown for each emission response in Table 20.

Table 20. Mass Emissions for Modal LPP Operation Mass Emissions ANOVA Summary for LPP Mode Analysis							
Response	**Fuel**	**LS Means**[1]	**Significant Fuel Groups**[2]	**Mode**	**LS Means**[1]	**Significant Mode Groups**[2]	**Significant Interaction**
BSPM	DF-2	0.2774	A	10	0.2522	A	Fuel*Mode
	CA	0.2471	AB	6	0.2273	A	
	ALS	0.2177	B	11	0.1809	B	
	ADMM15	0.1454	C	5	0.1614	B	
	FT-100	0.1397	C				
$BSNO_X$	DF-2	5.901	A	5	9.658	A	Fuel*Mode
	ADMM15	5.696	A	6	5.560	B	
	FT-100	5.241	B	10	3.556	C	
	CA	5.057	B	11	2.780	D	
	ALS	5.047	B				
BSHC	DF-2	1.031	A	10	1.185	A	Fuel*Mode
	CA	0.8661	B	11	0.9348	B	
	ALS	0.5625	C	6	0.3463	C	
	ADMM15	0.5191	C	5	0.1589	D	
	FT-100	0.3026	D				
BSCO	DF-2	3.616	A	10	5.052	A	Fuel*Mode
	CA	3.467	A	11	3.656	B	
	ALS	2.273	B	6	1.229	C	
	ADMM15	2.218	B	5	0.4263	D	
	FT-100	1.381	C				
$BSCO_2$	ADMM15	884.1	A	10	1056	A	NS
	DF-2	874.4	A	11	894.1	B	
	CA	844.7	B	6	779.3	C	
	ALS	844.0	B	5	678.4	D	
	FT-100	812.4	C				
BSSOF	DF-2	0.2091	A	10	0.2147	A	Fuel*Mode
	CA	0.1906	A	11	0.1377	B	
	ALS	0.1510	B	6	0.1343	B	
	ADMM15	0.1251	B	5	0.1189	B	
	FT-100	0.0812	C				

[1]Factor levels listed from highest to lowest least squares mean

[2]Letters designate groups of factor means within which there are no statistically significant differences

NS = no statistically significant differences in the mean response at the 5% level of significance

Table 20 includes the modal test severity for each regulated emission. Included are the least-square means from multifactor ANOVA, along with the statistically significant groupings for the average mass emissions at each test mode. The general trend for mode severity depends on the species of interest. Fuel*Mode interactions are indicated in Table 20 for each toxic air pollutant.

The discussions to follow are summaries of the multifactor ANOVA performed for each emission response for the modal operation, and refer to the results in Table 20.

6.1.1   Fuel Impact on Particulate

Statistically significant differences were apparent in the average total particulates among the fuels, modes, and fuel*mode interaction. The average particulate at fuels FT-100 and ADMM15 are not significantly different from one another, but are different than the other 3 fuels. The average particulate at Fuel ALS is significantly different than Fuel DF-2. The CA fuel is not significantly different than either the ALS or DF-2 fuel.

The average particulate at Modes 5 and 11 are not significantly different from one another. Average particulate at Modes 6 and 10 are not significantly different from one another. Average particulate at modes 5 and 11 are significantly different than modes 6 and 10.

The CA and DF-2 fuels have significantly different average total particulate at Modes 5 and 11 than at modes 6 and 10. All other fuels do not demonstrate significant differences in the average total particulate among the four modes.

6.1.2   Fuel Impact on NOx

Statistically significant differences were apparent in the average $BSNO_X$ among the fuels, modes, and fuel*mode interaction. There are two distinct fuel groupings with respect to the average $BSNO_X$. ADMM15 and DF-2 fuels are not significantly different from one another, but are different from the average $BSNO_X$ for the ALS, CA, and FT-100 fuels. The ALS, CA, and FT-100 fuels are not significantly different from one another.

All four modes are significantly different from one another with respect to the average $BSNO_X$.

While the ADMM15, ALS, CA, and FT-100 fuels all have significant differences in the average $BSNO_X$ between mode 6 and modes 10 and 11, the DF-2 fuel does not demonstrate this difference. The average $BSNO_X$ among modes 6, 10, and 11 for the DF-2 are not significantly different from one another.

6.1.3   Fuel Impact on HC

Statistically significant differences were apparent in the average BSHC among the fuels, modes, and the fuel*mode interaction. There are four distinct fuel groupings with respect to the average BSHC. FT-100, CA, and DF-2 fuels are all significantly different from one another. Also, fuels ADMM15 and ALS are not significantly different from one another, but they are both significantly different from the other three fuels.

All four modes are significantly different from one another with respect to the average BSHC.

The ALS, CA, DF-2 fuels have significantly different average BSHC at modes 10 and 11 than at modes 5 and 6. All other fuels do not demonstrate significant differences in the average BSHC among the four modes.

6.1.4   Fuel Impact on CO

Statistically significant differences were noted in the average BSCO among the fuels, modes, and fuel*mode interaction. There are three distinct fuel groupings with respect to the average BSCO. FT-100 is significantly different from the other four fuels. ADMM15 and ALS are not significantly different from one another. Fuels CA and DF-2 are not significantly different from one another, but are significantly different from the ADMM15 and ALS fuels.

All four modes are significantly different from one another with respect to the average BSCO.

The CA, DF-2, and FT-100 fuels have significantly different average BSCO at modes 10 and 11 than at modes 5 and 6.

6.1.5   Fuel Impact on CO_2

Statistically significant differences were apparent in the average $BSCO_2$ among the fuels and the modes. There are three distinct fuel groupings with respect to the average $BSCO_2$. FT-100 is significantly different from the other four fuels. ADMM15 and DF-2 fuels are not significantly different from one another. Fuels ALS and CA are not significantly different from one another, but are significantly different from the ADMM15 and DF-2 fuels.

All four modes are significantly different from one another with respect to the average $BSCO_2$.

No significant differences were observed among the fuel and mode combinations with respect to the average $BSCO_2$.

6.1.6   Fuel Impact on SOF of PM

Statistically significant differences were noted in the average BSSOF among the fuels, modes, and fuel*mode interaction. There are three distinct fuel groupings with respect to the average BSSOF. The FT-100 fuel is significantly different from the remaining four fuels. The DF-2 and CA fuels are not significantly different from one another, but are different from the other three fuels. Also, the ALS and ADMM15 fuels are not significantly different from one another, but are different from the other three fuels.

The average BSSOF for mode 10 is significantly different from the remaining three modes. The average BSSOF for modes 5, 6, and 11 are not significantly different from one another.

The trend in the average BSSOF across the fuels is different for mode 10 at the CA and DF-2 fuels. The trends in the average BSSOF across the fuels for modes 5, 6, and 11 do not appear to be different.

6.2   Fuel Impact on Four Clean Air Act Toxic Air Pollutants

Table 21 is the ranking of the test fuels from multifactor ANOVA for the four EPA Clean Air Act (CAA) toxic air pollutants. For the EPA toxic air pollutants, ADMM15 and FT-100 were statistically similar emitting fuels, and always in the lowest grouping for the modal average for LPP operation with pilot fuel injection turned off.

Table 21 includes the modal test severity for each CAA toxic air pollutant. Included are the least-square means from multifactor ANOVA, along with the statistically significant groupings for the average mass emissions at each test mode. The general trends were for mode 10 and mode 11 to have the highest toxic emissions, while mode 5 and mode 6 had the statistically lowest toxic emissions. Fuel*Mode interactions are indicated in Table 21 for each toxic air pollutant.

The discussions to follow are summaries of the multifactor ANOVA performed for each emission response for the modal operation, and refer to the results in Table 21. The ANOVA tables for the modal LPP Operation (modes 5,6,10,11) can be found in Appendix E.

6.2.1   Benzene

Statistically significant differences were apparent in the average benzene among the fuels, modes, and fuel*mode interaction. The average benzene for the ADMM15 and FT-100 fuels are not significantly different from one another, but are significantly different from the remaining three fuels. The average benzene for the ALS fuel is significantly different than the average benzene for the CA fuel.

There are three distinct mode groupings with respect to the average benzene. Modes 10 and 11 are not significantly different from one another, but are significantly different than the other two modes. Modes 5 and 6 are significantly different from one another and the other two modes.

The ALS, CA, and DF-2 fuels have significantly different average benzene at modes 10 and 11 than at modes 5 and 6. All other fuels do not demonstrate significant differences in the average Benzene among the four modes.

6.2.2 1,3-Butadiene

Statistically significant differences exist in the average 1,3 butadiene among the fuels, modes, and fuel*mode interaction. There are three distinct fuel groupings with respect to the average 1,3-butadiene. The average 1,3-butadiene for the FT-100 fuel is significantly different than the remaining four fuels. The ADMM15 and ALS fuels are not significantly different from one another, but are significantly different than the other three fuels. Also, the DF-2 and CA fuels are not significantly different from one another, but are significantly different from the other three fuels.

Table 21. Clean Air Act Toxic Air Pollutant Mass Emissions (mg/k Wh) ANOVA Summary for LPP Mode Analysis							
Response	Five Fuels, Modes 5, 6, 10 and 11						
	Fuel	LS Means[1]	Significant Fuel Groups[2]	Mode	LS Means[1]	Significant Mode Groups[2]	Significant Interaction
Benzene	CA	5.0951	A	10	5.8422	A	Fuel*Mode
	DF-2	4.3477	AB	11	5.0279	A	
	ALS	3.4599	B	6	1.7100	B	
	FT-100	1.8114	C	5	0.3923	C	
	ADMM15	1.5014	C				
1,3-Butadiene	CA	4.2291	A	10	6.3958	A	Fuel*Mode
	DF-2	3.9996	A	11	4.8603	B	
	ALS	3.1861	B	6	1.0916	C	
	ADMM15	2.7986	B	5	0.5601	C	
	FT-100	1.9214	C				
Formaldehyde	DF-2	343.9870	A	10	476.8070	A	Fuel*Mode
	CA	271.7800	AB	11	339.8470	B	
	ALS	258.6100	B	6	107.7750	C	
	ADMM15	195.5480	BC	5	59.7879	C	
	FT-100	160.3470	C				
Acetaldehyde	DF-2	128.3360	A	10	175.9990	A	Fuel*Mode
	CA	105.5910	A	11	127.3040	B	
	ALS	104.8070	A	6	43.4665	C	
	ADMM15	69.0340	B	5	26.3907	C	
	FT-100	58.6822	B				

[1]Factor levels listed from highest to lowest least squares mean

[2]Letters designate groups of factor means within which there are no statistically significant differences

NS = no statistically significant differences in the mean response at the 5% level of significance

There are three distinct mode groupings with respect to the average 1,3-butadiene. Modes 10 and 11 are significantly different from one another and the remaining two modes. Modes 5 and 6 are not significantly different from one another but are significantly different from the other two modes.

The DF-2 and CA fuels have significantly different average 1,3-butadiene at mode 10 than at the remaining three modes. All other fuels do not demonstrate significant differences in the average 1,3-butadiene among the four modes.

6.2.3   Formaldehyde

Statistically significant differences were noted in the average formaldehyde among the fuels, modes, and fuel*mode interaction. The average formaldehyde for the DF-2 fuel is not significantly different than the average formaldehyde for the CA fuel, but it is significantly different than the ADMM15, FT-100, and ALS fuels. The average formaldehyde at the FT-100 fuel is not significantly different than the ADMM15 fuel, but it is significantly different than the ALS, CA, and DF-2 fuels.

There are three distinct mode groupings with respect to the average formaldehyde. Modes 10 and 11 are significantly different from one another and the remaining two modes. Modes 5 and 6 are not significantly different from one another but are significantly different from the other two modes.

The ALS and DF-2 fuels have significantly different average formaldehyde at modes 10 and 11 than at the remaining two modes. All other fuels do not demonstrate this difference. However, the average formaldehyde for the CA fuel at mode 10 is significantly different than the other three modes.

6.2.4   Acetaldehyde

Statistically significant differences were apparent in the average acetaldehyde among the fuels, modes, and fuel*mode interaction. The average acetaldehyde for the FT-100 and ADMM15 fuels are not significantly different from one another. The average acetaldehyde for the ALS, CA, and

DF-2 fuels are not significantly different from one another, but are significantly different from the FT-100 and ADMM15 fuels.

There are three distinct mode groupings with respect to the average acetaldehyde. Modes 10 and 11 are significantly different from one another and the remaining two modes. Modes 5 and 6 are not significantly different from one another but are significantly different from the other two modes.

The ALS and DF-2 fuels have significantly different average acetaldehyde at modes 10 and 11 than at the remaining two modes. All other fuels do not demonstrate this difference. However, the average acetaldehyde for the CA fuel at mode 10 is significantly different than the other three modes.

6.3   Fuel Impact on Particulate Soluble Extract PAH Species

The fuel rankings for the particulate bound soluble phase PAH compounds are shown in Table 22. Due to non-detects, four PAH compounds were reanalyzed with a gas GC-high resolution mass spectrometer. The four compounds reanalyzed were benzo[a]pyrene, indeno(123-cd)pyrene, dibenzo(a,h)anthracene, and benzo(ghi)perylene. For the majority of PAH compounds DF-2 fuel was statistically different from the other test fuels. The ADMM15 and FT-100 fuels were in the statistically equivalent (95% confidence) lowest grouping for particulate bound PAH compounds.

The soluble extract PAH emissions rank the test modal severity as shown in Table 22. Included in Table 22 are the least-square means from multifactor ANOVA, along with the statistically significant groupings for the average mass emissions at each test mode. The general trends were for mode 10 to having the highest soluble extract PAH emissions, and mode 5 having the statistically lowest PAH emissions. Fuel*Mode interactions are indicated in Table 22 for each gaseous PAH species.

The discussions to follow are summaries of the multifactor ANOVA performed for each emission response for the modal operation. The ANOVA tables for the modal LPP Operation (modes 5,6,10,11) can be found in Appendix E.

Table 22. Soluble PAH Mass Emissions (µg/kWh) ANOVA Summary for LPP Mode Analysis							
	Five Fuels, Modes 5, 6, 10 and 11						
Response	Fuel	LS Means[1]	Significant Fuel Groups[2]	Mode	LS Means[1]	Significant Mode Groups[2]	Significant Interaction
Naphthalene	CA	45.50	A	10	44.80	A	NS
	DF-2	43.35	A	6	38.08	AB	
	FT-100	36.76	AB	11	34.32	AB	
	ADMM15	28.41	B	5	27.65	B	
	ALS	27.04	B				
Acenaphthylene	CA	0.9153	A	10	0.7630	NS	NS
	DF-2	0.7622	AB	6	0.6689		
	ALS	0.5971	AB	11	0.6559		
	FT-100	0.5449	B	5	0.5493		
	ADMM15	0.4768	B				
Acenaphthene	DF-2	6.393	NS	10	5.638	NS	NS
	CA	5.239		6	5.128		
	ADMM15	4.343		11	4.441		
	FT-100	4.144		5	3.801		
	ALS	3.643					
Fluorene	DF-2	11.35	A	10	9.249	NS	NS
	CA	9.128	AB	11	8.197		
	ALS	7.275	AB	6	7.834		
	ADMM15	7.043	AB	5	7.172		
	FT-100	5.769	B				
Phenanthrene	DF-2	88.83	A	6	64.4332	A	NS
	CA	74.61	A	10	61.7122	A	
	ALS	38.36	B	11	54.5710	AB	
	FT-100	38.16	B	5	34.0794	B	
	ADMM15	28.54	B				
Anthracene	CA	4.246	A	10	3.3277	A	NS
	DF-2	3.629	AB	6	3.1338	AB	
	FT-100	2.661	B	11	2.7156	AB	
	ADMM15	2.299	BC	5	2.0872	B	
	ALS	1.246	C				

Table 22. Soluble PAH Mass Emissions (μg/kWh) ANOVA Summary for LPP Mode Analysis (contd)							
Five Fuels, Modes 5, 6, 10 and 11							
Response	**Fuel**	**LS Means[1]**	**Significant Fuel Groups[2]**	**Mode**	**LS Means[1]**	**Significant Mode Groups[2]**	**Significant Interaction**
Fluoranthene	DF-2	40.77	A	10	25.8812	A	Fuel*Mode
	CA	20.35	B	6	24.5815	A	
	ALS	19.29	B	11	20.6494	AB	
	FT-100	14.82	B	5	12.6339	B	
	ADMM15	9.455	B				
Pyrene	DF-2	63.29	A	10	31.1162	A	Fuel*Mode
	ALS	19.18	B	11	28.2235	A	
	CA	16.05	B	6	24.5073	AB	
	FT-100	11.87	B	5	11.6778	B	
	ADMM15	9.020	B				
Benzo[a]anthracene	DF-2	1.995	A	10	1.1663	A	Fuel*Mode
	CA	1.163	B	11	0.8571	AB	
	ALS	0.7054	C	6	0.7489	B	
	FT-100	0.2040	D	5	0.6127	B	
	ADMM15	0.1636	D				
Chrysene	DF-2	6.774	A	10	3.2797	NS	NS
	CA	2.425	B	6	2.5967		
	ALS	2.250	BC	11	2.4567		
	FT-100	0.8623	BC	5	2.1010		
	ADMM15	0.7316	C				
Benzo[b]fluoranthene	CA	1.715	A	5	1.3636	NS	NS
	ALS	1.496	A	10	1.1534		
	DF-2	1.377	A	6	1.0215		
	ADMM15	0.4814	B	11	0.7956		
	FT-100	0.3485	B				
Benzo[k]fluoranthene	DF-2	2.226	A	10	1.4836	A	NS
	CA	1.394	AB	5	1.1171	AB	
	ALS	0.7976	BC	6	1.0296	AB	
	ADMM15	0.5213	BC	11	0.6652	B	
	FT-100	0.4298	C				

67

Table 22. Soluble PAH Mass Emissions (µg/kWh) ANOVA Summary for LPP Mode Analysis (contd)							
Five Fuels, Modes 5, 6, 10 and 11							
Response	**Fuel**	**LS Means[1]**	**Significant Fuel Groups[2]**	**Mode**	**LS Means[1]**	**Significant Mode Groups[2]**	**Significant Interaction**
Benzo[e]pyrene	CA	1.106	A	10	0.7553	NS	NS
	DF-2	0.9574	A	5	0.6853		
	ALS	0.5997	AB	6	0.6049		
	FT-100	0.2621	B	11	0.4718		
	ADMM15	0.2215	B				
Benzo[a]pyrene	ALS	0.3761	A	10	0.3038	A	Fuel*Mode
	CA	0.3388	A	11	0.1864	B	
	DF-2	0.1713	B	6	0.1703	B	
	FT-100	0.0598	BC	5	0.1404	B	
	ADMM15	0.0550	C				
Indeno(1,2,3-cd)pyrene	DF-2	0.3111	A	10	0.2457	A	Fuel*Mode
	ADMM15	0.0651	B	11	0.1649	AB	
	FT-100	0.0624	B	6	0.0947	B	
				5	0.0794	B	
Dibenzo[a,h]anthracene	DF-2	0.0818	A	10	0.0546	A	NS
	FT-100	0.0156	B	11	0.0413	AB	
	ADMM15	0.0122	B	6	0.0302	AB	
				5	0.0200	B	
Benzo[ghi]perylene	CA	0.5739	A	10	0.5886	A	Fuel*Mode
	DF-2	0.4977	A	11	0.4190	B	
	ADMM15	0.1747	B	6	0.2063	C	
	FT-100	0.1475	B	5	0.1799	C	

[1]Factor levels listed from highest to lowest least squares mean

[2]Letters designate groups of factor means within which there are no statistically significant differences

NS = no statistically significant differences in the mean response at the 5% level of significance

6.3.1   Naphthalene

Statistically significant differences were apparent in the average naphthalene among the fuels and the modes. The average naphthalene for the CA and DF-2 fuels are significantly different from the ADMM15 and ALS fuels, but not significantly different from one another. The average naphthalene for the ADMM15 and ALS fuels are not significantly different from one another.

The average naphthalene for mode 10 is significantly different from mode 5.

There is no significant interaction in the average naphthalene among the fuel and mode combinations.

6.3.2   Acenaphthylene

Statistically significant differences exist in the average acenaphthylene among the fuels. The average acenaphthylene for the CA fuel is significantly different than the FT-100 and ADMM15 fuels.

No statistically significant differences exist in the average acenaphthylene among the modes.

There is no significant interaction in the average acenaphthylene among the fuel and mode combinations.

6.3.3   Acenaphthene

No statistically significant differences were apparent in the average acenaphthene among the fuels, modes or interaction. No statistically significant differences exist in the average acenaphthene among the fuels.

No statistically significant differences were apparent in the average acenaphthene among the modes.

There is no significant interaction in the average acenaphthene among the fuel and mode combinations.

6.3.4 Fluorene

Statistically significant differences were noted in the average fluorene among the fuels. The average fluorene for the DF-2 fuel is significantly different from the FT-100 fuel.

There is no significant difference in the average fluorene among the modes.

There is no significant interaction in the average fluorene among the fuel and mode combinations.

6.3.5 Phenanthrene

Statistically significant differences were apparent in the average phenanthrene among the fuels and modes. There are two distinct fuel groupings with respect to the average phenanthrene. The average phenanthrene for the DF-2 and CA fuels are not significantly different from one another, but are significantly different from the remaining three fuels. The average phenanthrene for the ALS, FT-100, and ADMM15 fuels are not significantly different from one another.

The average phenanthrene for mode 5 is significantly different from modes 6 and 10.

There is no significant interaction in the average phenanthrene among the fuel and mode combinations.

6.3.6 Anthracene

Statistically significant differences were apparent in the average anthracene among the fuels and modes. The average anthracene for the CA fuel is significantly different from the FT-100, ADMM15, and ALS fuels. The average anthracene for the ALS fuel is significantly different than the DF-2 and FT-100 fuels.

The average anthracene for mode 10 is significantly different than mode 5.

There is no significant interaction in the average anthracene among the fuel and mode combinations.

6.3.7 Fluoranthene

Statistically significant differences exist in the average fluoranthene among the fuels, modes and fuel*mode interaction. The average fluoranthene for the DF-2 fuel is significantly different than the remaining four fuels. The average fluoranthene for the ADMM15, ALS, CA, and FT-100 fuels are not significantly different from one another.

The average fluoranthene for modes 6 and 10 are significantly different than mode 5, but not significantly different from one another.

The trend in the average fluoranthene across the modes for the DF-2 fuel is significantly different than the trends for the remaining four fuels. The average fluoranthene for the DF-2 fuel at modes 10 and 11 are significantly different than the other four fuels.

6.3.8 Pyrene

Statistically significant differences were noted in the average pyrene among the fuels, modes, and fuel*mode interaction. The average pyrene for the DF-2 fuel is significantly different than the remaining four fuels. The average pyrene for the ALS, CA, FT-100, and ADMM15 fuels are not significantly different from one another.

The average pyrene for modes 10 and 11 are significantly different than mode 5. The average pyrene for mode 6 is not significantly different than the remaining three modes.

The trend in the average pyrene across the modes for the DF-2 fuel is significantly different than the trends for the remaining four fuels. The average pyrene at modes 10 and 11 for the DF-2 fuel are significantly different than the other four fuels.

6.3.9 Benzo[a]anthracene

Statistically significant differences were apparent in the average benzo[a]anthracene among the fuels, modes, and fuel*mode interaction. There are four distinct fuel groupings with respect to the average benzo[a]anthracene. Fuels DF-2, CA, and ALS are significantly different from one another and the remaining two fuels. The FT-100 and ADMM15 fuels are not significantly

different from one another, but are significantly different than the other three fuels.

The average benzo[a]anthracene for mode 10 is significantly different than modes 5 and 6. The average benzo[a]anthracene for mode 11 is not significantly different than the remaining three modes.

The trend in the average benzo[a]anthracene across the modes for the DF-2 fuel is significantly different than the trends for the remaining four fuels. The average benzo[a]anthracene at modes 10 and 11 for the DF-2 fuel are significantly different than the other four fuels.

6.3.10   Chrysene

Statistically significant differences exist in the average chrysene among the fuels. The average chrysene for the DF-2 fuel is significantly different than the remaining four fuels. Also, the average chrysene for the CA fuel is significantly different than the ADMM15 fuel.

There is no significant difference in the average chrysene among the modes.

There is no significant interaction in the average chrysene among the fuel and mode combinations.

6.3.11   Benzo[b]fluoranthene

Statistically significant differences were apparent in the average benzo[b]fluoranthene among the fuels. There are two distinct fuel groupings with respect to the average benzo[b]fluoranthene. The CA, ALS, and DF-2 fuels are not significantly different from one another, but are different from the remaining two fuels. The ADMM15 and FT-100 fuels are not significantly different from one another.

There is not any significant difference in the average benzo[b]fluoranthene among the modes.

There is not any significant interaction in the average benzo[b]fluoranthene among the fuel and mode combinations.

6.3.12   Benzo[k]fluoranthene

Statistically significant differences were noted in the average benzo[k]fluoranthene among the fuels and modes. The average benzo[k]fluoranthene for the DF-2 fuel is significantly different than the ADMM15, ALS, and FT-100 fuels.   The average benzo[k]fluoranthene for the ADMM15, ALS, and FT-100 fuels are not significantly different from one another. Also, the average benzo[k]fluoranthene for the CA fuel is significantly different than the FT-100 fuel.

The average benzo[k]fluoranthene for mode 10 is significantly different than mode 11.

There is no significant interaction in the average benzo[k]fluoranthene among the fuel and mode combinations.

6.3.13   Benzo[e]pyrene

Statistically significant differences were apparent in the average benzo[e]pyrene among the fuels. The average benzo[e]pyrene for the CA and DF-2 fuels are significantly different than the FT-100 and ADMM15 fuels, but not significantly different from one another. Also, the average benzo[e]pyrene for the ALS fuel was not significantly different from the remaining four fuels.

There is no significant difference in the average benzo[e]pyrene among the modes.

There is no significant interaction in the average benzo[e]pyrene among the fuel and mode combinations.

6.3.14   Benzo[a]pyrene

Due to non-detects for benzo[a]pyrene using low-resolution GC/MS, the extracts were reanalyzed utilizing a high-resolution mass spectrometer. The selection criteria for reanalysis was any non-idle modal experiment that did not have a benzo[a]pyrene result. The ALS fuel had benzo[a]pyrene detects with the low resolution instrument, so the majority of the ALS extracts were not reanalyzed for the higher molecular weight PAH species.

Statistically significant differences exist in the average benzo[a]pyrene among the fuels, modes, and fuel*mode interaction. The average benzo[a]pyrene for the CA and ALS fuels are significantly different from the remaining three fuels but not different from one another. The average benzo[a]pyrene for the ADMM15 fuel is significantly different from the DF-2 fuel, but not significantly different from the FT-100 fuel.

The average benzo[a]pyrene for mode 10 is significantly different from the remaining three modes.

The trend in the average benzo[a]pyrene across the modes for the ALS fuel is significantly different than the trends for the remaining four fuels. Also, the average benzo[a]pyrene for the CA fuel is significantly different than the other fuels at mode 6.

6.3.15 Indeno(1,2,3-cd)pyrene

High-resolution mass spectral analysis of the extracts were also performed for the PAH indeno(1,2,3-cd)pyrene. Sufficient non-detects existed for CA and ALS fuels such that the CA and ALS fuels were not included in the multifactor ANOVA for indeno(1,2,3-cd)pyrene.

Statistically significant differences were apparent in the average indeno(1,2,3-cd)pyrene among the fuels, modes, and fuel*mode interaction. The average indeno(1,2,3-cd)pyrene for the DF-2 fuel is significantly different from the remaining two fuels. The ADMM15 and FT-100 fuels are not significantly different from one another with respect to the average indeno(1,2,3-cd)pyrene.

The average indeno(1,2,3-cd)pyrene for mode 10 is significantly different than modes 5 and 6. Mode 11 is not significantly different from the remaining three modes with respect to the average indeno(1,2,3-cd)pyrene.

The trend in the average indeno(1,2,3-cd)pyrene across the modes for the DF-2 fuel is significantly different than the trends in the remaining two fuels. The average indeno(1,2,3-cd)pyrene at modes 10 and 11 for the DF-2 fuel are significantly different than the ADMM15 and FT-100 fuels.

6.3.16   Dibenzo[a,h]anthracene

Although high-resolution mass spectral analysis was attempted on this PAH species, sufficient non-detects existed for CA and ALS fuels such that the multifactor ANOVA for dibenzo[a,h]anthracene was not be performed for the CA and ALS fuels.

Statistically significant differences were noted in the average dibenzo[a,h]anthracene among the fuels and modes analyzed. The average dibenzo[a,h]anthracene for the DF-2 fuel is significantly different from the remaining two fuels. The ADMM15 and FT-100 fuels are not significantly different from one another.

The average dibenzo[a,h]anthracene for mode 10 is significantly different from mode 5. Modes 6 and 11 are not significantly different from one another or the other two modes.

There is no significant interaction in the average dibenzo[a,h]anthracene among the fuel and mode combinations.

6.3.17   Benzo[ghi]perylene

High-resolution mass spectral analysis of the extracts were also performed for the PAH benzo[ghi]perylene except for several ALS fuel runs. Because sufficient non-detects existed for the ALS fuels, that ALS was not included in the multifactor ANOVA for benzo[ghi]perylene.

Statistically significant differences were apparent in the average benzo[ghi]perylene among the fuels, modes and fuel*mode interaction. There are two distinct fuel groupings with respect to the average benzo[ghi]perylene. The CA and DF-2 fuels are not significantly different from one another, but are different from the remaining two fuels. The ADMM15 and FT-100 fuels are not significantly different from one another.

There are three distinct mode groupings with respect to the average benzo[ghi]perylene. Modes 10 and 11 are significantly different from one another and the remaining two modes. Modes 5 and 6 are not significantly different from one another, but are significantly different than the other two modes.

The trend in the average benzo[ghi]perylene across the modes for the DF-2 and CA fuels is significantly different than the trends in the remaining two fuels. The average benzo[ghi]perylene at modes 10 and 11 for the DF-2 and CA fuels are significantly different than the ADMM15 and FT-100 fuels.

6.4   Fuel Impact on Gaseous PAH Species

The gas phase PAH emissions rank the test fuels in the general order shown in Table 23. Included in Table 23 are the least-square means from multifactor ANOVA, along with the statistically significant groupings for the modal average mass emissions. The general trends were for DF-2 to have the highest gas phase PAH emissions, while ADMM15 and FT-100 always had the statistically lowest PAH emissions. The ANOVA for gas phase PAH species indicated the oxygenated diesel fuel, ADMM15, was statistically equivalent to FT-100.

The gas phase PAH emissions rank the test modal severity as shown in Table 23. Included in Table 23 are the least-square means from multifactor ANOVA, along with the statistically significant groupings for the average mass emissions at each test mode. The general trends were for mode 10 and mode 11 to have the highest gas phase PAH emissions, while mode 5 and mode 6 had the statistically lowest PAH emissions. Fuel*Mode interactions are indicated in Table 23 for each gaseous PAH species.

The discussions to follow are summaries of the multifactor ANOVA performed for each emission response for the modal operation. The ANOVA tables for the modal LPP Operation (modes 5,6,10,11) can be found in Appendix D.

6.4.1   Naphthalene

Statistically significant differences were noted in the average naphthalene among the fuels, modes, and fuel*mode interaction. There are four distinct fuel groupings with respect to the average naphthalene. ALS, DF-2, and CA fuels are all significantly different from one another. Also, fuels ADMM15 and FT-100 are not significantly different from one another, but they are both significantly different from the other three fuels.

Table 23. Gaseous Phase PAH Mass Emissions (µ/kWh) ANOVA Summary for LPP Mode Analysis							
	Five Fuels, Modes 5, 6, 10 and 11						
Response	Fuel	LS Means[1]	Significant Fuel Groups[2]	Mode	LS Means[1]	Significant Mode Groups[2]	Significant Interaction
Naphthalene	CA	3881	A	10	2727	A	Fuel*Mode
	DF-2	2259	B	11	2191	B	
	ALS	950.0	C	6	883.5	C	
	ADMM15	352.7	D	5	323.1	D	
	FT-100	211.8	D				
2-Methylnaphthalene	DF-2	3291	A	10	2196	A	Fuel*Mode
	CA	2174	B	11	1949	A	
	ALS	646.6	C	6	694.0	B	
	ADMM15	183.3	C	5	282.9	B	
	FT-100	107.0	C				
1-Methylnaphthalene	DF-2	2257	A	10	1365	A	Fuel*Mode
	CA	1213	B	11	1229	A	
	ALS	363.9	C	6	421.1	B	
	ADMM15	86.50	C	5	170.7	B	
	FT-100	61.54	C				
2,6-Dimethylnaphthalene	DF-2	2402	A	10	1051	A	Fuel*Mode
	CA	522.1	B	11	1030	A	
	ALS	227.6	B	6	355.7	B	
	FT-100	43.52	B	5	152.3	B	
	ADMM15	41.35	B				
Acenaphthylene	DF-2	225.3	A	11	139.5	A	Fuel*Mode
	ALS	104.5	B	10	138.5	A	
	CA	82.82	B	6	82.40	AB	
	FT-100	40.01	B	5	30.83	B	
	ADMM15	36.39	B				
Acenaphthene	DF-2	358.3	A	11	158.7	A	Fuel*Mode
	CA	54.66	B	10	137.6	AB	
	ALS	32.11	B	6	54.50	BC	
	ADMM15	15.50	B	5	24.22	C	
	FT-100	8.100	B				

77

Table 23. Gaseous Phase PAH Mass Emissions (µ/kWh) ANOVA Summary for LPP Mode Analysis (contd)							
			Five Fuels, Modes 5, 6, 10 and 11				
Fluorene	DF-2	683.7	A	11	263.9	A	Fuel*Mode
	CA	83.73	B	10	220.7	AB	
	ALS	42.39	B	6	130.2	AB	
	FT-100	15.23	B	5	56.42	B	
	ADMM15	13.96	B				
Phenanthrene	DF-2	1343	A	10	424.0	NS	NS
	CA	179.9	B	11	412.7		
	ALS	139.7	B	6	342.6		
	FT-100	42.22	B	5	211.5		
	ADMM15	33.45	B				
Anthracene	DF-2	42.19	A	10	15.20	A	Fuel*Mode
	CA	8.300	B	11	14.41	AB	
	ALS	5.542	B	6	11.31	AB	
	ADMM15	1.770	B	5	6.635	B	
	FT-100	1.646	B				
Fluoranthene	DF-2	12.91	A	6	5.462	NS	NS
	CA	4.173	B	10	5.320		
	ALS	3.420	B	5	4.240		
	FT-100	1.972	B	11	4.201		
	ADMM15	1.550	B				
Pyrene	DF-2	16.84	A	6	5.853	NS	NS
	CA	3.323	B	10	5.518		
	ALS	3.008	B	11	4.894		
	FT-100	1.462	B	5	4.380		
	ADMM15	1.173	B				

[1]Factor levels listed from highest to lowest least squares mean

[2]Letters designate groups of factor means within which there are no statistically significant differences

NS = no statistically significant differences in the mean response at the 5% level of significance

All four modes are significantly different from one another with respect to the average naphthalene.

The CA and DF-2 fuels have significantly different average naphthalene at modes 10 and 11 than at modes 5 and 6. All other fuels do not demonstrate significant differences in the average naphthalene among the four modes.

6.4.2   2-Methylnaphthalene

Statistically significant differences were apparent in the average 2-methylnaphthalene among the fuels, modes, and fuel*mode interaction. Average 2-methylnaphthalene at Modes 5 and 6 are not significantly different from one another, but significantly different from modes 10 and 11. Modes 10 and 11 are not significantly different from one another with respect to the average 2-methylnaphthalene.

Average 2-methylnaphthalene for fuels FT-100, ADMM15, and ALS are not significantly different from one another. The average 2-methylnaphthalene for fuels CA and DF-2 are significantly different from one another.

Modes 10 and 11 have significantly different average 2-methylnaphthalene for the CA and DF-2 fuels. All other fuels do not demonstrate differences in the average 2-methylnaphthalene among the four modes.

6.4.3   1-Methylnaphthalene

Statistically significant differences exist in the average 1-methylnaphthalene among the fuels, modes and fuel*mode interaction. There were three distinct fuel groupings with respect to the average 1-methylnaphthalene. CA and DF-2 fuels were significantly different from one another and the other three fuels. ADMM15, ALS, and FT-100 fuels were not significantly different from one another.

Average 1-methylnaphthalene at modes 5 and 6 are not significantly different from one another. Average 1-methylnaphthalene at modes 10 and 11 are not significantly different from one another, but are significantly different from modes 5 and 6.

The CA and DF-2 fuels have significantly different average 1-methylnaphthalene at modes 10 and 11 than at modes 5 and 6. All other fuels do not demonstrate significant differences in the average 1-methylnaphthalene among the four modes.

6.4.4   2,6-Dimethylnaphthalene

Statistically significant differences were noted in the average 2,6-Dimethylnaphthalene among the fuels, modes, and fuel*mode interaction. The average 2,6-dimethylnaphthalene for the DF-2 fuel is significantly different than the other four fuels. The average 2,6-dimethylnaphthalene among the ADMM15, ALS, CA, and FT-100 fuels are not significantly different from one another.

Average 2,6-dimethylnaphthalene at modes 5 and 6 are not significantly different from one another. Average 2,6-dimethylnaphthalene at modes 10 and 11 are not significantly different from one another, but are significantly different than modes 5 and 6.

The DF-2 fuel has significantly different average 2,6-dimethylnaphthalene at modes 10 and 11 than at modes 5 and 6. All other fuels do not demonstrate significant differences in the average 2,6-dimethylnaphthalene among the four modes.

6.4.5   Acenaphthylene

Statistically significant differences were apparent in the average acenaphthylene among the fuels, modes, and fuel*mode interaction. Average acenaphthylene is significantly different at fuel DF-2 compared to the other four fuels. Average acenaphthylene at fuels ADMM15, ALS, CA, and FT-100 are not significantly different from one another.

Average acenaphthylene at Mode 5 is significantly different from modes 10 and 11.

Modes 10 and 11 have significantly different average acenaphthylene for the DF-2 fuel. All other fuels do not demonstrate differences in the average acenaphthylene among the four modes.

6.4.6   Acenaphthene

Statistically significant differences exist in the average acenaphthene among the fuels, modes, and fuel*mode interaction. The average acenaphthene for the DF-2 fuel is significantly different than the average acenaphthene for the remaining four fuels.

The average acenaphthene for mode 5 is significantly different than the average acenaphthene for modes 10 and 11.   The average acenaphthene for mode 6 is significantly different than the average acenaphthene for mode 11.

The average acenaphthene for the DF-2 fuel at modes 10 and 11 is significantly different than the average acenaphthene for modes 5 and 6. All the other fuels do not demonstrate differences in the average acenaphthene among the four modes.

6.4.7   Fluorene

Statistically significant differences were apparent in the average fluorene among the fuels, modes, and fuel*mode interaction. The average fluorene for the DF-2 fuel is significantly different than the average fluorene for the remaining four fuels.

The average fluorene for mode 5 is significantly different than the average fluorene for mode 11.

The average fluorene for the DF-2 fuel at modes 10 and 11 are significantly different than the average fluorene at mode 5. All the other fuels do not demonstrate differences in the average fluorene among the four modes.

6.4.8   Phenanthrene

Statistically significant differences were noted in the average phenanthrene among the fuels. The average phenanthrene for the DF-2 fuel is significantly different than the other four fuels. The average phenanthrene among the ADMM15, ALS, CA, and FT-100 fuels are not significantly different from one another.

No significant differences exist in the average phenanthrene among the four modes.

No significant differences were observed among the fuel and mode combinations with respect to the average phenanthrene.

6.4.9 Anthracene

Statistically significant differences were apparent in the average anthracene among the fuels, modes, and fuel*mode interaction. The average anthracene for the DF-2 fuel is significantly different than the other four fuels. The average anthracene among the ADMM15, ALS, CA, and FT-100 fuels are not significantly different from one another.

The average anthracene for mode 5 is significantly different than the average anthracene for mode 10.

The average anthracene for the DF-2 fuel at modes 6, 10, and 11 are significantly different than the anthracene for the other four fuels.

6.4.10 Fluoranthene

Statistically significant differences exist in the average fluoranthene among the fuels. The average fluoranthene for the DF-2 fuel is significantly different than the average fluoranthene for the remaining four fuels.

There is no significant difference in the average fluoranthene among the four modes.

There is no significant difference among the fuel and mode combinations with respect to the average fluoranthene.

6.4.11 Pyrene

Statistically significant differences were apparent in the average pyrene among the fuels. The average pyrene for the DF-2 fuel is significantly different than the average pyrene for the remaining four fuels.

There is no significant difference in the average pyrene among the modes.

There is no significant difference among the fuel and mode combinations with respect to the average pyrene.

7.0   FUEL IMPACT ON EMISSIONS-PILOT FUEL INJECTION STUDY

Fuel comparisons were made for the brake specific exhaust emissions with the engine operated utilizing three different control strategies. The control strategies were LPP(7°ATDC) control with the pilot fuel injection turned off, LPP control with the pilot fuel injection turned on (PilotA), and the OEM calibration strategy (PilotB). The multifactor ANOVA included fuel effects, pilot condition effects, mode effects,   Fuel*Mode interaction effects, Fuel*Pilot interaction effects, Pilot*Mode interaction effects, and Fuel*Mode*Pilot interaction effects. The ANOVA tables for the pilot fuel injection evaluation can be found in Appendix F.

7.1   Fuel Impact on Regulated Brake Specific Mass Emissions

Several statistically significant trends, at 95% confidence, were apparent from an ANOVA of the pilot fuel injection condition emissions data. Table 24 summarizes the general rank order of the fuels for the regulated mass emissions across the three pilot control conditions and two modes. The table displays the fuels rank from highest response to lowest response for the Least-Square means of the pilot condition and modal analysis. Statistically significant similar fuel groupings are also shown for each emission response in Table 24.

Table 24 includes the pilot condition severity across fuels and modes for each regulated emission. Included are the least-square means from multifactor ANOVA, along with the statistically significant groupings for the average mass emissions at each pilot condition. The general trend for pilot condition severity depends on the species of interest.

The mode severities across fuels and pilot condition for each regulated emission are also in Table 24. Included are the least-square means from multifactor ANOVA, along with the statistically significant groupings for the average mass emissions at each mode. The general trend is mode 10 has significantly higher emissions than mode 11 across the fuels and pilot conditions.   The Fuel*Mode, Fuel*Pilot, Pilot*Mode, and Fuel*Pilot*Mode interactions are indicated in Table 24 for each emission.

The discussions to follow are summaries of the multifactor ANOVA performed for each emission response for the pilot fuel injection study, and refer to the results in Table 24.

Response	Fuel	LS Means[1]	Significant Fuel Groups[2]	Pilot Condition	LS Means[1]	Significant Pilot Groups[2]	Mode	LS Means[1]	Significant Mode Groups[2]	Significant Interactions
					Table 24. Mass Emissions (g/kWh) ANOVA Summary for Pilot Fuel Injection Study					
					Five Fuels, Three Pilot Conditions, Modes 10 and 11					
BSPM	DF-2	0.4513	A	Pilot B	0.3876	A	10	0.3126	A	Pilot*Fuel Pilot*Mode
	CA	0.3424	B	Pilot A	0.2778	B	11	0.2754	B	
	ALS	0.2825	C	LPP	0.2166	C				
	FT-100	0.2094	D							
	ADMM15	0.1843	D							
BSNOX	DF-2	2.829	A	LPP	3.168	A	10	2.720	A	Pilot*Fuel Pilot*Mode Fuel*Mode
	CA	2.454	B	Pilot A	3.067	B	11	2.177	B	
	ADMM15	2.380	BC	Pilot B	1.112	C				
	ALS	2.322	C							
	FT-100	2.259	C							
BSHC	DF-2	2.110	A	Pilot A	1.395	A	10	1.487	A	Pilot*Fuel Pilot*Mode Fuel*Mode
	CA	1.691	B	Pilot B	1.327	A	11	1.035	B	
	ADMM15	0.9714	C	LPP	1.060	B				
	ALS	0.9651	C							
	FT-100	0.5656	D							
BSCO	DF-2	6.807	A	Pilot A	6.081	A	10	6.838	A	Pilot*Fuel Pilot*Mode Fuel*Mode Pilot*Fuel*Mode
	CA	6.302	B	Pilot B	5.313	B	11	3.661	B	
	ADMM15	5.436	C	LPP	4.354	C				
	ALS	4.506	D							
	FT-100	3.196	E							
BSCO2	ADMM15	1025	A	Pilot B	989.1	A	10	1064	A	Pilot*Fuel*Mode
	DF-2	1003	B	Pilot A	982.2	AB	11	900.6	B	
	CA	988.3	B	LPP	975.0	B				
	ALS	959.4	C							
	FT-100	935.1	D							
BSSOF	DF-2	0.3333	A	Pilot A	0.1844	A	10	0.1973	A	Pilot*Fuel Pilot*Mode Fuel*Mode Pilot*Fuel*Mode
	CA	0.1917	B	LPP	0.1762	AB	11	0.1503	B	
	ADMM15	0.1337	C	Pilot B	0.1609	B				
	ALS	0.1327	C							
	FT-100	0.0777	D							

[1]Factor levels listed from highest to lowest least squares mean

[2]Letters designate groups of factor means within which there are no statistically significant differences

NS = no statistically significant differences in the mean response at the 5% level of significance

7.1.1 Fuel Impact on Total Particulate

Statistically significant differences exist for the average total particulate among the fuels, modes, pilot conditions, and some of the two-way interactions. The average total particulate for the ALS, CA, and DF-2 fuels are significantly different from each other and the remaining two fuels as seen in Figure 44. The average total particulate for the ADMM15 and FT-100 fuels are not significantly different from one another.

The average total particulate at all three pilot conditions are significantly different from each other. Statistical groupings for engine control strategy, which includes pilot fuel injection effects, from the ANOVA for fuels and modes, are shown in Figure 45 for total particulate.

Modes 10 and 11 are significantly different from one another with respect to average total particulate.

The trend in the average total particulate across the pilot conditions for the DF-2 fuel is significantly different than the trends for the remaining four fuels. The average total particulate for the DF-2 at the Pilot B condition is significantly different than the other four fuels; however, there is not a significant difference at the LPP condition.

There is a significant interaction among the mode and pilot condition combinations. While the average total particulate at mode 11 is significantly different at the LPP and Pilot A conditions, there is not any significant difference at the Pilot B condition.

There is no significant interaction in the average total particulate among the fuel and mode combinations.

7.1.2 Fuel Impact on NO_X

Statistically significant differences exist for the average NO_X among the fuels, modes, pilot conditions, and two-way interactions. The average NO_X for the DF-2 fuel is significantly different than the remaining four fuels. The CA fuel has significantly different average NO_X than the ALS and FT-100 fuels. Also, the FT-100, CA, and ADMM15 fuels are not significantly different from one another. The fuels rankings across pilot conditions are shown in Figure 46.

All three pilot conditions are significantly different from one another with respect to the average NO_X. Statistical groupings for engine control strategy, which includes pilot fuel injection effects, from the ANOVA for fuels and modes, are shown in Figure 47 for NO_X.

Particulate Matter Emissions

Figure 44. Test Fuel Average Total Particulate Mass Emissions for Pilot Conditions and Modes (g/kWh)

Particulate Matter Emissions

Figure 45. Pilot Condition Average Total Particulate Mass Emissions for Fuels and Modes (g/kWh)

NOx Emissions

Figure 46. Test Fuel Average NO$_X$ Mass Emissions for Pilot Conditions and Modes (g/kWh)

NOx Emissions

Figure 47. Pilot Condition Average NO$_X$ Mass Emissions for Fuels and Modes (g/kWh)

Modes 10 and 11 are significantly different from one another with respect to the average NO_X.

The average NO_X for the DF-2 fuel is significantly different than the remaining four fuels at the LPP condition. This trend does not exist at the Pilot A or Pilot B conditions.

A significant interaction exists between the pilot condition and the modes. The difference in the average NO_X between modes 10 and 11 at the LPP condition is larger than the difference at the Pilot B condition.

A significant interaction exists between the mode and fuel levels. The difference in the average NO_X between modes 10 and 11 is the largest at the DF-2 fuel and the smallest at the FT-100 fuel.

7.1.3   Fuel Impact on HC

Statistically significant differences exist for the average BSHC among the fuels, modes, pilot conditions, and interactions. The average BSHC at the FT-100, CA, and DF-2 fuels are all significantly different from one another. The average BSHC for the ADMM15 and ALS fuels are not significantly different from one another, but are different from the other 3 fuels as shown in Figure 48.

Figure 49 shows the least-square means for the pilot conditions for hydrocarbon emissions. Average BSHC at the Pilot A and Pilot B conditions are not significantly different from one another, but both are different from the average BSHC at the LPP condition.

The average BSHC at modes 10 and 11 are significantly different from one another.

The CA and DF-2 fuels have significantly different trends in the average BSHC at the Pilot B condition than at the other two pilot conditions.

Mode 11 demonstrates a constant trend with respect to the average BSHC. However, mode 10 shows significantly different average BSHC at Pilot Conditions A and B than at the LPP condition.

Hydrocarbon Emissions

Figure 48. Test Fuel Average Hydrocarbon Mass Emissions for Pilot Conditions and Modes (g/kWh)

Hydrocarbon Emissions

Figure 49. Pilot Condition Average Hydrocarbon Mass Emissions for Fuels and Modes (g/kWh)

A significant interaction exists between the mode and fuel levels. The differences in the average BSHC between modes 10 and 11 are largest at the CA and DF-2 fuels and the smallest at the FT-100 fuel.

7.1.4   Fuel Impact on CO

Statistically significant differences were noted in the average BSCO among the fuels, pilot condition, modes, two-way interactions, and three-way interaction. In Figure 50 it can be seen all five fuels are significantly different from one another with respect to the average BSCO. Figure 51 shows all three pilot conditions are significantly different from one another with respect to the average BSCO.

Modes 10 and 11 are significantly different from one another with respect to the average BSCO.

The trend in the average BSCO for the ADMM15 fuel is significantly different across the pilot conditions than the trends for the remaining four fuels.

Mode 11 demonstrates a constant trend with respect to the average BSCO. However, mode 10 shows significantly different average BSCO at all three pilot conditions.

A significant interaction exists between the mode and fuel levels. The difference in the average BSCO between modes 10 and 11 is the largest at fuels CA and DF-2 and the smallest at the FT-100 fuel.

7.1.5   Fuel Impact on CO_2

Statistically significant differences were apparent in the average $BSCO_2$ among the fuels, modes, pilot conditions, and three-way interaction.   The average $BSCO_2$ is shown in Figure 52.   The average $BSCO_2$ for the FT-100, ALS, and ADMM15 fuels are significantly different from each other and the remaining two fuels. The average $BSCO_2$ for the CA and DF-2 fuels are not significantly different from one another.

The average $BSCO_2$ in Figure 53 show that the Pilot B condition is significantly different than the LPP condition.

Carbon Monoxide Emissions

Figure 50. Test Fuel Average Carbon Monoxide Mass Emissions for Pilot Conditions and Modes (g/kWh)

Carbon Monoxide Emissions

Figure 51. Pilot Condition Average Carbon Monoxide Mass Emissions for Fuels and Modes (g/kWh)

Carbon Dioxide Emissions

Figure 52. Test Fuel Average Carbon Dioxide Mass Emissions for Pilot Conditions and Modes (g/kWh)

Carbon Dioxide Emissions

Figure 53. Pilot Condition Average Carbon Dioxide Mass Emissions for Fuels and Modes (g/kWh)

Modes 10 and 11 are significantly different from one another with respect to the average $BSCO_2$.

No significant differences exist among the fuel and pilot condition combinations, the mode and pilot condition combinations, and the mode and fuel combinations with respect to the average $BSCO_2$.

7.1.6 Fuel Impact on SOF of Particulate

Statistically significant differences exist in the average BSSOF among the fuels, modes, pilot conditions, all two-factor interactions, and the three-factor interaction between the fuel*mode*pilot condition. The average BSSOF for the FT-100, CA, and DF-2 fuels are significantly different from one another and the remaining two fuels, as shown in Figure 54. The average BSSOF for the ADMM15 and ALS fuels are not significantly different from one another.

As seen in Figure 55 the average BSSOF for the Pilot A condition is significantly different from the Pilot B condition, but not different than the LPP condition.

The average BSSOF for modes 10 and 11 are statistically significant from one another.

The trend in the average BSSOF across the pilot conditions for the DF-2 fuel is significantly different than the trends for the remaining four fuels. The average BSSOF for the DF-2 fuel at the Pilot A and Pilot B conditions are significantly different than the other four fuels.

The average BSSOF at the LPP and Pilot A conditions for Mode 10 are significantly different than those at Mode 11. There is not a significant difference in the average BSSOF between the two modes at the Pilot B condition.

The trends in the average BSSOF across the two modes are different at fuels ADMM15 and CA. There does not appear to be differences in the average BSSOF for the two modes at the ALS, DF-2 or FT-100 fuels.

Soluble Organic Fraction of Particulate Emissions

Figure 54. Test Fuel Average SOF of Particulate Mass Emissions for Pilot Conditions and Modes (g/kWh)

Soluble Organic Fraction of Particulate Emissions

Figure 55. Pilot Condition Average SOF of Particulate Mass Emissions for Fuels and Modes (g/kWh)

The ratio of SOF to total particulate averaged across the test modes and pilot conditions is shown in Figure 56 for the test fuels. Although ADMM15 and FT-100 have statistically similar total PM response, the SOF for the two fuels are statistically different across the pilot conditions. The oxygenated fuel, ADMM15, has a significantly higher soluble organic fraction. From Figure 56 it is also seen that FT-100 has a smaller portion of soluble particulate matter than the other fuels.

Figure 57 shows the effect of pilot condition on the ratio of SOF to total particulate. Of interest is as the total particulate changes for the pilot conditions, the ratio of SOF /PM changes inversely. Figure 58 shows the average SOF/PM ratio plotted with the average exhaust temperature for each pilot condition. The data suggests the SOF is related to the exhaust temperature. Injection timing, EGR levels, and combustion characteristics all contribute to variations in the exhaust temperature for a constant BMEP.

7.2 Fuel Impact on Four Toxic Air Pollutants

Several statistically significant trends, at 95% confidence, were apparent from an ANOVA of the pilot fuel injection condition emissions data. Table 25 summarizes the general rank order of the fuels for the CAA toxic air pollutant mass emissions across the three pilot control conditions and two modes. The table displays the fuels rank from highest response to lowest response for the Least-Square means of the analysis. Statistically significant similar fuel groupings are also shown for each emission response in Table 25.

Table 25 includes the pilot condition severity across fuels and modes for each toxic air pollutant. Included are the least-square means from multifactor ANOVA, along with the statistically significant groupings for the average toxic emissions at each pilot condition. The general trend for pilot condition severity suggests LPP operation results in the lowest CAA toxic emissions.

The mode severity across fuels and pilot condition for each toxic air pollutant is also in Table 25. Included are the least-square means from multifactor ANOVA, along with the statistically significant groupings for the average toxic emissions at each mode. The general trend is mode 10 has significantly higher emissions than mode 11 across the fuels and pilot conditions. The Fuel*Pilot, Fuel*Mode, Pilot*Mode, and Fuel*Pilot*Mode interactions are indicated in Table 25 for each toxic air pollutant.

Relationship of SOF/PM for Pilot Condition Results

Figure 56. Test Fuel Average SOF/PM Ratio for Pilot Conditions and Modes

Relationship of SOF/PM for Pilot Condition Results

Figure 57. Pilot Condition Average SOF/PM Ratio for Test Fuels and Modes

Figure 58. Pilot Condition Average SOF/PM and Exhaust Temperature for Test Fuels and Modes

The discussions to follow are summaries of the multifactor ANOVA performed for each emission response for the pilot fuel injection study, and refer to the results in Table 25. The ANOVA tables for the pilot fuel injection evaluations can be found in Appendix F.

7.2.1 Benzene

Statistically significant differences were noted in the average benzene among the fuels, modes, pilot conditions, and the fuel*pilot condition interaction. The average benzene for the ALS, CA, and DF-2 fuels are significantly different from one another and the remaining two fuels, Figure 59. The average benzene for the ADMM15 and FT-100 fuels are not significantly different from one another.

The toxic air pollutant benzene response in Figure 60 indicates the two pilot conditions are statistically similar, but different from LPP operation with pilot turned off.

Response	Fuel	LS Means[1]	Significant Fuel Groups[2]	Pilot Condition	LS Means[1]	Significant Pilot Groups[2]	Mode	LS Means[1]	Significant Mode Groups[2]	Significant Interactions
Table 25. Clean Air Act Toxic Compound Mass Emissions (mg/kWh) for Pilot Fuel Injection Study										
Five Fuels, Three Pilot Conditions, Modes 10 and 11										
Benzene	DF-2	11.73	A	Pilot A	8.662	A	10	8.068	A	Pilot*Fuel
	CA	9.671	B	Pilot B	7.977	A	11	6.648	B	
	ALS	7.340	C	LPP	5.435	B				
	ADMM15	4.351	D							
	FT-100	3.700	D							
1,3-Butadiene	DF-2	8.974	A	Pilot B	7.474	A	10	8.024	A	Pilot*Fuel
	CA	7.004	B	Pilot A	6.701	B	11	5.178	B	Pilot*Mode
	ADMM15	6.294	BC	LPP	5.628	C				Fuel*Mode
	ALS	5.561	CD							
	FT-100	5.171	D							
Formaldehyde	DF-2	655.5	A	Pilot A	564.7	A	10	619.2	A	Pilot*Fuel
	CA	478.3	B	Pilot B	493.1	B	11	358.2	B	Pilot*Mode
	ALS	472.5	B	LPP	408.3	C				Fuel*Mode
	ADMM15	458.3	B							
	FT-100	379.0	C							
Acetaldehyde	DF-2	225.2	A	Pilot A	196.3	A	10	211.1	A	Pilot*Fuel
	ALS	175.1	B	Pilot B	159.6	B	11	127.3	B	Pilot*Mode
	CA	169.8	B	LPP	151.7	B				
	FT-100	139.8	C							
	ADMM15	136.0	C							

[1]Factor levels listed from highest to lowest least squares mean

[2]Letters designate groups of factor means within which there are no statistically significant differences

NS = no statistically significant differences in the mean response at the 5% level of significance

Benzene Emissions

Figure 59. Test Fuel Average Benzene Mass Emissions for Pilot Conditions and Modes (mg/kWh)

Benzene Emissions

Figure 60. Pilot Condition Average Benzene Mass Emissions for Test Fuels and Modes (mg/kWh)

The average benzene for modes 10 and 11 are significantly different from one another.

The trend in the average benzene across the pilot conditions for the DF-2 and CA fuels is significantly different than the trends for the remaining three fuels. The average benzene for the DF-2 fuel at the Pilot B condition is significantly different than the other four fuels, but not at the LPP condition. Also, the Pilot A condition demonstrates that the average benzene for the DF-2 and CA fuels are not significantly different from one another.

There is no significant interaction in the average benzene among the mode and pilot condition combinations.

There is no significant interaction in the average benzene among the mode and fuel combinations.

7.2.2   1,3-butadiene

Statistically significant differences were apparent in the average 1,3-butadiene among the fuels, modes, pilot conditions, and two-way interactions. There are several distinct fuel groupings with respect to the average 1,3-butadiene. The average 1,3-butadiene in Figure 61 for the DF-2 fuel is significantly different than the remaining four fuels. The FT-100 fuel is significantly different than the ADMM15 and CA fuels, but not significantly different than the ALS fuel. Also, the average 1,3-butadiene for the CA fuel is significantly different than the ALS fuel.

All three pilot conditions shown in Figure 62 are significantly different from one another with respect to the average 1,3-butadiene.

The average 1,3-butadiene for mode 10 is significantly different than mode 11.

The trends in the average 1,3-butadiene across the pilot conditions for the DF-2 and FT-100 fuels appear similar. However, the ALS fuel demonstrates an almost constant average 1,3-butadiene across all three pilot conditions while the CA fuel shows a significant decrease from the Pilot A to Pilot B conditions.

1,3-butadiene Emissions

Figure 61. Test Fuel Average 1,3-butadiene Mass Emissions for Pilot Conditions and Modes (mg/kWh)

1,3-butadiene Emissions

Figure 62. Pilot Condition Average 1,3-butadiene Mass Emissions for Test Fuels and Modes (mg/kWh)

A significant interaction exists between the pilot condition and the modes. The difference in the average 1,3-butadiene between the two modes at the LPP condition is smaller than the differences at the Pilot A and Pilot B conditions.

A significant interaction exists between the mode and the fuel levels. The difference in the average 1,3-butadiene between modes 10 and 11 is the largest at the DF-2 fuel and the smallest at the ALS fuel.

7.2.3   Formaldehyde

Statistically significant differences exist in the average formaldehyde among the fuels, modes, pilot conditions, and two-way interactions. Figure 63 shows there are three distinct fuel groupings with respect to the average formaldehyde. Fuels FT-100 and DF-2 are significantly different from one another and the remaining three fuels. The ADMM15, ALS, and CA fuels are not significantly different from one another, but are significantly different than the other two fuels.

All three pilot conditions in Figure 64 are significantly different from one another with respect to the average formaldehyde.

The average formaldehyde for mode 10 is significantly different than mode 11.

The trends in the average formaldehyde across the pilot conditions for the CA and ALS fuels appear similar. However, the ADMM15 fuel demonstrates an increase in the average formaldehyde from the Pilot A to the Pilot B conditions, whereas the CA and ALS fuels showed a decrease.

A significant interaction exists between the pilot conditions and the modes. The difference in the average formaldehyde between the two modes at the LPP condition is smaller than the differences at the Pilot A and Pilot B conditions.

A significant interaction exists between the mode and the fuel levels. The difference in the average formaldehyde between modes 10 and 11 is the largest at the DF-2 fuel and the smallest at the ALS fuel.

Formaldehyde Emissions

Figure 63. Test Fuel Average Formaldehyde Mass Emissions for Pilot Conditions and Modes (mg/kWh)

Formaldehyde Emissions

Figure 64. Pilot Condition Average Formaldehyde Mass Emissions for Test Fuels and Modes (mg/kWh)

7.2.4 Acetaldehyde

Statistically significant differences were apparent in the average acetaldehyde among the fuels, modes, pilot conditions, and some two-way interactions. There are three distinct fuel groupings in Figure 65 with respect to the average acetaldehyde. The DF-2 fuel is significantly different from the remaining four fuels. The ADMM15 and FT-100 fuels are not significantly different from one another, but are different from the other fuels. Also, the CA and ALS fuels are not significantly different from one another, but are different from the other fuels.

The average acetaldehyde in Figure 66 for the LPP and Pilot B conditions are not significantly different from one another, but are different from the Pilot A condition.

The average acetaldehyde for mode 10 is significantly different than mode 11.

The trends in the average acetaldehyde across the pilot conditions for the CA and ALS fuels appear similar. While the ADMM15 fuel demonstrates an increase in the average acetaldehyde from the Pilot A to Pilot B conditions, the CA and ALS fuels showed a decrease.

 A significant interaction exists between the pilot condition and the modes. The difference in the average acetaldehyde between the two modes at the LPP condition is smaller than the differences at the Pilot A and Pilot B conditions.

There is no significant interaction in the average acetaldehyde among the fuel and mode combinations.

7.3   Fuel Impact on Particulate Soluble Extract PAH Species

Table 26 summarizes the general rank order of the fuels for the particulate soluble extract PAH mass emissions across the three pilot control conditions and two modes. The table displays the fuels rank from highest response to lowest response for the least-square means for the analysis. In general, ADMM15 and FT-100 are in the lowest statistically significant emissions grouping. Statistically significant similar fuel groupings are also shown for each emission response in Table 26.

Acetaldehyde Emissions

Figure 65. Test Fuel Average Acetaldehyde Mass Emissions for Pilot Conditions and Modes (mg/kWh)

Acetaldehyde Emissions

Figure 66. Pilot Condition Average Acetaldehyde Mass Emissions for Test Fuels and Modes (mg/kWh)

Response	Fuel	LS Means[1]	Significant Fuel Groups[2]	Pilot Condition	LS Means[1]	Significant Pilot Groups[2]	Mode	LS Means[1]	Significant Mode Groups[2]	Significant Interactions
colspan="11"	**Table 26. Soluble Phase PAH Mass Emissions (µg/kWh) for Pilot Fuel Injection Study**
colspan="11"	**Five Fuels, Three Pilot Conditions, Modes 10 and 11**
Phenanthrene	DF-2	262.9	A	Pilot B	145.8	A	10	106.3	NS	Pilot*Fuel
	ALS	90.80	B	Pilot A	113.4	A	11	105.3		
	CA	75.94	B	LPP	58.14	B				
	FT-100	52.92	B							
	ADMM15	46.48	B							
Anthracene	DF-2	8.800	A	Pilot B	6.441	A	10	4.811	NS	Pilot*Fuel Fuel*Mode Pilot*Fuel*Mode
	ALS	4.944	B	Pilot A	3.779	B	11	4.017		
	CA	4.508	B	LPP	3.022	B				
	FT-100	2.040	C							
	ADMM15	1.777	C							
Fluoranthene	DF-2	53.34	A	Pilot A	35.74	A	10	34.73	A	Pilot*Fuel Fuel*Mode
	CA	33.73	B	Pilot B	33.62	A	11	27.03	B	
	ALS	29.76	B	LPP	23.27	B				
	FT-100	18.84	C							
	ADMM15	18.71	C							
Pyrene	DF-2	86.69	A	Pilot A	42.34	A	10	41.14	A	Pilot*Fuel
	CA	33.44	B	Pilot B	41.79	A	11	34.73	B	
	ALS	32.75	B	LPP	29.67	B				
	ADMM15	21.70	BC							
	FT-100	15.09	C							
Naphthalene	CA	52.04	A	Pilot A	41.23	NS	10	44.49	A	NS
	DF-2	42.12	AB	LPP	39.56		11	34.53	B	
	FT-100	37.11	B	Pilot B	37.73					
	ALS	36.69	B							
	ADMM15	29.57	B							
Acenaphthylene	FT-100	1.402	A	Pilot B	1.517	A	11	1.116	NS	Pilot*Fuel Pilot*Mode Fuel*Mode Pilot*Fuel*Mode
	ALS	1.070	AB	Pilot A	0.9369	B	10	0.9928		
	DF-2	1.068	AB	LPP	0.7094	B				
	CA	1.038	AB							
	ADMM15	0.6940	B							

Response	Fuel	LS Means[1]	Significant Fuel Groups[2]	Pilot Condition	LS Means[1]	Significant Pilot Groups[2]	Mode	LS Means[1]	Significant Mode Groups[2]	Significant Interactions
				Table 26. Soluble Phase PAH Mass Emissions (µg/kWh) for Pilot Fuel Injection Study (contd)						
				Five Fuels, Three Pilot Conditions, Modes 10 and 11						
Acenaphthene	CA	7.070	A	Pilot A	6.322	A	10	6.509	A	Pilot*Fuel
	ALS	6.209	AB	Pilot B	5.984	AB	11	5.055	B	
	DF-2	5.473	AB	LPP	5.040	B				
	ADMM15	5.159	B							
	FT-100	4.998	B							
Fluorene	ALS	11.92	A	Pilot B	10.53	NS	10	10.89	A	Pilot*Fuel
	DF-2	10.71	AB	Pilot A	10.22		11	8.758	B	
	CA	10.66	AB	LPP	8.723					
	ADMM15	8.466	BC							
	FT-100	7.376	C							
Benzo[a]anthracene	DF-2	5.970	A	Pilot A	2.664	A	10	2.263	A	Pilot*Fuel
	CA	2.610	B	Pilot B	2.489	A	11	1.846	B	
	ALS	0.9662	C	LPP	1.012	B				
	ADMM15	0.4249	C							
	FT-100	0.3019	C							
Chrysene	DF-2	13.96	A	Pilot A	6.189	A	10	5.265	A	Pilot*Fuel
	CA	5.796	B	Pilot B	5.531	A	11	4.460	B	
	ALS	2.273	C	LPP	2.868	B				
	ADMM15	1.280	C							
	FT-100	1.008	C							
Benzo[b]Fluoranthene	DF-2	4.220	A	Pilot A	2.477	A	10	2.043	A	Pilot*Fuel Pilot*Mode Pilot*Fuel*Mode
	CA	2.557	B	Pilot B	1.867	B	11	1.503	B	
	ALS	1.188	C	LPP	0.9745	C				
	FT-100	0.4590	D							
	ADMM15	0.4403	D							
Benzo[k]Fluoranthene	DF-2	3.605	A	Pilot A	2.271	A	10	1.933	A	Pilot*Mode Pilot*Fuel*Mode
	CA	1.811	B	Pilot B	1.561	B	11	1.338	B	
	ALS	1.418	BC	LPP	1.074	C				
	ADMM15	0.8179	CD							
	FT-100	0.5250	D							

Response	Fuel	LS Means[1]	Significant Fuel Groups[2]	Pilot Condition	LS Means[1]	Significant Pilot Groups[2]	Mode	LS Means[1]	Significant Mode Groups[2]	Significant Interactions
Table 26. Soluble Phase PAH Mass Emissions (µg/kWh) for Pilot Fuel Injection Study (contd)										
Five Fuels, Three Pilot Conditions, Modes 10 and 11										
Benzo[e]Pyrene	DF-2	2.576	A	Pilot A	1.715	A	10	1.414	A	Pilot*Fuel Pilot*Mode
	CA	1.736	B	Pilot B	1.336	B	11	1.029	B	
	ALS	0.8744	C	LPP	0.6136	C				
	ADMM15	0.5445	CD							
	FT-100	0.3756	D							
Benzo[a]Pyrene	DF-2	1.605	A	Pilot A	1.174	A	10	0.9299	A	Pilot*Fuel Pilot*Mode Fuel*Mode Pilot*Fuel*Mode
	CA	1.272	B	Pilot B	0.9329	B	11	0.6380	B	
	ALS	0.6400	C	LPP	0.2451	C				
	ADMM15	0.2424	D							
	FT-100	0.1609	D							
Indeno(1,2,3-cd)Pyrene	DF-2	1.139	A	Pilot A	0.6665	A	10	0.5068	NS	Pilot*Fuel Pilot*Mode Pilot*Fuel*Mode
	CA	0.5813	B	Pilot B	0.4817	B	11	0.4315		
	ADMM15	0.1084	C	LPP	0.2592	C				
	FT-100	0.0485	C							
Benzo[ghi]perylene	DF-2	1.718	A	Pilot A	1.072	A	10	0.8596	A	Pilot*Fuel Pilot*Mode Pilot*Fuel*Mode
	CA	1.054	B	Pilot B	0.8007	B	11	0.7248	B	
	ADMM15	0.2483	C	LPP	0.5038	C				
	FT-100	0.1488	C							

[1]Factor levels listed from highest to lowest least squares mean

[2]Letters designate groups of factor means within which there are no statistically significant differences

NS = no statistically significant differences in the mean response at the 5% level of significance

Table 26 includes the pilot condition severity across fuels and modes for each soluble extract PAH compound. Included are the least-square means from multifactor ANOVA, along with the statistically significant groupings for the average PAH compound emissions at each pilot condition. The general trend for pilot condition severity suggests LPP operation results in the lowest PAH emissions.

The mode severity across fuels and pilot condition for each toxin is also in Table 26. Included are the least-square means from multifactor ANOVA, along with the statistically significant groupings for the average soluble PAH emissions at each mode. The general trend is mode 10 has significantly higher emissions than mode 11 across the fuels and pilot conditions. The Fuel*Pilot, Fuel*Mode, Pilot*Mode, and Fuel*Pilot*Mode interactions are indicated in Table 26 for each compound.

The discussions to follow are summaries of the multifactor ANOVA performed for each emission response for the pilot fuel injection study, and refer to the results in Table 26. The ANOVA tables for the pilot fuel injection evaluations can be found in Appendix F.

7.3.1   Naphthalene

Statistically significant differences exist in the average naphthalene among the fuels and modes. The average naphthalene response for the CA fuel is significantly different from the ADMM15, ALS and FT-100 fuels, Figure 67. There are not any statistically significant differences in the average naphthalene response across the pilot conditions, Figure 68.

The average naphthalene for modes 10 and 11 are significantly different from one another.

There is no significant interaction in the average naphthalene among the fuel and pilot condition, the mode and pilot condition, the mode and fuel combinations.

Particulate Naphthalene Emissions

Figure 67. Test Fuel Average Particulate Phase Naphthalene Mass Emissions for Pilot Conditions and Modes (µg/kWh)

Particulate Naphthalene Emissions

Figure 68. Pilot Condition Average Particulate Phase Naphthalene Mass Emissions for Test Fuels and Modes (µg/kWh)

7.3.2 Acenaphthylene

Statistically significant differences exist in the average acenaphthylene among the pilot conditions, fuels, two-factor interactions, and the three-factor interaction fuel*mode*pilot condition. From Figure 69, the average acenaphthylene for the ADMM15 fuel is significantly different from the FT-100 fuel. The CA, DF-2, and ALS fuels are not significantly different from either the ADMM15 or the FT-100 fuels with respect to the average acenaphthylene.

The average acenaphthylene for the LPP and Pilot A conditions are not significantly different from one another, but are significantly different from the Pilot B condition as seen in Figure 70.

The average acenaphthylene for modes 10 and 11 are not significantly different from one another.

The trend in the average acenaphthylene across the pilot conditions for the FT-100 fuel is significantly different than the trends for the remaining four fuels. The average acenaphthylene for the FT-100 fuel at the Pilot B condition is significantly different than the other four fuels, but not at the LPP or the Pilot A condition.

The average acenaphthylene at the Pilot B condition for Mode 11 is significantly different than Mode 10. There is not any significant difference in the average acenaphthylene between the two modes at the LPP or Pilot A conditions.

The trend in the average acenaphthylene across the two modes is different at the FT-100 fuel. There does not appear to be differences in the average acenaphthylene for the two modes at the ADMM15, ALS, CA, or DF-2 fuels.

Particulate Acenaphthylene Emissions

Figure 69. Test Fuel Average Particulate Phase Acenaphthylene Mass Emissions for Pilot Conditions and Modes (µg/kWh)

Particulate Acenaphthylene Emissions

Figure 70. Pilot Condition Average Particulate Phase Acenaphthylene Mass Emissions for Test Fuels and Modes (µg/kWh)

7.3.3   Acenaphthene

Statistically significant differences were apparent in the average acenaphthene among the pilot conditions, fuels, modes, and pilot condition*fuel interaction. The average acenaphthene for the CA fuel is significantly different from the ADMM15 and the FT-100 fuels. Figure 71 shows the acenaphthene response for the test fuels averaged across the pilot conditions and modes.

The average acenaphthene responses for the pilot conditions are shown in Figure 72. The average acenaphthene for the LPP condition is significantly different than the Pilot A condition. The average acenaphthene for the Pilot B condition is not significantly different from with either the LPP or the Pilot A conditions.

The average acenaphthene for modes 10 and 11 are significantly different from one another.

The trends in the average acenaphthene for the ALS and CA fuels are significantly different than the DF-2 fuel between the LPP and Pilot A conditions.

There is no significant interaction in the average acenaphthene among the pilot condition and mode combinations.

There is no significant interaction in the average acenaphthene among the fuel and mode combinations.

7.3.4   Fluorene

Statistically significant differences were noted in the average fluorene among the fuels, modes, and pilot condition*fuel interaction. The average fluorene for the ALS, CA, and DF-2 fuels are significantly different from the FT-100 fuel, but not significantly different from one another. Also, the average fluorene for the ALS fuel is significantly different from the ADMM15 fuel. The fluorene response for the test fuels is shown in Figure 73.

Figure 74 reveals that there were no significant differences in the average fluorene among the pilot conditions.

Particulate Acenaphthene Emissions

Figure 71. Test Fuel Average Particulate Phase Acenaphthene Mass Emissions for Pilot Conditions and Modes (µg/kWh)

Particulate Acenaphthene Emissions

Figure 72. Pilot Condition Average Particulate Phase Acenaphthene Mass Emissions for Test Fuels and Modes (µg/kWh)

Particulate Fluorene Emissions

Figure 73. Test Fuel Average Particulate Phase Fluorene Mass Emissions for Pilot Conditions and Modes (µg/kWh)

Particulate Fluorene Emissions

Figure 74. Pilot Condition Average Particulate Phase Fluorene Mass Emissions for Test Fuels and Modes (µg/kWh)

The average fluorene for modes 10 and 11 are significantly different from one another,

The trend in the average fluorene for the DF-2 fuel is significantly different than the ALS fuel between the LPP and Pilot A conditions. The CA, ADMM15, and FT-100 fuels demonstrate similar trends across the pilot conditions with respect to the average fluorene.

There is no significant interaction in the average fluorene among the pilot condition and mode combinations.

There is no significant interaction in the average fluorene among the fuel and mode combinations.

7.3.5   Phenanthrene

Statistically significant differences exist in the average phenanthrene among the pilot conditions, fuels, and pilot condition*fuel interaction. The average phenanthrene for the DF-2 fuel is significantly different than the remaining four fuels as shown in Figure 75. The average phenanthrene for the ADMM15, FT-100, Ca, and ALS fuels are not significantly different from one another.

The average phenanthrene, Figure 76, for the Pilot A and Pilot B conditions are not significantly different from one another, but are significantly different from the LPP condition.

There is no significant difference in the average phenanthrene among the two modes.

The trend in the average phenanthrene across the pilot conditions for the DF-2 fuel is significantly different than the trends for the remaining four fuels. The average phenanthrene for the DF-2 fuel at the Pilot A and Pilot B conditions are significantly different than the other four fuels.

There is no significant interaction in the average phenanthrene among the pilot condition and mode combinations.

Particulate Phenanthrene Emissions

Figure 75. Test Fuel Average Particulate Phase Phenanthrene Mass Emissions for Pilot Conditions and Modes (µg/kWh)

Particulate Phenanthrene Emissions

Figure 76. Pilot Condition Average Particulate Phase Phenanthrene Mass Emissions for Test Fuels and Modes (µg/kWh)

There is no significant interaction in the average phenanthrene among the fuel and mode combinations.

7.3.6   Anthracene

Statistically significant differences were noted in the average anthracene among the pilot conditions, fuels, pilot condition*fuel interaction, fuel*mode interaction, and the three-factor interaction. Figure 77 reveals there are three distinct fuel groupings with respect to the average anthracene. The average anthracene for the DF-2 fuel is significantly different than the remaining four fuels. The ADMM15 and FT-100 fuels are not significantly different from one another, but are significantly different than the remaining three fuels. Also, the CA and ALS fuels are not significantly different from one another, but are significantly different from the remaining fuels.

The average anthracene for the LPP and Pilot A conditions are not significantly different from one another, but are significantly different from the Pilot B condition as seen in Figure 78.

There is no significant difference in the average anthracene among the two modes.

The trends in the average anthracene across the pilot conditions for the DF-2 and ALS fuels are significantly different than the trends for the remaining three fuels. The average anthracene for the DF-2 fuel at the Pilot A and Pilot B conditions are significantly different than the CA, FT-100, and ADMM15 fuels.

There is no significant interaction in the average anthracene among the pilot condition and mode combinations.

The trends in the average anthracene for modes 10 and 11 are significantly different at the CA fuel. Otherwise, the average anthracene for the two modes are not significantly different across the remaining four fuels.

Particulate Anthracene Emissions

Figure 77. Test Fuel Average Particulate Phase Anthracene Mass Emissions for Pilot Conditions and Modes (µg/kWh)

Particulate Anthracene Emissions

Figure 78. Pilot Condition Average Particulate Phase Anthracene Mass Emissions for Test Fuels and Modes (µg/kWh)

7.3.7   Fluoranthene

Statistically significant differences were apparent in the average fluoranthene among the pilot conditions, fuels, modes, pilot condition*fuel interaction, and fuel*mode interaction. There are three distinct fuel groupings with respect to the average fluoranthene shown in Figure 79. The average fluoranthene for the DF-2 fuel is significantly different than the remaining four fuels. The ADMM15 and FT-100 fuels are not significantly different from one another, but are significantly different than the remaining three fuels. Also, the CA and ALS fuels are not significantly different from one another, but are significantly different from the remaining fuels.

The average fluoranthene for the Pilot A and Pilot B conditions are not significantly different from one another, Figure 80, but are significantly different from the LPP condition.

The average fluoranthene for modes 10 and 11 are significantly different from one another.

The trend in the average fluoranthene across the pilot conditions for the DF-2 fuel is significantly different than the trends for the remaining four fuels. The average fluoranthene for the DF-2 fuel at the LPP condition is significantly different than the other four fuels.

There is no significant interaction in the average fluoranthene among the pilot condition and mode combinations.

The trends in the average fluoranthene for modes 10 and 11 are significantly different at the CA fuel. Otherwise, the average fluoranthene for the two modes are not significantly different across the remaining four fuels.

7.3.8   Pyrene

Statistically significant differences exist in the average pyrene among the pilot conditions, fuels, modes, and pilot condition*fuel interaction. From Figure 81, it is seen that there are several distinct fuel groupings with respect to the average pyrene. The average pyrene for the DF-2 fuel is significantly different than the remaining four fuels. The FT-100 fuel is significantly different than the ALS and CA fuels, but not significantly different than the ADMM15 fuel. The average pyrene for modes 10 and 11 are significantly different from one another.

The average pyrene, shown in Figure 82, for the Pilot A and Pilot B conditions are not significantly different from one another, but are significantly different from the LPP condition.

Particulate Fluoranthene Emissions

Figure 79. Test Fuel Average Particulate Phase Fluoranthene Mass Emissions for Pilot Conditions and Modes (μg/kWh)

Particulate Fluoranthene Emissions

Figure 80. Pilot Condition Average Particulate Phase Fluoranthene Mass Emissions for Test Fuels and Modes (μg/kWh)

Particulate Pyrene Emissions

Figure 81. Test Fuel Average Particulate Phase Pyrene Mass Emissions for Pilot Conditions and Modes (µg/kWh)

Particulate Pyrene Emissions

Figure 82. Pilot Condition Average Particulate Phase Pyrene Mass Emissions for Test Fuels and Modes (µg/kWh)

The trend in the average pyrene across the pilot conditions for the DF-2 fuel is significantly different than the trends for the remaining four fuels.

There is no significant interaction in the average pyrene among the pilot condition and mode combinations.

There is no significant interaction in the average pyrene among the fuel and mode combinations.

7.3.9   Benzo[a]anthracene

Statistically significant differences exist in the average benzo[a]anthracene among the pilot conditions, fuels, modes, and pilot condition*mode interaction. Figure 83 shows three distinct fuel groupings with respect to the average benzo[a]anthracene. Fuels DF-2 and CA are significantly different from one another and the remaining three fuels. The FT-100, ADMM15, and ALS fuels are not significantly different from one another, but are significantly different than the other two fuels.

The average benzo[a]anthracene for the Pilot A and Pilot B conditions are not significantly different from one another, but are significantly different from the LPP condition as seen in Figure 84.

The average benzo[a]anthracene for mode 10 is significantly different than mode 11.

The trends in the average benzo[a]anthracene across the pilot conditions for the DF-2 and CA fuels are significantly different than the trends for the remaining three fuels. The average benzo[a]anthracene for the DF-2 and CA fuels at the Pilot A and Pilot B conditions are significantly different than the ADMM15, ALS, and FT-100 fuels.

There is no significant interaction in the average benzo[a]anthracene among the pilot condition and mode combinations.

There is no significant interaction in the average benzo[a]anthracene among the fuel and mode combinations.

Particulate Benzo[a]anthracene Emissions

Figure 83. Test Fuel Average Particulate Phase Benzo[a]anthracene Mass Emissions for Pilot Conditions and Modes (μg/kWh)

Particulate Benzo[a]anthracene Emissions

Figure 84. Pilot Condition Average Particulate Phase Benzo[a]anthracene Mass Emissions for Test Fuels and Modes (μg/kWh)

7.3.10   Chrysene

Statistically significant differences were apparent in the average chrysene among the pilot conditions, fuels, modes, and pilot condition*fuel interaction. There are three distinct fuel groupings with respect to the average chrysene in Figure 85. Fuels DF-2 and CA are significantly different from one another and the remaining three fuels. The FT-100, ADMM15, and ALS fuels are not significantly different from one another, but are significantly different than the other two fuels.

The particulate bound PAH Chrysene emissions in Figure 86 show the two pilot operation conditions to be different from LPP operation..

The average chrysene for mode 10 is significantly different than mode 11.

The trends in the average chrysene across the pilot conditions for the DF-2 and CA fuels are significantly different than the trends for the remaining three fuels. The average chrysene for the DF-2 and CA fuels at the Pilot A and Pilot B conditions are significantly different than the ADMM15, FT-100, and ALS fuels.

There is no significant interaction in the average chrysene among the pilot condition and mode combinations, or among the fuel and mode combinations.

7.3.11   Benzo[b]fluoranthene

Statistically significant differences were noted in the average benzo[b]fluoranthene among the pilot conditions, fuels, modes, pilot condition*fuel interaction, pilot condition*mode interaction, and the three-factor interaction. The average benzo[b]fluoranthene for the ALS, CA, and DF-2 fuels are significantly different from one another and the remaining two fuels, Figure 87. The average benzo[b]fluoranthene for the ADMM15 and FT-100 fuels are not significantly different from one another.

The average benzo[b]fluoranthene for the three pilot conditions are all significantly different from one another, Figure 88.

Particulate Chrysene Emissions

Figure 85. Test Fuel Average Particulate Phase Chrysene Mass Emissions for Pilot Conditions and Modes (µg/kWh)

Particulate Chrysene Emissions

Figure 86. Pilot Condition Average Particulate Phase Chrysene Mass Emissions for Test Fuels and Modes (µg/kWh)

Particulate Benzo[b]fluoranthene Emissions

Figure 87 Test Fuel Average Particulate Phase Benzo[b]fluoranthene Mass Emissions for Pilot Conditions and Modes (µg/kWh)

Particulate Benzo[b]fluoranthene Emissions

Figure 88. Pilot Condition Average Particulate Phase Benzo[b]fluoranthene Mass Emissions for Test Fuels and Modes (µg/kWh)

The average benzo[b]fluoranthene for modes 10 and 11 are significantly different from one another.

The trends in the average benzo[b]fluoranthene across the pilot conditions for the DF-2 and CA fuels are significantly different than the trends for the remaining three fuels. The average benzo[b]fluoranthene for the DF-2 and CA fuels at the Pilot A and Pilot B conditions are significantly different than the ADMM15, FT-100, and ALS fuels.

The average benzo[b]fluoranthene at the Pilot A condition for Mode 10 is significantly different than Mode 11. There is not any significant difference in the average benzo[b]fluoranthene between the two modes at the LPP or Pilot B conditions.

There is no significant interaction in the average benzo[b]fluoranthene among the fuel and mode combinations.

7.3.12 Benzo[k]fluoranthene

Statistically significant differences exist in the average benzo[b]fluoranthene among the pilot conditions, fuels, modes, pilot condition*mode interaction, and the three-factor interaction. There are several distinct fuel groupings with respect to the average benzo[k]fluoranthene shown in Figure 89. The DF-2 fuel is significantly different from the remaining four fuels. The CA fuel is significantly different than the ADMM15 and the FT-100 fuels, but not significantly different than the ALS fuel. Also, the ALS fuel is significantly different than the FT-100 fuel.

In Figure 90, the average benzo[f]fluoranthene for the three pilot conditions are shown to be significantly different from one another.

The average benzo[k]fluoranthene for mode 10 is significantly different than mode 11.

There is no significant interaction in the average benzo[k]fluoranthene among the fuel and pilot condition combinations.

The average benzo[k]fluoranthene at the Pilot A condition for Mode 10 is significantly different than Mode 11. There is not any significant difference in the average benzo[k]fluoranthene between the two modes at the LPP or Pilot B conditions.

Particulate Benzo[k]fluoranthene Emissions

Figure 89. Test Fuel Average Particulate Phase Benzo[k]fluoranthene Mass Emissions for Pilot Conditions and Modes (µg/kWh)

Particulate Benzo[k]fluoranthene Emissions

Figure 90. Pilot Condition Average Particulate Phase Benzo[k]fluoranthene Mass Emissions for Test Fuels and Modes (µg/kWh)

There is no significant interaction in the average benzo[k]fluoranthene among the fuel and mode combinations.

7.3.13   Benzo[e]pyrene

Statistically significant differences were noted in the average benzo[e]pyrene among the pilot conditions, fuels, modes, pilot condition*fuel interaction, and pilot condition*mode interaction. There are several distinct fuel groupings with respect to the average benzo[e]pyrene. The DF-2 and CA fuels are significantly different from the remaining three fuels. Also, the ALS fuel is significantly different than the FT-100 fuel, Figure 91.

The average benzo[e]pyrene for the three pilot conditions are significantly different from one another, Figure 92.

The average benzo[e]pyrene for mode 10 is significantly different than mode 11.

The trends in the average benzo[e]pyrene across the pilot conditions for the DF-2 and CA fuels are significantly different than the trends for the remaining three fuels.   The average benzo[e]pyrene for the DF-2 and CA fuels at the Pilot A and Pilot B conditions are significantly different than the ADMM15, FT-100, and ALS fuels.

The average benzo[e]pyrene at the Pilot A condition for Mode 10 is significantly different than Mode 11. There is not any significant difference in the average benzo[e]pyrene between the two modes at the LPP or Pilot B conditions.

There is no significant interaction in the average benzo[e]pyrene among the fuel and mode combinations.

Particulate Benzo[e]pyrene Emissions

Figure 91. Test Fuel Average Particulate Phase Benzo[e]pyrene Mass Emissions for Pilot Conditions and Modes (µg/kWh)

Particulate Benzo[e]pyrene Emissions

Figure 92. Pilot Condition Average Particulate Phase Benzo[e]pyrene Mass Emissions for Test Fuels and Modes (µg/kWh)

7.3.14 Benzo[a]pyrene

Statistically significant differences were noted in the average benzo[a]pyrene among the pilot conditions, fuels, modes, two-factor interactions, and the three-factor interaction fuel*mode*pilot condition. Figure 93 shows the average benzo[a]pyrene for the DF-2, CA, and ALS fuels to be significantly different from one another and the remaining two fuels. The average benzo[a]pyrene for the ADMM15 and FT-100 fuels are not significantly different from one another.

From Figure 94 the average benzo[a]pyrene for the three pilot conditions is seen to be significantly different from each another.

The average benzo[a]pyrene for mode 10 is significantly different than mode 11.

The trends in the average benzo[a]pyrene across the pilot conditions for the CA and DF-2 fuels are significantly different than the trends for the remaining three fuels. The average benzo[a]pyrene for the CA and DF-2 fuels at the Pilot A and Pilot B conditions are significantly different than the ADMM15, FT-100, and ALS fuels.

The average benzo[a]pyrene at the Pilot A condition for mode 10 is significantly different than mode 11. There is not any significant difference in the average benzo[a]pyrene between the two modes at the LPP or Pilot B conditions.

The average benzo[a]pyrene for the CA and DF-2 fuels for mode 10 is significantly different than mode 11. There is not any significant difference in the average benzo[a]pyrene between the modes for the ADMM15, ALS, or FT-100 fuels.

7.3.15 Indeno(1,2,3-cd)pyrene

For the PAH indeno(1,2,3-cd)pyrene, sufficient interference in the chromatograms from the ALS fuel extracts for the pilot conditions existed that there were numerous non-detects with the low-resolution mass spectrometer. The high-resolution instrument was only used on those extracts when the LPP control condition was utilized AND that did not have a benzo[a]pyrene response. The ALS fuel at the LPP control condition had low-resolution response for benzo[a]pyrene, but non-detects for indeno(1,2,3-cd)pyrene. There were also numerous non-detects at the conditions with pilot fuel injection enabled. Thus ALS was not included in the ANOVA for indeno(1,2,3-cd)pyrene.

Particulate Benzo[a]pyrene Emissions

Figure 93. Test Fuel Average Particulate Phase Benzo[a]pyrene Mass Emissions for Pilot Conditions and Modes (µg/kWh)

Particulate Benzo[a]pyrene Emissions

Figure 94. Pilot Condition Average Particulate Phase Benzo[a]pyrene Mass Emissions for Test Fuels and Modes (µg/kWh)

Statistically significant differences exist in the average indeno(1,2,3-cd)pyrene among the pilot conditions, fuels, pilot condition*fuel interaction, pilot condition*mode interaction, and the three-factor interaction pilot condition*fuel*mode. The average indeno(1,2,3-cd)pyrene for the DF-2 and CA fuels are significantly different from one another and the remaining two fuels, Figure 95. The average indeno(1,2,3-cd)pyrene for the FT-100 and ADMM15 fuels are not significantly different from one another.

The average indeno(1,2,3-cd)pyrene for the three pilot conditions are significantly different from one another, Figure 96.

There is no significant difference in the average indeno(1,2,3-cd)pyrene among the two modes.

The trends in the average indeno(1,2,3-cd)pyrene across the pilot conditions for the CA and DF-2 fuels are significantly different than the trends for the remaining two fuels. The average indeno(1,2,3-cd)pyrene for the CA and DF-2 fuels at the Pilot A condition are significantly different than the ADMM15 and FT-100 fuels.

The average indeno(1,2,3-cd)pyrene at the Pilot A condition for mode 10 is significantly different than mode 11.

There is no significant interaction in the average indeno(1,2,3-cd)pyrene among the fuel and mode combinations.

7.3.16   Dibenzo[a,h]anthracene

For the PAH dibenzo[a,h]anthracene there was interference in the chromatograms from all test fuel extracts. The high-resolution instrument was only used on those extracts when the LPP control condition was utilized. There were numerous non-detects for dibenzo[a,h]anthracene at the conditions with pilot fuel injection enabled for all test fuels. Thus insufficient data existed to perform the ANOVA for dibenzo[a,h]anthracene.

Particulate Indeno(1,2,3-cd)pyrene Emissions

Figure 95. Test Fuel Average Particulate Phase Indeno(1,2,3-cd)pyrene Mass Emissions for Pilot Conditions and Modes (µg/kWh)

Particulate Indeno(1,2,3-cd)pyrene Emissions

Figure 96. Pilot Condition Average Particulate Phase Indeno(1,2,3-cd)pyrene Mass Emissions for Test Fuels and Modes (µg/kWh)

7.3.17 Benzo[ghi]perylene

For the PAH benzo[ghi]perylene, sufficient interference in the chromatograms from the ALS fuel extracts for the pilot conditions existed that there were numerous non-detects with the low-resolution mass spectrometer. The high-resolution instrument was only used on those extracts when the LPP control condition was utilized AND that did not have a benzo[a]pyrene response. The ALS fuel at the LPP control condition had low-resolution response for benzo[a]pyrene, but non-detects for benzo[ghi]perylene. There were also numerous non-detects at the conditions with pilot fuel injection enabled.   The ALS fuel was not included in the ANOVA for benzo[ghi]perylene.

Statistically significant differences were apparent in the average benzo[ghi]perylene among the pilot conditions, fuels, modes, pilot condition*fuel interaction, pilot condition*mode interaction, and the three-factor interaction pilot condition*fuel*mode. The average benzo[ghi]perylene for the DF-2 and CA fuels are significantly different from one another and the remaining two fuels. The average benzo[ghi]perylene for the FT-100 and ADMM15 fuels are not significantly different from one another, Figure 97.

The average benzo[ghi]perylene for the three pilot conditions shown in Figure 98, are significantly different from one another.

The average benzo[ghi]perylene for mode 10 is significantly different than mode 11.

The trends in the average benzo[ghi]perylene across the pilot conditions for the DF-2 and CA fuels are significantly different than the trends for the remaining two fuels.   The average benzo[ghi]perylene for the CA and DF-2 fuels at the Pilot A condition are significantly different than the ADMM15 and FT-100 fuels.

The average benzo[ghi]perylene at the Pilot A condition for mode 10 is significantly different than mode 11.

There is no significant interaction in the average benzo[ghi]perylene among the fuel and mode combinations.

Particulate Benzo[ghi]perylene Emissions

Figure 97. Test Fuel Average Particulate Phase Benzo[ghi]perylene Mass Emissions for Pilot Conditions and Modes (μg/kWh)

Particulate Benzo[ghi]perylene Emissions

Figure 98. Pilot Condition Average Particulate Phase Benzo[ghi]perylene Mass Emissions for Test Fuels and Modes (μg/kWh)

7.4   Fuel Impact on Gaseous PAH Species

Table 27 summarizes the general rank order of the fuels for the gas phase PAH mass emissions across the three pilot control conditions and two modes. The table displays the fuels rank from highest response to lowest response for the Least-Square means for the analysis.   In general, ADMM15 and FT-100 are in the lowest statistically significant emissions grouping. Statistically significant similar fuel groupings are shown for each emission response in Table 27.

Table 27 includes the pilot condition severity across fuels and modes for each gaseous PAH compound.   Included are the least-square means from multifactor ANOVA, along with the statistically significant groupings for the average gaseous PAH compound emissions at each pilot condition. The pilot condition severity for most compounds suggests LPP operation results in the lowest PAH emissions; however, the rankings differ for some compounds.

The mode severity across fuels and pilot condition for each toxin is also in Table 27.   Included are the least-square means from multifactor ANOVA, along with the statistically significant groupings for the average gaseous PAH emissions at each mode. The mode ranking depends on the compound. The Fuel*Pilot, Fuel*Mode, Pilot*Mode, and Fuel*Pilot*Mode interactions are indicated in Table 27 for each compound.

The discussions to follow are summaries of the multifactor ANOVA performed for each emission response for the pilot fuel injection study, and refer to the results in Table 27.   The ANOVA tables for the pilot fuel injection evaluations can be found in Appendix F.

7.4.1   Naphthalene

Statistically significant differences were noted in the average naphthalene among the fuels, modes, pilot conditions, the pilot condition*fuel interaction, and the fuel*mode interaction. The average naphthalene for the CA and DF-2 fuels are significantly different from one another and the remaining three fuels.   The ALS and FT-100 fuels demonstrate significantly different average naphthalene; however, neither one of these fuels was significantly different than the ADMM15 fuel.

The average naphthalene for the Pilot A and Pilot B conditions are not significantly different from one another, but are significantly different from the LPP condition as shown in Figure 100.

Response	Fuel	LS Means[1]	Significant Fuel Groups[2]	Pilot Condition	LS Means[1]	Significant Pilot Groups[2]	Mode	LS Means[1]	Significant Mode Groups[2]	Significant Interactions
colspan										

Response	Fuel	LS Means[1]	Significant Fuel Groups[2]	Pilot Condition	LS Means[1]	Significant Pilot Groups[2]	Mode	LS Means[1]	Significant Mode Groups[2]	Significant Interactions

Table 27. Gaseous Phase PAH Mass Emissions (µg/kWh) for Control/Pilot Fuel Injection Study

Five Fuels,   Three Pilot Conditions,   Modes 10 and 11

Response	Fuel	LS Means[1]	Significant Fuel Groups[2]	Pilot Condition	LS Means[1]	Significant Pilot Groups[2]	Mode	LS Means[1]	Significant Mode Groups[2]	Significant Interactions
Naphthalene	CA	7813	A	Pilot A	3417	A	10	3347	A	Pilot*Fuel Fuel*Mode
	DF-2	5046	B	Pilot B	3350	A	11	2804	B	
	ALS	1323	C	LPP	2459	B				
	ADMM15	872.0	CD							
	FT-100	323.9	D							
2-Methylnaphthalene	DF-2	6870	A	Pilot B	2929	A	10	2687	NS	Pilot*Fuel Fuel*Mode
	CA	4869	B	Pilot A	2800	A	11	2514		
	ALS	802.9	C	LPP	2072	B				
	ADMM15	376.4	C							
	FT-100	84.62	C							
1-Methylnaphthalene	DF-2	4869	A	Pilot B	1922	A	10	1723	NS	Pilot*Fuel Fuel*Mode
	CA	2868	B	Pilot A	1848	A	11	1655		
	ALS	468.0	C	LPP	1297	B				
	ADMM15	185.7	C							
	FT-100	53.49	C							
2,6-Dimethylnaphthalene	DF-2	4930	A	Pilot B	1570	A	11	1373	NS	Pilot*Fuel
	CA	1430	B	Pilot A	1404	AB	10	1304		
	ALS	237.6	C	LPP	1041	B				
	ADMM15	61.71	C							
	FT-100	33.12	C							
Acenaphthylene	DF-2	606.1	A	Pilot A	282.3	A	10	227.6	NS	Pilot*Fuel
	CA	239.2	B	Pilot B	259.3	A	11	226.2		
	ALS	147.4	BC	LPP	139.0	B				
	ADMM15	89.68	C							
	FT-100	52.04	C							
Acenaphthene	DF-2	723.2	A	Pilot B	213.5	NS	11	200.4	NS	NS
	CA	137.5	B	Pilot A	203.4		10	176.3		
	ALS	48.29	BC	LPP	148.1					
	ADMM15	24.81	BC							
	FT-100	7.888	C							

Response	Fuel	LS Means[1]	Significant Fuel Groups[2]	Pilot Condition	LS Means[1]	Significant Pilot Groups[2]	Mode	LS Means[1]	Significant Mode Groups[2]	Significant Interactions
Fluorene	DF-2	1152	A	Pilot B	323.5	NS	11	307.8	NS	NS
	CA	193.0	B	Pilot A	292.4		10	264.4		
	ALS	50.08	B	LPP	242.3					
	ADMM15	21.51	B							
	FT-100	14.25	B							
Phenanthrene	DF-2	1815	A	Pilot A	604.4	NS	11	535.7	NS	Pilot*Fuel
	CA	557.6	B	Pilot B	545.9		10	510.0		
	ALS	169.2	C	LPP	418.4					
	ADMM15	43.16	C							
	FT-100	29.23	C							
Anthracene	DF-2	56.23	A	Pilot B	18.05	NS	10	16.93	NS	Pilot*Fuel
	CA	17.39	B	Pilot A	16.37		11	15.89		
	ALS	4.566	C	LPP	14.81					
	ADMM15	2.718	C							
	FT-100	1.144	C							
Fluoranthene	DF-2	5.871	A	LPP	4.760	A	10	3.222	NS	Pilot*Fuel
	CA	3.655	B	Pilot A	2.457	B	11	2.689		
	ALS	2.344	BC	Pilot B	1.649	B				
	FT-100	1.590	BC							
	ADMM15	1.318	C							
Pyrene	DF-2	7.599	A	LPP	5.206	A	10	3.213	NS	Pilot*Fuel
	CA	3.372	B	Pilot A	2.398	B	11	2.944		
	ALS	2.174	B	Pilot B	1.631	B				
	FT-100	1.165	B							
	ADMM15	1.081	B							

Table 27. Gaseous Phase PAH Mass Emissions (µg/kWh) for Control/Pilot Fuel Injection Study (contd)

Five Fuels, Three Pilot Conditions, Modes 10 and 11

[1]Factor levels listed from highest to lowest least squares mean

[2]Letters designate groups of factor means within which there are no statistically significant differences

NS = no statistically significant differences in the mean response at the 5% level of significance

Gaseous Naphthalene Emissions

Figure 99. Test Fuel Average Gaseous Phase Naphthalene Mass Emissions for Pilot Conditions and Modes (µg/kWh)

Gaseous Naphthalene Emissions

Figure 100. Pilot Condition Average Gaseous Phase Naphthalene Mass Emissions for Test Fuels and Modes (µg/kWh)

The average naphthalene for modes 10 and 11 are significantly different from one another.

The trend in the average naphthalene across the pilot conditions for the ADMM15, ALS, and FT-100 fuels is significantly different than the trends for the CA and DF-2 fuels. Whereas, the trends in the ADMM15, ALS, and FT-100 fuels across the three pilot conditions are relatively constant, the CA and DF-2 fuels show an increase in the average naphthalene from the LPP to the Pilot A and Pilot B conditions.

There is no significant interaction in the average naphthalene among the mode and pilot condition combinations.

A significant interaction exists between the fuels and modes. The difference in the average naphthalene between the two modes is significant at the CA fuel. However, the remaining four fuels do not demonstrate a significant difference between the two modes with respect to the average naphthalene.

7.4.2   2-Methylnaphthalene

Statistically significant differences exist in the average 2-methylnaphthalene among the pilot conditions, fuels, pilot condition*fuel interaction, and the fuel*mode interaction. The average 2-methylnaphthalene for the CA and DF-2 fuels are significantly different from one another and the remaining three fuels, Figure 101. The average 2-methylnaphthalene for the ADMM15, ALS, and FT-100 fuels are not significantly different from one another.

The average 2-methylnaphthalene for the Pilot A and Pilot B conditions are not significantly different from one another, but are significantly different from the LPP condition, Figure 102.

The average 2-methylnaphthalene for modes 10 and 11 are not significantly different from one another.

The trend in the average 2-methylnaphthalene across the pilot conditions for the ADMM15, ALS, and FT-100 fuels is significantly different than the trends for the CA and DF-2 fuels. Whereas, the trends in the ADMM15, ALS, and FT-100 fuels across the three pilot conditions are relatively constant, the CA and DF-2 fuels show an increase in the average 2-methylnaphthalene from the LPP to the Pilot A and Pilot B conditions.

Gaseous 2-Methylnaphthalene Emissions

Figure 101. Test Fuel Average Gaseous Phase 2-Methylnaphthalene Mass Emissions for Pilot Conditions and Modes (µg/kWh)

Gaseous 2-Methylnaphthalene Emissions

Figure 102. Pilot Condition Average Gaseous Phase 2-Methylnaphthalene Mass Emissions for Test Fuels and Modes (µg/kWh)

There is not any significant interaction in the average 2-methylnaphthalene among the mode and pilot condition combinations.

A significant interaction exists between the fuels and modes. The difference in the average 2-methylnaphthalene between the two modes is significant at the CA fuel. However, the remaining four fuels do not demonstrate a significant difference between the two modes with respect to the average 2-methylnaphthalene.

7.4.3   1-Methylnaphthalene

Statistically significant differences were apparent in the average 1-methylnaphthalene among the pilot conditions, fuels, pilot condition*fuel interaction, and fuel*mode interaction. The average 1-methylnaphthalene for the CA and DF-2 fuels are significantly different from one another and the remaining three fuels, Figure 103. The average 1-methylnaphthalene for the ADMM15, ALS, and FT-100 fuels are not significantly different from one another.

In Figure 104, the average 1-methylnaphthalene for the Pilot A and Pilot B conditions are not significantly different from one another, but are significantly different from the LPP condition.

The average 1-methylnaphthalene for modes 10 and 11 is not significantly different from one another.

The trend in the average 1-methylnaphthalene across the pilot conditions for the ADMM15, ALS, and FT-100 fuels is significantly different than the trends for the CA and DF-2 fuels. Whereas, the trends in the ADMM15, ALS, and FT-100 fuels across the three pilot conditions are relatively constant, the CA and DF-2 fuels show an increase in the average 1-methylnaphthalene from the LPP to the Pilot A and Pilot B conditions.

There is no significant interaction in the average 1-methylnapthalene among the mode and pilot condition combinations.

A significant interaction exists between the fuels and modes. The difference in the average 1-methylnaphthalene between the two modes is significant at the CA fuel. However, the remaining four fuels do not demonstrate a significant difference between the two modes with respect to the average 1-methylnaphthalene.

Gaseous 1-Methylnaphthalene Emissions

Figure 103. Test Fuel Average Gaseous Phase 1-Methylnaphthalene Mass Emissions for Pilot Conditions and Modes (µg/kWh)

Gaseous 1-Methylnaphthalene Emissions

Figure 104. Pilot Condition Average Gaseous Phase 1-Methylnaphthalene Mass Emissions for Test Fuels and Modes (µg/kWh)

7.4.4   2,6-Dimethylnaphthalene

Statistically significant differences were noted in the average 2,6-dimethylnaphthalene among the pilot conditions, fuels, and pilot condition*fuel interaction. The average 2,6-dimethylnaphthalene for the CA and DF-2 fuels are significantly different from one another and the remaining three fuels. The average 2,6-dimethylnaphthalene for the ADMM15, ALS, and FT-100 fuels are not significantly different from one another, Figure 105.

In Figure 106, the average 2,6-dimethylnaphthalene for the Pilot B condition is significantly different than the LPP condition.

The average 2,6-dimethylnaphthalene for modes 10 and 11 are not significantly different from one another.

The trend in the average 2,6-dimethylnaphthalene across the pilot conditions for the ADMM16, ALS, CA, and FT-100 fuels is significantly different than the trend for the DF-2 fuel. Whereas, the trends in the ADMM15, ALS, CA, and FT-100 fuels are relatively constant, the DF-2 fuel shows an increase in the average 2,6-dimethylnaphthalene from the LPP to the Pilot A and Pilot B conditions.

There is no significant interaction in the average 2,6-dimethylnaphthalene among the pilot condition and mode combinations.

There is no significant interaction in the average 2,6-dimethylnaphthalene among the fuel and mode combinations.

7.4.5   Acenaphthylene

Statistically significant differences exist in the average acenaphthylene among the pilot conditions, fuels, and pilot condition*fuel interaction. There are several distinct fuel groupings with respect to the average acenaphthylene. The average acenaphthylene for the DF-2 fuel is significantly different from the remaining four fuels, Figure 107. The CA fuel is significantly different than the ADMM15 and FT-100 fuels, but not significantly different than the ALS fuel.

The average acenaphthylene for the Pilot A and Pilot B conditions are not significantly different from one another, but are significantly different from the LPP conditions, Figure 108.

Gaseous 2,6-Dimethylnaphthalene Emissions

Figure 105. Test Fuel Average Gaseous Phase 2,6-Dimethylnaphthalene Mass Emissions for Pilot Conditions and Modes (µg/kWh)

Gaseous 2,6-Dimethylnaphthalene Emissions

Figure 106. Pilot Condition Average Gaseous Phase 2,6-Dimethylnaphthalene Mass Emissions for Test Fuels and Modes (µg/kWh)

Gaseous Acenaphthylene Emissions

Figure 107. Test Fuel Average Gaseous Phase Acenaphthylene Mass Emissions for Pilot Conditions and Modes (μg/kWh)

Gaseous Acenaphthylene Emissions

Figure 108. Pilot Condition Average Gaseous Phase Acenaphthylene Mass Emissions for Test Fuels and Modes (μg/kWh)

The average acenaphthylene for modes 10 and 11 are not significantly different from one another.

The trend in the average acenaphthylene across the pilot conditions for the ADMM15, ALS, CA, and FT-100 fuels is significantly different than the trend for the DF-2 fuel. Whereas, the trends in the ADMM15, ALS, CA, and FT-100 fuels are relatively constant, the DF-2 fuel shows an increase in the average acenaphthylene from the LPP to the Pilot A and Pilot B conditions.

There is no significant interaction in the average acenaphthylene among the pilot condition and mode combinations.

There is no significant interaction in the average acenaphthylene among the fuel and mode combinations.

7.4.6   Acenaphthene

Statistically significant differences were apparent in the average acenaphthene among the fuels. There are several distinct fuel groupings with respect to the average acenaphthene. The average acenaphthene for the DF-2 fuel is significantly different than the remaining four fuels. Also, the CA fuel is significantly different than the FT-100 fuel, but not significantly different than the ADMM15 or ALS fuels, Figure 109.

The average acenaphthene in Figure 110 for the three pilot conditions are not significantly different from one another.

The average acenaphthene for modes 10 and 11 are not significantly different from one another.

There is no significant interaction in the average acenaphthene among the fuel and pilot condition combinations, the mode and pilot condition combinations, and the fuel and mode combinations.

Gaseous Acenaphthene Emissions

Figure 109. Test Fuel Average Gaseous Phase Acenaphthene Mass Emissions for Pilot Conditions and Modes (µg/kWh)

Gaseous Acenaphthene Emissions

Figure 110. Pilot Condition Average Gaseous Phase Acenaphthene Mass Emissions for Test Fuels and Modes (µg/kWh)

7.4.7   Fluorene

Statistically significant differences exist for the average fluorene among the fuels. The average fluorene for the DF-2 fuel is significantly different than the remaining four fuels, Figure 111.

From Figure 112, the average fluorene for the three pilot conditions are not significantly different from one another.

The average fluorene for modes 10 and 11 are not significantly different from one another.

There is no significant interaction in the average fluorene among the fuel and pilot condition combinations, the pilot condition and mode combinations, and the fuel and mode combinations.

7.4.8   Phenanthrene

Statistically significant differences were noted in the average phenanthrene among the fuels and pilot condition*fuel interaction. The average phenanthrene for the DF-2 and CA fuels is significantly different than the remaining three fuels shown in Figure 113.   The average phenanthrene for the ADMM15, ALS, and FT-100 fuels are not significantly different from one another.

There is no significant difference in the average phenanthrene among the three pilot conditions as shown in Figure 114.

The average phenanthrene for modes 10 and 11 are not significantly different from one another.

The trend in the average phenanthrene across the pilot conditions for the ADMM15, ALS, and FT-100 fuels is significantly different than the trend for the DF-2 and CA fuels. Whereas, the trends in the ADMM15, ALS, and FT-100 fuels are relatively constant, the DF-2 fuel shows an increase in the average phenanthrene from the LPP to the Pilot A and Pilot B conditions. Also, the CA fuel demonstrates an increase in the Pilot A condition.

There is no significant interaction in the average phenanthrene among the pilot conditions and mode combinations or among the fuel and mode combinations.

Gaseous Fluorene Emissions

Figure 111. Test Fuel Average Gaseous Phase Fluorene Mass Emissions for Pilot Conditions and Modes (µg/kWh)

Gaseous Fluorene Emissions

Figure 112. Pilot Condition Average Gaseous Phase Fluorene Mass Emissions for Test Fuels and Modes (µg/kWh)

Gaseous Phenanthrene Emissions

Figure 113. Test Fuel Average Gaseous Phase Phenanthrene Mass Emissions for Pilot Conditions and Modes (µg/kWh)

Gaseous Phenanthrene Emissions

Figure 114. Pilot Condition Average Gaseous Phase Phenanthrene Mass Emissions for Test Fuels and Modes (µg/kWh)

7.4.9   Anthracene

Statistically significant differences were apparent in the average anthracene among the fuels and pilot condition*fuel interaction. The average anthracene for the DF-2 and CA fuels is significantly different than the remaining three fuels shown in Figure 115. The average anthracene for the ADMM15, ALS, and FT-100 fuels are not significantly different from one another.

There are no significant differences in the average anthracene among the three pilot conditions as shown in Figure 116.

The average anthracene for modes 10 and 11 are not significantly different from one another.

The trend in the average anthracene across the pilot conditions for the ADMM15, ALS, and FT-100 fuels is significantly different than the trend for the DF-2 and CA fuels. Whereas, the trends in the ADMM15, ALS, and FT-100 fuels are relatively constant, the DF-2 fuel demonstrates a slight increase from the LPP to the Pilot B condition. Also, the CA fuel shows an increase in the Pilot A condition.

There is no significant interaction in the average anthracene among the pilot condition and mode combinations or among the fuel and mode combinations.

7.4.10   Fluoranthene

Statistically significant differences exist in the average fluoranthene among the pilot conditions, fuels, and pilot condition*fuel interaction. There are several distinct fuel groupings with respect to the average fluoranthene as shown in Figure 117. The average fluoranthene for the DF-2 fuel is significantly different from the remaining four fuels. The CA fuel is significantly different than the ADMM15 fuel, but not significantly different than the ALS or FT-100 fuels.

The average fluoranthene for the Pilot A and Pilot B conditions are not significantly different from one another, but are significantly different from the LPP conditions as seen in Figure 118.

Gaseous Anthracene Emissions

Figure 115. Test Fuel Average Gaseous Phase Anthracene Mass Emissions for Pilot Conditions and Modes (µg/kWh)

Gaseous Anthracene Emissions

Figure 116. Pilot Condition Average Gaseous Phase Anthracene Mass Emissions for Test Fuels and Modes (µg/kWh)

Figure 117. Test Fuel Average Gaseous Phase Fluoranthene Mass Emissions for Pilot Conditions and Modes (µg/kWh)

Figure 118. Pilot Condition Average Gaseous Phase Fluoranthene Mass Emissions for Test Fuels and Modes (µg/kWh)

The average fluoranthene for modes 10 and 11 are not significantly different from one another.

The trend in the average fluoranthene across the pilot conditions for the ADMM15, ALS, CA, and FT-100 fuels is significantly different than the trend for the DF-2 fuel. Whereas, the trends in the ADMM15, ALS, CA, and FT-100 fuels are relatively constant, the DF-2 fuel shows an increase in the average fluoranthene at the LPP condition.

There is no significant interaction in the average fluoranthene among the pilot condition and mode combinations or among the fuel and mode combinations.

7.4.11   Pyrene

Statistically significant differences were noted in the average pyrene among the pilot conditions, fuels, and pilot condition*fuel interaction. In Figure 119, the average pyrene for the DF-2 fuel is shown to be significantly different than the other four fuels. The average pyrene among the ADMM15, ALS, CA, and FT-100 fuels are not significantly different from one another.

From Figure 120, the average pyrene for the Pilot A and Pilot B conditions are not significantly different from one another, but are significantly different from the LPP condition.

The average pyrene for modes 10 and 11 are not significantly different from one another.

The trend in the average pyrene across the pilot conditions for the ADMM15, ALS, CA, and FT-100 fuels is significantly different than the trend for the DF-2 fuel. Whereas, the trends in the ADMM15, ALS, CA, and FT-100 fuels are relatively constant, the DF-2 fuel shows an increase in the average pyrene at the LPP condition.

There is no significant interaction in the average pyrene among the pilot condition and mode combinations or among the fuel and mode combinations.

Gaseous Pyrene Emissions

Figure 119. Test Fuel Average Gaseous Phase Pyrene Mass Emissions for Pilot Conditions and Modes (µg/kWh)

Gaseous Pyrene Emissions

Figure 120. Pilot Condition Average Gaseous Phase Pyrene Mass Emissions for Test Fuels and Modes (µg/kWh)

8.0   FUEL IMPACT ON EMISSIONS - MODE 12 (IDLE) LPP OPERATION

Fuel comparisons were made for brake specific exhaust emissions with the engine operated under LPP control with pilot fuel injection turned off for the Mode 12 idle condition. Due to the variability of the Mode 12 data, primarily due to engine load control, the idle data was analyzed separately from the other modal data. The ANOVA tables for the Mode 12 averages can be found in Appendix G.

8.1   Fuel Impact on Regulated Brake Specific Mass Emissions

Statistically significant trends, at 95% confidence, were not apparent from an ANOVA of the Mode 12 brake specific emissions data. Table 28 summarizes the general rank order for the regulated Mode 12 mass emissions during LPP engine operation with pilot fuel injection turned off. The table displays the fuels rank from highest response to lowest response for the Least-Square means of the analysis.

The discussions to follow are summaries of the multifactor ANOVA performed for each emission response for Mode 12, and refer to the results in Table 28. The ANOVA tables for the Mode 12 can be found in Appendix G.

8.1.1   Fuel Impact on Total Particulate, NO_X, HC, CO, CO_2, SOF of PM

At the 95% confidence level, no statistically significant differences were observed in the average regulated mass emissions among the test fuels at the idle condition.

8.2   Fuel Impact on Four Clean Air Act Toxic Air Pollutants

Table 29 is the ranking of the test fuels from multifactor ANOVA for the four EPA Clean Air Act toxic air pollutant compounds. For the EPA toxic air pollutants, ADMM15 and FT-100 were statistically similar emitting fuels.

The discussions to follow are summaries of the multifactor ANOVA performed for each emission response and refer to the results in Table 29. The ANOVA tables for the Mode 12 averages can be found in Appendix G.

Table 28. Mode 12 Mass Emissions (g/kWh) for LPP Operation			
Response	**LPP Only - Mode 12**		
	Fuel	**LS Means[1]**	**Significant Fuel Groups[2]**
BSPM	ALS	8.860	NS
	DF-2	8.418	
	CA	6.765	
	FT-100	3.546	
	ADMM15	2.903	
BSNO$_X$	ADMM15	20.85	NS
	DF-2	19.32	
	FT-100	18.78	
	ALS	18.71	
	CA	17.30	
BSHC	ALS	54.08	NS
	DF-2	53.40	
	CA	36.86	
	ADMM15	36.76	
	FT-100	28.17	
BSCO	DF-2	195.7	NS
	ALS	190.5	
	ADMM15	159.4	
	CA	127.7	
	FT-100	106.0	
BSCO$_2$	ALS	7174	NS
	FT-100	6754	
	ADMM15	6465	
	DF-2	5665	
	CA	4960	
BSSOF	ALS	8.602	NS
	DF-2	7.866	
	CA	6.365	
	FT-100	3.168	
	ADMM15	2.838	

[1]Fuels listed from highest to lowest least squares mean

[2]Letters designate groups of fuel means within which there are no statistically significant differences

NS = no statistically significant differences in the mean response at the 5% level of significance

Table 29.	Clean Air Act Toxic Air Pollutant Mass Emissions (mg/kWh) for Mode 12, LPP Operation		
Response	**LPP Only - Mode 12**		
	Fuel	**LS Means[1]**	**Significant Fuel Groups[2]**
Benzene	ALS	333.9	NS
	CA	249.6	
	DF-2	241.5	
	ADMM15	178.2	
	FT-100	118.0	
1,3-Butadiene	ALS	460.2	NS
	FT-100	282.9	
	DF-2	229.3	
	ADMM15	216.5	
	CA	196.9	
Formaldehyde	ALS	32241.5	NS
	DF-2	30348.2	
	ADMM15	29186.9	
	FT-100	23723.0	
	CA	18177.0	
Acetaldehyde	DF-2	13400.4	A
	ADMM15	10477.5	AB
	FT-100	8856.8	AB
	ALS	5079.8	B
	CA	2928.5	B

[1]Fuels listed from highest to lowest least squares mean

[2]Letters designate groups of fuel means within which there are no statistically significant differences

NS = no statistically significant differences in the mean response at the 5% level of significance

8.2.1 Benzene, 1,3-Butadiene, Formaldehyde

At the 95% confidence level, no statistically significant differences were apparent in the average benzene, 1,3-butadiene, or formaldehyde mass emissions among the fuels at the idle condition.

8.2.2 Acetaldehyde

The average acetaldehyde for the DF-2 fuel is significantly different than the ALS and CA fuels. The ADMM15 and FT100 fuels had statistically similar results for acetaldehyde.

8.3   Fuel Impact on Particulate Soluble Extract PAH Species – Mode 12

The fuel rankings for thirteen of the particulate bound soluble phase PAH compounds are shown in Table 30. Due to non-detects, four PAH compounds had insufficient data for the ANOVA modeling.   The   four   compounds   were   benzo[a]pyrene,   indeno(123-cd)pyrene, dibenzo(a,h)anthracene, and benzo(ghi)perylene. For the majority of PAH compounds, DF-2 fuel was statistically different from the other test fuels. The ADMM15 and FT-100 fuels were in the statistically equivalent (95% confidence) lowest grouping for the particulate bound PAH compounds.

The discussions to follow are summaries of the multifactor ANOVA performed for each emission response for Mode 12, and refer to the results in Table 30. The ANOVA tables for the Mode 12 averages can be found in Appendix G.

8.3.1 Naphthalene

No statistically significant differences were noted in the average naphthalene among the fuels.

8.3.2 Acenaphthylene

The average acenaphthylene for the DF-2 fuel is significantly different than the remaining four fuels.   The average acenaphthylene for the ADMM15, ALS, CA, and FT-100 fuels are not significantly different.

8.3.3 Acenaphthene

No statistically significant differences exist in the average acenaphthene among the fuels.

8.3.4 Fluorene

The average fluorene for the DF-2 fuel is significantly different than the ALS fuel.

	Table 30. Mode 12 Soluble Phase PAH Mass Emissions (µg/kWh) for LPP Operation		
Response	**LPP Only - Mode 12**		
	Fuel	**LS Means[1]**	**Significant Fuel Groups[2]**
Naphthalene	FT-100	822.2	NS
	DF-2	732.5	
	ADMM15	553.7	
	CA	541.6	
	ALS	192.2	
Acenaphthylene	DF-2	55.81	A
	CA	23.13	B
	ALS	11.38	B
	FT-100	10.55	B
	ADMM15	10.25	B
Acenaphthene	DF-2	120.1	NS
	FT-100	98.01	
	CA	94.66	
	ADMM15	78.07	
	ALS	29.89	
Fluorene	DF-2	334.9	A
	CA	219.8	AB
	FT-100	126.6	AB
	ADMM15	118.4	AB
	ALS	59.06	B
Phenanthrene	DF-2	11231	A
	CA	2331	B
	ALS	736.5	B
	FT-100	572.4	B
	ADMM15	459.1	B
Anthracene	DF-2	313.0	A
	CA	66.31	B
	FT-100	46.72	B
	ADMM15	37.82	B
	ALS	25.75	B
Fluoranthene	DF-2	1459.1	A
	CA	375.5	B
	ALS	205.0	B
	FT-100	144.6	B
	ADMM15	98.22	B
Pyrene	DF-2	4002	A
	CA	317.9	B
	ALS	307.0	B
	ADMM15	122.3	B
	FT-100	112.6	B

Table 30. Mode 12 Soluble Phase PAH Mass Emissions (μg/kWh) for LPP Operation (contd)			
Response	**LPP Only - Mode 12**		
	Fuel	**LS Means[1]**	**Significant Fuel Groups[2]**
Benzo[a]anthracene	DF-2	111.5	A
	CA	26.93	B
	ALS	11.47	B
	FT-100	4.490	B
	ADMM15	2.813	B
Chrysene	DF-2	310.1	A
	CA	57.34	B
	ALS	25.55	B
	FT-100	15.39	B
	ADMM15	8.133	B
Benzo[b]fluoranthene	DF-2	49.24	A
	CA	21.76	B
	ALS	16.87	B
	FT-100	10.49	B
	ADMM15	4.117	B
Benzo[k]fluoranthene	DF-2	35.45	A
	CA	15.26	B
	ALS	12.61	B
	FT-100	8.636	B
	ADMM15	5.015	B
Benzo[e]pyrene	DF-2	33.53	A
	CA	14.12	B
	ALS	10.28	B
	FT-100	9.774	B
	ADMM15	3.537	B
[1]Fuels listed from highest to lowest least squares mean			
[2]Letters designate groups of fuel means within which there are no statistically significant differences			
NS = no statistically significant differences in the mean response at the 5% level of significance			

8.3.5 Phenanthrene

The average phenanthrene for the DF-2 fuel is significantly different than the remaining four fuels. The average phenanthrene for the ADMM15, FT-100, ALS, and CA fuels are not significantly different from one another.

8.3.6 Anthracene

The average anthracene for the DF-2 fuel is significantly different than the remaining four fuels. The average anthracene for the ADMM15, ALS, CA, and FT-100 fuels are not significantly different from one another.

8.3.7 Fluoranthene

The average fluoranthene for the DF-2 fuel is significantly different than the remaining four fuels. The average fluoranthene for the ADMM15, ALS, CA, and FT-100 fuels are not significantly different from one another.

8.3.8 Pyrene

The average pyrene for the DF-2 fuel is significantly different than the remaining four fuels. The average pyrene for the ADMM15, ALS, CA, and FT-100 fuels are not significantly different from one another.

8.3.9 Benzo[a]anthracene

The average benzo[a]anthracene for the DF-2 fuel is significantly different than the remaining four fuels. The average benzo[a]anthracene for the ADMM15, ALS, CA, and FT-100 fuels are not significantly different from one another.

8.3.10   Chrysene

The average chrysene for the DF-2 fuel is significantly different than the remaining four fuels. The average chrysene for the ADMM15, ALS, CA, and FT-100 fuels are not significantly different from one another.

8.3.11   Benzo[b]fluoranthene

The average benzo[b]fluoranthene for the DF-2 fuel is significantly different than the remaining four fuels. The average benzo[b]fluoranthene for the ADMM15, ALS, CA, and FT-100 fuels are not significantly different from one another.

8.3.12   Benzo[k]fluoranthene

The average benzo[k]fluoranthene for the DF-2 fuel is significantly different than the remaining four fuels. The average benzo[k]fluoranthene for the ADMM15, ALS, CA, and FT-100 fuels are not significantly different from one another.

8.3.13   Benzo[e]pyrene

The average benzo[e]pyrene for the DF-2 fuel is significantly different than the remaining four fuels. The average benzo[e]pyrene for the ADMM15, ALS, CA, and FT-100 fuels are not significantly different from one another.

8.4   Fuel Impact on Gaseous PAH Species

The gas phase PAH emissions rank the test fuels in the general order shown in Table 31. Included in Table 31 are the least-square means from multifactor ANOVA, along with the statistically significant groupings for the Mode 12 mass emissions. The general trends were for DF-2 to have the highest gas phase PAH emissions, while ADMM15 and FT-100 were always in the statistically lowest grouping. The ANOVA for gas phase PAH species indicated the oxygenated diesel fuel, ADMM15, was statistically equivalent to FT-100 at the Mode 12, idle operating condition.

The discussions to follow are summaries of the multifactor ANOVA performed for each emission response for Mode 12, and refer to the results in Table 31. The ANOVA tables for the Mode 12 analysis can be found in Appendix G.

8.4.1 Naphthalene

There are two distinct fuel groupings with respect to the average naphthalene. The DF-2 and CA fuels are not significantly different from one another but are significantly different from the remaining three fuels. The ALS, ADMM15, and FT-100 fuels are not significantly different from one another, but are significantly different from the remaining two fuels.

8.4.2 2-Methylnaphthalene

There are three distinct fuel groupings with respect to the average 2-methylnaphthalene. The FT-100, ADMM15, and ALS fuels are not significantly different from one another, but are significantly different from the remaining two fuels. The CA and DF-2 fuels are significantly different from one another and the remaining three fuels.

Table 31. Mode 12 Gaseous Phase PAH Mass Emissions (µg/kWh) for LPP Operation			
Response	**LPP Only - Mode 12**		
	Fuel	**LS Means**[1]	**Significant Fuel Groups**[2]
Naphthalene	CA	182116	A
	DF-2	130839	A
	ALS	56374	B
	ADMM15	23713	B
	FT-100	6058	B
2-Methylnaphthalene	DF-2	212921	A
	CA	106437	B
	ALS	40671	C
	ADMM15	17201	C
	FT-100	2256	C
1-Methylnaphthalene	DF-2	139827	A
	CA	73642	B
	ALS	21018	C
	ADMM15	8078	C
	FT-100	1429	C
2,6-Dimethylnaphthalene	DF-2	127567	A
	CA	26261	B
	ALS	11261	B
	ADMM15	2048	B
	FT-100	1362	B
Acenaphthylene	DF-2	5591	A
	ALS	2638	B
	CA	1926	B
	ADMM15	953.8	B
	FT-100	888.2	B
Acenaphthene	DF-2	16107	A
	CA	2386	B
	ALS	1707	B
	ADMM15	907.6	B
	FT-100	195.8	B
Fluorene	DF-2	23660	A
	CA	2767	B
	ALS	939.1	B
	FT-100	305.1	B
	ADMM15	296.7	B
Phenanthrene	DF-2	25421	A
	CA	2267	B
	ALS	1891	B
	FT-100	699.8	B
	ADMM15	457.2	B

Table 31. Mode 12 Gaseous Phase PAH Mass Emissions (μg/kWh) for LPP Operation (contd)			
Response	LPP Only - Mode 12		
	Fuel	**LS Means[1]**	**Significant Fuel Groups[2]**
Anthracene	DF-2	533.1	A
	CA	129.7	B
	ALS	54.22	B
	FT-100	29.41	B
	ADMM15	22.40	B
Fluoranthene	CA	40.41	NS
	ALS	39.96	
	DF-2	29.95	
	FT-100	27.46	
	ADMM15	14.04	
Pyrene	DF-2	46.40	A
	ALS	39.48	AB
	CA	33.29	AB
	FT-100	21.80	AB
	ADMM15	12.70	B
[1]Fuels listed from highest to lowest least squares mean			
[2]Letters designate groups of fuel means within which there are no statistically significant differences			
NS = no statistically significant differences in the mean response at the 5% level of significance			

8.4.3 1-Methylnaphthalene

There are three distinct fuel groupings with respect to the average 1-methylnaphthalene. The FT-100, ADMM15, and ALS fuels are not significantly different from one another, but are significantly different from the remaining two fuels. The CA and DF-2 fuels are significantly different from one another and the remaining three fuels.

8.4.4 2,6-Dimethylnaphthalene

The average 2,6-dimethylnaphthalene for the DF-2 fuel is significantly different than the remaining four fuels. The average 2,6-dimethylnaphthalene for the ADMM15, ALS, CA, and FT-100 fuels are not significantly different from one another.

8.4.5 Acenaphthylene

The average acenaphthylene for the DF-2 fuel is significantly different than the remaining four fuels. The average acenaphthylene for the ADMM15, ALS, CA, and FT-100 fuels are not significantly different from one another.

8.4.6 Acenaphthene

The average acenaphthene for the DF-2 fuel is significantly different than the remaining four fuels. The average acenaphthene for the FT-100, ADMM15, ALS, and CA fuels are not significantly different from one another.

8.4.7 Fluorene

The average fluorene for the DF-2 fuel is significantly different than the remaining four fuels. The average fluorene for the ADMM15, ALS, CA, and FT-100 fuels are not significantly different from one another.

8.4.8 Phenanthrene

The average phenanthrene for the DF-2 fuel is significantly different than the remaining four fuels. The average phenanthrene for the ADMM15, ALS, CA, and FT-100 fuels are not significantly different from one another.

8.4.9 Anthracene

The average anthracene for the DF-2 fuel is significantly different than the remaining four fuels. The average anthracene for the ADMM15, ALS, CA, and FT-100 fuels are not significantly different from one another.

8.4.10   Fluoranthene

No statistically significant differences were apparent for the average fluoranthene among the fuels.

8.4.11   Pyrene

The average pyrene for the DF-2 fuel is significantly different than the ADMM15 fuel.

9.0   CONCLUSIONS

The project plan was fully coordinated with DOE and Industry through the Auto/Energy CIDI Ad Hoc Fuels Group. The industrial leaders specified the cylinder balance approach, specified the EGR levels for each of the five speed load conditions, and determined the modal weighting factors for the weighted averages. All fuels were evaluated in triplicate for five modes, with pilot injection off, IMEP of cylinders balanced within 5%, and the Location of Peak Pressure of combustion controlled to 7°ATDC.

Statistically significant (95% confidence) fuel effects on weighted average exhaust emissions were identified for both regulated and unregulated species, including CAA toxic and PAH compounds. The low sulfur fuel containing 15%v/v of the oxygenate dimethoxy methane (ADMM15) or Fischer-Tropsch (FT-100) fuels had the lowest overall weighted average emission response of the test fuels. For unburned hydrocarbons and carbon monoxide, FT-100 had the lowest significant ranking, with ADMM15 and its parent fuel in the next highest rank. DF-2 and pseudo-CARB fuel had the highest regulated emission rankings. For NOx, ADMM15 and FT-100 were not the highest emitters, but were in the second highest significant grouping. The oxygenated low sulfur diesel fuel was statistically the same as Fischer-Tropsch fuel for toxic air pollutants, gaseous and soluble PAH, and PM emissions. Although ADMM15 and FT-100 have statistically similar total PM response, the SOF for the two fuels is statistically different. The ADMM15 fuel has a larger fraction of SOF than the FT-100 fuel, which has the statistically smallest SOF of all test fuels.

For the regulated mass emissions the fuel rank order for the Modal LPP tests (modes 5,6,10,11), with pilot fuel injection off, reflect the results seen for the weighted averages. For HC, CO, and CO_2, the Modal emissions are significantly inversely proportional to BMEP. For NOx, the Modal emissions the results are significantly proportional to BMEP. There are two significant mode groupings for PM, modes 10 and 6 in one group, and modes 11 and 5 in another. There are Fuel * Mode interactions with the regulated emissions. For the CAA toxic compounds, the modal fuel rankings align with the weighted results, with some significant mode groupings. The mode groupings appear inversely proportional to BMEP for the toxic compounds. There are significant Fuel*Mode interactions with each toxic compound. The general trend for the PAH compounds during modal operation reflects the results seen in the weighted average case for fuel rank order.

The general modal effect for both gaseous and soluble PAH emissions were compound specific, and to some effect dependent on BMEP and the molecular weight of the compound.

A pilot fuel injection effect evaluation for all fuels was completed in triplicate for two modes and two pilot fuel injection control strategies. An ANOVA was performed on the pilot fuel injection data along with the same modal data from the non-pilot LPP control strategy. The LPP control with pilot fuel injection turned off was statistically the lowest control strategy for the four toxic air pollutants. The same statistical conclusion could be made for the other particulate PAH compounds. The effect of pilot fuel injection on exhaust emissions, compared to the LPP operation with pilot off, can be summarized as follows:

- PM emissions increase with pilot fuel injection
- NOx emissions decrease with pilot fuel injection
- The ratio of SOF/PM changed with pilot fuel injection condition, and appeared to be a function of the exhaust temperature
- Toxic air pollutant levels increase
- Both soluble and gas phase PAH increase with pilot fuel injection.

The fuel rank order for exhaust emissions with pilot fuel injection operation can be summarized as follows:

- PM rank for ADMM15 and FT-100 lowest, with DF-2 highest
- NOx rank is FT100 lowest, ADMM15 middle, and DF-2 highest
- The SOF of the PM was statistically lowest for FT-100
- Toxic air pollutant rank is FT-100 and ADMM15 lowest, with DF-2 highest
- Both soluble and gas phase PAH rank is FT100 and ADMM15 statistically similar as lowest, with DF-2 the highest emitting fuel.
- Pilot fuel injection changes the magnitude of the emission response, but does not significantly alter the fuel rank order.

Due to the variability of the Mode 12 data, primarily due to engine load control, the idle data was analyzed separately from the other modal data. No statistically significant (95% confidence) fuel effects on exhaust emissions were identified for the regulated species. For the CAA toxic compounds acetaldehyde at mode 12, there were significant fuel effects, with DF-2, ADMM15

and FT-100 being in the highest emitting significant group. For both soluble and gaseous PAH compounds there was either no significant groups or two groups with DF-2 always being in the highest emitting group. The ADMM15 and FT-100 fuels were generally the lowest emitting fuels or were in the lowest emitting group for the PAH compounds at idle.

10.0   RECOMMENDATIONS

The demonstrated effect of the oxygenate compound blended into low sulfur diesel fuel on lowering both regulated and unregulated emissions warrants further investigation. Although the oxygenate utilized in this study, dimethoxy methane, has shown positive emissions benefits, it is a poor choice for commercialization due to volatility characteristics. A parallel oxygenates program[14] has identified two suitable oxygen bearing compounds which warrant investigation as to oxygenate composition effects on toxic or PAH emissions.

There is evidence, Hilden[15] and Figure 121, that suggests oxygen bearing diesel fuels would tolerate further EGR before a smoke limit is reached, thus being beneficial for lowering engine out NOx. The impact on toxic emissions with increased EGR with oxygen bearing fuels warrants investigation.

Another effect of oxygen is the tendency to increase the SOF content of the total particulate matter, which may be beneficial for PM control with an oxidation catalyst. The oxidation of SOF in a catalyst may crack higher molecular weight PAH compounds into smaller ringed components and increased levels of gaseous PAH or toxic emissions. It would be recommended to evaluate the effect of an oxidation catalyst on toxic and PAH emissions.

To meet Tier 2 emission levels, engine out NOx emissions will need to be reduced, which will result in an increase in PM emissions. Thus, the use of a Diesel Particulate Filter (DPF) to meet Tier 2 PM emission levels may be required. However, the DPF will act as a trap that will periodically need regeneration to lower engine backpressure. The DPF may act as a PAH sponge, trapping toxic compounds that could be subject to the effects of thermopherisis. The potential change in gaseous PAH levels due to the accumulation of PM on a DPF warrants investigation.

Figure 121. OM611 Engine NOx-PM Emission Index Trade Off with Oxygenated Low Sulfur Diesel Fuel

11.0   REFERENCES

1. Sirman, M.B., Owens, E.C., Whitney, K.A., "Emissions Comparison of Alternative Fuels in an Advanced Automotive Diesel Engine," SAE Paper 2000-01-2048 (2000).

2. Likos, W.E., "Evaluation of Advanced Petroleum-Based Fuels, Interim Report TFLRF No. 356, January 2001.

3. Truax, T.J., and Norbeck, J.M., "Evaluation of Factors that Affect Diesel Exhaust Toxicity," Contract No. 94-312, California Air Resources Board, July 1998.

4. Schramm, J., Foldager, I.,Olsen, N. and Gratz, L., "Emissions from a Diesel Vehicle Operated on Alternative Fuels in Copenhagen," SAE Technical Paper 1999-01-3603, 1999.

5. Westerholm, R., Christensen, A., de Serves,C., Almen, J., "Determination of Polycyclic Aromatic Hydrocarbons (PAH) in Size Fractionated Diesel Particles from a Light Duty Vehicle", SAE Technical Paper 1999-01-3533, 1999.

6. Kuljukka, T., Savela, K., Peltonen, K., Mikkonen, S., Rantanen, L., "Effect of Fuel Reformulation on Diesel Particulate Emissions-Application of DNA Adduct Test," SAE Technical Paper 982650, 1998.

7. Collier, A., Jemma, C., Wedekind, B., Hall, D., and Heinze, P., "Sampling and Analysis of Vapor-Phase and Particulate-Bound PAH from Vehicle Exhaust," SAE Technical Paper 982727, 1998.

8. Tanaka, S., Takizawa, H., Shimizu, T., and Sanse, K., "Effect of Fuel Compositions on PAH in Particulate Matter from DI Diesel Engine," SAE Technical Paper 982648, 1998.

9. Doel, R. C., "Fuel Property Effects on Polyaromatic Hydrocarbon Emissions from Modern Heavy-Duty Engines," SAE Technical Paper 964117, 1996.

10. Andrews, G., Ishaq, R., Farrar-Khan, J., Shen. Y., and Williams, P., "The Influence of Speciated Diesel Fuel Composition on Speciated Particulate SOF Emissions," SAE Technical Paper 980527, 1998.

11. Mason, R.L., Gunst, R.F., and Hess, J.L., <u>Statistical Design and Analysis of Experiments with Applications to Engineering and Science</u>, John Wiley &Sons, Inc, 1989.

12. Milliken, G.A. and Johnson, D.E., <u>Analysis of Messy Data, Volume I: Designed Experiments</u>, Van Nostrand Reinhold, 1984.

13. Szymkowicz, P.G., French, D.T., and Crellin, C.C., "Effects of Advanced Fuels on the Particulate and NOx Emissions from an Optimized Light-Duty CIDI Engine," SAE Paper 2001-01-0148 (2001).

14. Naegeli, D.W., Moulton, S., Owens, E.C., and Frame, E.A., "Oxygenates for Advanced Petroleum-Based Diesel Fuels," Interim Report No. 357, February 2001.

15. Hilden, D.L., Eckstrom, J.C., and Wolf, L.R., "The Emissions Performance of Oxygenated Diesel Fuels in a Prototype DI Diesel Engine," SAE paper 2001-01-0650 (2001).

APPENDIX A

Toxic Air Pollutant Sample Procedure

COLLECTION OF ALDEHYDE ON SOLID PHASE DNPH CARTRIDGES AND GASEOUS HYDROCARBONS IN TEDLAR BAGS USING A GAS METERING CART

Leak Check

- Close sampling point valves on tunnel and dilution air box.

- Aldehyde Sampling Cart - Attach the intake and suction lines together without a DNPH cartridge in line.

- Turn on the "Sampling" Switch and observe the digital flow meter. The flow should diminish to at least 0.20 L/min on the number 1 sample counter.

- Open sampling point valves (2 each) on tunnel and (1 each) on dilution air box. Attach 1 Tedlar sample bag each to the ASample≅ pump and the Abackground≅ air pump.

- Attach 1 each labeled DNPH aldehyde cartridge to the "Sample" side and the "background" side of the sampling cart. (Blue coded line for background(1) and Yellow coded line for sample(2)). Flows are regulated so that the sample flow rate is 5 times the background flow rate.

Start of Test:

- In concert with the start of particulate sampling, begin timing the tests (30 min) with a stop watch. At start of test move the "sample" toggle switch 2 clicks upward. Simultaneously turn on the power strip to supply power to the bag sampling pumps.

- (The technician operating the particulate cart will give a "Start" sign.)

- After two minutes turn off the power to the "background" bag sampling pump.

- Sample with the DNPH cartridge and gas "sample" bag for 30 minutes.

- At some time during the test, record the barometric pressure, the LFE intake air temperature, and the ambient air temperatures. (These are displayed on the computer monitor on the test cell console.)

End of Test:

- Move "sample" toggle switch to bottom position.

- Turn off power to the bag sampling pump.

- Record the numbers on both top and bottom digital flow meters.

- Disconnect Sample Bag from Pump.

- Return background pump line switch to the Aon≅ position.

- As soon as practical, deliver the ASample≅ bag to DER GC lab.

- Leave background bag attached until end of test day. (Two minutes for each test.)

- Remove DNPH Sample Cartridge from flow stream cap ends and verify correct label.

- At end of test session, place the aggregate of DNPH cartridges in a zip-lock bag and deliver to DER lab #2 small refrig., under lab bench near vent hood.

REVISION 1

**COLLECTION OF ALDEHYDES ON SOLID PHASE DNPH CARTRIDGES
AND GASEOUS HYDROCARBONS IN TEDLAR BAGS USING GAS
METERING CART**

Revision 3/09/00

Due to overloading of some of the aldehyde cartridges,(using up all of the DNPH reagent), the sampling regime was modified as follows:

Zero Time

- ♦ Start Aldehyde Cart pumps, (no cartridges installed)
- ♦ Start Bag pumps

At 2 minutes

- ♦ Stop background bag pump
- ♦ Stop Aldehyde cart pumps
- ♦ Install cartridges, (sample and background)
- ♦ (this 2 minutes purges the sample lines with current sample)

At 3 minutes

- ♦ Start aldehyde cart pumps

At 8 minutes

- ♦ Close toggle valve to aldehyde "sample" cartridge.
- ♦ Read flow totalizer for "sample"
- ♦ Remove "sample" cartridge from flow stream
- ♦ (5-minute "sample" collection)

At 30 minutes

- ♦ Stop aldehyde cartridge pumps
- ♦ Stop "sample" bag pump
- ♦ Read flow totalizer for Background
- ♦ Remove background cartridge from flow stream, (set aside to reinstall 2 minutes into next test)
- ♦ Remove "sample bag" and transport to the chem lab for analyses.

APPENDIX B

Fuel Property Analysis

DOE Fuels Analysis 12/23/99			FISCHER-TROPSCH (FT100)	FISCHER-TROPSCH (FT100)	California Reference (CA)	California Reference (CA)	ALTER LOW S (ALS)	ALTER LOW S (ALS)	DMM/ALS BLEND (ADMM15)	DMM/ALS BLEND (ADMM15)	2D CERT (2D)
PROPERTY	UNITS	ASTM	SwRI	Core	SwRI	Core	SwRI	Core	SwRI	Core	SwRI
Density @ 15C	g/ml	D4052	0.7812		0.8378		0.8160		0.8201		0.8426
Distillation		D2887									
IBP	°C		145		145		140		58		
10%	°C		266		192		202		179		
50%	°C		302		251		280		273		
90%	°C		351		325		344		344		
95%	°C		359		339		362		360		
End point	°C		377		372		416		413		
Distillation		D86									
IBP	°C		215	233	189	192	207	210	42	40	183
10%	°C		258	256	215	214	232	232	73	61	216
50%	°C		289	287	255	253	276	275	264	261	260
90%	°C		325	323	309	308	322	321	319	312	309
95%	°C		332	330	321	321	334	334	332	325	325
End Point	°C		337	336	331	331	344	344	342	338	340
Cetane Number		D613	84	87	45	49	63	62	59		44
Cetane Index		D976	78		48		61		57		48
Kinematic Viscosity at 40°C	cSt	D445	3.2	3.1	2.4	2.3	2.9	2.9	1.9	1.7	2.4
Flash Point	°C	D93	98	99	72	70	87	87	<2(D56)	<24	71
Hydrogen	wt%	D5291	15.1		13.4		14.4		13.7		13.0
Carbon	wt%	D5291	84.8		86.4		85.6		81.6		86.7
Oxygen	wt%	difference	0.1		0.2		0.0		4.7		0.3
Nitrogen	μg/g	D4629	7.8		<1.0		<1		<1		60
Sulfur	ppm	D2622	1		176		1		1		337

DOE Fuels Analysis 12/23/99			FISCHER-TROPSCH (FT100)	FISCHER-TROPSCH (FT100)	California Reference (CA)	California Reference (CA)	ALTER LOW S (ALS)	ALTER LOW S (ALS)	DMM/ALS BLEND (ADMM15)	DMM/ALS BLEND (ADMM15)	2D CERT (2D)
PROPERTY	UNITS	ASTM	SwRI	Core	SwRI	Core	SwRI	Core	SwRI	Core	SwRI
Hydrocarbon Type:											
Total Aromatics	wt%	D5186	0.2	<0.1	18.9	18.6	9.0	9.1	8.2*	9	30.3
Mono	wt%	D5186	0.2		15.1		8.5		7.8*		21.4
Poly(Di+Tri)	wt%	D5186	<0.1		3.8		0.5		0.4*		8.9
Parafins	wt%	D2425	97.1		44.2		54.5		54.2*		42.8
Napthenes	wt%	D2425	2.9		37.8		36.9		31.9*		28.8
Water	ppm	D4928	45.0		105.0		77.0		368.0		98.0
Color		D1500	LO.5		L0.5		L0.5		L0.5		1.0
Clear and Bright		D4176	PASS		PASS		PASS		PASS		PASS
Particulates	mg/L	D6217	4.3		<0.01		0.8		0.7**		0.3
Copper Strip Corrosion		D130	1a		1a		1a(50C)		1a		1a
Cloud Point	°C	D2500	-1		-27		-4		-7		-18
Pour Point	°C	D976	-2		-32		-5		-9		-24
Carbon Residue	%	D524	0.071		0.220		0.080		0.038		0.240
Acid Number	mgKOH/g	D664	0.03		0.02		0.02		0.02		0.02
Oxidation Stability		D2274	0.20		0.20		<0.01		0.25***		<0.01
Net Heat of Combustion	MJ/kg	D240	43.9		42.7		43.3		40.8		42.5
Gross Heat of Combustion	MJ/kg	D241		47.2		46.0		46.8		42.0	
Lubricity	mm	D6079	0.59		0.27		0.57		0.49		0.57
BOCLE Scuff	grams	D6078	1900		4300		1600		1950		2850
Detergent	yes/no	unknown									
Sullfur by X-ray Spect	wt%	D4294				0.021					

*The DMM is interfering with these results

**DMM altered shape of filter and may be interfering with results

***Vigorious boiling occurred as sample came to temperature.

APPENDIX C

Pilot Fuel Injection Screening Study

PM Analysis Project: Pilot Fuel Injection Study

Objective
To determine if pilot injection on a direct-injected diesel engine with a Common-Rail fuel system exhibits impacts on engine gaseous and PM exhaust emissions. Ascertain if those impacts may effect the toxicity of the diesel exhaust.

Approach

Operate engine at each of five test modes utilizing three differing control strategies, using CARB fuel. The control approaches consisted of Location of Peak Pressure (LPP) without pilot injection, LPP with Pilot Injection (PILOT A), and the calibrated (PILOT B) engine strategy which also uses pilot injection. The LPP and PILOT A strategies were performed using an RPECS controller. Under RPECS control each cylinder was balanced within 5% of the engine average IMEP. The PILOT B strategy was performed with the OEM controller. The LPP was determined by fixing injection rail pressure, specified EGR, and setting the injector pulse width which met the BMEP setting for the mode. The Main Start of Injection timing was swept and the LPP was noted which produced best torque. When the location of peak pressure during PILOT A operation was determined, the Pilot-to-Main injection pulse width ratio, and the Pilot-to-Main timing gap was kept the same as the Calibrated settings for the mode.

The timings for the differing control strategies are outlined in Table C1 for each of the five test modes. Also shown in Table C1 are the EGR settings for the differing control modes. For the LPP and PILOT A strategies EGR was controlled at levels specified by the Ad Hoc Diesel Fuels committee. The PILOT B strategy controlled to EGR levels mapped by the engine manufacturer. Increased EGR levels are expected to decrease NOx response and increase PM response.

			LPP			PILOT B				PILOT A			
Mode	Speed	BMEP, bar	LPP*	MSOI‡	EGR, %	LPP	PSOI†	MSOI	EGR, %	LPP	PSOI	MSOI	EGR, %
12	900	.1	7	5	40	0	9	0	60	5	17	8	40
11	1500	2.62	7	9	30	12	18	2	36	7	24	8	30
10	2000	2	7	12	30	15	23	2	35	7	31	10	30
6	2300	4.2	7	14	15	10	28	4	19	7	38	13	15
5	2600	8.8	7	18	5	8	36	8	13	8	42	14	5

Table C1. Timing Parameters for Pilot Injection Study

*LPP - Location of Peak Pressure, dATDC
‡MSOI - Main Start of Injection, dBTDC
†PSOI - Pilot Start of Injection, dBTDC

The gaseous and Particulate Matter (PM) emissions were obtained for each test condition. The PM was then analyzed for the percentage of SOF. The hypothesis being major variations in PM and SOF mass emission rates between the control strategies would also result in different PAH levels.

Discussion

__Brake Specific Fuel Consumption__ – The brake specific fuel consumption (BSFC) for the different control strategies for the non-idle modes are shown in Figure C1. The engine was controlled to the same approximate brake output. Fuel consumption variations should reflect relative energy conversion efficiencies. In general the PILOT B control strategy sacrificed fuel

consumption with respect to either of the LPP control approaches. In general, the PILOT A has marginally higher BSFC, most likely due to an advanced initial burn caused by the advanced pilot injection. The idle BSFC shown in Figure C2 shows an improved BSFC for the PILOT B mode. Again the PILOT A has a slightly higher BSFC than the LPP mode. From Table A1, the idle mode (mode 12) has a slightly advanced pressure peak for best torque during PILOT A operation than the LPP mode. The peak pressure location for idle in the PILOT B mode appeared at TDC, however, there was a burn evident later in the cycle around 15° ATDC. For all modes during pilot, the location of peak pressure was not as steady, probably due to the variability of the ignition delay of the pilot injected fuel.

Oxides of Nitrogen – The Oxides of Nitrogen Emission Index (NOxEI) is shown in Figure C3. The NOxEI is the NOx mass emission rate as a percentage of the fuel flow for each mode and control strategy. From Figure C3, it is apparent that either LPP control approach results in higher NOxEI emissions than the PILOT B strategy. The PILOT B strategy appears to concentrate on lower NOxEI, at the expense of efficiency. Also apparent from Figure C3 is that the PILOT A approach reveals lower NOxEI levels than LPP control without pilot injection. The pilot operation has a reduced premixed burn, which may account for the lower NOxEI levels. The differences in EGR levels would also account for some of the NOxEI response seen between the PILOT B, LPP, and PILOT A control strategies. Higher EGR levels tend to result in a lower NOxEI.

Particulate Matter – The Particulate Matter Emission Index (PMEI) data are shown in Figure C4. The PMEI is the PM mass emission rate as a percentage of the fuel flow. As expected due to the NOxEI response, the PMEI levels are higher when pilot injection is utilized. The PILOT B strategy results in a the highest PMEI levels.

For the PM and the Soluble Organic Fraction (SOF) of the PM, specific mass emission rates are shown in Figures C5 and C6 respectively for the non-idle modes. The PM specific emissions are higher for the PILOT A and PILOT B mode of operation. The 2000 RPM/ 2 bar BMEP mode for PILOT B operation may have been influenced by a sample leak, the results do not follow the trends of the other modes. The SOF data in Figure C6 is plotted on the same scale as the PM results, thus relative SOF levels can be ascertained due to the mode of operation. Distinct SOF levels are apparent between the control strategies and each operating modes. Overall pilot injection appears to increase PM but reduce the level of SOF.

For the PM, and the Soluble Organic Fraction (SOF) of the PM, specific mass emission rates are shown in Figures C7 for the idle mode. The PM emission for the idle mode is higher for the PILOT B and PILOT A operation compared to LPP. The SOF is in similar proportions for the LPP and PILOT B modes of operation at idle.

Combustion – Cylinder pressure histories were recorded for each test mode and control strategy. Figure C8 is the cylinder pressure histories from cylinder #1 for Mode 11, 1500 RPM and 2.62 bar BMEP. From the pressure histories, it is evident the rate of pressure rise is lower when pilot operation is utilized. This is evident in the audible noise during engine operation.

The apparent heat release rates were calculated and are shown in Figure C9 for each control strategy. The relative timings of the pilot and main injection events are shown on the heat release curves. From the heat release traces the early burn is evident for the cases where pilot injection is utilized, PILOT B and PILOT A. Combustion occurs before TDC with pilot injection. Due to the very advanced injection in the PILOT A control mode, combustion appears to initiate around

8 degrees before TDC. Combustion initiates during PILOT B operation at around 6 degrees before TDC.

High initial combustion rates would be expected to correlate with NOx formation. The NOxEI data ranks the control strategies as would be expected from the burn rates. The magnitude of the tail of the burn curve would be expected to suggest relative PM levels. The PMEI data ranks with the relative magnitude of the tail of the burn curves for the three control strategies.

The shape and phasing of the burn curves suggest the timing of the pilot injection for the PILOT A control strategy may be to far advanced.   The pilot-to-main injection gap utilized under PILOT B operation was maintained for the PILOT A operation. A timing sweep study was performed to evaluate the effect of the Pilot-toMain Gap (PMGap) on BSFC, NOx, and Bosch Smoke Number (BSN). The sweeps were performed at mode 11, 1500 RPM/2.62 bar BMEP. The typical PILOT B values for this mode are a PMGap of 1.8 ms with a MSOI of 2 DBTDC. The MSOI utilized for LPP control is 8 DBTDC. The PMGap and MSOI for the PILOT A strategy was 1.8 ms and 8 DBTDC respectively. The range of PMGap was chosen by fixing injection quantity, and looking for a change in the torque response at different PMGaps. PMGaps longer than 1.8 ms and shorter than 1.4 ms resulted in large torque decreases. The sweeps were performed with constant injection pulse widths.

The data in Figure C10 represents one reading for BSFC at each PMGap and MSOI timing. As seen in Figure C11, a PMGap of 1.6 ms resulted in the most efficient operation, at all MSOI timings.

The NOx response shown in Figure C11 indicate MSOI timing is more critical than PMGap. As MSOI timing is advanced, NOx increases. The PMGap at 1.6 ms had the highest NOx response at each MSOI timing. Considering the efficiency improvement seen at 1.6ms PMGap, the higher NOx response is not unexpected.

The variations in BSN for the timing sweeps shown in Figure C12 were not expected. The BSN decreases with advanced MSOI, which coincides with PM-NOx tradeoff, and the NOx response. What was not anticipated was the smoke number relationship with respect to PMGap. The PMGap for the highest efficiency has the highest smoke levels, and as seen from Figure C12 the highest NOx.

	LPP{7ATDC}	Pilot "B"{OEM:LPP12-15}	Pilot "A"{LPP7}
☐ 2600 RPM/8.8 bar	0.358	0.377	0.359
☐ M6: 2300 RPM/4.2 bar	0.419	0.443	0.418
■ M10: 2000 RPM/2 bar	0.579	0.595	0.585
☐ M11: 1500 RPM/2.62 bar	0.461	0.472	0.457

Figure C1.   Brake Specific Fuel Consumption as a Function of Control Strategy

	LPP{7ATDC}	Pilot "B"{OEM:LPP12-15}	Pilot "A"{LPP7}
■ M12: 900 RPM/.1 bar	2.512	3.317	3.268

Figure C2. Idle Mode BSFC as a Function of Control Strategy

Figure C3. Oxides of Nitrogen Emission Index as a Function of Control Strategy

	LPP{7ATDC}	Pilot "B"{OEM:LPP12-15}	Pilot "A"{LPP7}
2600 RPM/8.8 bar	4.232%	1.354%	3.125%
M6: 2300 RPM/4.2 bar	2.123%	0.775%	2.004%
M10: 2000 RPM/2 bar	1.004%	0.292%	0.832%
M11: 1500 RPM/2.62 bar	0.960%	0.271%	0.810%
M12: 900 RPM/.1 bar	0.906%	0.053%	0.735%

Figure C4. Particulate Matter Emission Index as a Function of Control Strategy

	LPP{7ATDC}	Pilot "B"{OEM:LPP12-15}	Pilot "A"{LPP7}
2600 RPM/8.8 bar	0.077%	0.174%	0.080%
M6: 2300 RPM/4.2 bar	0.115%	0.268%	0.119%
M10: 2000 RPM/2 bar	0.091%	0.102%	0.111%
M11: 1500 RPM/2.62 bar	0.083%	0.145%	0.091%
M12: 900 RPM/.1 bar	0.726%	0.811%	0.777%

Figure C5. PM Specific Mass Emission Rates

Figure C6. Soluble Organic Fraction Specific Mass Emission Rates

Figure C7. Idle Mode PM Specific Mass Emission Rates

Figure C8. Cylinder Pressure Histories as a Function of Control Strategy

Mode 11; 1500rpm/2.62bar

PSOI = Pilot Start of Injection
MSOI = Main Start of Injection

Legend:
- LPP
- Pilot "B"
- Pilot "A"

Y-axis: Apparent Heat Release Rate, J/deg.
X-axis: Crank Angle

Labels: PSOI(Pilot "A"), MSOI(LPP), MSOI(Pilot "B"), PSOI(Pilot "B"), MSOI(Pilot "B")

Figure C9. Heat Release Rates as a Function of Control Strategy

Mode 11: BSFC vs. MSOI & PM Gap

Y-axis: BSFC (lb/hp-hr)
X-axis: MSOI (DBTDC): 2, 5, 8, 10
Depth axis: PM Gap (ms): 1.4, 1.6, 1.8

Figure C10. Brake Specific Fuel Consumption for Mode 11 Timing Sweeps

C-10

Mode 11: NO$_x$ vs. MSOI & PM Gap

Figure C11. Oxides on Nitrogen for Mode 11 Timing Sweeps

Mode 11: Smoke vs. MSOI & PM Gap

Figure C12. Bosch Smoke Number for Mode 11 Timing Sweeps

APPENDIX D

ANOVA for Weighted Averages

TABLE OF CONTENTS

```
Multifactor ANOVA - Total Particulates (g/kW-hr)
                 LPP Only    Weighted Modes 5, 6, 10, and 11

Analysis Summary

Dependent variable: wpm
Factors:
        fuel

Number of complete cases: 15
```

Scatterplot by Level Code


```
Analysis of Variance for wpm - Type III Sums of Squares
--------------------------------------------------------------------------------
Source                Sum of Squares    Df    Mean Square    F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                   0.0584894     4      0.0146223      48.38    0.0000

RESIDUAL                  0.00302259   10     0.000302259
--------------------------------------------------------------------------------
TOTAL (CORRECTED)         0.061512     14
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.
```

CONCLUSION: Statistically significant differences in the average weighted
particulates among the fuels.

Means and 95% Tukey HSD Intervals

CONCLUSION: Average particulate at fuels FT-100 and ADMM15 are not significantly
different from one another, but are different than the other three fuels. The average
particulate at Fuel ALS is significantly different than Fuel DF-2. The CA fuel is not
significantly different than either the ALS or DF-2 fuel.

```
Multiple Range Tests for wpm by fuel

--------------------------------------------------------------------------------
```

```
Method: 95.0 percent Tukey HSD
fuel            Count    LS Mean         Homogeneous Groups
--------------------------------------------------------------------------------
FT-100          3        0.133692        X
ADMM15          3        0.143126        X
ALS             3        0.224882         X
CA              3        0.262719         XX
DF-2            3        0.288757          X
--------------------------------------------------------------------------------
Contrast                                 Difference        +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                             *-0.0817558       0.0467219
ADMM15 - CA                              *-0.119593        0.0467219
ADMM15 - DF-2                            *-0.145631        0.0467219
ADMM15 - FT-100                           0.00943372       0.0467219
ALS - CA                                 -0.0378373        0.0467219
ALS - DF-2                               *-0.0638755       0.0467219
ALS - FT-100                             *0.0911895        0.0467219
CA - DF-2                                 -0.0260382       0.0467219
CA - FT-100                              *0.129027         0.0467219
DF-2 - FT-100                            *0.155065         0.0467219
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

D-4

```
Multifactor ANOVA - BSNOX (g/Kw-hr)
                  LPP Only   Weighted Modes 5, 6, 10, and 11

Analysis Summary

Dependent variable: wbsnox
Factors:
        fuel

Number of complete cases: 15
```

Scatterplot by Level Code


```
Analysis of Variance for wbsnox - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                  2.42468      4        0.60617     27.97    0.0000

RESIDUAL                 0.21674     10        0.021674
--------------------------------------------------------------------------------
TOTAL (CORRECTED)        2.64142     14
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.
```

```
CONCLUSION:  Statistically significant differences in the average weighted BSNOX
among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average weighted BSNOX for the DF-2 fuel is significantly different
from the remaining for fuels.  The other finding is the average weighted BSNOX for the
ADMM15 fuel is significantly different than the ALS fuel.

Multiple Range Tests for wbsnox by fuel

--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
fuel            Count     LS Mean          Homogeneous Groups
```

D-5

```
---------------------------------------------------------------------------
ALS             3        3.14535          X
CA              3        3.43069          XX
FT-100          3        3.4413           XX
ADMM15          3        3.71901           X
DF-2            3        4.33103            X
---------------------------------------------------------------------------
Contrast                                Difference      +/-  Limits
---------------------------------------------------------------------------
ADMM15 - ALS                            *0.573659       0.39564
ADMM15 - CA                              0.28832        0.39564
ADMM15 - DF-2                           *-0.612027      0.39564
ADMM15 - FT-100                          0.277703       0.39564
ALS - CA                                -0.28534        0.39564
ALS - DF-2                              *-1.18569       0.39564
ALS - FT-100                            -0.295956       0.39564
CA - DF-2                               *-0.900347      0.39564
CA - FT-100                             -0.0106164      0.39564
DF-2 - FT-100                           *0.889731       0.39564
---------------------------------------------------------------------------
```

* denotes a statistically significant difference.

D-6

```
Multifactor ANOVA - BSHC (g/kW-hr)
                   LPP Only   Weighted Modes 5, 6, 10, and 11

Analysis Summary

Dependent variable: wbshc
Factors:
        fuel

Number of complete cases: 15
```

Scatterplot by Level Code


```
Analysis of Variance for wbshc - Type III Sums of Squares
-------------------------------------------------------------------------------
Source               Sum of Squares   Df   Mean Square   F-Ratio   P-Value
-------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                  2.10344       4     0.52586      79.11     0.0000

RESIDUAL                 0.0664694    10    0.00664694
-------------------------------------------------------------------------------
TOTAL (CORRECTED)        2.16991      14
-------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.


CONCLUSION:  Statistically significant differences in the average weighted BSHC
among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average weighted BSHC for the FT-100 fuel is significantly different
from the remaining four fuels.  The other fuels can be divided into two distinct fuel
groupings.  The ADMM15 and ALS fuels are not significantly different from one another,
but are different from the CA and DF-2 fuels.  The CA and DF-2 fuels are not
significantly
different from one another.

Multiple Range Tests for wbshc by fuel
```

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
fuel          Count    LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
FT-100          3       0.39346          X
ADMM15          3       0.676601          X
ALS             3       0.784842          X
CA              3       1.22085            X
DF-2            3       1.42769            X
--------------------------------------------------------------------------------
Contrast                                  Difference        +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                               -0.108241        0.2191
ADMM15 - CA                               *-0.54425         0.2191
ADMM15 - DF-2                             *-0.751084        0.2191
ADMM15 - FT-100                           *0.283142         0.2191
ALS - CA                                  *-0.436009        0.2191
ALS - DF-2                                *-0.642843        0.2191
ALS - FT-100                              *0.391383         0.2191
CA - DF-2                                  -0.206834        0.2191
CA - FT-100                               *0.827392         0.2191
DF-2 - FT-100                             *1.03423          0.2191
--------------------------------------------------------------------------------
* denotes a statistically significant difference.
```

```
Multifactor ANOVA - BSCO (g/kW-hr)
                   LPP Only   Weighted Modes 5, 6, 10, and 11


Analysis Summary


Dependent variable: wbsco
Factors:
        fuel


Number of complete cases: 15
```

Scatterplot by Level Code


```
Analysis of Variance for wbsco - Type III Sums of Squares
--------------------------------------------------------------------------------
Source               Sum of Squares   Df   Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                    22.2863     4      5.57158     116.78    0.0000


RESIDUAL                  0.477119    10    0.0477119
--------------------------------------------------------------------------------
TOTAL (CORRECTED)          22.7635    14
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.


CONCLUSION:  Statistically significant differences in the average weighted BSCO
among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average weighted BSCO for the FT-100 fuel is significantly different
from the remaining four fuels.  The other fuels can be dividied into two distinct fuel
groupings.  The ADMM15 and the ALS fuels are not significantly different from one
another,
but are different from the CA and DF-2 fuels.  The CA and DF-2 fuels are not
significantly
different from one another.


Multiple Range Tests for wbsco by fuel
```

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
fuel            Count     LS Mean         Homogeneous Groups
--------------------------------------------------------------------------------
FT-100          3         1.82976         X
ADMM15          3         3.0948           X
ALS             3         3.23579          X
CA              3         4.93057           X
DF-2            3         5.06338           X
--------------------------------------------------------------------------------
Contrast                                   Difference        +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                                -0.140994        0.587008
ADMM15 - CA                                *-1.83578         0.587008
ADMM15 - DF-2                              *-1.96858         0.587008
ADMM15 - FT-100                            *1.26504          0.587008
ALS - CA                                   *-1.69478         0.587008
ALS - DF-2                                 *-1.82759         0.587008
ALS - FT-100                               *1.40603          0.587008
CA - DF-2                                    -0.132808       0.587008
CA - FT-100                                *3.10082          0.587008
DF-2 - FT-100                              *3.23362          0.587008
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

```
Multifactor ANOVA - BSCO2 (g/kW-hr)
                LPP Only   Weighted Modes 5, 6, 10, and 11

Analysis Summary

Dependent variable: wbsco2
Factors:
        fuel

Number of complete cases: 15
```

Scatterplot by Level Code


```
Analysis of Variance for wbsco2 - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                 13720.5       4       3430.12      16.43    0.0002

RESIDUAL                2087.39      10        208.739
--------------------------------------------------------------------------------
TOTAL (CORRECTED)       15807.9      14
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average weighted BSCO2
among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average weighted BSCO2 for the ADMM15 fuel is significantly different
than the ALS, CA, and FT-100 fuels.  Also, the average weighted BSCO2 for the FT-100
fuel is significantly different than the DF-2 fuel.

Multiple Range Tests for wbsco2 by fuel

--------------------------------------------------------------------------------
```

```
Method: 95.0 percent Tukey HSD
fuel            Count    LS Mean        Homogeneous Groups
--------------------------------------------------------------------------------
FT-100          3        874.221         X
ALS             3        910.932         XX
CA              3        911.941         XX
DF-2            3        947.978          XX
ADMM15          3        959.394          X
--------------------------------------------------------------------------------
Contrast                                Difference        +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                            *48.4621           38.8269
ADMM15 - CA                             *47.4526           38.8269
ADMM15 - DF-2                            11.4164           38.8269
ADMM15 - FT-100                         *85.1726           38.8269
ALS - CA                                 -1.00949          38.8269
ALS - DF-2                              -37.0457           38.8269
ALS - FT-100                            36.7105            38.8269
CA - DF-2                               -36.0362           38.8269
CA - FT-100                             37.72              38.8269
DF-2 - FT-100                           *73.7562           38.8269
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

```
Multifactor ANOVA - BSSOF (g/kW-hr)
                 LPP Only   Weighted Modes 5, 6, 10, and 11

Analysis Summary

Dependent variable: wbssof
Factors:
        fuel

Number of complete cases: 14
```

Scatterplot by Level Code


```
Analysis of Variance for wbssof - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares   Df   Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel               0.0434396       4     0.0108599     65.70    0.0000

RESIDUAL              0.00148772      9   0.000165303
--------------------------------------------------------------------------------
TOTAL (CORRECTED)    0.0449273       13
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average weighted BSSOF
among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  There are four distinct fuel groupings with respect to the average
weighted BSSOF.  The FT-100, ADMM15, and ALS fuels are significantly different from
one another and the remaining two fuels.  The CA and DF-2 fuels are not significantly
different from one another, but are significantly different from the other three fuels.

Multiple Range Tests for wbssof by fuel

--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
```

```
fuel            Count   LS Mean         Homogeneous Groups
-----------------------------------------------------------------------------
FT-100          2       0.0722652       X
ADMM15          3       0.123734         X
ALS             3       0.160837          X
CA              3       0.220703           X
DF-2            3       0.227858           X
-----------------------------------------------------------------------------
Contrast                                Difference      +/-  Limits
-----------------------------------------------------------------------------
ADMM15 - ALS                            *-0.0371037     0.0352706
ADMM15 - CA                             *-0.096969      0.0352706
ADMM15 - DF-2                           *-0.104124      0.0352706
ADMM15 - FT-100                         *0.0514686      0.0394337
ALS - CA                                *-0.0598653     0.0352706
ALS - DF-2                              *-0.0670201     0.0352706
ALS - FT-100                            *0.0885723      0.0394337
CA - DF-2                                -0.00715478    0.0352706
CA - FT-100                             *0.148438       0.0394337
DF-2 - FT-100                           *0.155592       0.0394337
-----------------------------------------------------------------------------
```

* denotes a statistically significant difference.

D-14

```
Multifactor ANOVA - Benzene (mg/kW-hr)   Toxic Gaseous Emissions
                    LPP Only   Weighted Modes 5, 6, 10, and 11

Analysis Summary

Dependent variable: wbenz
Factors:
        fuel

Number of complete cases: 15
```

Scatterplot by Level Code


```
Analysis of Variance for wbenz - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares   Df    Mean Square   F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                63.8974        4      15.9744      25.90     0.0000

RESIDUAL               6.16766       10      0.616766
--------------------------------------------------------------------------------
TOTAL (CORRECTED)     70.0651        14
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.


CONCLUSION:  Statistically significant differences in the average weighted benzene
among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  Average weighted benzene at fuels ADMM15 and FT-100 are not significantly
different from one another, but are different than the other three fuels.  The
average weighted benzene at fuel ALS is significantly different than fuel CA.  The
DF-2 fuel is not significantly different than either the ALS or CA fuel.

Multiple Range Tests for wbenz by fuel

--------------------------------------------------------------------------------
```

D-15

```
Method: 95.0 percent Tukey HSD
fuel          Count    LS Mean         Homogeneous Groups
----------------------------------------------------------------------------
ADMM15          3       2.07455          X
FT-100          3       2.50431          X
ALS             3       5.01701           X
DF-2            3       6.35954           XX
CA              3       7.29669            X
----------------------------------------------------------------------------
Contrast                                 Difference       +/-  Limits
----------------------------------------------------------------------------
ADMM15 - ALS                             *-2.94246        2.11053
ADMM15 - CA                              *-5.22215        2.11053
ADMM15 - DF-2                            *-4.28499        2.11053
ADMM15 - FT-100                           -0.429765       2.11053
ALS - CA                                 *-2.27968        2.11053
ALS - DF-2                                -1.34253        2.11053
ALS - FT-100                             *2.5127          2.11053
CA - DF-2                                  0.937154       2.11053
CA - FT-100                              *4.79238         2.11053
DF-2 - FT-100                            *3.85523         2.11053
----------------------------------------------------------------------------
* denotes a statistically significant difference.
```

```
Multifactor ANOVA - 1,3 Butadiene (mg/Kw-hr)   Toxic Gaseous Emissions
                  LPP Only   Weighted Modes 5, 6, 10, and 11

Analysis Summary

Dependent variable: wbutad
Factors:
        fuel

Number of complete cases: 15
```

Scatterplot by Level Code


```
Analysis of Variance for wbutad - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares   Df   Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                  23.8799      4      5.96997      23.71    0.0000

RESIDUAL                 2.51827     10      0.251827
--------------------------------------------------------------------------------
TOTAL (CORRECTED)        26.3981     14
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average weighted
1,3 butadiene among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average weighted 1,3 butadiene for the CA and DF-2 fuels are not
significantly different from one another, but are sigificantly different than the
ADMM15 and FT-100 fuels.  The ADMM15 and FT-100 fuels are not significantly different
from one another.  Also, the average weighted 1,3 butadiene for the ALS fuel is
significantly different than the FT-100 fuel.


Multiple Range Tests for wbutad by fuel
```

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
fuel            Count    LS Mean         Homogeneous Groups
--------------------------------------------------------------------------------
FT-100          3        2.64965         X
ADMM15          3        3.921           XX
ALS             3        4.81705          XX
DF-2            3        5.77838           X
CA              3        6.10812           X
--------------------------------------------------------------------------------
Contrast                                 Difference        +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                             -0.896042         1.3486
ADMM15 - CA                             *-2.18711          1.3486
ADMM15 - DF-2                           *-1.85738          1.3486
ADMM15 - FT-100                          1.27135           1.3486
ALS - CA                                 -1.29107          1.3486
ALS - DF-2                               -0.961334         1.3486
ALS - FT-100                            *2.16739           1.3486
CA - DF-2                                0.329738          1.3486
CA - FT-100                             *3.45846           1.3486
DF-2 - FT-100                           *3.12873           1.3486
--------------------------------------------------------------------------------

* denotes a statistically significant difference.
```

D-18

```
Multifactor ANOVA - Formaldehyde (mg/kW-hr)   Toxic Gaseous Emissions
                 LPP Only   Weighted Modes 5, 6, 10, and 11

Analysis Summary

Dependent variable: wform
Factors:
        fuel

Number of complete cases: 14
```

Scatterplot by Level Code


```
Analysis of Variance for wform - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                132754.0       4       33188.4      9.01     0.0033

RESIDUAL                33150.2       9       3683.35
--------------------------------------------------------------------------------
TOTAL (CORRECTED)      165904.0      13
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average weighted
formaldehyde among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average weighted formaldehyde for the DF-2 fuel is significantly
different than the FT-100 and the ADMM15 fuels.


Multiple Range Tests for wform by fuel

--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
fuel            Count     LS Mean          Homogeneous Groups
```

```
--------------------------------------------------------------------------------
FT-100          3          206.837          X
ADMM15          3          267.08           X
CA              2          332.429          XX
ALS             3          366.759          XX
DF-2            3          484.198           X
--------------------------------------------------------------------------------
Contrast                                    Difference      +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                                 -99.6792       166.493
ADMM15 - CA                                  -65.3484       186.144
ADMM15 - DF-2                               *-217.118       166.493
ADMM15 - FT-100                               60.2428       166.493
ALS - CA                                      34.3309       186.144
ALS - DF-2                                   -117.439       166.493
ALS - FT-100                                 159.922        166.493
CA - DF-2                                    -151.77        186.144
CA - FT-100                                  125.591        186.144
DF-2 - FT-100                               *277.361        166.493
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

```
Multifactor ANOVA - Acetaldehyde (mg/kW-hr)   Toxic Gaseous Emissions
                   LPP Only   Weighted Modes 5, 6, 10, and 11

Analysis Summary

Dependent variable: wacet
Factors:
        fuel

Number of complete cases: 14
```

Scatterplot by Level Code

Analysis of Variance for wacet - Type III Sums of Squares

Source	Sum of Squares	Df	Mean Square	F-Ratio	P-Value
MAIN EFFECTS					
A:fuel	20482.6	4	5120.64	9.15	0.0031
RESIDUAL	5037.78	9	559.754		
TOTAL (CORRECTED)	25520.3	13			

```
All F-ratios are based on the residual mean square error.
```

```
CONCLUSION:  Statistically significant differences in the average weighted
acetaldehyde among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average weighted acetaldehyde for the DF-2 fuel is significantly
different than the FT-100 or ADMM15 fuels.  The FT-100 and ADMM15 fuels are not
significantly different from one another.  Also, the average weighted acetaldehyde
for the FT-100 fuel is significantly different than the ALS fuel.
```

```
Multiple Range Tests for wacet by fuel
```

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
fuel           Count     LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
FT-100         3         75.0123          X
ADMM15         3         92.391           XX
CA             2         126.023          XXX
ALS            3         148.784           XX
DF-2           3         177.029           X
--------------------------------------------------------------------------------
Contrast                                  Difference         +/-   Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                              -56.3933           64.904
ADMM15 - CA                               -33.6324           72.5649
ADMM15 - DF-2                             *-84.6377          64.904
ADMM15 - FT-100                           17.3787            64.904
ALS - CA                                  22.7609            72.5649
ALS - DF-2                                -28.2445           64.904
ALS - FT-100                              *73.772            64.904
CA - DF-2                                 -51.0053           72.5649
CA - FT-100                               51.0111            72.5649
DF-2 - FT-100                             *102.016           64.904
--------------------------------------------------------------------------------

* denotes a statistically significant difference.
```

```
Multifactor ANOVA - Naphthalene (micro g/kW-hr)   Gaseous PAH
                    LPP Only   Weighted Modes 5, 6, 10, and 11

Analysis Summary

Dependent variable: wgnap
Factors:
        fuel

Number of complete cases: 15
```

Scatterplot by Level Code


```
Analysis of Variance for wgnap - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                5.82625E7      4     1.45656E7      63.89    0.0000

RESIDUAL               2.27967E6     10      227967.0
--------------------------------------------------------------------------------
TOTAL (CORRECTED)      6.05421E7     14
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.


CONCLUSION:  Statistically significant differences in the average weighted
naphthalene among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  There are three distinct fuel groupings with respect to the average
weighted naphthalene.  FT-100, ADMM15, and ALS fuels are not significantly different
from one another, but they are significantly different from the other two fuels.
The DF-2 and CA fuels are significantly different from one another and the remaining
three fuels.


Multiple Range Tests for wgnap by fuel
```

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
fuel          Count     LS Mean         Homogeneous Groups
--------------------------------------------------------------------------------
FT-100        3         252.517         X
ADMM15        3         467.144         X
ALS           3         1126.8          X
DF-2          3         3226.07          X
CA            3         5435.61           X
--------------------------------------------------------------------------------
Contrast                                Difference        +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                            -659.659          1283.12
ADMM15 - CA                             *-4968.46         1283.12
ADMM15 - DF-2                           *-2758.93         1283.12
ADMM15 - FT-100                          214.627          1283.12
ALS - CA                                *-4308.8          1283.12
ALS - DF-2                              *-2099.27         1283.12
ALS - FT-100                             874.286          1283.12
CA - DF-2                               *2209.53          1283.12
CA - FT-100                             *5183.09          1283.12
DF-2 - FT-100                           *2973.56          1283.12
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

```
Multifactor ANOVA - 2-Methylnaphthalene (micro g/kW-hr)   Gaseous PAH
                  LPP Only   Weighted Modes 5, 6, 10, and 11

Analysis Summary

Dependent variable: wmeth2
Factors:
        fuel

Number of complete cases: 15
```


Scatterplot by Level Code

```
Analysis of Variance for wmeth2 - Type III Sums of Squares
--------------------------------------------------------------------------------
Source                Sum of Squares    Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                   5.0131E7        4     1.25327E7      40.17     0.0000

RESIDUAL                  3.12018E6       10     312018.0
--------------------------------------------------------------------------------
TOTAL (CORRECTED)         5.32512E7       14
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average weighted
2-Methylnaphthalene among the fuels.
```


Means and 95% Tukey HSD Intervals

```
CONCLUSION:  There are three distinct fuel groupings with respect to the average
weighted 2-Methylnaphthalene.  FT-100, ADMM15, and ALS fuels are not significantly
different from one another, but they are significantly different from the other two
fuels.  The DF-2 and CA fuels are significantly different from one another and the
remaining three fuels.

Multiple Range Tests for wmeth2 by fuel
```

D-25

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
fuel            Count      LS Mean        Homogeneous Groups
--------------------------------------------------------------------------------
FT-100          3          113.904        X
ADMM15          3          238.762        X
ALS             3          737.313        X
CA              3          3064.71         X
DF-2            3          4750.08         X
--------------------------------------------------------------------------------
Contrast                                  Difference       +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                              -498.551         1501.14
ADMM15 - CA                               *-2825.95        1501.14
ADMM15 - DF-2                             *-4511.32        1501.14
ADMM15 - FT-100                           124.858          1501.14
ALS - CA                                  *-2327.4         1501.14
ALS - DF-2                                *-4012.77        1501.14
ALS - FT-100                              623.409          1501.14
CA - DF-2                                 *-1685.37        1501.14
CA - FT-100                               *2950.8          1501.14
DF-2 - FT-100                             *4636.18         1501.14
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

D-26

```
Multifactor ANOVA - 1-Methylnaphthalene (micro g/kW-hr)   Gaseous PAH
                  LPP Only   Weighted Modes 5, 6, 10, and 11

Analysis Summary

Dependent variable: wmeth1
Factors:
        fuel

Number of complete cases: 15
```


Scatterplot by Level Code

```
Analysis of Variance for wmeth1 - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares    Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                2.27955E7        4     5.69887E6      40.86     0.0000

RESIDUAL               1.39457E6       10      139457.0
--------------------------------------------------------------------------------
TOTAL (CORRECTED)      2.419E7         14
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average weighted
1-Methylnapthalene among the fuels.
```


Means and 95% Tukey HSD Intervals

```
CONCLUSION:  There are three distinct fuel groupings with respect to the average
weighted 1-Methylnaphthalene.  FT-100, ADMM15, and ALS fuels are not significantly
different from one another, but they are significantly different from the other
two fuels.  The DF-2 and CA fuels are significantly different from one another and
the remaining three fuels.


Multiple Range Tests for wmeth1 by fuel
```

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
fuel            Count    LS Mean        Homogeneous Groups
--------------------------------------------------------------------------------
FT-100          3        65.7216           X
ADMM15          3        111.076           X
ALS             3        409.914           X
CA              3        1712.61            X
DF-2            3        3267.99            X
--------------------------------------------------------------------------------
Contrast                                Difference        +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                              -298.838         1003.58
ADMM15 - CA                             *-1601.54          1003.58
ADMM15 - DF-2                           *-3156.91          1003.58
ADMM15 - FT-100                           45.3542          1003.58
ALS - CA                                *-1302.7           1003.58
ALS - DF-2                              *-2858.08          1003.58
ALS - FT-100                              344.192          1003.58
CA - DF-2                               *-1555.38          1003.58
CA - FT-100                             *1646.89           1003.58
DF-2 - FT-100                           *3202.27           1003.58
--------------------------------------------------------------------------------

* denotes a statistically significant difference.
```

D-28

```
Multifactor ANOVA - 2,6-Dimethylnaphthalene (micro g/kW-hr)   Gaseous PAH
                     LPP Only   Weighted Modes 5, 6, 10, and 11

Analysis Summary

Dependent variable: wdimeth
Factors:
        fuel

Number of complete cases: 15
```


Scatterplot by Level Code

```
Analysis of Variance for wdimeth - Type III Sums of Squares
--------------------------------------------------------------------------------
Source                 Sum of Squares    Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                   2.54445E7        4     6.36112E6      31.74     0.0000

RESIDUAL                  2.00436E6       10     200436.0
--------------------------------------------------------------------------------
TOTAL (CORRECTED)         2.74488E7       14
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average weighted
2,6-Dimethylnaphthalene among the fuels.
```


Means and 95% Tukey HSD Intervals

```
CONCLUSION:  The average weighted 2,6-Dimethylnaphthalene for the DF-2 fuel is
significantly different than the other four fuels.  The average weighted
2,6-Dimethylnaphthalene among the FT-100, ADMM15, ALS, and CA fuels are not
significantly different from one another.


Multiple Range Tests for wdimeth by fuel
```

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
fuel            Count      LS Mean           Homogeneous Groups
--------------------------------------------------------------------------------
FT-100          3          44.7092           X
ADMM15          3          48.8125           X
ALS             3          242.317           X
CA              3          722.341           X
DF-2            3          3461.53            X
--------------------------------------------------------------------------------
Contrast                                     Difference        +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                                 -193.504          1203.15
ADMM15 - CA                                  -673.529          1203.15
ADMM15 - DF-2                                *-3412.71         1203.15
ADMM15 - FT-100                              4.10334           1203.15
ALS - CA                                     -480.025          1203.15
ALS - DF-2                                   *-3219.21         1203.15
ALS - FT-100                                 197.607           1203.15
CA - DF-2                                    *-2739.19         1203.15
CA - FT-100                                  677.632           1203.15
DF-2 - FT-100                                *3416.82          1203.15
--------------------------------------------------------------------------------

* denotes a statistically significant difference.
```

D-30

```
Multifactor ANOVA - Acenaphthylene (micro g/kW-hr)   Gaseous PAH
                   LPP Only   Weighted Modes 5, 6, 10, and 11

Analysis Summary

Dependent variable: wgace
Factors:
        fuel

Number of complete cases: 15
```

Scatterplot by Level Code


```
Analysis of Variance for wgace - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares    Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                 158784.0       4        39696.0      11.47     0.0009

RESIDUAL                 34611.0      10         3461.1
--------------------------------------------------------------------------------
TOTAL (CORRECTED)       193395.0      14
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average weighted
acenaphthylene among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average weighted acenaphthylene for the DF-2 fuel is significantly
different than the other four fuels.  The average weighted acenaphthylene among the
FT-100, ADMM15, CA, and ALS fuels are not significantly different from one another.

Multiple Range Tests for wgace by fuel

--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
fuel            Count     LS Mean          Homogeneous Groups
```

```
--------------------------------------------------------------------------------
FT-100          3       45.2115         X
ADMM15          3       46.4444         X
CA              3       102.196         X
ALS             3       122.207         X
DF-2            3       324.783                 X
--------------------------------------------------------------------------------
Contrast                                Difference      +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                            -75.7629        158.102
ADMM15 - CA                             -55.7518        158.102
ADMM15 - DF-2                           *-278.339       158.102
ADMM15 - FT-100                         1.23286         158.102
ALS - CA                                20.011          158.102
ALS - DF-2                              *-202.576       158.102
ALS - FT-100                            76.9957         158.102
CA - DF-2                               *-222.587       158.102
CA - FT-100                             56.9847         158.102
DF-2 - FT-100                           *279.571        158.102
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

```
Multifactor ANOVA - Acenaphthene (micro g/kW-hr)   Gaseous PAH
                  LPP Only   Weighted Modes 5, 6, 10, and 11

Analysis Summary

Dependent variable: wacen
Factors:
        fuel

Number of complete cases: 15
```

Scatterplot by Level Code


```
Analysis of Variance for wacen - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                566067.0       4      141517.0     17.32     0.0002

RESIDUAL               81710.1       10       8171.01
--------------------------------------------------------------------------------
TOTAL (CORRECTED)     647777.0       14
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average weighted
acenaphthene among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average weighted acenaphthene for the DF-2 fuel is significantly
different than the other four fuels.  The average weighted acenaphthene among
the FT-100, ADMM15, ALS, and CA fuels are not significantly different from
one another.

Multiple Range Tests for wacen by fuel
```

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
fuel            Count   LS Mean         Homogeneous Groups
--------------------------------------------------------------------------------
FT-100          3       8.5014          X
ADMM15          3       19.1396         X
ALS             3       37.6132         X
CA              3       75.3734         X
DF-2            3       517.467          X
--------------------------------------------------------------------------------
Contrast                                Difference        +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                            -18.4736          242.923
ADMM15 - CA                             -56.2338          242.923
ADMM15 - DF-2                           *-498.327         242.923
ADMM15 - FT-100                         10.6382           242.923
ALS - CA                                -37.7602          242.923
ALS - DF-2                              *-479.854         242.923
ALS - FT-100                            29.1118           242.923
CA - DF-2                               *-442.094         242.923
CA - FT-100                             66.872            242.923
DF-2 - FT-100                           *508.966          242.923
--------------------------------------------------------------------------------

* denotes a statistically significant difference.
```

```
Multifactor ANOVA - Fluorene (micro g/kW-hr)   Gaseous PAH
                  LPP Only   Weighted Modes 5, 6, 10, and 11

Analysis Summary

Dependent variable: wgflue
Factors:
        fuel

Number of complete cases: 15
```

Scatterplot by Level Code


```
Analysis of Variance for wgflue - Type III Sums of Squares
--------------------------------------------------------------------------------
Source                 Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                    1.89876E6      4      474690.0     11.55    0.0009

RESIDUAL                    410827.0     10       41082.7
--------------------------------------------------------------------------------
TOTAL (CORRECTED)          2.30959E6     14
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average weighted
fluorene among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average weighted fluorene for the DF-2 fuel is significantly
different than the other four fuels.  The average weighted fluorene among the
ADMM15, FT-100, ALS, and CA fuels are not significantly different from
one another.


Multiple Range Tests for wgflue by fuel
```

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
fuel            Count    LS Mean         Homogeneous Groups
--------------------------------------------------------------------------------
ADMM15          3        15.5368         X
FT-100          3        15.9082         X
ALS             3        45.8231         X
CA              3        108.559         X
DF-2            3        931.876          X
--------------------------------------------------------------------------------
Contrast                                 Difference         +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                             -30.2864           544.704
ADMM15 - CA                              -93.022            544.704
ADMM15 - DF-2                            *-916.339          544.704
ADMM15 - FT-100                          -0.371457          544.704
ALS - CA                                 -62.7356           544.704
ALS - DF-2                               *-886.053          544.704
ALS - FT-100                             29.9149            544.704
CA - DF-2                                *-823.317          544.704
CA - FT-100                              92.6505            544.704
DF-2 - FT-100                            *915.968           544.704
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

```
Multifactor ANOVA - Phenanthrene (micro g/Kw-hr)   Gaseous PAH
                    LPP Only   Weighted Modes 5, 6, 10, and 11

Analysis Summary

Dependent variable: wgphe
Factors:
        fuel

Number of complete cases: 15
```

Scatterplot by Level Code


```
Analysis of Variance for wgphe - Type III Sums of Squares
--------------------------------------------------------------------------------
Source                Sum of Squares    Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                   5.3621E6       4      1.34053E6      12.39      0.0007

RESIDUAL                  1.082E6       10       108200.0
--------------------------------------------------------------------------------
TOTAL (CORRECTED)        6.4441E6       14
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average weighted
phenanthrene among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average weighted phenanthrene for the DF-2 fuel is significantly
different than the other four fuels.  The average weighted phenanthrene among the
ADMM15, FT-100, ALS, and CA fuels are not significantly different from one
another.

Multiple Range Tests for wgphe by fuel
```

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
fuel            Count    LS Mean        Homogeneous Groups
--------------------------------------------------------------------------------
ADMM15          3        35.5657        X
FT-100          3        40.9851        X
ALS             3        120.072        X
CA              3        199.485        X
DF-2            3        1586.24         X
--------------------------------------------------------------------------------
Contrast                                Difference        +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                            -84.5058          883.985
ADMM15 - CA                             -163.92           883.985
ADMM15 - DF-2                           *-1550.67         883.985
ADMM15 - FT-100                         -5.41939          883.985
ALS - CA                                -79.4138          883.985
ALS - DF-2                              *-1466.17         883.985
ALS - FT-100                            79.0864           883.985
CA - DF-2                               *-1386.75         883.985
CA - FT-100                             158.5             883.985
DF-2 - FT-100                           *1545.25          883.985
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

D-38

```
Multifactor ANOVA - Anthracene (micro g/Kw-hr)   Gaseous PAH
                  LPP Only   Weighted Modes 5, 6, 10, and 11


Analysis Summary

Dependent variable: wgant
Factors:
        fuel

Number of complete cases: 15
```

Scatterplot by Level Code

```
Analysis of Variance for wgant - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                 5422.74       4       1355.68      18.26    0.0001

RESIDUAL                742.275      10       74.2275
--------------------------------------------------------------------------------
TOTAL (CORRECTED)       6165.01      14
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average weighted
anthracene among the fuels.
```

Means and 95% Tukey HSD Intervals

```
CONCLUSION:  The average weighted anthracene for the DF-2 fuel is significantly
different than the other four fuels.  The average weighted anthracene among the
FT-100, ADMM15, ALS, and CA fuels are not significantly different from
one another.


Multiple Range Tests for wgant by fuel

--------------------------------------------------------------------------------
```

```
Method: 95.0 percent Tukey HSD
fuel           Count    LS Mean        Homogeneous Groups
--------------------------------------------------------------------------------
FT-100           3      1.67593            X
ADMM15           3      1.95378            X
ALS              3      5.36358            X
CA               3      9.23519            X
DF-2             3      51.5939             X
--------------------------------------------------------------------------------
Contrast                                 Difference        +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                             -3.4098            23.1533
ADMM15 - CA                              -7.28141           23.1533
ADMM15 - DF-2                            *-49.6401          23.1533
ADMM15 - FT-100                          0.277852           23.1533
ALS - CA                                 -3.87161           23.1533
ALS - DF-2                               *-46.2303          23.1533
ALS - FT-100                             3.68765            23.1533
CA - DF-2                                *-42.3587          23.1533
CA - FT-100                              7.55926            23.1533
DF-2 - FT-100                            *49.9179           23.1533
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

D-40

```
Multifactor ANOVA - Fluoranthene (micro g/kW-hr)   Gaseous PAH
                 LPP Only   Weighted Modes 5, 6, 10, and 11

Analysis Summary

Dependent variable: wgflua
Factors:
        fuel

Number of complete cases: 15
```

Scatterplot by Level Code


```
Analysis of Variance for wgflua - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares    Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                 280.999        4       70.2498      8.50     0.0029

RESIDUAL                82.6177       10        8.26177
--------------------------------------------------------------------------------
TOTAL (CORRECTED)      363.617        14
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average weighted
fluoranthene among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average weighted fluoranthene for the DF-2 fuel is significantly
different than the other four fuels.  The average weighted fluoranthene among the
ADMM15, FT-100, ALS, and CA fuels are not significantly different from
one another.


Multiple Range Tests for wgflua by fuel

--------------------------------------------------------------------------------
```

```
Method: 95.0 percent Tukey HSD
fuel            Count    LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
ADMM15            3       1.4535            X
FT-100            3       1.86965           X
ALS               3       3.29502           X
CA                3       3.92077           X
DF-2              3       13.2175            X
--------------------------------------------------------------------------------
Contrast                                   Difference       +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                               -1.84153         7.72445
ADMM15 - CA                                -2.46727         7.72445
ADMM15 - DF-2                              *-11.764         7.72445
ADMM15 - FT-100                            -0.416153        7.72445
ALS - CA                                   -0.625743        7.72445
ALS - DF-2                                 *-9.92247        7.72445
ALS - FT-100                               1.42538          7.72445
CA - DF-2                                  *-9.29672        7.72445
CA - FT-100                                2.05112          7.72445
DF-2 - FT-100                              *11.3478         7.72445
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

```
Multifactor ANOVA - Pyrene (micro g/kW-hr)   Gaseous PAH
                  LPP Only   Weighted Modes 5, 6, 10, and 11

Analysis Summary

Dependent variable: wgpyr
Factors:
        fuel

Number of complete cases: 15
```

Scatterplot by Level Code


```
Analysis of Variance for wgpyr - Type III Sums of Squares
--------------------------------------------------------------------------------
Source               Sum of Squares   Df   Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                  579.075        4     144.769      10.09     0.0015

RESIDUAL                 143.425       10     14.3425
--------------------------------------------------------------------------------
TOTAL (CORRECTED)        722.499       14
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average weighted
pyrene among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average weighted pyrene for the DF-2 fuel is significantly different
than the other four fuels.  The average weighted pyrene for the ADMM15, FT-100,
ALS, and CA fuels are not significantly different from one another.

Multiple Range Tests for wgpyr by fuel

--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
fuel          Count     LS Mean          Homogeneous Groups
```

D-43

```
--------------------------------------------------------------------------------
ADMM15          3           1.14171             X
FT-100          3           1.40629             X
ALS             3           2.83773             X
CA              3           3.13677             X
DF-2            3           17.5421                 X
--------------------------------------------------------------------------------
Contrast                                Difference          +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                            -1.69601            10.1775
ADMM15 - CA                             -1.99505            10.1775
ADMM15 - DF-2                          *-16.4003            10.1775
ADMM15 - FT-100                         -0.264572           10.1775
ALS - CA                                -0.299041           10.1775
ALS - DF-2                             *-14.7043            10.1775
ALS - FT-100                            1.43144             10.1775
CA - DF-2                              *-14.4053            10.1775
CA - FT-100                             1.73048             10.1775
DF-2 - FT-100                          *16.1358             10.1775
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

```
Multifactor ANOVA - Naphthalene (micro g/kW-hr)  Soluble PAH
                   LPP Only   Weighted Modes 5, 6, 10, and 11

Analysis Summary

Dependent variable: wnaphth
Factors:
        fuel

Number of complete cases: 15
```

Scatterplot by Level Code


```
Analysis of Variance for wnaphth - Type III Sums of Squares
--------------------------------------------------------------------------------
Source               Sum of Squares   Df   Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                  1451.85        4     362.963      5.31     0.0147

RESIDUAL                 682.982       10      68.2982
--------------------------------------------------------------------------------
TOTAL (CORRECTED)       2134.84        14
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average naphthalene
among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average weighted naphthalene for the ALS fuel is significantly
different from the CA and DF-2 fuels.

Multiple Range Tests for wnaphth by fuel

--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
```

```
fuel          Count    LS Mean          Homogeneous Groups
--------------------------------------------------------------------------
ALS           3        23.446           X
ADMM15        3        28.43            XX
FT-100        3        39.378           XX
CA            3        46.1776           X
DF-2          3        48.7122           X
--------------------------------------------------------------------------
Contrast                                Difference       +/-  Limits
--------------------------------------------------------------------------
ADMM15 - ALS                            4.98395          22.2093
ADMM15 - CA                             -17.7476         22.2093
ADMM15 - DF-2                           -20.2822         22.2093
ADMM15 - FT-100                         -10.948          22.2093
ALS - CA                                *-22.7315        22.2093
ALS - DF-2                              *-25.2661        22.2093
ALS - FT-100                            -15.9319         22.2093
CA - DF-2                               -2.53459         22.2093
CA - FT-100                             6.79963          22.2093
DF-2 - FT-100                           9.33422          22.2093
--------------------------------------------------------------------------
* denotes a statistically significant difference.
```

D-46

```
Multifactor ANOVA - Acenaphthylene (micro g/kW-hr)    Soluble PAH
                    LPP Only    Weighted Modes 5, 6, 10, and 11

NOTE:  ALS data was imputed for repeat runs #2 and #3 because of non-detects
       in mode 5.

Analysis Summary

Dependent variable: wacenap
Factors:
        fuel

Number of complete cases: 14
```


Scatterplot by Level Code

```
Analysis of Variance for wacenap - Type III Sums of Squares
--------------------------------------------------------------------------------
Source                 Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                   0.588575       4      0.147144      4.65     0.0260

RESIDUAL                  0.284701       9      0.0316334
--------------------------------------------------------------------------------
TOTAL (CORRECTED)         0.873276      13
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.
```

CONCLUSION: Statistically significant differences in the average weighted
acenaphthylene among the fuels.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average weighted acenaphthylene for the CA fuel is significantly
different from the ADMM15 and ALS fuels.

```
Multiple Range Tests for wacenap by fuel

--------------------------------------------------------------------------------
```

```
Method: 95.0 percent Tukey HSD
fuel            Count   LS Mean         Homogeneous Groups
--------------------------------------------------------------------------------
ALS             3       0.47797         X
ADMM15          3       0.480728        X
FT-100          3       0.603505        XX
DF-2            2       0.807415        XX
CA              3       0.996603         X
--------------------------------------------------------------------------------
Contrast                                Difference      +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                            0.00275813      0.487917
ADMM15 - CA                            *-0.515875       0.487917
ADMM15 - DF-2                           -0.326687       0.545508
ADMM15 - FT-100                         -0.122777       0.487917
ALS - CA                               *-0.518633       0.487917
ALS - DF-2                              -0.329445       0.545508
ALS - FT-100                            -0.125536       0.487917
CA - DF-2                               0.189188        0.545508
CA - FT-100                             0.393098        0.487917
DF-2 - FT-100                           0.203909        0.545508
--------------------------------------------------------------------------------

* denotes a statistically significant difference.
```

D-48

```
Multifactor ANOVA - Acenaphthene (micro g/kW-hr)   Soluble PAH
                    LPP Only   Weighted Modes 5, 6, 10, and 11

Analysis Summary

Dependent variable: wacenat
Factors:
        fuel

Number of complete cases: 13
```

Scatterplot by Level Code


```
Analysis of Variance for wacenat - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares   Df   Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                 19.9901       4     4.99754       3.18     0.0767

RESIDUAL                12.5657       8     1.57072
--------------------------------------------------------------------------------
TOTAL (CORRECTED)       32.5559      12
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  No statistically significant differences in the average acenaphthene
among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  No statistically significant differences in the average acenaphthene
among the fuels.

Multiple Range Tests for wacenat by fuel

--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
fuel            Count     LS Mean           Homogeneous Groups
--------------------------------------------------------------------------------
```

D-49

```
ALS              2         2.31375          X
ADMM15           3         4.33291          X
FT-100           3         4.47144          X
CA               3         5.32256          X
DF-2             2         6.56407          X
--------------------------------------------------------------------------------
Contrast                                 Difference        +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                             2.01916           3.94549
ADMM15 - CA                             -0.989647          3.52895
ADMM15 - DF-2                           -2.23116           3.94549
ADMM15 - FT-100                         -0.138534          3.52895
ALS - CA                                -3.0088            3.94549
ALS - DF-2                              -4.25032           4.32207
ALS - FT-100                            -2.15769           3.94549
CA - DF-2                               -1.24151           3.94549
CA - FT-100                              0.851114          3.52895
DF-2 - FT-100                            2.09263           3.94549
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

```
Multifactor ANOVA - Fluorene (micro g/kW-hr)   Soluble PAH
                   LPP Only   Weighted Modes 5, 6, 10, and 11

NOTE:  ALS data was imputed for repeat runs #3 and #3 because of non-detects
       in modes 5 and 11.

Analysis Summary

Dependent variable: wfluore
Factors:
        fuel

Number of complete cases: 15
```

Scatterplot by Level Code


```
Analysis of Variance for wfluore - Type III Sums of Squares
--------------------------------------------------------------------------------
Source                 Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                    119.377       4       29.8442      8.09     0.0035

RESIDUAL                   36.8724      10       3.68724
--------------------------------------------------------------------------------
TOTAL (CORRECTED)          156.249      14
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average weighted
fluorene among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average weighted fluorene for the DF-2 fuel is significantly
different from the ADMM15, FT-100, and ALS fuels.

Multiple Range Tests for wfluore by fuel

--------------------------------------------------------------------------------
```

```
Method: 95.0 percent Tukey HSD
fuel            Count    LS Mean        Homogeneous Groups
--------------------------------------------------------------------------------
ALS             3        4.21444        X
FT-100          3        6.20745        X
ADMM15          3        7.17305        X
CA              3        9.22614        XX
DF-2            3        12.4896         X
--------------------------------------------------------------------------------
Contrast                                Difference        +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                            2.95861           5.16038
ADMM15 - CA                             -2.05309          5.16038
ADMM15 - DF-2                           *-5.31652         5.16038
ADMM15 - FT-100                         0.965605          5.16038
ALS - CA                                -5.01171          5.16038
ALS - DF-2                              *-8.27514         5.16038
ALS - FT-100                            -1.99301          5.16038
CA - DF-2                               -3.26343          5.16038
CA - FT-100                             3.0187            5.16038
DF-2 - FT-100                           *6.28213          5.16038
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

```
Multifactor ANOVA - Phenanthrene (micro g/kW-hr)   Soluble PAH
                  LPP Only   Weighted Modes 5, 6, 10, and 11

Analysis Summary

Dependent variable: wphenant
Factors:
        fuel

Number of complete cases: 15
```

Scatterplot by Level Code


```
Analysis of Variance for wphenant - Type III Sums of Squares
--------------------------------------------------------------------------------
Source                 Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                   11232.8        4       2808.19      8.58     0.0028

RESIDUAL                  3271.32       10       327.132
--------------------------------------------------------------------------------
TOTAL (CORRECTED)         14504.1       14
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.
```

```
CONCLUSION:  Statistically significant differences in the average weighted
phenanthrene among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average weighted phenanthrene for the DF-2 fuel is significantly
different than the ADMM15, ALS, and FT-100 fuels.  The average weighted phenanthrene
for the ADMM15, ALS, FT-100, and CA fuels are not significantly different from
one another.


Multiple Range Tests for wphenant by fuel

--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
```

D-53

```
fuel            Count    LS Mean           Homogeneous Groups
-----------------------------------------------------------------------------
ADMM15          3        29.8105           X
ALS             3        36.0033           X
FT-100          3        43.0115           X
CA              3        72.8461           XX
DF-2            3        103.015            X
-----------------------------------------------------------------------------
Contrast                                   Difference        +/-  Limits
-----------------------------------------------------------------------------
ADMM15 - ALS                               -6.19275          48.6063
ADMM15 - CA                                -43.0356          48.6063
ADMM15 - DF-2                              *-73.2044         48.6063
ADMM15 - FT-100                            -13.201           48.6063
ALS - CA                                   -36.8428          48.6063
ALS - DF-2                                 *-67.0116         48.6063
ALS - FT-100                               -7.00828          48.6063
CA - DF-2                                  -30.1688          48.6063
CA - FT-100                                29.8346           48.6063
DF-2 - FT-100                              *60.0034          48.6063
-----------------------------------------------------------------------------
```

* denotes a statistically significant difference.

```
Multifactor ANOVA - Anthracene (micro g/kW-hr)    Soluble PAH
                 LPP Only   Weighted Modes 5, 6, 10, and 11

Analysis Summary

Dependent variable: wanthr
Factors:
        fuel

Number of complete cases: 14
```

Scatterplot by Level Code


```
Analysis of Variance for wanthr - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares    Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                20.1205         4        5.03012      18.78     0.0002

RESIDUAL                2.41047        9        0.26783
--------------------------------------------------------------------------------
TOTAL (CORRECTED)      22.531         13
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average weighted
anthracene among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average weighted anthracene for the ALS fuel is significantly
different from the CA, DF-2, and FT-100 fuels.  Also, the ADMM15 fuel has a
significantly different weighted anthracene than the CA and DF-2 fuels.


Multiple Range Tests for wanthr by fuel

--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
fuel           Count     LS Mean          Homogeneous Groups
```

```
--------------------------------------------------------------------------------
ALS              2          0.737556          X
ADMM15           3          2.28698           XX
FT-100           3          2.91967           XX
CA               3          4.16059            X
DF-2             3          4.19718            X
--------------------------------------------------------------------------------
Contrast                                 Difference      +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                              1.54942        1.5873
ADMM15 - CA                             *-1.87361        1.41972
ADMM15 - DF-2                           *-1.91021        1.41972
ADMM15 - FT-100                          -0.632691       1.41972
ALS - CA                                *-3.42303        1.5873
ALS - DF-2                              *-3.45963        1.5873
ALS - FT-100                            *-2.18211        1.5873
CA - DF-2                                -0.0365957      1.41972
CA - FT-100                               1.24092        1.41972
DF-2 - FT-100                             1.27752        1.41972
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

```
Multifactor ANOVA - Fluoranthene (micro g/kW-hr)    Soluble PAH
                    LPP Only   Weighted Mode 5, 6, 10, and 11

Analysis Summary

Dependent variable: wfluora
Factors:
        fuel

Number of complete cases: 15
```

Scatterplot by Level Code


```
Analysis of Variance for wfluora - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares    Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                 3191.45        4       797.862      10.78      0.0012

RESIDUAL                739.933       10        73.9933
--------------------------------------------------------------------------------
TOTAL (CORRECTED)      3931.38       14
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average weighted fluoranthene
among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average weighted fluoranthene for the DF-2 fuel is significantly
different from the remaining four fuels.  The ADMM15, FT-100, CA, and ALS fuels
are not significantly different from one another with respect to the average
weighted fluoranthene.

Multiple Range Tests for wfluora by fuel

--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
```

```
fuel            Count    LS Mean        Homogeneous Groups
--------------------------------------------------------------------------
ADMM15          3        9.82889        X
FT-100          3        15.4822        X
CA              3        17.7845        X
ALS             3        19.5387        X
DF-2            3        51.1942         X
--------------------------------------------------------------------------
Contrast                                Difference      +/-  Limits
--------------------------------------------------------------------------
ADMM15 - ALS                            -9.70982        23.1168
ADMM15 - CA                             -7.95564        23.1168
ADMM15 - DF-2                           *-41.3653       23.1168
ADMM15 - FT-100                         -5.65329        23.1168
ALS - CA                                1.75417         23.1168
ALS - DF-2                              *-31.6555       23.1168
ALS - FT-100                            4.05653         23.1168
CA - DF-2                               *-33.4097       23.1168
CA - FT-100                             2.30236         23.1168
DF-2 - FT-100                           *35.712         23.1168
--------------------------------------------------------------------------
```

* denotes a statistically significant difference.

D-58

```
Multifactor ANOVA - Pyrene (micro g/kW-hr)    Soluble PAH
                  LPP Only   Weighted Modes 5, 6, 10, and 11

Analysis Summary

Dependent variable: wpyrene
Factors:
        fuel

Number of complete cases: 15
```

Scatterplot by Level Code


```
Analysis of Variance for wpyrene - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                 11677.2       4        2919.3     17.72     0.0002

RESIDUAL                1647.19      10        164.719
--------------------------------------------------------------------------------
TOTAL (CORRECTED)       13324.4      14
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average weighted
pyrene among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average weighted pyrene for the DF-2 fuel is significantly
different than the remaining four fuels.  The ADMM15, FT-100, CA, and ALS fuels
are not significantly different from one another with respect to the weighted
pyrene.

Multiple Range Tests for wpyrene by fuel

--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
fuel            Count     LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
```

```
ADMM15          3          9.98398          X
FT-100          3          12.7075          X
CA              3          13.6715          X
ALS             3          21.2961          X
DF-2            3          83.5337           X
--------------------------------------------------------------------------------
Contrast                                 Difference          +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                              -11.3121           34.4908
ADMM15 - CA                               -3.68749           34.4908
ADMM15 - DF-2                            *-73.5497           34.4908
ADMM15 - FT-100                           -2.7235            34.4908
ALS - CA                                  7.62463            34.4908
ALS - DF-2                               *-62.2376           34.4908
ALS - FT-100                              8.58862            34.4908
CA - DF-2                                *-69.8622           34.4908
CA - FT-100                               0.963989           34.4908
DF-2 - FT-100                            *70.8262            34.4908
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

```
Multifactor ANOVA - Benzo[a]anthracene (micro g/kW-hr)   Soluble PAH
                 LPP Only   Weighted Modes 5, 6, 10, and 11

Analysis Summary

Dependent variable: wbenzoaa
Factors:
        fuel

Number of complete cases: 13
```


Scatterplot by Level Code

```
Analysis of Variance for wbenzoaa - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares   Df    Mean Square   F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                  9.85566      4       2.46391      30.83     0.0001

RESIDUAL                0.639289      8     0.0799112
--------------------------------------------------------------------------------
TOTAL (CORRECTED)        10.4949     12
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average weighted
benzo[a]anthracene among the fuels.
```


Means and 95% Tukey HSD Intervals

```
CONCLUSION:  The average weighted benzo[a]anthracene for the DF-2 fuel is
significantly different than the remaining four fuels.  Also, the average
weighted benzo[a]anthracene for the CA fuel is significantly different than
the ADMM15 fuel.

Multiple Range Tests for wbenzoaa by fuel

--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
```

D-61

```
fuel          Count    LS Mean         Homogeneous Groups
--------------------------------------------------------------------------------
ADMM15        3        0.154966        X
FT-100        2        0.253052        XX
ALS           3        0.712476        XX
CA            2        1.06269          X
DF-2          3        2.45533          X
--------------------------------------------------------------------------------
Contrast                               Difference        +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                            -0.55751         0.795977
ADMM15 - CA                            *-0.907724        0.88993
ADMM15 - DF-2                          *-2.30037         0.795977
ADMM15 - FT-100                         -0.0980866       0.88993
ALS - CA                                -0.350214        0.88993
ALS - DF-2                             *-1.74286         0.795977
ALS - FT-100                            0.459424         0.88993
CA - DF-2                              *-1.39264         0.88993
CA - FT-100                             0.809638         0.974869
DF-2 - FT-100                          *2.20228          0.88993
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

```
Multifactor ANOVA - Chrysene (micro g/kW-hr)   Soluble PAH
                LPP Only   Weighted Modes 5, 6, 10, and 11

Analysis Summary

Dependent variable: wchrysen
Factors:
        fuel

Number of complete cases: 15
```

Scatterplot by Level Code


```
Analysis of Variance for wchrysen - Type III Sums of Squares
--------------------------------------------------------------------------------
Source                 Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                    102.637        4      25.6593      24.85    0.0000

RESIDUAL                   10.3272       10       1.03272
--------------------------------------------------------------------------------
TOTAL (CORRECTED)          112.964       14
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average weighted
chyrsene among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average weighted chrysene for the DF-2 fuel is significantly
different than the remaining four fuels.  The ADMM15, FT-100, ALS, and CA
fuels are not significantly different from one another with respect to the
average weighted chrysene.

Multiple Range Tests for wchrysen by fuel

--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
fuel            Count    LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
```

```
ADMM15          3          0.585974          X
FT-100          3          0.773542          X
ALS             3          1.93602           X
CA              3          2.39139           X
DF-2            3          7.73531            X
-----------------------------------------------------------------------------
Contrast                               Difference        +/-  Limits
-----------------------------------------------------------------------------
ADMM15 - ALS                            -1.35005          2.73101
ADMM15 - CA                             -1.80542          2.73101
ADMM15 - DF-2                          *-7.14934          2.73101
ADMM15 - FT-100                         -0.187568         2.73101
ALS - CA                                -0.455369         2.73101
ALS - DF-2                             *-5.79929          2.73101
ALS - FT-100                            1.16248           2.73101
CA - DF-2                              *-5.34392          2.73101
CA - FT-100                             1.61785           2.73101
DF-2 - FT-100                          *6.96177           2.73101
-----------------------------------------------------------------------------
```

* denotes a statistically significant difference.

```
Multifactor ANOVA - Benzo[b]fluoranthene (micro g/kW-hr)   Soluble PAH
                   LPP Only   Weighted Modes 5, 6, 10, and 11

NOTE:  CA data was imputed for repeat runs #1 and #2 because of non-detects
       in modes 5 and 11.

Analysis Summary

Dependent variable: wbenzobf
Factors:
       fuel

Number of complete cases: 15
```


Scatterplot by Level Code

```
Analysis of Variance for wbenzobf - Type III Sums of Squares
--------------------------------------------------------------------------------
Source                Sum of Squares    Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                   3.67553        4      0.918882       23.96     0.0000

RESIDUAL                 0.383537       10      0.0383537
--------------------------------------------------------------------------------
TOTAL (CORRECTED)        4.05907        14
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average weighted
benzo[b]fluoranthene among the fuels.
```


Means and 95% Tukey HSD Intervals

```
CONCLUSION:  There are two distinct fuel groupings with respect to the average
weighted benzo[b]fluoranthene.  The ADMM15 and FT-100 fuels are not significantly
different from one another, but are different from the remaining three fuels.  The ALS,
CA, and DF-2 fuels are not significantly different from one another.
```

```
Multiple Range Tests for wbenzobf by fuel

--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
fuel           Count    LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
FT-100         3        0.3046           X
ADMM15         3        0.389343         X
CA             3        1.18968           X
ALS            3        1.25332           X
DF-2           3        1.53819           X
--------------------------------------------------------------------------------
Contrast                               Difference         +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                           *-0.863973         0.526302
ADMM15 - CA                            *-0.800341         0.526302
ADMM15 - DF-2                          *-1.14885          0.526302
ADMM15 - FT-100                         0.0847435         0.526302
ALS - CA                                0.063632          0.526302
ALS - DF-2                             -0.284877          0.526302
ALS - FT-100                           *0.948716          0.526302
CA - DF-2                              -0.348509          0.526302
CA - FT-100                            *0.885084          0.526302
DF-2 - FT-100                          *1.23359           0.526302
--------------------------------------------------------------------------------
* denotes a statistically significant difference.
```

```
Multifactor ANOVA - Benzo[k]fluoranthene (micro g/kW-hr)    Soluble PAH
                  LPP Only    Weighted Modes 5, 6, 10, and 11

Analysis Summary

Dependent variable: wbenzokf
Factors:
        fuel

Number of complete cases: 14
```

Scatterplot by Level Code


```
Analysis of Variance for wbenzokf - Type III Sums of Squares
--------------------------------------------------------------------------------
Source                Sum of Squares    Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                      7.67509      4        1.91877      22.00     0.0001

RESIDUAL                    0.784911      9      0.0872123
--------------------------------------------------------------------------------
TOTAL (CORRECTED)               8.46     13
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average benzo[k]fluoranthene
among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average weighted benzo[k]fluoranthene for the DF-2 fuel is significantly
different than the remaining four fuels.  The FT-100, ADMM15, ALS, and CA fuels
are not significantly different from one another with respect to the average weighted
benzo[k]fluoranthene.

Multiple Range Tests for wbenzokf by fuel

--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
```

D-67

```
fuel            Count    LS Mean        Homogeneous Groups
------------------------------------------------------------------------
FT-100          3        0.353869       X
ADMM15          3        0.423556       X
ALS             3        0.657605       X
CA              2        1.18863        X
DF-2            3        2.29314         X
------------------------------------------------------------------------
Contrast                               Difference      +/-  Limits
------------------------------------------------------------------------
ADMM15 - ALS                           -0.234049       0.810144
ADMM15 - CA                            -0.765074       0.905768
ADMM15 - DF-2                          *-1.86958       0.810144
ADMM15 - FT-100                         0.0696864      0.810144
ALS - CA                               -0.531025       0.905768
ALS - DF-2                             *-1.63553       0.810144
ALS - FT-100                            0.303735       0.810144
CA - DF-2                              *-1.10451       0.905768
CA - FT-100                             0.83476        0.905768
DF-2 - FT-100                          *1.93927        0.810144
------------------------------------------------------------------------
```

* denotes a statistically significant difference.

D-68

```
Multifactor ANOVA - Benzo[e]pyrene (micro g/kW-hr)   Soluble PAH
                    LPP Only   Weighted Modes 5, 6, 10, and 11

NOTE:  DF-2 data was imputed for repeat runs #2 and #3 because of non-detects
       in modes 5 and 6.

Analysis Summary

Dependent variable: wbenzoep
Factors:
       fuel

Number of complete cases: 12
```

Scatterplot by Level Code


```
Analysis of Variance for wbenzoep - Type III Sums of Squares
--------------------------------------------------------------------------------
Source                 Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                      1.17031     4       0.292577      8.63    0.0077

RESIDUAL                    0.237445     7      0.0339207
--------------------------------------------------------------------------------
TOTAL (CORRECTED)           1.40775    11
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average weighted
benzo[e]pyrene among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average weighted benzo[e]pyrene for the DF-2 fuel is
significantly different than the ADMM15 and FT-100 fuels.

Multiple Range Tests for wbenzoep by fuel

--------------------------------------------------------------------------------
```

```
Method: 95.0 percent Tukey HSD
fuel          Count    LS Mean        Homogeneous Groups
--------------------------------------------------------------------------------
ADMM15          2       0.210091        X
FT-100          2       0.267075        X
ALS             3       0.620611        XX
CA              2       0.679916        XX
DF-2            3       1.05916          X
--------------------------------------------------------------------------------
Contrast                              Difference        +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                          -0.41052         0.599891
ADMM15 - CA                           -0.469825        0.657148
ADMM15 - DF-2                        *-0.84907         0.599891
ADMM15 - FT-100                       -0.0569841       0.657148
ALS - CA                              -0.0593047       0.599891
ALS - DF-2                            -0.43855         0.536559
ALS - FT-100                          0.353536         0.599891
CA - DF-2                             -0.379245        0.599891
CA - FT-100                           0.412841         0.657148
DF-2 - FT-100                        *0.792086         0.599891
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

```
Multifactor ANOVA - Benzo[a]pyrene (micro g/kW-hr)   Soluble PAH
                 LPP Only   Weighted Modes 5, 6, 10, and 11

Analysis Summary

Dependent variable: wbenzoapy
Factors:
        fuel

Number of complete cases: 15
```

Scatterplot by Level Code


```
Analysis of Variance for wbenzoapy - Type III Sums of Squares
--------------------------------------------------------------------------------
Source             Sum of Squares   Df    Mean Square    F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                0.338272      4      0.084568       19.40    0.0001

RESIDUAL              0.0435972     10     0.00435972
--------------------------------------------------------------------------------
TOTAL (CORRECTED)     0.381869      14
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.
```

```
CONCLUSION:  Statistically significant differences in the average benzo[a]pyrene
among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average weighted benzo[a]pyrene for the ADMM15 and FT-100 fuels
is significantly different than the CA and ALS fuels.  Also, ALS fuel has a significantly
different weighted benzo[a]pyrene than the DF-2 fuel.


Multiple Range Tests for wbenzoapy by fuel

--------------------------------------------------------------------------------
```

```
Method: 95.0 percent Tukey HSD
fuel            Count    LS Mean         Homogeneous Groups
--------------------------------------------------------------------------------
ADMM15          3        0.05479         X
FT-100          3        0.06841         X
DF-2            3        0.200233        XX
CA              3        0.346693         XX
ALS             3        0.434583         X
--------------------------------------------------------------------------------
Contrast                                 Difference       +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                             *-0.379793       0.177444
ADMM15 - CA                              *-0.291903       0.177444
ADMM15 - DF-2                            -0.145443        0.177444
ADMM15 - FT-100                          -0.01362         0.177444
ALS - CA                                 0.08789          0.177444
ALS - DF-2                               *0.23435         0.177444
ALS - FT-100                             *0.366173        0.177444
CA - DF-2                                0.14646          0.177444
CA - FT-100                              *0.278283        0.177444
DF-2 - FT-100                            0.131823         0.177444
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

D-72

```
Multifactor ANOVA - Indeno(1,2,3-cd)pyrene (micro g/kW-hr)    Soluble PAH
                  LPP Only for Three Fuels    Weighted Modes 5,6,10, and 11

Analysis Summary

Dependent variable: windeno
Factors:
        fuel

Number of complete cases: 8
```

Scatterplot by Level Code


```
Analysis of Variance for windeno - Type III Sums of Squares
--------------------------------------------------------------------------------
Source               Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                  0.206571      2      0.103285      26.79     0.0021

RESIDUAL                 0.0192752     5     0.00385505
--------------------------------------------------------------------------------
TOTAL (CORRECTED)        0.225846      7
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.


CONCLUSION:  Statistically significant differences in the average indeno(1,2,3-cd)pyrene
among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average indeno(1,2,3-cd)pyrene for the ADMM15 and FT-100 fuels are not
significantly different from one another, but both at significantly different from the
DF-2 fuel.


Multiple Range Tests for windeno by fuel
```

D-73

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
fuel            Count    LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
FT-100          3        0.0612667        X
ADMM15          2        0.073095         X
DF-2            3        0.397783          X
--------------------------------------------------------------------------------
Contrast                                  Difference       +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - DF-2                             *-0.324688        0.184423
ADMM15 - FT-100                            0.0118283        0.184423
DF-2 - FT-100                             *0.336517         0.164953
--------------------------------------------------------------------------------

* denotes a statistically significant difference.
```

```
Multifactor ANOVA - Benzo[ghi]perylene (micro g/kW-hr)   Soluble PAH
                  LPP Only for Four Fuels   Weighted Modes 5,6,10, and 11

Analysis Summary

Dependent variable: wbenzogpe
Factors:
        fuel

Number of complete cases: 10
```

Scatterplot by Level Code

```
Analysis of Variance for wbenzogpe - Type III Sums of Squares
--------------------------------------------------------------------------------
Source             Sum of Squares   Df   Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                0.615787      3     0.205262      35.64    0.0003

RESIDUAL               0.0345556     6    0.00575926
--------------------------------------------------------------------------------
TOTAL (CORRECTED)      0.650342      9
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.
```

```
CONCLUSION:  Statistically significant differences in the average benzo[ghi]perylene
among the fuels.
```

Means and 95% Tukey HSD Intervals

```
CONCLUSION:  The average benzo[ghi]perylene for the FT-100 and ADMM15 fuels are
significantly different from the DF-2 and CA fuels, but not significantly different
from one another.  Also, the DF-2 and CA fuels are not significantly different from
one another.


Multiple Range Tests for wbenzogpe by fuel
```

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
fuel            Count    LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
FT-100            3       0.154067          X
ADMM15            2       0.208495          X
DF-2              3       0.64388            X
CA                2       0.70622            X
--------------------------------------------------------------------------------
Contrast                                  Difference        +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - CA                               *-0.497725         0.261841
ADMM15 - DF-2                             *-0.435385         0.239027
ADMM15 - FT-100                            0.0544283         0.239027
CA - DF-2                                  0.06234           0.239027
CA - FT-100                               *0.552153          0.239027
DF-2 - FT-100                             *0.489813          0.213793
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

APPENDIX E

ANOVA for Modal LPP

TABLE OF CONTENTS

```
Multifactor ANOVA - Total Particulates (g/kW-hr)
                 LPP Only   Modes 5,6,10,11


Analysis Summary

Dependent variable: PARTIC
Factors:
        FUEL
        MODE
Selection variable: MODE < 12

Number of complete cases: 62
```

Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for PARTIC - Type III Sums of Squares
--------------------------------------------------------------------------------
Source                Sum of Squares    Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:FUEL                    0.180096       4     0.0450239      55.43     0.0000
 B:MODE                    0.0812661      3     0.0270887      33.35     0.0000

INTERACTIONS
 AB                        0.0203674     12     0.00169728      2.09     0.0392

RESIDUAL                   0.0341148     42     0.000812257
--------------------------------------------------------------------------------
TOTAL (CORRECTED)          0.31392       61
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average particulates
among the fuels, modes, and fuel*mode interaction.
```

Means and 95% Tukey HSD Intervals

CONCLUSION: Average particulate at Modes 5 and 11 are not significantly different
from one another. Average particulate at Modes 6 and 10 are not significantly
different from one another. Average particulate at modes 5 and 11 are significantly
different than modes 6 and 10.

Means and 95% Tukey HSD Intervals

CONCLUSION: Average particulate at fuels FT-100 and ADMM15 are not significantly
different
from one another, but are different than the other 3 fuels. The average particulate
at Fuel ALS is significantly different than Fuel DF-2. The CA fuel is not significantly
different than either the ALS or DF-2 fuel.

Multiple Range Tests for PARTIC by MODE

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
MODE            Count     LS Mean            Homogeneous Groups
--------------------------------------------------------------------------------
5               16        0.161392           X
11              15        0.180949           X
6               15        0.227259            X
10              16        0.252179            X
--------------------------------------------------------------------------------
Contrast                                     Difference         +/-  Limits
--------------------------------------------------------------------------------
5 - 6                                        *-0.0658665        0.0274018
5 - 10                                       *-0.0907872        0.0269563
5 - 11                                        -0.0195566        0.0274018
6 - 10                                        -0.0249207        0.0274018
6 - 11                                       *0.04631           0.0278403
10 - 11                                      *0.0712306         0.0274018
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

Multiple Range Tests for PARTIC by FUEL

```
--------------------------------------------------------------------------------
```

```
Method: 95.0 percent Tukey HSD
FUEL          Count    LS Mean        Homogeneous Groups
--------------------------------------------------------------------------------
FT-100          12      0.13969          X
ADMM15          12      0.145389         X
ALS             14      0.217693          X
CA              12      0.247083          XX
DF-2            12      0.277368           X
--------------------------------------------------------------------------------
Contrast                                 Difference        +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                            *-0.0723034        0.0319542
ADMM15 - CA                             *-0.101694         0.0331604
ADMM15 - DF-2                           *-0.131979         0.0331604
ADMM15 - FT-100                          0.00569934        0.0331604
ALS - CA                                 -0.0293907        0.0319542
ALS - DF-2                              *-0.0596755        0.0319542
ALS - FT-100                            *0.0780028         0.0319542
CA - DF-2                                -0.0302847        0.0331604
CA - FT-100                             *0.107394          0.0331604
DF-2 - FT-100                           *0.137678          0.0331604
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: The CA and DF-2 fuels have significantly different average particulate
at Modes 5 and 11 than at modes 6 and 10. All other fuels do not demonstrate significant
differences in the average particulate among the four modes.

```
Multifactor ANOVA - BSNOX (g/kW-hr)
                LPP Only   Modes 5,6,10,11


Analysis Summary

Dependent variable: BSNOX
Factors:
        FUEL
        MODE
Selection variable: MODE<12

Number of complete cases: 62
```

Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for BSNOX - Type III Sums of Squares
--------------------------------------------------------------------------------
Source                Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:FUEL                    7.45754       4      1.86438      16.79    0.0000
 B:MODE                    443.319       3      147.773    1330.52    0.0000

INTERACTIONS
 AB                        6.14855      12     0.512379      4.61     0.0001

RESIDUAL                   4.66468      42     0.111064
--------------------------------------------------------------------------------
TOTAL (CORRECTED)          464.749      61
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average BSNOX among the
fuels, modes, and fuel*mode interaction.
```

Means and 95% Tukey HSD Intervals

CONCLUSION: There are two distinct fuel groupings with respect to the average BSNOX.
ADMM15 and DF-2 fuels are not significantly different from one another, but are different
from the average BSNOX for the ALS, CA, and FT-100 fuels. The ALS, CA, and FT-100 fuels
are not significantly different from one another.

Means and 95% Tukey HSD Intervals

CONCLUSION: All four modes are significantly different from one another with respect to
the average BSNOX.

Multiple Range Tests for BSNOX by FUEL

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
FUEL            Count     LS Mean           Homogeneous Groups
--------------------------------------------------------------------------------
ALS             14        5.04671           X
CA              12        5.05677           X
FT-100          12        5.24116           X
ADMM15          12        5.69599            X
DF-2            12        5.9005             X
--------------------------------------------------------------------------------
Contrast                                    Difference        +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                                *0.649278         0.373652
ADMM15 - CA                                 *0.63922          0.387757
ADMM15 - DF-2                                -0.204506        0.387757
ADMM15 - FT-100                             *0.45483          0.387757
ALS - CA                                     -0.0100577       0.373652
ALS - DF-2                                  *-0.853784        0.373652
ALS - FT-100                                 -0.194448        0.373652
CA - DF-2                                   *-0.843726        0.387757
CA - FT-100                                  -0.184391        0.387757
DF-2 - FT-100                               *0.659336         0.387757
--------------------------------------------------------------------------------
```
* denotes a statistically significant difference.

Multiple Range Tests for BSNOX by MODE

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
MODE         Count    LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
11           15       2.77949          X
10           16       3.55572           X
6            15       5.55988            X
5            16       9.65782             X
--------------------------------------------------------------------------------
Contrast                                 Difference        +/-  Limits
--------------------------------------------------------------------------------
5 - 6                                    *4.09794          0.32042
5 - 10                                   *6.1021           0.315209
5 - 11                                   *6.87832          0.32042
6 - 10                                   *2.00416          0.32042
6 - 11                                   *2.78039          0.325547
10 - 11                                  *0.776228         0.32042
--------------------------------------------------------------------------------

* denotes a statistically significant difference.
```

Interaction and 95% Tukey HSD Intervals

CONCLUSION: While the ADMM15, ALS, CA, and FT-100 fuels all have significant differences
in the average BSNOX between mode 6 and modes 10 and 11, the DF-2 fuel does not
demonstrate this difference. The average BSNOX among modes 6, 10, and 11 for the DF-2
are not
significantly different from one another.

```
Multifactor ANOVA - BSHC (g/kW-hr)
                 LPP Only   Modes 5,6,10,11
Analysis Summary

Dependent variable: BSHC
Factors:
        FUEL
        MODE
Selection variable: MODE<12

Number of complete cases: 62
```

Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for BSHC - Type III Sums of Squares
--------------------------------------------------------------------------------
Source                Sum of Squares    Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:FUEL                     4.05731      4        1.01433     104.34     0.0000
 B:MODE                     10.9203      3        3.64011     374.43     0.0000

INTERACTIONS
 AB                          2.4476     12       0.203967      20.98     0.0000

RESIDUAL                   0.408308     42     0.00972163
--------------------------------------------------------------------------------
TOTAL (CORRECTED)           17.7211     61
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average BSHC among the
fuels, modes, and the fuel*mode interaction.
```

Means and 95% Tukey HSD Intervals

CONCLUSION: There are four distinct fuel groupings with respect to the average
BSHC. FT-100, CA, and DF-2 fuels are all significantly different from one another.
Also, fuels ADMM15 and ALS are not significantly different from one another, but they are
both significantly different from the other three fuels.

Means and 95% Tukey HSD Intervals

CONCLUSION: All four modes are significantly different from one another with respect to
the average BSHC.

Multiple Range Tests for BSHC by FUEL

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
FUEL          Count    LS Mean        Homogeneous Groups
--------------------------------------------------------------------------------
FT-100         12       0.302624      X
ADMM15         12       0.519087       X
ALS            14       0.562475       X
CA             12       0.866077        X
DF-2           12       1.03069          X
--------------------------------------------------------------------------------
Contrast                              Difference         +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                           -0.0433876         0.110548
ADMM15 - CA                           *-0.346989          0.114721
ADMM15 - DF-2                         *-0.5116            0.114721
ADMM15 - FT-100                       *0.216463           0.114721
ALS - CA                              *-0.303602          0.110548
ALS - DF-2                            *-0.468212          0.110548
ALS - FT-100                          *0.259851           0.110548
CA - DF-2                             *-0.16461           0.114721
CA - FT-100                           *0.563453           0.114721
DF-2 - FT-100                         *0.728063           0.114721
--------------------------------------------------------------------------------
* denotes a statistically significant difference.
```


Multiple Range Tests for BSHC by MODE

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
MODE            Count    LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
5               16       0.158889         X
6               15       0.346341          X
11              15       0.934782           X
10              16       1.18475             X
--------------------------------------------------------------------------------
Contrast                                  Difference        +/-   Limits
--------------------------------------------------------------------------------
5 - 6                                     *-0.187453        0.0947987
5 - 10                                    *-1.02586         0.0932572
5 - 11                                    *-0.775893        0.0947987
6 - 10                                    *-0.838407        0.0947987
6 - 11                                    *-0.58844         0.0963156
10 - 11                                   *0.249966         0.0947987
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: The ALS, CA, DF-2 fuels have significantly different average BSHC at modes 10 and 11 than at modes 5 and 6. All other fuels do not demonstrate significant differences in the average BSHC among the four modes.

```
Multifactor ANOVA - BSCO (g/kW-hr)
                 LPP Only   Modes 5,6,10,11


Analysis Summary

Dependent variable: BSCO
Factors:
        FUEL
        MODE
Selection variable: MODE<12

Number of complete cases: 62
```

Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for BSCO - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:FUEL                  42.4521      4        10.613     178.05    0.0000
 B:MODE                  214.449      3       71.4832    1199.21    0.0000

INTERACTIONS
 AB                      33.0659     12        2.7555      46.23    0.0000

RESIDUAL                 2.50355     42     0.0596084
--------------------------------------------------------------------------------
TOTAL (CORRECTED)        290.354     61
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average BSCO among the
fuels, modes, and fuel*mode interaction.
```

Means and 95% Tukey HSD Intervals

CONCLUSION: There are three distinct fuel groupings with respect to the average BSCO. FT-100 is significantly different from the other four fuels. ADMM15 and ALS are not significantly different from one another. Fuels CA and DF-2 are not significantly different from one another, but are significantly different from the ADMM15 and ALS fuels.

Means and 95% Tukey HSD Intervals

CONCLUSION: All four modes are significantly different from one another with respect to the average BSCO.

```
Multiple Range Tests for BSCO by FUEL

--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
FUEL            Count    LS Mean        Homogeneous Groups
--------------------------------------------------------------------------------
FT-100          12       1.38081        X
ADMM15          12       2.21783         X
ALS             14       2.27253         X
CA              12       3.46699          X
DF-2            12       3.61618          X
--------------------------------------------------------------------------------
Contrast                                 Difference        +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                              -0.0547025       0.273738
ADMM15 - CA                              *-1.24916         0.284071
ADMM15 - DF-2                            *-1.39835         0.284071
ADMM15 - FT-100                          *0.837021         0.284071
ALS - CA                                 *-1.19446         0.273738
ALS - DF-2                               *-1.34365         0.273738
ALS - FT-100                             *0.891724         0.273738
CA - DF-2                                 -0.149189        0.284071
CA - FT-100                              *2.08618          0.284071
DF-2 - FT-100                            *2.23537          0.284071
--------------------------------------------------------------------------------
* denotes a statistically significant difference.
```

```
Multiple Range Tests for BSCO by MODE

--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
MODE            Count     LS Mean            Homogeneous Groups
--------------------------------------------------------------------------------
5               16        0.426311           X
6               15        1.22936             X
11              15        3.65545              X
10              16        5.05234               X
--------------------------------------------------------------------------------
Contrast                                   Difference        +/-  Limits
--------------------------------------------------------------------------------
5  - 6                                      *-0.803049        0.23474
5  - 10                                     *-4.62603         0.230923
5  - 11                                     *-3.22914         0.23474
6  - 10                                     *-3.82299         0.23474
6  - 11                                     *-2.42609         0.238496
10 - 11                                     *1.3969           0.23474
--------------------------------------------------------------------------------
* denotes a statistically significant difference.
```

Interaction and 95% Tukey HSD Intervals

CONCLUSION: The CA, DF-2, and FT-100 fuels have significantly different average
BSCO at modes 10 and 11 than at modes 5 and 6.

```
Multifactor ANOVA - BSCO2 (g/kW-hr)
                 LPP Only   Modes 5,6,10,11


Analysis Summary

Dependent variable: BSCO2
Factors:
        FUEL
        MODE
Selection variable: MODE<12

Number of complete cases: 62
```

Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for BSCO2 - Type III Sums of Squares
--------------------------------------------------------------------------------
Source                 Sum of Squares   Df   Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:FUEL                       38712.5    4       9678.13     36.18    0.0000
 B:MODE                     1.23777E6    3      412592.0   1542.24    0.0000

INTERACTIONS
 AB                           4961.4    12        413.45      1.55    0.1463

RESIDUAL                     11236.1    42        267.527
--------------------------------------------------------------------------------
TOTAL (CORRECTED)          1.30255E6    61
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average BSCO2 among
the fuels and the modes.
```

Means and 95% Tukey HSD Intervals

CONCLUSION: There are three distinct fuel groupings with respect to the
average BSCO2. FT-100 is significantly different from the other four fuels.
ADMM15 and DF-2 fuels are not significantly different from one another. Fuels
ALS and CA are not significantly different from one another, but are significantly
different from the ADMM15 and DF-2 fuels.

Means and 95% Tukey HSD Intervals

CONCLUSION: All four modes are significantly different from one another with
respect to the average BSCO2.

Multiple Range Tests for BSCO2 by FUEL

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
FUEL          Count    LS Mean              Homogeneous Groups
--------------------------------------------------------------------------------
FT-100        12       812.402              X
ALS           14       843.98                X
CA            12       844.665               X
DF-2          12       874.424                X
ADMM15        12       884.069                X
--------------------------------------------------------------------------------
Contrast                                 Difference          +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                             *40.0882            18.3385
ADMM15 - CA                              *39.4037            19.0308
ADMM15 - DF-2                             9.64418            19.0308
ADMM15 - FT-100                          *71.6664            19.0308
ALS - CA                                 -0.68448            18.3385
ALS - DF-2                               *-30.444            18.3385
ALS - FT-100                             *31.5783            18.3385
CA - DF-2                                *-29.7595           19.0308
CA - FT-100                              *32.2628            19.0308
DF-2 - FT-100                            *62.0223            19.0308
--------------------------------------------------------------------------------
* denotes a statistically significant difference.
```

```
Multiple Range Tests for BSCO2 by MODE

--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
MODE            Count       LS Mean           Homogeneous Groups
--------------------------------------------------------------------------------
5               16          678.385           X
6               15          779.339            X
11              15          894.059             X
10              16          1055.85              X
--------------------------------------------------------------------------------
Contrast                                      Difference        +/-  Limits
--------------------------------------------------------------------------------
5  - 6                                         *-100.954         15.7259
5  - 10                                        *-377.464         15.4702
5  - 11                                        *-215.674         15.7259
6  - 10                                        *-276.51          15.7259
6  - 11                                        *-114.72          15.9776
10 - 11                                        *161.79           15.7259
--------------------------------------------------------------------------------
* denotes a statistically significant difference.
```


Interaction and 95% Tukey HSD Intervals

```
CONCLUSION:  No significant differences among the fuel and mode combinations
with respect to the average BSCO2.
```

```
Multifactor ANOVA - BSSOF (g/kW-hr)
                LPP Only   Modes 5,6,10,11


Analysis Summary

Dependent variable: bssof
Factors:
        fuel
        mode
Selection variable: mode<12

Number of complete cases: 61
```

Scatterplot by Level Code


```
Analysis of Variance for bssof - Type III Sums of Squares
--------------------------------------------------------------------------------
Source               Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                  0.119091      4     0.0297726      47.06     0.0000
 B:mode                  0.0867779     3     0.028926       45.73     0.0000

INTERACTIONS
 AB                      0.0319369    12     0.0026614       4.21     0.0003

RESIDUAL                 0.025936     41     0.000632586
--------------------------------------------------------------------------------
TOTAL (CORRECTED)        0.25938      60
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.


CONCLUSION:  Statistically significant differences in the average BSSOF among the
fuels, modes, and fuel*mode interaction.
```

Means and 95% Tukey Intervals


```
CONCLUSION: There are three distinct fuel groupings with respect to the average
```

BSSOF. The FT-100 fuel is significantly different from the remaining four fuels.
The DF-2 and CA fuels are not significantly different from one another, but are
different from the other three fuels. Also, the ALS and ADMM15 fuels are not
significantly different from one another, but are different from the other
three fuels.

Means and 95% Tukey Intervals

CONCLUSION: The average BSSOF for mode 10 is significantly different from the
remaining three modes. The average BSSOF for modes 5, 6, and 11 are not significantly
different from one another.

Multiple Range Tests for bssof by fuel

Method: 95.0 percent Tukey HSD
fuel   Count   LS Mean   Homogeneous Groups

FT-100   11   0.0812057   X
ADMM15   12   0.125126   X
ALS   14   0.151043   X
CA   12   0.190591   X
DF-2   12   0.209108   X

Contrast   Difference   +/- Limits

ADMM15 - ALS   -0.0259175   0.0282299
ADMM15 - CA   *-0.0654649   0.0292956
ADMM15 - DF-2   *-0.0839822   0.0292956
ADMM15 - FT-100   *0.04392   0.029954
ALS - CA   *-0.0395474   0.0282299
ALS - DF-2   *-0.0580647   0.0282299
ALS - FT-100   *0.0698376   0.0289126
CA - DF-2   -0.0185173   0.0292956
CA - FT-100   *0.109385   0.029954
DF-2 - FT-100   *0.127902   0.029954
----
* denotes a statistically significant difference.

Multiple Range Tests for bssof by mode

Method: 95.0 percent Tukey HSD
mode   Count   LS Mean   Homogeneous Groups
----
5   16   0.118924   X
6   15   0.13431   X
11   14   0.137743   X
10   16   0.214683   X

Contrast   Difference   +/- Limits
----
5 - 6   -0.0153858   0.0242062
5 - 10   *-0.0957587   0.0238126

E-19

```
5 - 11                                          -0.0188186            0.0246484
6 - 10                                         *-0.0803729            0.0242062
6 - 11                                          -0.00343286           0.0250289
10 - 11                                         *0.0769401            0.0246484
------------------------------------------------------------------------------
* denotes a statistically significant difference.
```


Interactions and 95% Tukey HSD Intervals

```
CONCLUSION:  The trend in the average BSSOF across the fuels is different for
mode 10 at the CA and DF-2 fuels.  The trends in the average BSSOF across the fuels
for modes 5, 6, and 11 do not appear to be different.
```

```
Multifactor ANOVA - BENZENE (mg/kW-hr)   Toxic Gaseous Emissions
                    LPP Only   Modes 5,6,10,11

Analysis Summary

Dependent variable: BENZENE
Factors:
        FUEL
        MODE
Selection variable: MODE<12

Number of complete cases: 62
```

Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for BENZENE - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares   Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:FUEL                117.444        4       29.361       36.42      0.0000
 B:MODE                318.024        3      106.008      131.48      0.0000

INTERACTIONS
 AB                     71.702       12      5.97517       7.41       0.0000

RESIDUAL                33.8638      42      0.806281
--------------------------------------------------------------------------------
TOTAL (CORRECTED)      545.5         61
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.
```

CONCLUSION: Statistically significant differences in the average benzene among the
fuels, modes, and fuel*mode interaction.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average benzene for the ADMM15 and FT-100 fuels are not significantly different from one another, but are significantly different from the remaining three fuels. The average benzene for the ALS fuel is significantly different than the average benzene for the CA fuel.

Means and 95% Tukey HSD Intervals

CONCLUSION: There are three distinct mode groupings with respect to the average benzene. Modes 10 and 11 are not significantly different from one another, but are significantly different than the other two modes. Modes 5 and 6 are significantly different from one another and the other two modes.

```
Multiple Range Tests for BENZENE by FUEL


--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
FUEL            Count     LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
ADMM15          12        1.50136          X
FT-100          12        1.81143          X
ALS             14        3.45994           X
DF-2            12        4.34774           XX
CA              12        5.0951            X
--------------------------------------------------------------------------------
Contrast                                Difference          +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                            *-1.95858           1.00676
ADMM15 - CA                             *-3.59373           1.04476
ADMM15 - DF-2                           *-2.84638           1.04476
ADMM15 - FT-100                          -0.310068          1.04476
ALS - CA                                *-1.63515           1.00676
ALS - DF-2                               -0.8878            1.00676
ALS - FT-100                            *1.64851            1.00676
CA - DF-2                                0.747355           1.04476
CA - FT-100                             *3.28366            1.04476
DF-2 - FT-100                           *2.53631            1.04476
--------------------------------------------------------------------------------
* denotes a statistically significant difference.
```

```
Multiple Range Tests for BENZENE by MODE

--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
MODE            Count      LS Mean            Homogeneous Groups
--------------------------------------------------------------------------------
5               16         0.392344           X
6               15         1.70996             X
11              15         5.02793              X
10              16         5.84222              X
--------------------------------------------------------------------------------
Contrast                                      Difference         +/-  Limits
--------------------------------------------------------------------------------
5 - 6                                         *-1.31762          0.863329
5 - 10                                        *-5.44988          0.84929
5 - 11                                        *-4.63559          0.863329
6 - 10                                        *-4.13226          0.863329
6 - 11                                        *-3.31797          0.877143
10 - 11                                        0.814288          0.863329
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: The ALS, CA, and DF-2 fuels have significantly different average
benzene at modes 10 and 11 than at modes 5 and 6. All other fuels do not demonstrate
significant differences in the average benzene among the four modes.

```
Multifactor ANOVA - 1,3 Butadiene (mg/kW-hr)   Toxic Gaseous Emissions
                    LPP Only  Modes 5,6,10,11

Analysis Summary

Dependent variable: BUTAD
Factors:
        MODE
        FUEL
Selection variable: MODE<12

Number of complete cases: 62
```

Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for BUTAD - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares    Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:MODE                 379.258        3       126.419     304.67      0.0000
 B:FUEL                 41.8936        4       10.4734      25.24      0.0000

INTERACTIONS
 AB                     36.8996       12       3.07497       7.41      0.0000

RESIDUAL                17.4272       42      0.414933
--------------------------------------------------------------------------------
TOTAL (CORRECTED)       475.499       61
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average 1,3 butadiene
among the fuels, modes, and fuel*mode interaction.
```

Means and 95% Tukey HSD Intervals

CONCLUSION: There are three distinct fuel groupings with respect to the average 1,3
butadiene.
The average 1,3 butadiene for the FT-100 fuel is significantly different than the
remaining
four fuels. The ADMM15 and ALS fuels are not significantly different from one another,
but
are significantly different than the other three fuels. Also, the DF-2 and CA fuels are
not significantly different from one another, but are significantly different from the
other three fuels.

Means and 95% Tukey HSD Intervals

CONCLUSION: There are three distinct mode groupings with respect to the average
1,3 butadiene. Modes 10 and 11 are significantly different from one another and the
remaining two modes. Modes 5 and 6 are not significantly different from one another
but are significantly different from the other two modes.

Multiple Range Tests for BUTAD by FUEL


```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
FUEL            Count     LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
FT-100          12        1.92136          X
ADMM15          12        2.79864           X
ALS             14        3.18606           X
DF-2            12        3.99958            X
CA              12        4.22908            X
--------------------------------------------------------------------------------
Contrast                                 Difference          +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                              -0.387414          0.722221
ADMM15 - CA                              *-1.43044           0.749484
ADMM15 - DF-2                            *-1.20094           0.749484
ADMM15 - FT-100                          *0.877277           0.749484
ALS - CA                                 *-1.04303           0.722221
ALS - DF-2                               *-0.813527          0.722221
ALS - FT-100                             *1.26469            0.722221
```

E-25

```
CA - DF-2                                     0.229499              0.749484
CA - FT-100                                  *2.30772               0.749484
DF-2 - FT-100                                *2.07822               0.749484
-------------------------------------------------------------------------------
* denotes a statistically significant difference.



Multiple Range Tests for BUTAD by MODE


-------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
MODE           Count     LS Mean          Homogeneous Groups
-------------------------------------------------------------------------------
5              16        0.560078          X
6              15        1.09161           X
11             15        4.86034            X
10             16        6.39576             X
-------------------------------------------------------------------------------
Contrast                                     Difference            +/-  Limits
-------------------------------------------------------------------------------
5  - 6                                        -0.531529             0.61933
5  - 10                                      *-5.83568              0.609259
5  - 11                                      *-4.30026              0.61933
6  - 10                                      *-5.30415              0.61933
6  - 11                                      *-3.76873              0.62924
10 - 11                                      *1.53542               0.61933
-------------------------------------------------------------------------------
* denotes a statistically significant difference.
```

Interaction and 95% Tukey HSD Intervals

CONCLUSION: The DF-2 and CA fuels have significantly different average
1,3 butadiene at mode 10 than at the remaining three modes. All other
fuels do not demonstrate significant differences in the average 1,3 butadiene
among the four modes.

E-26

```
Multifactor ANOVA - Formaldehyde (mg/kW-hr)   Toxic Gaseous Emissions
                    LPP Only   Modes 5,6,10,11

Analysis Summary

Dependent variable: FORMALD
Factors:
        MODE
        FUEL
Selection variable: MODE<12

Number of complete cases: 61
```

Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for FORMALD - Type III Sums of Squares
--------------------------------------------------------------------------------
Source                  Sum of Squares   Df     Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:MODE                      1.78043E6     3        593477.0    140.26    0.0000
 B:FUEL                       243068.0     4         60766.9     14.36    0.0000

INTERACTIONS
 AB                           226880.0    12         18906.7      4.47    0.0001

RESIDUAL                      173482.0    41          4231.27
--------------------------------------------------------------------------------
TOTAL (CORRECTED)           2.44233E6     60
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average formaldehyde
among the fuels, modes, and fuel*mode interaction.
```

Means and 95% Tukey HSD Intervals

CONCLUSION: The average formaldehyde for the DF-2 fuel is not significantly different than the average formaldehyde for the CA fuel, but it is significantly different than the ADMM15, FT-100, and ALS fuels. The average formaldehyde at the FT-100 fuel is not significantly different than the ADMM15 fuel, but it is significantly different than the ALS, CA, and DF-2 fuels.

Means and 95% Tukey HSD Intervals

CONCLUSION: There are three distinct mode groupings with respect to the average formaldehyde. Modes 10 and 11 are significantly different from one another and the remaining two modes. Modes 5 and 6 are not significantly different from one another but are significantly different from the other two modes.

Multiple Range Tests for FORMALD by FUEL

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
FUEL          Count     LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
FT-100         12       160.347            X
ADMM15         12       195.548            XX
ALS            14       258.61              X
CA             11       271.78             XX
DF-2           12       343.987             X
--------------------------------------------------------------------------------
Contrast                                  Difference        +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                               -63.0621          73.0105
ADMM15 - CA                                -76.2323          77.4694
ADMM15 - DF-2                             *-148.439          75.7666
ADMM15 - FT-100                            35.2004           75.7666
ALS - CA                                   -13.1703          74.7761
ALS - DF-2                                *-85.3773          73.0105
ALS - FT-100                              *98.2624           73.0105
CA - DF-2                                  -72.207           77.4694
CA - FT-100                               *111.433           77.4694
DF-2 - FT-100                             *183.64            75.7666
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

E-28

```
Multiple Range Tests for FORMALD by MODE

--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
MODE            Count    LS Mean           Homogeneous Groups
--------------------------------------------------------------------------------
5               16       59.7879           X
6               14       107.775           X
11              15       339.847            X
10              16       476.807             X
--------------------------------------------------------------------------------
Contrast                                   Difference        +/-  Limits
--------------------------------------------------------------------------------
5 - 6                                      -47.9867          63.7477
5 - 10                                     *-417.02          61.5861
5 - 11                                     *-280.059         62.6041
6 - 10                                     *-369.033         63.7477
6 - 11                                     *-232.073         64.7317
10 - 11                                    *136.96           62.6041
--------------------------------------------------------------------------------

* denotes a statistically significant difference.
```

Interaction and 95% Tukey HSD Intervals

CONCLUSION: The ALS and DF-2 fuels have significantly different average formaldehyde
at modes 10 and 11 than at the remaining two modes. All other fuels do not
demonstrate this difference. However, the average formaldehyde for the CA fuel at
mode 10 is significantly different than the other three modes.

```
Multifactor ANOVA - Acetaldehyde (mg/kW-hr)   Toxic Gaseous Emissions
                  LPP Only   Modes 5,6,10,11

Analysis Summary

Dependent variable: ACETALD
Factors:
        MODE
        FUEL
Selection variable: MODE<12

Number of complete cases: 61
```

Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for ACETALD - Type III Sums of Squares
--------------------------------------------------------------------------------
Source                Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:MODE                   229776.0      3       76591.9     117.33    0.0000
 B:FUEL                    39603.9      4       9900.99      15.17    0.0000

INTERACTIONS
 AB                        30463.6     12       2538.64       3.89    0.0005

RESIDUAL                   26765.0     41       652.805
--------------------------------------------------------------------------------
TOTAL (CORRECTED)         330272.0     60
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average acetaldehyde
among the fuels, modes, and fuel*mode interaction.
```

Means and 95% Tukey HSD Intervals

CONCLUSION: The average acetaldehyde for the FT-100 and ADMM15 fuels are not
significantly different from one another. The average acetaldehyde for the ALS, CA,
and DF-2 fuels are not significantly different from one another, but are
significantly different from the FT-100 and ADMM15 fuels.

Means and 95% Tukey HSD Intervals

CONCLUSION: There are three distinct mode groupings with respect to the
average acetaldehyde. Modes 10 and 11 are significantly different from one another
and the remaining two modes. Modes 5 and 6 are not significantly different
from one another but are significantly different from the other two modes.

Multiple Range Tests for ACETALD by FUEL

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
FUEL            Count    LS Mean       Homogeneous Groups
--------------------------------------------------------------------------------
FT-100          12       58.6822          X
ADMM15          12       69.034           X
ALS             14       104.807           X
CA              11       105.591           X
DF-2            12       128.336           X
--------------------------------------------------------------------------------
Contrast                                Difference       +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                            *-35.773         28.6775
ADMM15 - CA                             *-36.5574        30.4289
ADMM15 - DF-2                           *-59.3016        29.7601
ADMM15 - FT-100                          10.3518         29.7601
ALS - CA                                 -0.784358       29.371
ALS - DF-2                               -23.5285        28.6775
ALS - FT-100                            *46.1248         28.6775
CA - DF-2                                -22.7442        30.4289
CA - FT-100                             *46.9092         30.4289
DF-2 - FT-100                           *69.6533         29.7601
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

```
Multiple Range Tests for ACETALD by MODE

--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
MODE            Count     LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
5               16        26.3907          X
6               14        43.4665          X
11              15        127.304           X
10              16        175.999            X
--------------------------------------------------------------------------------
Contrast                                   Difference        +/-  Limits
--------------------------------------------------------------------------------
5  - 6                                      -17.0759          25.0392
5  - 10                                    *-149.608          24.1902
5  - 11                                    *-100.913          24.59
6  - 10                                    *-132.532          25.0392
6  - 11                                    *-83.8375          25.4257
10 - 11                                    *48.6949           24.59
--------------------------------------------------------------------------------

* denotes a statistically significant difference.
```


Interaction and 95% Tukey HSD Intervals

```
CONCLUSION:  The ALS and DF-2 fuels have significantly different average acetaldehyde
at modes 10 and 11 than at the remaining two modes.  All other fuels do not
demonstrate this difference.  However, the average acetaldehyde for the CA fuel at
mode 10 is significantly different than the other three modes.
```

```
Multifactor ANOVA - NAPHTHALENE (µg/kW-hr)   Gaseous PAH
                 LPP Only   Modes 5,6,10,11

Analysis Summary

Dependent variable: GNAPHTH
Factors:
        FUEL
        MODE
Selection variable: MODE<12

Number of complete cases: 62
```

Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for GNAPHTH - Type III Sums of Squares
--------------------------------------------------------------------------------
Source                Sum of Squares    Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:FUEL                  1.14822E8        4     2.87056E7      127.16     0.0000
 B:MODE                  5.84374E7        3     1.94791E7       86.29     0.0000

INTERACTIONS
 AB                      6.52183E7       12     5.43486E6       24.08     0.0000

RESIDUAL                 9.48109E6       42      225740.0
--------------------------------------------------------------------------------
TOTAL (CORRECTED)        2.44846E8       61
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average naphthalene
among the fuels, modes, and fuel*mode interaction.
```

Means and 95% Tukey HSD Intervals

CONCLUSION: There are four distinct fuel groupings with respect to the average naphthalene. ALS, DF-2, and CA fuels are all significantly different from one another. Also, fuels ADMM15 and FT-100 are not significantly different from one another, but they are both significantly different from the other three fuels.

Means and 95% Tukey HSD Intervals

CONCLUSION: All four modes are significantly different from one another with respect to the average naphthalene.

Multiple Range Tests for GNAPHTH by FUEL

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
FUEL            Count    LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
FT-100          12       211.807          X
ADMM15          12       352.674          X
ALS             14       950.021           X
DF-2            12       2259.44            X
CA              12       3881.48             X
--------------------------------------------------------------------------------
Contrast                                   Difference       +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                               *-597.347        532.703
ADMM15 - CA                                *-3528.81        552.812
ADMM15 - DF-2                              *-1906.76        552.812
ADMM15 - FT-100                             140.867         552.812
ALS - CA                                   *-2931.46        532.703
ALS - DF-2                                 *-1309.41        532.703
ALS - FT-100                               *738.214         532.703
CA - DF-2                                  *1622.05         552.812
CA - FT-100                                *3669.67         552.812
DF-2 - FT-100                              *2047.63         552.812
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

Multiple Range Tests for GNAPHTH by MODE

E-34

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
MODE          Count    LS Mean         Homogeneous Groups
--------------------------------------------------------------------------------
5              16       323.13          X
6              15       883.544          X
11             15       2190.63           X
10             16       2727.03            X
--------------------------------------------------------------------------------
Contrast                                  Difference         +/-  Limits
--------------------------------------------------------------------------------
5 - 6                                     *-560.415          456.812
5 - 10                                    *-2403.9           449.384
5 - 11                                    *-1867.5           456.812
6 - 10                                    *-1843.48          456.812
6 - 11                                    *-1307.09          464.121
10 - 11                                   *536.397           456.812
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: The CA and DF-2 fuels have significantly different average naphthalene
at modes 10 and 11 than at modes 5 and 6. All other fuels do not demonstrate
significant differences in the average naphthalene among the four modes.

```
Multifactor ANOVA - 2-Methylnaphthalene (µg/kW-hr)  Gaseous PAH
                  LPP Only   Modes 5,6,10,11

Analysis Summary

Dependent variable: METHYL2
Factors:
        FUEL
        MODE
Selection variable: MODE < 12

Number of complete cases: 62
```

Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for METHYL2 - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:FUEL                 9.45452E7     4     2.36363E7     89.10     0.0000
 B:MODE                 4.08008E7     3     1.36003E7     51.27     0.0000

INTERACTIONS
 AB                     5.19123E7     12    4.32603E6     16.31     0.0000

RESIDUAL                1.11418E7     42     265281.0
--------------------------------------------------------------------------------
TOTAL (CORRECTED)       1.96183E8     61
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

Conclusion:  Statistically significant differences in the average 2-Methylnaphthalene
among the fuels, modes, and fuel*mode interaction.
```

Means and 95% Tukey HSD Intervals

CONCLUSION: Average 2-methylnaphthalene at Modes 5 and 6 are not significantly different from one another, but significantly different from modes 10 and 11. Modes 10 and 11 are not significantly different from one another with respect to the average 2-methylnaphthalene.

Means and 95% Tukey HSD Intervals

CONCLUSION: Average 2-methylnaphthalene for fuels FT-100, ADMM15, and ALS are not significantly different from one another. The average 2-methylnaphthalene for fuels CA and DF-2 are significantly different from one another.

```
Multiple Range Tests for METHYL2 by MODE


--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
MODE          Count     LS Mean           Homogeneous Groups
--------------------------------------------------------------------------------
5             16        282.936           X
6             15        693.966           X
11            15        1948.64            X
10            16        2195.93            X
--------------------------------------------------------------------------------
Contrast                                  Difference        +/-  Limits
--------------------------------------------------------------------------------
5 - 6                                      -411.03          495.207
5 - 10                                    *-1912.99         487.154
5 - 11                                    *-1665.7          495.207
6 - 10                                    *-1501.96         495.207
6 - 11                                    *-1254.67         503.13
10 - 11                                    247.288          495.207
--------------------------------------------------------------------------------
* denotes a statistically significant difference.



Multiple Range Tests for METHYL2 by FUEL
```

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
FUEL            Count    LS Mean        Homogeneous Groups
--------------------------------------------------------------------------------
FT-100          12       107.033        X
ADMM15          12       183.294        X
ALS             14       646.591        X
CA              12       2173.94         X
DF-2            12       3290.98          X
--------------------------------------------------------------------------------
Contrast                                 Difference        +/-   Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                             -463.297          577.476
ADMM15 - CA                             *-1990.65          599.276
ADMM15 - DF-2                           *-3107.68          599.276
ADMM15 - FT-100                          76.2607           599.276
ALS - CA                                *-1527.35          577.476
ALS - DF-2                              *-2644.38          577.476
ALS - FT-100                             539.557           577.476
CA - DF-2                               *-1117.03          599.276
CA - FT-100                             *2066.91           599.276
DF-2 - FT-100                           *3183.94           599.276
--------------------------------------------------------------------------------

* denotes a statistically significant difference.
```


Interaction and 95% Tukey HSD Intervals

```
CONCLUSION:  Modes 10 and 11 have significantly different average 2-methylnaphthalene
for the CA and DF-2 fuels.  All other fuels do not demonstrate differences in the
average 2-methylnaphthalene among the four modes.
```

```
Multifactor ANOVA - 1-Methylnaphthalene (µg/kW-hr)   Gaseous PAH
                    LPP Only   Modes 5,6,10,11

Analysis Summary

Dependent variable: METHYL1
Factors:
        FUEL
        MODE
Selection variable: MODE<12

Number of complete cases: 62
```

Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for METHYL1 - Type III Sums of Squares
--------------------------------------------------------------------------------
Source               Sum of Squares    Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:FUEL                 4.27538E7        4     1.06885E7     83.75    0.0000
 B:MODE                 1.61965E7        3     5.39884E6     42.30    0.0000

INTERACTIONS
 AB                     2.33649E7       12     1.94707E6     15.26    0.0000

RESIDUAL                5.36042E6       42      127629.0
--------------------------------------------------------------------------------
TOTAL (CORRECTED)       8.67884E7       61
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average 1-methylnaphthalene
among the fuels, modes and fuel*mode interaction.
```

Means and 95% Tukey HSD Intervals

CONCLUSION: There were three distinct fuel groupings with respect to the average
1-methylnaphthalene. CA and DF-2 fuels were significantly different from one another and
the other three fuels. ADMM15, ALS, and FT-100 fuels were not significantly
different from one another.

Means and 95% Tukey HSD Intervals

CONCLUSION: Average 1-methylnaphthalene at modes 5 and 6 are not significantly
different from one another. Average 1-methylnaphthalene at modes 10 and 11
are not significantly different from one another, but are significantly
different from modes 5 and 6.

Multiple Range Tests for METHYL1 by FUEL

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
FUEL            Count      LS Mean           Homogeneous Groups
--------------------------------------------------------------------------------
FT-100          12         61.5376           X
ADMM15          12         86.5013           X
ALS             14         363.927           X
CA              12         1212.87            X
DF-2            12         2256.67             X
--------------------------------------------------------------------------------
Contrast                                     Difference       +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                                 -277.426         400.549
ADMM15 - CA                                 *-1126.37         415.669
ADMM15 - DF-2                               *-2170.17         415.669
ADMM15 - FT-100                               24.9637         415.669
ALS - CA                                    *-848.947         400.549
ALS - DF-2                                  *-1892.74         400.549
ALS - FT-100                                  302.389         400.549
CA - DF-2                                   *-1043.8          415.669
CA - FT-100                                 *1151.34          415.669
DF-2 - FT-100                               *2195.13          415.669
--------------------------------------------------------------------------------
```
* denotes a statistically significant difference.

E-40

```
Multiple Range Tests for METHYL1 by MODE


--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
MODE          Count     LS Mean           Homogeneous Groups
--------------------------------------------------------------------------------
5             16        170.726           X
6             15        421.11            X
11            15        1228.57            X
10            16        1364.8             X
--------------------------------------------------------------------------------
Contrast                                  Difference        +/-  Limits
--------------------------------------------------------------------------------
5  - 6                                     -250.385          343.485
5  - 10                                   *-1194.07          337.899
5  - 11                                   *-1057.85          343.485
6  - 10                                   *-943.689          343.485
6  - 11                                   *-807.464          348.981
10 - 11                                    136.225           343.485
--------------------------------------------------------------------------------
* denotes a statistically significant difference.
```

Interaction and 95% Tukey HSD Intervals

CONCLUSION: The CA and DF-2 fuels have significantly different average
1-methylnaphthalene at modes 10 and 11 than at modes 5 and 6. All other
fuels do not demonstrate significant differences in the average
1-methylnaphthalene among the four modes.

```
Multifactor ANOVA - 2,6-Dimethylnaphthalene (µg/kW-hr)   Gaseous PAH
                    LPP Only   Modes 5,6,10,11

Analysis Summary

Dependent variable: DIMETHYL
Factors:
        FUEL
        MODE
Selection variable: MODE<12

Number of complete cases: 62
```


Scatterplot by Level Code

Scatterplot by Level Code

```
Analysis of Variance for DIMETHYL - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:FUEL                 4.83445E7      4      1.20861E7    69.59    0.0000
 B:MODE                 9.92486E6      3      3.30829E6    19.05    0.0000

INTERACTIONS
 AB                     2.31461E7     12      1.92884E6    11.11    0.0000

RESIDUAL                7.29431E6     42       173674.0
--------------------------------------------------------------------------------
TOTAL (CORRECTED)       8.81659E7     61
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average 2,6-Dimethylnaphthalene
among the fuels, modes, and fuel*mode interaction.
```

Means and 95% Tukey HSD Intervals

CONCLUSION: The average 2,6-dimethylnaphthalene for the DF-2 fuel is significantly different than the other four fuels. The average 2,6-dimethylnaphthalene among the ADMM15, ALS, CA, and FT-100 fuels are not significantly different from one another.

Means and 95% Tukey HSD Intervals

CONCLUSION: Average 2,6-dimethylnaphthalene at modes 5 and 6 are not significantly different from one another. Average 2,6-dimethylnaphthalene at modes 10 and 11 are not significantly different from one another, but are significantly different than modes 5 and 6.

Multiple Range Tests for DIMETHYL by FUEL

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
FUEL          Count    LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
ADMM15        12       41.3485          X
FT-100        12       43.5168          X
ALS           14       227.587          X
CA            12       522.143          X
DF-2          12       2402.48           X
--------------------------------------------------------------------------------
Contrast                                Difference         +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                            -186.238           467.249
ADMM15 - CA                             -480.795           484.887
ADMM15 - DF-2                           *-2361.14          484.887
ADMM15 - FT-100                         -2.16827           484.887
ALS - CA                                -294.556           467.249
ALS - DF-2                              *-2174.9           467.249
ALS - FT-100                             184.07            467.249
CA - DF-2                               *-1880.34          484.887
CA - FT-100                              478.626           484.887
DF-2 - FT-100                           *2358.97           484.887
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

E-43

```
Multiple Range Tests for DIMETHYL by MODE

--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
MODE          Count    LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
5             16       152.253          X
6             15       355.65           X
11            15       1030.29           X
10            16       1051.47           X
--------------------------------------------------------------------------------
Contrast                                 Difference      +/-  Limits
--------------------------------------------------------------------------------
5  - 6                                    -203.396        400.683
5  - 10                                  *-899.217        394.167
5  - 11                                  *-878.036        400.683
6  - 10                                  *-695.821        400.683
6  - 11                                  *-674.64         407.094
10 - 11                                   21.1803         400.683
--------------------------------------------------------------------------------

* denotes a statistically significant difference.
```


Interaction and 95% Tukey HSD Intervals

CONCLUSION: The DF-2 fuel has significantly different average 2,6-dimethylnaphthalene
at modes 10 and 11 than at modes 5 and 6. All other fuels do not demonstrate
significant differences in the average 2,6-dimethylnaphthalene among the four modes.

```
Multifactor ANOVA - Acenaphthylene (µg/kW-hr)   Gaseous PAH
                   LPP Only   Modes 5,6,10,11

Analysis Summary

Dependent variable: GACENAPH
Factors:
        MODE
        FUEL
Selection variable: MODE < 12

Number of complete cases: 62
```

Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for GACENAPH - Type III Sums of Squares
--------------------------------------------------------------------------------
Source               Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:MODE                  126587.0      3       42195.7     10.52     0.0000
 B:FUEL                  283597.0      4       70899.2     17.68     0.0000

INTERACTIONS
 AB                      165392.0     12       13782.6      3.44     0.0014

RESIDUAL                 168412.0     42        4009.81
--------------------------------------------------------------------------------
TOTAL (CORRECTED)        739866.0     61
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.
Multiple Range Tests for GACENAPH by MODE

CONCLUSION:  Statistically significant differences in the average acenaphthylene
among the fuels, modes, and fuel*mode interaction.
```

Means and 95% Tukey HSD Intervals

CONCLUSION: Average acenaphthylene at Mode 5 is significantly different from modes 10 and 11.

Means and 95% Tukey HSD Intervals

CONCLUSION: Average acenaphthylene is significantly different at fuel DF-2 compared to the
other four fuels. Average acenaphthylene at fuels ADMM15, ALS, CA, and FT-100 are not significantly different from one another.

Multiple Range Tests for GACENAPH by MODE

Method: 95.0 percent Tukey HSD
MODE   Count   LS Mean   Homogeneous Groups
----
5   16   30.8267   X
6   15   82.4049   XX
10   16   138.499   X
11   15   139.484   X

Contrast   Difference   +/- Limits
----
5 - 6   -51.5782   60.8828
5 - 10   *-107.672   59.8928
5 - 11   *-108.657   60.8828
6 - 10   -56.094   60.8828
6 - 11   -57.0787   61.857
10 - 11   -0.984737   60.8828
----
* denotes a statistically significant difference.

Multiple Range Tests for GACENAPH by FUEL

Method: 95.0 percent Tukey HSD
FUEL   Count   LS Mean   Homogeneous Groups

E-46

```
--------------------------------------------------------------------------------
ADMM15          12       36.3934           X
FT-100          12       40.0148           X
CA              12       82.8226           X
ALS             14      104.521            X
DF-2            12      225.265               X
--------------------------------------------------------------------------------
Contrast                                   Difference        +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                                -68.1281          70.9974
ADMM15 - CA                                 -46.4292          73.6775
ADMM15 - DF-2                              *-188.872          73.6775
ADMM15 - FT-100                              -3.62141         73.6775
ALS - CA                                     21.6988          70.9974
ALS - DF-2                                 *-120.744          70.9974
ALS - FT-100                                 64.5067          70.9974
CA - DF-2                                  *-142.443          73.6775
CA - FT-100                                  42.8078          73.6775
DF-2 - FT-100                              *185.25            73.6775
--------------------------------------------------------------------------------
* denotes a statistically significant difference.
Multifactor ANOVA - GACENAPH (MODE<12)
```

Interaction and 95% Tukey HSD Intervals


```
CONCLUSION:  Modes 10 and 11 have significantly different average acenaphthylene
for the DF-2 fuel.  All other fuels do not demonstrate differences in the average
acenaphthylene among the four modes.
```

```
Multifactor ANOVA - Acenaphthene (µg/kW-hr)   Gaseous PAH
                   LPP Only   Modes 5,6,10,11

Analysis Summary

Dependent variable: ACENAPTH
Factors:
        FUEL
        MODE
Selection variable: MODE<12

Number of complete cases: 62
```

Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for ACENAPTH - Type III Sums of Squares
--------------------------------------------------------------------------------
Source               Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:FUEL                   1.07169E6     4       267923.0     29.63    0.0000
 B:MODE                   192968.0      3        64322.8      7.11    0.0006

INTERACTIONS
 AB                       471924.0     12        39327.0      4.35    0.0002

RESIDUAL                  379788.0     42        9042.56
--------------------------------------------------------------------------------
TOTAL (CORRECTED)         2.10838E6    61
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average acenaphthene among
the fuels, modes, and fuel*mode interaction.
```

Means and 95% Tukey HSD Intervals

CONCLUSION: The average acenaphthene for the DF-2 fuel is significantly different than the average acenaphthene for the remaining four fuels.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average acenaphthene for mode 5 is significantly different than the average acenaphthene for modes 10 and 11. The average acenaphthene for mode 6 is significantly different than the average acenaphthene for mode 11.

```
Multiple Range Tests for ACENAPTH by FUEL

--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
FUEL            Count     LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
FT-100          12        8.10026          X
ADMM15          12        15.5047          X
ALS             14        32.1103          X
CA              12        54.6557          X
DF-2            12        358.314           X
--------------------------------------------------------------------------------
Contrast                                  Difference        +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                              -16.6056          106.617
ADMM15 - CA                               -39.151           110.642
ADMM15 - DF-2                             *-342.809         110.642
ADMM15 - FT-100                            7.40444          110.642
ALS - CA                                  -22.5454          106.617
ALS - DF-2                                *-326.204         106.617
ALS - FT-100                               24.01            106.617
CA - DF-2                                 *-303.658         110.642
CA - FT-100                                46.5554          110.642
DF-2 - FT-100                             *350.214          110.642
--------------------------------------------------------------------------------
* denotes a statistically significant difference.




Multiple Range Tests for ACENAPTH by MODE
```

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
MODE            Count       LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
5               16          24.2191          X
6               15          54.4957          XX
10              16          137.565           XX
11              15          158.668            X
--------------------------------------------------------------------------------
Contrast                                     Difference        +/-  Limits
--------------------------------------------------------------------------------
5 - 6                                         -30.2766         91.4279
5 - 10                                       *-113.346         89.9412
5 - 11                                       *-134.449         91.4279
6 - 10                                        -83.0696         91.4279
6 - 11                                       *-104.172         92.8908
10 - 11                                       -21.1024         91.4279
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: The average acenaphthene for the DF-2 fuel at modes 10 and 11 is
is significantly different than the average acenaphthene for modes 5 and 6. All the
other fuels do not demonstrate differences in the average acenaphthene among the
four modes.

```
Multifactor ANOVA - Fluorene (µg/kW-hr)   Gaseous PAH
                 LPP Only   Modes 5,6,10,11


Analysis Summary

Dependent variable: GFLUOREN
Factors:
        FUEL
        MODE
Selection variable: MODE<12

Number of complete cases: 62
```

Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for GFLUOREN - Type III Sums of Squares
--------------------------------------------------------------------------------
Source                Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:FUEL                   4.05735E6      4      1.01434E6    25.79    0.0000
 B:MODE                    399950.0      3       133317.0     3.39    0.0266

INTERACTIONS
 AB                       1.14654E6     12        95545.3     2.43    0.0169

RESIDUAL                  1.65166E6     42        39325.3
--------------------------------------------------------------------------------
TOTAL (CORRECTED)         7.23726E6     61
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average fluorene among
the fuels, modes, and fuel*mode interaction.
```

Means and 95% Tukey HSD Intervals

CONCLUSION: The average fluorene for the DF-2 fuel is significantly different than
the average fluorene for the remaining four fuels.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average fluorene for mode 5 is significantly different than the
average fluorene for mode 11.

Multiple Range Tests for GFLUOREN by FUEL

Method: 95.0 percent Tukey HSD
FUEL   Count   LS Mean   Homogeneous Groups

ADMM15   12   13.9645   X
FT-100   12   15.2342   X
ALS   14   42.389   X
CA   12   83.7276   X
DF-2   12   683.736   X

Contrast   Difference   +/- Limits

ADMM15 - ALS   -28.4245   222.34
ADMM15 - CA   -69.7631   230.733
ADMM15 - DF-2   *-669.772   230.733
ADMM15 - FT-100   -1.26976   230.733
ALS - CA   -41.3386   222.34
ALS - DF-2   *-641.347   222.34
ALS - FT-100   27.1547   222.34
CA - DF-2   *-600.009   230.733
CA - FT-100   68.4933   230.733
DF-2 - FT-100   *668.502   230.733
----
* denotes a statistically significant difference.

Multiple Range Tests for GFLUOREN by MODE

E-52

```
-------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
MODE          Count    LS Mean        Homogeneous Groups
-------------------------------------------------------------------------------
5              16       56.4247          X
6              15       130.158          XX
10             16       220.709          XX
11             15       263.949           X
-------------------------------------------------------------------------------
Contrast                                  Difference        +/-  Limits
-------------------------------------------------------------------------------
5 - 6                                      -73.7337          190.664
5 - 10                                    -164.284           187.564
5 - 11                                   *-207.525           190.664
6 - 10                                     -90.5503          190.664
6 - 11                                    -133.791           193.715
10 - 11                                    -43.2405          190.664
-------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

Interaction and 95%Tukey HSD Intervals

CONCLUSION: The average fluorene for the DF-2 fuel at modes 10 and 11 are significantly
different than the average fluorene at mode 5. All the other fuels do not demonstrate
differences in the average fluorene among the four modes.

```
Multifactor ANOVA - Phenanthrene  (µg/kW-hr)   Gaseous PAH
                   LPP Only   Modes 5,6,10,11

Analysis Summary

Dependent variable: GPHENANT
Factors:
        MODE
        FUEL
Selection variable: MODE<12

Number of complete cases: 62
```

Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for GPHENANT - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:MODE                 448855.0      3      149618.0      1.58     0.2096
 B:FUEL                1.51272E7      4      3.78179E6    39.81     0.0000

INTERACTIONS
 AB                     1.2989E6     12      108242.0      1.14     0.3562

RESIDUAL               3.98957E6     42       94989.8
--------------------------------------------------------------------------------
TOTAL (CORRECTED)      2.08233E7     61
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average phenanthrene
among the fuels.
```

Means and 95% Tukey HSD Intervals

CONCLUSION: No significant differences in the average phenanthrene among the
four modes.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average phenanthrene for the DF-2 fuel is significantly different
than the other four fuels. The average phenanthrene among the ADMM15, ALS, CA, and
FT-100 fuels are not significantly different from one another.

```
Multiple Range Tests for GPHENANT by MODE

--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
MODE            Count     LS Mean            Homogeneous Groups
--------------------------------------------------------------------------------
5               16        211.458            X
6               15        342.612            X
11              15        412.734            X
10              16        424.024            X
--------------------------------------------------------------------------------
Contrast                                     Difference        +/-  Limits
--------------------------------------------------------------------------------
5 - 6                                        -131.154          296.327
5 - 10                                       -212.566          291.509
5 - 11                                       -201.276          296.327
6 - 10                                       -81.4119          296.327
6 - 11                                       -70.1218          301.069
10 - 11                                      11.29             296.327
--------------------------------------------------------------------------------
* denotes a statistically significant difference.



Multiple Range Tests for GPHENANT by FUEL

--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
FUEL            Count     LS Mean            Homogeneous Groups
--------------------------------------------------------------------------------
```

E-55

```
ADMM15          12        33.4535          X
FT-100          12        42.2233          X
ALS             14        139.715          X
CA              12        179.898          X
DF-2            12        1343.24           X
-------------------------------------------------------------------------------
Contrast                                  Difference        +/-   Limits
-------------------------------------------------------------------------------
ADMM15 - ALS                               -106.261         345.557
ADMM15 - CA                                -146.445         358.601
ADMM15 - DF-2                             *-1309.79         358.601
ADMM15 - FT-100                            -8.76979         358.601
ALS - CA                                   -40.1836         345.557
ALS - DF-2                                *-1203.53         345.557
ALS - FT-100                                97.4916         345.557
CA - DF-2                                 *-1163.35         358.601
CA - FT-100                                137.675          358.601
DF-2 - FT-100                             *1301.02          358.601
-------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: No significant differences among the fuel and mode combinations with
respect to the average phenanthrene.

```
Multifactor ANOVA - Anthracene (µg/kW-hr)   Gaseous PAH
                   LPP Only   Modes 5,6,10,11

Analysis Summary

Dependent variable: GANTHR
Factors:
        MODE
        FUEL
Selection variable: MODE<12

Number of complete cases: 62
```

### Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for GANTHR - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:MODE                   709.29      3        236.43      3.54    0.0226
 B:FUEL                 14208.9       4       3552.23     53.11    0.0000

INTERACTIONS
 AB                      1879.1      12        156.592     2.34    0.0210

RESIDUAL                 2809.0      42         66.881
--------------------------------------------------------------------------------
TOTAL (CORRECTED)       19552.0      61
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average anthracene among
the fuels, modes, and fuel*mode interaction.
```

Means and 95% Tukey HSD Intervals

CONCLUSION: The average anthracene for the DF-2 fuel is significantly different
than the other four fuels. The average anthracene among the ADMM15, ALS, CA,
and FT-100 fuels are not significantly different from one another.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average anthracene for mode 5 is significantly different than the
average anthracene for mode 10.

```
Multiple Range Tests for GANTHR by FUEL


--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
FUEL            Count    LS Mean        Homogeneous Groups
--------------------------------------------------------------------------------
FT-100          12       1.64574        X
ADMM15          12       1.77037        X
ALS             14       5.54145        X
CA              12       8.30015        X
DF-2            12       42.1875         X
--------------------------------------------------------------------------------
Contrast                                Difference       +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                            -3.77108         9.16922
ADMM15 - CA                             -6.52978         9.51535
ADMM15 - DF-2                           *-40.4171        9.51535
ADMM15 - FT-100                          0.124628        9.51535
ALS - CA                                -2.7587          9.16922
ALS - DF-2                              *-36.6461        9.16922
ALS - FT-100                             3.89571         9.16922
CA - DF-2                               *-33.8874        9.51535
CA - FT-100                              6.6544          9.51535
DF-2 - FT-100                           *40.5418         9.51535
--------------------------------------------------------------------------------
* denotes a statistically significant difference.



Multiple Range Tests for GANTHR by MODE
```

E-58

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
MODE            Count    LS Mean         Homogeneous Groups
--------------------------------------------------------------------------------
5               16       6.63453         X
6               15       11.311          XX
11              15       14.414          XX
10              16       15.1967          X
--------------------------------------------------------------------------------
Contrast                                 Difference       +/-  Limits
--------------------------------------------------------------------------------
5  - 6                                    -4.67649         7.86293
5  - 10                                  *-8.56213         7.73507
5  - 11                                   -7.77945         7.86293
6  - 10                                   -3.88563         7.86293
6  - 11                                   -3.10296         7.98875
10 - 11                                   0.782677         7.86293
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: The average anthracene for the DF-2 fuel at modes 6, 10, and 11 are
significantly different than the anthracene for the other four fuels.

```
Multifactor ANOVA - Fluoranthene (µg/kW-hr)   Gaseous PAH
                  LPP Only   Modes 5,6,10,11


Analysis Summary

Dependent variable: GFLUORAN
Factors:
        FUEL
        MODE
Selection variable: MODE<12

Number of complete cases: 62
```


Scatterplot by Level Code

Scatterplot by Level Code

```
Analysis of Variance for GFLUORAN - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:FUEL                 1043.04       4      260.761      29.88     0.0000
 B:MODE                 21.1821       3      7.06069       0.81     0.4960

INTERACTIONS
 AB                     46.5359      12      3.87799       0.44     0.9350

RESIDUAL                366.514      42      8.72654
--------------------------------------------------------------------------------
TOTAL (CORRECTED)       1474.87      61
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant difference in the average fluoranthene
among the fuels.
```

Means and 95% Tukey HSD Intervals

CONCLUSION: The average fluoranthene for the DF-2 fuel is significantly different than the average fluoranthene for the remaining four fuels.

Means and 95% Tukey HSD Intervals

CONCLUSION: No significant differences in the average fluoranthene among the four modes.

Multiple Range Tests for GFLUORAN by FUEL

Method: 95.0 percent Tukey HSD
FUEL   Count   LS Mean   Homogeneous Groups

ADMM15   12   1.55023   X
FT-100   12   1.97221   X
ALS   14   3.42001   X
CA   12   4.17341   X
DF-2   12   12.9117   X

Contrast   Difference   +/- Limits

ADMM15 - ALS   -1.86978   3.31209
ADMM15 - CA   -2.62318   3.43712
ADMM15 - DF-2   *-11.3614   3.43712
ADMM15 - FT-100   -0.421982   3.43712
ALS - CA   -0.753401   3.31209
ALS - DF-2   *-9.49167   3.31209
ALS - FT-100   1.4478   3.31209
CA - DF-2   *-8.73827   3.43712
CA - FT-100   2.2012   3.43712
DF-2 - FT-100   *10.9395   3.43712
----
* denotes a statistically significant difference.

Multiple Range Tests for GFLUORAN by MODE

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
MODE          Count    LS Mean        Homogeneous Groups
--------------------------------------------------------------------------------
11            15       4.20058        X
5             16       4.2397         X
10            16       5.32028        X
6             15       5.46146        X
--------------------------------------------------------------------------------
Contrast                                Difference        +/-  Limits
--------------------------------------------------------------------------------
5  - 6                                   -1.22176          2.84023
5  - 10                                  -1.08058          2.79405
5  - 11                                  0.0391235         2.84023
6  - 10                                  0.14118           2.84023
6  - 11                                  1.26088           2.88568
10 - 11                                  1.1197            2.84023
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

Interaction and 95% Tukey HSD Intervals

```
CONCLUSION:  No significant differences among the fuel and mode combinations with
respect to the average fluoranthene.
```

```
Multifactor ANOVA - Pyrene (µg/kW-hr)   Gaseous PAH
                     LPP Only   Modes 5,6,10,11

Analysis Summary

Dependent variable: GPYRENE
Factors:
        MODE
        FUEL
Selection variable: MODE<12

Number of complete cases: 62
```

Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for GPYRENE - Type III Sums of Squares
--------------------------------------------------------------------------------
Source               Sum of Squares   Df    Mean Square   F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:MODE                  19.8872       3       6.62908      0.46      0.7140
 B:FUEL                  2095.77       4       523.943      36.10     0.0000

INTERACTIONS
 AB                      66.5375       12      5.54479      0.38      0.9628

RESIDUAL                 609.636       42      14.5151
--------------------------------------------------------------------------------
TOTAL (CORRECTED)        2787.64       61
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average pyrene among
the fuels.
```

E-63

Means and 95% Tukey HSD Intervals

CONCLUSION: The average pyrene for the DF-2 fuel is significantly different than the average pyrene for the remaining four fuels.

Means and 95% Tukey HSD Intervals

CONCLUSION: No significant differences in the average pyrene among the modes.

Multiple Range Tests for GPYRENE by FUEL

Method: 95.0 percent Tukey HSD
FUEL   Count   LS Mean   Homogeneous Groups

ADMM15   12   1.17274   X
FT-100   12   1.46172   X
ALS   14   3.00746   X
CA   12   3.32296   X
DF-2   12   16.8399   X

Contrast   Difference   +/- Limits

ADMM15 - ALS   -1.83472   4.27161
ADMM15 - CA   -2.15021   4.43286
ADMM15 - DF-2   *-15.6672   4.43286
ADMM15 - FT-100   -0.288977   4.43286
ALS - CA   -0.315494   4.27161
ALS - DF-2   *-13.8324   4.27161
ALS - FT-100   1.54574   4.27161
CA - DF-2   *-13.5169   4.43286
CA - FT-100   1.86124   4.43286
DF-2 - FT-100   *15.3782   4.43286
----
* denotes a statistically significant difference.

Multiple Range Tests for GPYRENE by MODE

Method: 95.0 percent Tukey HSD
MODE   Count   LS Mean   Homogeneous Groups

E-64

```
5              16        4.38002            X
11             15        4.89347            X
10             16        5.51762            X
6              15        5.85271            X
---------------------------------------------------------------------------
Contrast                                 Difference       +/-  Limits
---------------------------------------------------------------------------
5 - 6                                    -1.47269         3.66306
5 - 10                                   -1.1376          3.60349
5 - 11                                   -0.513451        3.66306
6 - 10                                   0.335096         3.66306
6 - 11                                   0.959242         3.72167
10 - 11                                  0.624146         3.66306
---------------------------------------------------------------------------
* denotes a statistically significant difference.
```

Interaction and 95% Tukey HSD Intervals


```
CONCLUSION:  No significant differences among the fuel and mode combinations with
respect to the average pyrene.
```

```
Multifactor ANOVA - Naphthalene (µg/kW-hr)   Soluble PAH
                LPP Only   Modes 5,6,10,11

Analysis Summary

Dependent variable: naphth
Factors:
        fuel
        mode
Selection variable: mode<12

Number of complete cases: 62
```

Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for naphth - Type III Sums of Squares
--------------------------------------------------------------------------------
Source                Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                   3529.36       4        882.34      2.92     0.0323
 B:mode                   2429.66       3        809.885     2.68     0.0592

INTERACTIONS
 AB                       2205.48      12        183.79      0.61     0.8231

RESIDUAL                 12698.1       42        302.335
--------------------------------------------------------------------------------
TOTAL (CORRECTED)        20659.1       61
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.


CONCLUSION:  Statistically significant differences in the average naphthalene
among the fuels and the modes.
```

E-66

Means and 95% Tukey Intervals

CONCLUSION: The average naphthalene for the CA and DF-2 fuels are significantly
different from the ADMM15 and ALS fuels, but not significantly different from one
another. The average naphthalene for the ADMM15 and ALS fuels are not significantly
different from one another.

Means and 95% Tukey Intervals

CONCLUSION: The average naphthalene for mode 10 is significantly different
from mode 5.

Multiple Range Tests for naphth by fuel

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
fuel          Count    LS Mean         Homogeneous Groups
--------------------------------------------------------------------------------
ALS           14       27.0444         X
ADMM15        12       28.4129         X
FT-100        12       36.7585         XX
DF-2          12       43.3494          X
CA            12       45.5031          X
--------------------------------------------------------------------------------
Contrast                                Difference        +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                            1.36846           13.8043
ADMM15 - CA                            *-17.0902          14.3254
ADMM15 - DF-2                          *-14.9365          14.3254
ADMM15 - FT-100                         -8.34559          14.3254
ALS - CA                               *-18.4587          13.8043
ALS - DF-2                             *-16.305           13.8043
ALS - FT-100                            -9.71405          13.8043
CA - DF-2                               2.15369           14.3254
CA - FT-100                             8.74463           14.3254
DF-2 - FT-100                           6.59093           14.3254
--------------------------------------------------------------------------------
```
* denotes a statistically significant difference.

Multiple Range Tests for naphth by mode

E-67

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
mode          Count     LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
5              16       27.6477              X
11             15       34.3223              XX
6              15       38.0808              XX
10             16       44.8038               X
--------------------------------------------------------------------------------
Contrast                                    Difference       +/-   Limits
--------------------------------------------------------------------------------
5 - 6                                        -10.4332         16.7177
5 - 10                                      *-17.1562         16.4459
5 - 11                                        -6.67461        16.7177
6 - 10                                        -6.72301        16.7177
6 - 11                                         3.75857        16.9852
10 - 11                                       10.4816         16.7177
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

Interactions and 95% Tukey HSD Intervals

```
CONCLUSION:  There is no significant interaction in the average naphthalene
among the fuel and mode combinations.
```

```
Multifactor ANOVA - Acenaphthylene (µg/kW-hr)   Soluble PAH
                 LPP Only   Modes 5,6,10,11

Analysis Summary

Dependent variable: acenaph
Factors:
        fuel
        mode
Selection variable: mode<12

Number of complete cases: 59
```

Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for acenaph - Type III Sums of Squares
--------------------------------------------------------------------------------
Source                Sum of Squares    Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                     1.49999      4       0.374998       4.66     0.0036
 B:mode                    0.335426      3       0.111809       1.39     0.2600

INTERACTIONS
 AB                         1.32025     12       0.110021       1.37     0.2221

RESIDUAL                    3.13513     39      0.0803879
--------------------------------------------------------------------------------
TOTAL (CORRECTED)           6.44463     58
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.


CONCLUSION:  Statistically significant differences in the average acenaphthylene
among the fuels.
```

E-69

Means and 95% Tukey Intervals

CONCLUSION: The average acenaphthylene for the CA fuel is significantly different than the FT-100 and ADMM15 fuels.

Means and 95% Tukey Intervals

CONCLUSION: No statistically significant differences in the average acenaphthylene among the modes.


Multiple Range Tests for acenaph by fuel

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
fuel           Count    LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
ADMM15         12       0.476752         X
FT-100         12       0.544934         X
ALS            12       0.597067         XX
DF-2           11       0.762226         XX
CA             12       0.915322          X
--------------------------------------------------------------------------------
Contrast                                 Difference          +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                             -0.120315           0.331015
ADMM15 - CA                             *-0.43857            0.331015
ADMM15 - DF-2                            -0.285475           0.338455
ADMM15 - FT-100                          -0.0681826          0.331015
ALS - CA                                 -0.318255           0.331015
ALS - DF-2                               -0.16516            0.338455
ALS - FT-100                             0.0521325           0.331015
CA - DF-2                                0.153096            0.338455
CA - FT-100                             *0.370388            0.331015
DF-2 - FT-100                            0.217292            0.338455
--------------------------------------------------------------------------------
* denotes a statistically significant difference.
```


Multiple Range Tests for acenaph by mode

```
--------------------------------------------------------------------------------
```

```
Method: 95.0 percent Tukey HSD
mode            Count    LS Mean         Homogeneous Groups
--------------------------------------------------------------------------------
5               14       0.549292        X
11              15       0.65586         X
6               14       0.668896        X
10              16       0.762994        X
--------------------------------------------------------------------------------
Contrast                                Difference      +/-  Limits
--------------------------------------------------------------------------------
5 - 6                                   -0.119604       0.28759
5 - 10                                  -0.213702       0.278458
5 - 11                                  -0.106568       0.282757
6 - 10                                  -0.0940977      0.278458
6 - 11                                  0.0130359       0.282757
10 - 11                                 0.107134        0.273463
--------------------------------------------------------------------------------
* denotes a statistically significant difference.
```


Interactions and 95% Tukey HSD Intervals

```
CONCLUSION:  There is no significant interaction in the average acenaphthylene
among the fuel and mode combinations.
```

```
Multifactor ANOVA - Acenaphthene (µg/kW-hr)   Soluble PAH
                 LPP Only   Modes 5,6,10,11

Analysis Summary

Dependent variable: acenapth
Factors:
        fuel
        mode
Selection variable: mode<12

Number of complete cases: 60
```

Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for acenapth - Type III Sums of Squares
--------------------------------------------------------------------------------
Source               Sum of Squares   Df   Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                  53.5982        4     13.3995      2.42     0.0646
 B:mode                  29.3303        3     9.77675      1.76     0.1699

INTERACTIONS
 AB                      37.0561       12      3.088       0.56     0.8629

RESIDUAL                 221.911       40     5.54777
--------------------------------------------------------------------------------
TOTAL (CORRECTED)        338.487       59
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.


CONCLUSION:  No statistically significant differences in the average acenaphthene
among the fuels, modes or interaction.
```

Means and 95% Tukey Intervals

CONCLUSION: No statistically significant differences in the average acenaphthene among the fuels.

Means and 95% Tukey Intervals

CONCLUSION: No statistically significant differences in the average acenaphthene among the modes.

Multiple Range Tests for acenapth by fuel

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
fuel            Count    LS Mean         Homogeneous Groups
--------------------------------------------------------------------------------
ALS             13       3.64246         X
FT-100          12       4.14432         X
ADMM15          12       4.34272         X
CA              12       5.23877         X
DF-2            11       6.3927          X
--------------------------------------------------------------------------------
Contrast                              Difference          +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                          0.700254            2.69325
ADMM15 - CA                           -0.896057           2.74659
ADMM15 - DF-2                         -2.04998            2.80832
ADMM15 - FT-100                       0.198397            2.74659
ALS - CA                              -1.59631            2.69325
ALS - DF-2                            -2.75023            2.75618
ALS - FT-100                          -0.501857           2.69325
CA - DF-2                             -1.15392            2.80832
CA - FT-100                           1.09445             2.74659
DF-2 - FT-100                         2.24838             2.80832
--------------------------------------------------------------------------------
* denotes a statistically significant difference.
```


Multiple Range Tests for acenapth by mode

```
--------------------------------------------------------------------------------
```

```
Method: 95.0 percent Tukey HSD
mode          Count    LS Mean         Homogeneous Groups
--------------------------------------------------------------------------------
5             15       3.80127         X
11            15       4.44134         X
6             14       5.12813         X
10            16       5.63804         X
--------------------------------------------------------------------------------
Contrast                                 Difference      +/-  Limits
--------------------------------------------------------------------------------
5  - 6                                    -1.32686        2.34637
5  - 10                                   -1.83677        2.26925
5  - 11                                   -0.640065       2.30556
6  - 10                                   -0.509911       2.3107
6  - 11                                   0.686793        2.34637
10 - 11                                   1.1967          2.26925
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

Interactions and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average acenaphthene among the fuel and mode combinations.

```
Multifactor ANOVA - Fluorene (µg/kW-hr)   Soluble PAH
                 LPP Only   Modes 5,6,10,11


Analysis Summary

Dependent variable: fluorene
Factors:
        fuel
        mode
Selection variable: mode<12

Number of complete cases: 59
```

Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for fluorene - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                  224.986      4       56.2465       3.31     0.0198
 B:mode                  33.6482      3       11.2161       0.66     0.5811

INTERACTIONS
 AB                      212.384     12       17.6986       1.04     0.4317

RESIDUAL                 661.915     39       16.9722
--------------------------------------------------------------------------------
TOTAL (CORRECTED)       1158.59      58
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.


CONCLUSION:  Statistically significant differences in the average fluorene among
the fuels.
```

Means and 95% Tukey Intervals

CONCLUSION: The average fluorene for the DF-2 fuel is significantly different from the FT-100 fuel.

Means and 95% Tukey Intervals

CONCLUSION: There is no significant difference in the average fluorene among the modes.

Multiple Range Tests for fluorene by fuel

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
fuel           Count     LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
FT-100         12        5.76877          X
ADMM15         12        7.04309          XX
ALS            11        7.27518          XX
CA             12        9.12758          XX
DF-2           12        11.3521           X
--------------------------------------------------------------------------------
Contrast                                  Difference         +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                              -0.232095          4.91784
ADMM15 - CA                               -2.08449           4.80974
ADMM15 - DF-2                             -4.30904           4.80974
ADMM15 - FT-100                           1.27432            4.80974
ALS - CA                                  -1.8524            4.91784
ALS - DF-2                                -4.07695           4.91784
ALS - FT-100                              1.50641            4.91784
CA - DF-2                                 -2.22455           4.80974
CA - FT-100                               3.35881            4.80974
DF-2 - FT-100                             *5.58336           4.80974
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

Multiple Range Tests for fluorene by mode

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
```

```
mode            Count    LS Mean          Homogeneous Groups
-----------------------------------------------------------------------------
5               14       7.17223          X
6               15       7.83432          X
11              14       8.19741          X
10              16       9.24944          X
-----------------------------------------------------------------------------
Contrast                                  Difference       +/-  Limits
-----------------------------------------------------------------------------
5 - 6                                     -0.662093        4.10853
5 - 10                                    -2.07721         4.04607
5 - 11                                    -1.02518         4.17876
6 - 10                                    -1.41512         3.97349
6 - 11                                    -0.363092        4.10853
10 - 11                                   1.05203          4.04607
-----------------------------------------------------------------------------
```

* denotes a statistically significant difference.

Interactions and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average fluorene among
the fuel and mode combinations.

```
Multifactor ANOVA - Phenanthrene (µg/kW-hr)   Soluble PAH
                  LPP Only   modes 5,6,10,11

Analysis Summary

Dependent variable: phenanth
Factors:
        fuel
        mode
Selection variable: mode<12

Number of complete cases: 62
```

Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for phenanth - Type III Sums of Squares
--------------------------------------------------------------------------------
Source                Sum of Squares    Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                    33757.8       4        8439.44      11.05     0.0000
 B:mode                    8830.11       3        2943.37       3.85     0.0159

INTERACTIONS
 AB                        9241.53      12        770.128       1.01     0.4585

RESIDUAL                   32075.1      42        763.693
--------------------------------------------------------------------------------
TOTAL (CORRECTED)          83646.1      61
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.


CONCLUSION:  Statistically significant differences in the average phenanthrene
among the fuels and modes.
```

Means and 95% Tukey HSD Intervals

CONCLUSION: There are two distinct fuel groupings with respect to the average
phenanthrene. The average phenanthrene for the DF-2 and CA fuels are not
significantly different from one another, but are significantly different from
the remaining three fuels. The average phenanthrene for the ALS, FT-100,
and ADMM15 fuels are not significantly different from one another.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average phenanthrene for mode 5 is significantly different
from modes 6 and 10.

```
Multiple Range Tests for phenanth by fuel


--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
fuel          Count     LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
ADMM15        12        28.5429          X
FT-100        12        38.1595          X
ALS           14        38.3617          X
CA            12        74.605            X
DF-2          12        88.8256           X
--------------------------------------------------------------------------------
Contrast                               Difference          +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                            -9.8188             30.9842
ADMM15 - CA                            *-46.0621            32.1538
ADMM15 - DF-2                          *-60.2827            32.1538
ADMM15 - FT-100                         -9.61664            32.1538
ALS - CA                               *-36.2433            30.9842
ALS - DF-2                             *-50.4639            30.9842
ALS - FT-100                            0.202164            30.9842
CA - DF-2                               -14.2206            32.1538
CA - FT-100                            *36.4455             32.1538
DF-2 - FT-100                          *50.6661             32.1538
--------------------------------------------------------------------------------
* denotes a statistically significant difference.
```

```
Multiple Range Tests for phenanth by mode

--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
mode            Count     LS Mean            Homogeneous Groups
--------------------------------------------------------------------------------
5               16        34.0794            X
11              15        54.571             XX
10              16        61.7122             X
6               15        64.4332             X
--------------------------------------------------------------------------------
Contrast                                     Difference          +/-  Limits
--------------------------------------------------------------------------------
5 - 6                                        *-30.3539           26.57
5 - 10                                       *-27.6329           26.138
5 - 11                                        -20.4916           26.57
6 - 10                                         2.72099           26.57
6 - 11                                         9.86225           26.9952
10 - 11                                        7.14126           26.57
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

Interactions and 95% Tukey HSD Intervals

```
CONCLUSION:  There is no significant interaction in the average phenanthrene
among the fuel and mode combinations.
```

E-80

```
Multifactor ANOVA - Anthracene (µg/kW-hr)  Soluble PAH
                 LPP Only   Modes 5,6,10,11

Analysis Summary

Dependent variable: anthr
Factors:
        fuel
        mode
Selection variable: mode<12

Number of complete cases: 61
```

Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for anthr - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares   Df   Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                 67.4897       4      16.8724      12.74    0.0000
 B:mode                 13.7647       3      4.58822       3.46    0.0248

INTERACTIONS
 AB                     13.3777      12      1.11481       0.84    0.6090

RESIDUAL                54.3166      41       1.3248
--------------------------------------------------------------------------------
TOTAL (CORRECTED)       150.016      60
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.


CONCLUSION:  Statistically significant differences in the average anthracene
among the fuels and modes.
```

E-81

Means and 95% Tukey HSD Intervals

CONCLUSION: The average anthracene for the CA fuel is significantly different
from the FT-100, ADMM15, and ALS fuels. The average anthracene for the ALS fuel
is significantly different than the DF-2 and FT-100 fuels.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average anthracene for mode 10 is significantly different than
mode 5.

Multiple Range Tests for anthr by fuel

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
fuel            Count      LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
ALS             13         1.2457           X
ADMM15          12         2.29932          XX
FT-100          12         2.66069           X
DF-2            12         3.62913           XX
CA              12         4.24561            X
--------------------------------------------------------------------------------
Contrast                                Difference          +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                             1.05362            1.31462
ADMM15 - CA                             *-1.94629           1.34065
ADMM15 - DF-2                            -1.32981           1.34065
ADMM15 - FT-100                          -0.361364          1.34065
ALS - CA                                *-2.99991           1.31462
ALS - DF-2                              *-2.38344           1.31462
ALS - FT-100                            *-1.41499           1.31462
CA - DF-2                                0.616475           1.34065
CA - FT-100                             *1.58492            1.34065
DF-2 - FT-100                            0.968447           1.34065
--------------------------------------------------------------------------------
* denotes a statistically significant difference.
```

Multiple Range Tests for anthr by mode

```
--------------------------------------------------------------------------------
```

```
Method: 95.0 percent Tukey HSD
mode            Count    LS Mean      Homogeneous Groups
--------------------------------------------------------------------------------
5               15       2.08723      X
11              15       2.7156       XX
6               15       3.13382      XX
10              16       3.32771       X
--------------------------------------------------------------------------------
Contrast                              Difference       +/-  Limits
--------------------------------------------------------------------------------
5  - 6                                -1.0466          1.12548
5  - 10                               *-1.24048        1.10775
5  - 11                               -0.628376        1.12548
6  - 10                               -0.193884        1.10775
6  - 11                               0.418221         1.12548
10 - 11                               0.612105         1.10775
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

Interactions and 95% Tukey HSD Intervals


```
CONCLUSION:  There is no significant interaction in the average anthracene among
the fuel and mode combinations.
```

```
Multifactor ANOVA - Fluoranthene (µg/kW-hr)   Soluble PAH
                  LPP Only   Modes 5,6,10,11

Analysis Summary

Dependent variable: fluoran
Factors:
        fuel
        mode
Selection variable: mode<12

Number of complete cases: 62
```

### Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for fluoran - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares    Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                   6792.8       4        1698.2     14.46     0.0000
 B:mode                  1674.88       3       558.292      4.75     0.0061

INTERACTIONS
 AB                       3754.7      12       312.892      2.66     0.0094

RESIDUAL                 4933.61      42       117.467
--------------------------------------------------------------------------------
TOTAL (CORRECTED)        17092.2      61
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.


CONCLUSION:  Statistically significant differences in the average fluoranthene
among the fuels, modes and fuel*mode interaction.
```

Means and 95% Tukey HSD Intervals

CONCLUSION: The average fluoranthene for the DF-2 fuel is significantly different
than the remaining four fuels. The average fluoranthene for the ADMM15, ALS, CA, and
FT-100 fuels are not significantly different from one another.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average fluoranthene for modes 6 and 10 are signficantly different
than mode 5, but not significantly different from one another.

Multiple Range Tests for fluoran by fuel

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
fuel            Count      LS Mean           Homogeneous Groups
--------------------------------------------------------------------------------
ADMM15          12         9.4552            X
FT-100          12         14.8235           X
ALS             14         19.2862           X
CA              12         20.3461           X
DF-2            12         40.7715            X
--------------------------------------------------------------------------------
Contrast                                Difference           +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                             -9.83103            12.1517
ADMM15 - CA                              -10.8909            12.6105
ADMM15 - DF-2                           *-31.3163            12.6105
ADMM15 - FT-100                          -5.36831            12.6105
ALS - CA                                 -1.0599             12.1517
ALS - DF-2                              *-21.4853            12.1517
ALS - FT-100                             4.46272             12.1517
CA - DF-2                               *-20.4254            12.6105
CA - FT-100                              5.52262             12.6105
DF-2 - FT-100                           *25.948             12.6105
--------------------------------------------------------------------------------
* denotes a statistically significant difference.
```


Multiple Range Tests for fluoran by mode

```
--------------------------------------------------------------------------------
```

```
Method: 95.0 percent Tukey HSD
mode          Count    LS Mean        Homogeneous Groups
--------------------------------------------------------------------------------
5              16      12.6339         X
11             15      20.6494         XX
6              15      24.5815          X
10             16      25.8812          X
--------------------------------------------------------------------------------
Contrast                                 Difference        +/-  Limits
--------------------------------------------------------------------------------
5  - 6                                   *-11.9476         10.4206
5  - 10                                  *-13.2473         10.2511
5  - 11                                   -8.01553         10.4206
6  - 10                                   -1.29968         10.4206
6  - 11                                    3.93205         10.5873
10 - 11                                    5.23173         10.4206
--------------------------------------------------------------------------------

* denotes a statistically significant difference.
```

Interactions and 95% Tukey HSD Intervals

CONCLUSION: The trend in the average fluoranthene across the modes for the DF-2
fuel is significantly different than the trends for the remaining four fuels.
The average fluoranthene for the DF-2 fuel at modes 10 and 11 are significantly
different than the other four fuels.

```
Multifactor ANOVA - Pyrene (µg/kW-hr)   Soluble PAH
                   LPP Only   Modes 5,6,10,11


Analysis Summary

Dependent variable: pyrene
Factors:
        fuel
        mode
Selection variable: mode<12

Number of complete cases: 62
```

Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for pyrene - Type III Sums of Squares
--------------------------------------------------------------------------------
Source               Sum of Squares    Df     Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                   24058.4       4         6014.59      31.97     0.0000
 B:mode                    3466.4       3         1155.47       6.14     0.0015

INTERACTIONS
 AB                       9336.65      12         778.054       4.14     0.0003

RESIDUAL                  7901.13      42         188.122
--------------------------------------------------------------------------------
TOTAL (CORRECTED)         44659.6      61
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.


CONCLUSION:  Statistically significant differences in the average pyrene among
the fuels, modes, and fuel*mode interaction.
```

Means and 95% Tukey HSD Intervals

CONCLUSION: The average pyrene for the DF-2 fuel is significantly different
than the remaining four fuels. The average pyrene for the ASL, CA, FT-100, and
ADMM15 fuels are not significantly different from one another.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average pyrene for modes 10 and 11 are significantly different
than mode 5. The average pyrene for mode 6 is not significantly different
than the remaining three modes.


```
Multiple Range Tests for pyrene by fuel


--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
fuel            Count    LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
ADMM15          12       9.0201           X
FT-100          12       11.872           X
CA              12       16.0453          X
ALS             14       19.177           X
DF-2            12       63.2917           X
--------------------------------------------------------------------------------
Contrast                                  Difference          +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                              -10.1569            15.378
ADMM15 - CA                               -7.02516            15.9585
ADMM15 - DF-2                             *-54.2716           15.9585
ADMM15 - FT-100                           -2.85191            15.9585
ALS - CA                                  3.13175             15.378
ALS - DF-2                                *-44.1147           15.378
ALS - FT-100                              7.30501             15.378
CA - DF-2                                 *-47.2464           15.9585
CA - FT-100                               4.17325             15.9585
DF-2 - FT-100                             *51.4197            15.9585
--------------------------------------------------------------------------------
* denotes a statistically significant difference.


Multiple Range Tests for pyrene by mode
```

```
----------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
mode          Count     LS Mean          Homogeneous Groups
----------------------------------------------------------------------------
5             16        11.6778          X
6             15        24.5073          XX
11            15        28.2235           X
10            16        31.1162           X
----------------------------------------------------------------------------
Contrast                                  Difference       +/-   Limits
----------------------------------------------------------------------------
5 - 6                                     -12.8295         13.1872
5 - 10                                    *-19.4385        12.9728
5 - 11                                    *-16.5458        13.1872
6 - 10                                    -6.60898         13.1872
6 - 11                                    -3.71629         13.3982
10 - 11                                    2.8927          13.1872
----------------------------------------------------------------------------
```

* denotes a statistically significant difference.

Interactions and 95% Tukey HSD Intervals

```
CONCLUSION:  The trend in the average pyrene across the modes for the DF-2
fuel is significantly different than the trends for the remaining four
fuels.  The average pyrene at modes 10 and 11 for the DF-2 fuel are significantly
different than the other four fuels.
```

```
Multifactor ANOVA - Benzo[a]anthracene (µg/kW-hr)   Soluble PAH
                  LPP Only   Modes 5,6,10,11

Analysis Summary

Dependent variable: benzoaan
Factors:
        fuel
        mode
Selection variable: mode<12

Number of complete cases: 60
```

Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for benzoaan - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                 27.1788       4       6.79471      44.20     0.0000
 B:mode                 2.53806       3       0.84602       5.50     0.0029

INTERACTIONS
 AB                     6.32452      12       0.527043      3.43     0.0016

RESIDUAL                6.14848      40       0.153712
--------------------------------------------------------------------------------
TOTAL (CORRECTED)      42.1988       59
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.


CONCLUSION:  Statistically significant differences in the average benzo[a]anthracene
among the fuels, modes, and fuel*mode interaction.
```

Means and 95% Tukey HSD Intervals

CONCLUSION: There are four distinct fuel groupings with respect to the average
benzo[a]anthracene. Fuels DF-2, CA, and ALS are significantly different from one
another and the remaining two fuels. The FT-100 and ADMM15 fuels are not
significantly different from one another, but are significantly different than
the other three fuels.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average benzo[a]anthracene for mode 10 is significantly
different than modes 5 and 6. The average benzo[a]anthracene for mode 11 is
not significantly different than the remaining three modes.

Multiple Range Tests for benzoaan by fuel

Method: 95.0 percent Tukey HSD
fuel   Count   LS Mean   Homogeneous Groups

ADMM15   12   0.163625   X
FT-100   11   0.204025   X
ALS   14   0.70536   X
CA   11   1.16275   X
DF-2   12   1.99543   X

Contrast   Difference   +/- Limits

ADMM15 - ALS   *-0.541735   0.440551
ADMM15 - CA   *-0.999128   0.467457
ADMM15 - DF-2   *-1.83181   0.457182
ADMM15 - FT-100   -0.0404   0.467457
ALS - CA   *-0.457393   0.451205
ALS - DF-2   *-1.29007   0.440551
ALS - FT-100   *0.501335   0.451205
CA - DF-2   *-0.832681   0.467457
CA - FT-100   *0.958728   0.477511
DF-2 - FT-100   *1.79141   0.467457
----

* denotes a statistically significant difference.

E-91

```
Multiple Range Tests for benzoaan by mode

--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
mode           Count     LS Mean           Homogeneous Groups
--------------------------------------------------------------------------------
5              15        0.612678          X
6              15        0.748889          X
11             14        0.857056          XX
10             16        1.16633            X
--------------------------------------------------------------------------------
Contrast                                   Difference        +/-  Limits
--------------------------------------------------------------------------------
5  - 6                                      -0.136211         0.383771
5  - 10                                    *-0.553656         0.377727
5  - 11                                     -0.244377         0.390563
6  - 10                                    *-0.417445         0.377727
6  - 11                                     -0.108166         0.390563
10 - 11                                      0.309279         0.384626
--------------------------------------------------------------------------------

* denotes a statistically significant difference.
```

Interactions and 95% Tukey HSD Intervals

CONCLUSION: The trend in the average benzo[a]anthracene across the modes for the
DF-2 fuel is significantly different than the trends for the remaining four
fuels. The average benzo[a]anthracene at modes 10 and 11 for the DF-2 fuel are
significantly different than the other four fuels.

```
Multifactor ANOVA - Chrysene (µg/kW-hr)   Soluble PAH
                  LPP Only   Modes 5,6,10,11

Analysis Summary

Dependent variable: chrysene
Factors:
        fuel
        mode
Selection variable: mode<12

Number of complete cases: 62
```

Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for chrysene - Type III Sums of Squares
--------------------------------------------------------------------------------
Source                Sum of Squares    Df     Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                   289.281        4        72.3202       34.50     0.0000
 B:mode                   11.5288        3        3.84294        1.83     0.1558

INTERACTIONS
 AB                       36.6934       12        3.05779        1.46     0.1788

RESIDUAL                  88.0472       42        2.09636
--------------------------------------------------------------------------------
TOTAL (CORRECTED)         424.358       61
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.


CONCLUSION:  Statistically significant differences in the average chrysene among
the fuels.
```

Means and 95% Tukey HSD Intervals

CONCLUSION: The average chrysene for the DF-2 fuel is significantly different
than the remaining four fuels. Also, the average chrysene for the CA fuel is
significantly different than the ADMM15 fuel.

Means and 95% Tukey HSD Intervals

CONCLUSION: There is no significant difference in the average chrysene among
the modes.

Multiple Range Tests for chrysene by fuel

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
fuel            Count    LS Mean        Homogeneous Groups
--------------------------------------------------------------------------------
ADMM15          12       0.731573       X
FT-100          12       0.86227        XX
ALS             14       2.24956        XX
CA              12       2.42491         X
DF-2            12       6.77433         X
--------------------------------------------------------------------------------
Contrast                                Difference          +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                            -1.51799            1.62336
ADMM15 - CA                             *-1.69334           1.68464
ADMM15 - DF-2                           *-6.04276           1.68464
ADMM15 - FT-100                         -0.130697           1.68464
ALS - CA                                -0.175346           1.62336
ALS - DF-2                              *-4.52476           1.62336
ALS - FT-100                            1.38729             1.62336
CA - DF-2                               *-4.34942           1.68464
CA - FT-100                             1.56264             1.68464
DF-2 - FT-100                           *5.91206            1.68464
--------------------------------------------------------------------------------
```
* denotes a statistically significant difference.

Multiple Range Tests for chrysene by mode

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
mode              Count     LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
5                 16        2.10097          X
11                15        2.45668          X
6                 15        2.59673          X
10                16        3.27974          X
--------------------------------------------------------------------------------
Contrast                                     Difference       +/-  Limits
--------------------------------------------------------------------------------
5  - 6                                        -0.495764        1.39209
5  - 10                                       -1.17877         1.36945
5  - 11                                       -0.355715        1.39209
6  - 10                                       -0.683006        1.39209
6  - 11                                        0.140048        1.41436
10 - 11                                        0.823054        1.39209
--------------------------------------------------------------------------------

* denotes a statistically significant difference.
```

Interactions and 95% Tukey HSD Intervals


```
CONCLUSION:  There is no significant interaction in the average chrysene among
the fuel and mode combinations.
```

```
Multifactor ANOVA - Benzo[b]fluoranthene (µg/kW-hr)   Soluble PAH
                    LPP Only   Modes 5,6,10,11

Analysis Summary

Dependent variable: benzobfl
Factors:
        fuel
        mode
Selection variable: mode<12

Number of complete cases: 60
```

Scatterplot by Level Code

Benzo[b]fluoranthene vs Fuel (ADMM15, ALS, CA, DF-2, FT-100)

Scatterplot by Level Code

Benzo[b]fluoranthene vs Mode (5, 6, 10, 11)

```
Analysis of Variance for benzobfl - Type III Sums of Squares
--------------------------------------------------------------------------------
Source                  Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                    18.0149        4      4.50373       8.36     0.0001
 B:mode                     2.38476       3      0.79492       1.47     0.2359

INTERACTIONS
 AB                         6.23245      12      0.519371      0.96     0.4978

RESIDUAL                   21.5616       40      0.53904
--------------------------------------------------------------------------------
TOTAL (CORRECTED)          48.7599       59
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.


CONCLUSION:  Statistically significant differences in the average benzo[b]fluoranthene
among the fuels.
```

E-96

Means and 95% Tukey HSD Intervals

CONCLUSION: There are two distinct fuel groupings with respect to the average benzo[b]fluoranthene. The CA, ALS, and DF-2 fuels are not significantly different from one another, but are different from the remaining two fuels. The ADMM15 and FT-100 fuels are not significantly different from one another.

Means and 95% Tukey HSD Intervals

CONCLUSION: There is no significant difference in the average benzo[b]fluoranthene among the modes.

```
Multiple Range Tests for benzobfl by fuel

--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
fuel          Count    LS Mean         Homogeneous Groups
--------------------------------------------------------------------------------
FT-100        12       0.348473        X
ADMM15        12       0.48136         X
DF-2          12       1.37735          X
ALS           14       1.49583          X
CA            10       1.71464          X
--------------------------------------------------------------------------------
Contrast                               Difference        +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                           *-1.01447         0.824998
ADMM15 - CA                            *-1.23328         0.897928
ADMM15 - DF-2                          *-0.895986        0.85614
ADMM15 - FT-100                         0.132886         0.85614
ALS - CA                               -0.218812         0.868285
ALS - DF-2                              0.118483         0.824998
ALS - FT-100                           *1.14736          0.824998
CA - DF-2                               0.337295         0.897928
CA - FT-100                            *1.36617          0.897928
DF-2 - FT-100                          *1.02887          0.85614
--------------------------------------------------------------------------------
* denotes a statistically significant difference.
```

```
Multiple Range Tests for benzobfl by mode

--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
mode            Count      LS Mean         Homogeneous Groups
--------------------------------------------------------------------------------
11              14         0.795638        X
6               15         1.02147         X
10              16         1.15339         X
5               15         1.36363         X
--------------------------------------------------------------------------------
Contrast                                   Difference       +/-  Limits
--------------------------------------------------------------------------------
5 - 6                                      0.342159         0.718667
5 - 10                                     0.210239         0.707349
5 - 11                                     0.567988         0.731388
6 - 10                                     -0.13192         0.707349
6 - 11                                     0.225829         0.731388
10 - 11                                    0.357749         0.72027
--------------------------------------------------------------------------------
* denotes a statistically significant difference.
```

Interactions and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average benzo[b]fluoranthene
among the fuel and mode combinations.

E-98

```
Multifactor ANOVA - Benzo[k]fluoranthene (µg/kW-hr)   Soluble PAH
                    LPP Only   Modes 5,6,10,11

Analysis Summary

Dependent variable: benzokfl
Factors:
        fuel
        mode
Selection variable: mode<12

Number of complete cases: 61
```

Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for benzokfl - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                 26.7077       4      6.67693      10.92     0.0000
 B:mode                 4.97265       3      1.65755       2.71     0.0574

INTERACTIONS
 AB                     7.48971      12      0.624142      1.02     0.4490

RESIDUAL                25.0787      41      0.611676
--------------------------------------------------------------------------------
TOTAL (CORRECTED)       64.3624      60
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.


CONCLUSION:  Statistically significant differences in the average benzo[k]fluoranthene
among the fuels and modes.
```

Means and 95% Tukey HSD Intervals

CONCLUSION: The average benzo[k]fluoranthene for the DF-2 fuel is significantly
different than the ADMM15, ALS, and FT-100 fuels. The average benzo[k]fluoranthene
for the ADMM15, ALS, and FT-100 fuels are not significantly different from one
another. Also, the average benzo[k]fluoranthene for the CA fuel is significantly
different than the FT-100 fuel.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average benzo[k]fluoranthene for mode 10 is significantly
different than mode 11.

Multiple Range Tests for benzokfl by fuel

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
fuel          Count    LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
FT-100        12       0.429788         X
ADMM15        12       0.521305         XX
ALS           14       0.79762          XX
CA            11       1.39424           XX
DF-2          12       2.22632           X
--------------------------------------------------------------------------------
Contrast                              Difference          +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                          -0.276314           0.87783
ADMM15 - CA                           -0.872935           0.931441
ADMM15 - DF-2                        *-1.70502            0.910967
ADMM15 - FT-100                       0.0915172           0.910967
ALS - CA                              -0.596621           0.899059
ALS - DF-2                           *-1.4287             0.87783
ALS - FT-100                          0.367832            0.87783
CA - DF-2                             -0.832082           0.931441
CA - FT-100                          *0.964452            0.931441
DF-2 - FT-100                        *1.79653             0.910967
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

E-100

```
Multiple Range Tests for benzokfl by mode

--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
mode           Count     LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
11             14        0.665197         X
6              15        1.02958          XX
5              16        1.11709          XX
10             16        1.48356           X
--------------------------------------------------------------------------------
Contrast                                  Difference       +/-  Limits
--------------------------------------------------------------------------------
5  - 6                                     0.0875137        0.75271
5  - 10                                   -0.366465         0.74047
5  - 11                                    0.451894         0.76646
6  - 10                                   -0.453979         0.75271
6  - 11                                    0.36438          0.778291
10 - 11                                   *0.818359         0.76646
--------------------------------------------------------------------------------
* denotes a statistically significant difference.
```


Interactions and 95% Tukey HSD Intervals

```
CONCLUSION:  There is no significant interaction in the average benzo[k]fluoranthene
among the fuel and mode combinations.
```

E-101

```
Multifactor ANOVA - Benzo[e]pyrene (μg/kW-hr)   Soluble PAH
                 LPP Only   Modes 5,6,10,11

Analysis Summary

Dependent variable: benzoepy
Factors:
        fuel
        mode
Selection variable: mode<12

Number of complete cases: 57
```

Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for benzoepy - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                  6.67906      4       1.66977      7.66     0.0001
 B:mode                  0.67039      3      0.223463      1.02     0.3929

INTERACTIONS
 AB                      3.16355     12       0.26363      1.21     0.3137

RESIDUAL                 8.07046     37       0.21812
--------------------------------------------------------------------------------
TOTAL (CORRECTED)       18.3948      56
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.


CONCLUSION:  Statistically significant differences in the average benzo[e]pyrene
among the fuels.
```

E-102

Means and 95% Tukey HSD Intervals

CONCLUSION: The average benzo[e]pyrene for the CA and DF-2 fuels are significantly different than the FT-100 and ADMM15 fuels, but not significantly different from one another. Also, the average benzo[e]pyrene for the ALS fuel is not significantly different from the remaining four fuels.

Means and 95% Tukey HSD Intervals

CONCLUSION: There is no significant difference in the average benzo[e]pyrene among the modes.

Multiple Range Tests for benzoepy by fuel

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
fuel           Count    LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
ADMM15         11       0.221489         X
FT-100         11       0.262074         X
ALS            14       0.599731         XX
DF-2           10       0.957389          X
CA             11       1.10608           X
--------------------------------------------------------------------------------
Contrast                                 Difference         +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                             -0.378242          0.539519
ADMM15 - CA                              *-0.884591         0.570973
ADMM15 - DF-2                            *-0.7359           0.585073
ADMM15 - FT-100                          -0.0405851         0.570973
ALS - CA                                 -0.506349          0.539519
ALS - DF-2                               -0.357658          0.55442
ALS - FT-100                             0.337657           0.539519
CA - DF-2                                0.148691           0.585073
CA - FT-100                              *0.844006          0.570973
DF-2 - FT-100                            *0.695315          0.585073
--------------------------------------------------------------------------------
```
* denotes a statistically significant difference.

Multiple Range Tests for benzoepy by mode

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
mode            Count     LS Mean        Homogeneous Groups
--------------------------------------------------------------------------------
11              15        0.471842       X
6               12        0.60491        X
5               14        0.68533        X
10              16        0.755329       X
--------------------------------------------------------------------------------
Contrast                                  Difference       +/-  Limits
--------------------------------------------------------------------------------
5 - 6                                     0.0804202        0.49425
5 - 10                                    -0.0699989       0.459781
5 - 11                                    0.213488         0.466878
6 - 10                                    -0.150419        0.479781
6 - 11                                    0.133068         0.486587
10 - 11                                   0.283487         0.451533
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

Interactions and 95% Tukey HSD Intervals

```
CONCLUSION:  There is no significant interaction in the average benzo[e]pyrene
among the fuel and mode combinations.
```

E-104

```
Multifactor ANOVA - Benzo[a]pyrene (μg/kW-hr)    Soluble PAH
                    LPP Only    Modes 5,6,10,11

Analysis Summary

Dependent variable: benzoapy
Factors:
        fuel
        mode
Selection variable: mode<12

Number of complete cases: 62
```

Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for benzoapy - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                 1.15306       4      0.288266      31.27    0.0000
 B:mode                 0.242293      3      0.0807643      8.76    0.0001

INTERACTIONS
 AB                     0.373391     12      0.0311159      3.37    0.0017

RESIDUAL                0.387228     42      0.00921972
--------------------------------------------------------------------------------
TOTAL (CORRECTED)       2.27649      61
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average benzo[a]pyrene
among the fuels, modes, and fuel*mode interaction.
```

E-105

Means and 95% Tukey Intervals

CONCLUSION: The average benzo[a]pyrene for the CA and ALS fuels are significantly
different from the remaining three fuels but not different from one another.
The average benzo[a]pyrene for the ADMM15 fuel is significantly different from
the DF-2 fuel, but not significantly different from the FT-100 fuel.

Means and 95% Tukey Intervals

CONCLUSION: The average benzo[a]pyrene for mode 10 is significantly different
from the remaining three modes.

Multiple Range Tests for benzoapy by fuel

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
fuel            Count      LS Mean           Homogeneous Groups
--------------------------------------------------------------------------------
ADMM15          12         0.0549743         X
FT-100          12         0.0598222         XX
DF-2            12         0.171345           X
CA              12         0.338816            X
ALS             14         0.376119            X
--------------------------------------------------------------------------------
Contrast                                  Difference           +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                              *-0.321145           0.107656
ADMM15 - CA                               *-0.283842           0.11172
ADMM15 - DF-2                             *-0.116371           0.11172
ADMM15 - FT-100                            -0.00484792         0.11172
ALS - CA                                   0.0373028           0.107656
ALS - DF-2                                *0.204774            0.107656
ALS - FT-100                              *0.316297            0.107656
CA - DF-2                                 *0.167471            0.11172
CA - FT-100                               *0.278994            0.11172
DF-2 - FT-100                              0.111523            0.11172
--------------------------------------------------------------------------------
* denotes a statistically significant difference.
```

Multiple Range Tests for benzoapy by mode

E-106

```
-----------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
mode            Count      LS Mean              Homogeneous Groups
-----------------------------------------------------------------------------
5                16        0.140402             X
6                15        0.170284             X
11               15        0.18635              X
10               16        0.303826              X
-----------------------------------------------------------------------------
Contrast                                     Difference          +/-  Limits
-----------------------------------------------------------------------------
5  - 6                                        -0.029882           0.0923192
5  - 10                                      *-0.163424           0.0908179
5  - 11                                        -0.0459479         0.0923192
6  - 10                                      *-0.133542           0.0923192
6  - 11                                        -0.0160659         0.0937964
10 - 11                                      *0.117476            0.0923192
-----------------------------------------------------------------------------
```

* denotes a statistically significant difference.

Interactions and 95% Tukey HSD Intervals

CONCLUSION: The trend in the average benzo[a]pyrene across the modes for the
ALS fuel is significantly different than the trends for the remaining four
fuels. Also, the average benzo[a]pyrene for the CA fuel is significantly different
than the other fuels at mode 6.

```
Multifactor ANOVA - Indeno(1,2,3-cd)pyrene (µg/kW-hr)    Soluble PAH
                    LPP and DF-2, FT-100, ADMM15 Fuels Only    Modes 5,6,10,11

Analysis Summary

Dependent variable: indeno
Factors:
        fuel
        mode
Selection variable: mode<12

Number of complete cases: 35
```

Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for indeno - Type III Sums of Squares
--------------------------------------------------------------------------------
Source                Sum of Squares   Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                  0.480412        2     0.240206       57.54     0.0000
 B:mode                  0.15027         3     0.0500901      12.00     0.0001

INTERACTIONS
 AB                      0.151044        6     0.0251739       6.03     0.0007

RESIDUAL                 0.0960184      23     0.00417471
--------------------------------------------------------------------------------
TOTAL (CORRECTED)        0.888817       34
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average indeno(1,2,3-cd)pyrene
among the fuels, modes, and fuel*mode interaction.
```

E-108

Means and 95% Tukey HSD Intervals

CONCLUSION: The average indeno(1,2,3-cd)pyrene for the DF-2 fuel is significantly
different from the remaining two fuels. The ADMM15 and FT-100 fuels are not
significantly different from one another with respect to the average
indeno(1,2,3-cd)pyrene.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average indeno(1,2,3-cd)pyrene for mode 10 is significantly
different than modes 5 and 6. Mode 11 is not significantly different from the
remaining three modes with respect to the average indeno(1,2,3-cd)pyrene.

Multiple Range Tests for indeno by fuel


```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
fuel            Count     LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
FT-100          12        0.062351         X
ADMM15          11        0.0651034        X
DF-2            12        0.31108           X
--------------------------------------------------------------------------------
Contrast                                   Difference        +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - DF-2                              *-0.245977        0.0675663
ADMM15 - FT-100                             0.00275231       0.0675663
DF-2 - FT-100                              *0.248729         0.0660811
--------------------------------------------------------------------------------
* denotes a statistically significant difference.
```


Multiple Range Tests for indeno by mode


```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
mode            Count     LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
5               8         0.0794008        X
6               9         0.0947125        X
11              9         0.164935         XX
```

```
10                9            0.245665            X
------------------------------------------------------------------------------
Contrast                                    Difference        +/-   Limits
------------------------------------------------------------------------------
5 - 6                                        -0.0153117        0.0869054
5 - 10                                      *-0.166264         0.0869054
5 - 11                                       -0.085534         0.0869054
6 - 10                                      *-0.150952         0.0843106
6 - 11                                       -0.0702223        0.0843106
10 - 11                                       0.0807299        0.0843106
------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

Interactions and 95% Tukey HSD Intervals

CONCLUSION: The trend in the average indeno(1,2,3-cd)pyrene across the modes for
the DF-2 fuel is significantly different than the trends in the remaining two
fuels. The average indeno(1,2,3-cd)pyrene at modes 10 and 11 for the DF-2 fuel
are significantly different than the ADMM15 and FT-100 fuels.

```
Multifactor ANOVA - Dibenzo[a,h]anthracene (µg/kW-hr)   Soluble PAH
                LPP and DF-2, FT-100, ADMM15 Fuels Only  Modes 5,6,10,11

Analysis Summary

Dependent variable: dibenzo
Factors:
        fuel
        mode
Selection variable: mode<12

Number of complete cases: 31
```

Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for dibenzo - Type III Sums of Squares
--------------------------------------------------------------------------------
Source                 Sum of Squares    Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                   0.0316789        2      0.0158394      32.39     0.0000
 B:mode                   0.00516132       3      0.00172044      3.52     0.0351

INTERACTIONS
 AB                       0.00710011       6      0.00118335      2.42     0.0658

RESIDUAL                  0.00929022      19     0.000488959
--------------------------------------------------------------------------------
TOTAL (CORRECTED)         0.0581359       30
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average dibenzo[a,h]anthracene
among the fuels and modes.
```

Means and 95% Tukey HSD Intervals

CONCLUSION: The average dibenzo[a,h]anthracene for the DF-2 fuel is
significantly different from the remaining two fuels. The ADMM15 and FT-100
fuels are not significantly different from one another.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average dibenzo[a,h]anthracene for mode 10 is significantly
different from mode 5. Modes 6 and 11 are not significantly different from one
another or the other two modes.

Multiple Range Tests for dibenzo by fuel

Method: 95.0 percent Tukey HSD
fuel   Count   LS Mean   Homogeneous Groups

ADMM15   10   0.0121819   X
FT-100   10   0.0155898   X
DF-2   11   0.0817954   X

Contrast   Difference   +/- Limits

ADMM15 - DF-2   *-0.0696135   0.0245556
ADMM15 - FT-100   -0.00340796   0.0251335
DF-2 - FT-100   *0.0662056   0.0245556
----
* denotes a statistically significant difference.

Multiple Range Tests for dibenzo by mode

--
Method: 95.0 percent Tukey HSD
mode   Count   LS Mean   Homogeneous Groups
----
5   7   0.0199922   X
6   7   0.0302323   XX
11   8   0.0412534   XX

E-112

```
10                9              0.0546116              X
-----------------------------------------------------------------------------
Contrast                                   Difference        +/-  Limits
-----------------------------------------------------------------------------
5  - 6                                     -0.0102401         0.0332468
5  - 10                                   *-0.0346194         0.0313454
5  - 11                                    -0.0212612         0.0321911
6  - 10                                    -0.0243793         0.0313454
6  - 11                                    -0.0110211         0.0321911
10 - 11                                     0.0133582         0.0302233
-----------------------------------------------------------------------------
* denotes a statistically significant difference.
```


Interactions and 95% Tukey HSD Intervals

```
CONCLUSION:  There is no significant interaction in the average dibenzo[a,h]anthracene
among the fuel and mode combinations.
```

```
Multifactor ANOVA - Benzo[ghi]perylene (µg/kW-hr)    Soluble PAH
                    LPP and CA, DF-2, FT-100, ADMM15 Fuels Only   Modes 5,6,10,11

Analysis Summary

Dependent variable: benzogpe
Factors:
        fuel
        mode
Selection variable: mode<12

Number of complete cases: 46
```

### Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for benzogpe - Type III Sums of Squares
--------------------------------------------------------------------------------
Source                 Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                    1.61627       3      0.538758      58.74    0.0000
 B:mode                    1.26649       3      0.422165      46.03    0.0000

INTERACTIONS
 AB                       0.581746       9      0.0646384      7.05    0.0000

RESIDUAL                  0.275134      30     0.00917113
--------------------------------------------------------------------------------
TOTAL (CORRECTED)         3.89934       45
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average benzo[ghi]perylene
among the fuels, modes and fuel*mode interaction.
```

Means and 95% Tukey HSD Intervals

CONCLUSION: There are two distinct fuel groupings with respect to the average benzo[ghi]perylene. The CA and DF-2 fuels are not significantly different from one another, but are different from the remaining two fuels. The ADMM15 and FT-100 fuels are not significantly different from one another.

Means and 95% Tukey HSD Intervals

CONCLUSION: There are three distinct mode groupings with respect to the average benzo[ghi]perylene. Modes 10 and 11 are significantly different from one another and the remaining two modes. Modes 5 and 6 are not significantly different from one another, but are significantly different than the other two modes.

Multiple Range Tests for benzogpe by fuel

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
fuel            Count     LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
FT-100          12        0.147474         X
ADMM15          11        0.174669         X
DF-2            12        0.497732          X
CA              11        0.573893          X
--------------------------------------------------------------------------------
Contrast                                  Difference          +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - CA                               *-0.399224          0.111054
ADMM15 - DF-2                             *-0.323063          0.108716
ADMM15 - FT-100                            0.0271954          0.108716
CA - DF-2                                  0.0761614          0.108716
CA - FT-100                               *0.426419           0.108716
DF-2 - FT-100                             *0.350258           0.106326
--------------------------------------------------------------------------------
* denotes a statistically significant difference.
```

Multiple Range Tests for benzogpe by mode

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
mode            Count     LS Mean          Homogeneous Groups
```

```
--------------------------------------------------------------------------------
5               11          0.179922            X
6               11          0.206259            X
11              12          0.419015             X
10              12          0.588573              X
--------------------------------------------------------------------------------
Contrast                                    Difference          +/-  Limits
--------------------------------------------------------------------------------
5 - 6                                       -0.0263369          0.111054
5 - 10                                      *-0.408651          0.108716
5 - 11                                      *-0.239093          0.108716
6 - 10                                      *-0.382314          0.108716
6 - 11                                      *-0.212756          0.108716
10 - 11                                     *0.169558           0.106326
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

Interactions and 95% Tukey HSD Intervals

CONCLUSION: The trend in the average benzo[ghi]perylene across the modes for the
DF-2 and CA fuels is significantly different than the trends in the remaining
two fuels. The average benzo[ghi]perylene at modes 10 and 11 for the DF-2 and
CA fuels are significantly different than the ADMM15 and FT-100 fuels.

E-116

APPENDIX F

ANOVA for Pilot Condition

TABLE OF CONTENTS

```
Multifactor ANOVA - Total Particulates (g/kW-hr)
                   Three Pilot Conditions   Modes 10 and 11

Analysis Summary

Dependent variable: PARTIC
Factors:
         COND
         FUEL
         MODE

Number of complete cases: 91
```

Scatterplot by Level Code

Particulates vs Pilot Condition (LPP, PilotA, PilotB)

Scatterplot by Level Code

Particulates vs Fuel (ADMM15, ALS, CA, DF-2, FT-100)

Scatterplot by Level Code

Particulates vs Mode (10, 11)

```
Analysis of Variance for PARTIC - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares    Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:COND                  0.455465      2      0.227733      114.53     0.0000
 B:FUEL                  0.835454      4      0.208864      105.04     0.0000
 C:MODE                  0.0313438     1      0.0313438      15.76     0.0002
```

F-3

```
INTERACTIONS
 AB                              0.105563      8    0.0131954    6.64   0.0000
 AC                              0.0543366     2    0.0271683   13.66   0.0000
 BC                              0.0110984     4    0.0027746    1.40   0.2462
 ABC                            0.0140696      8    0.0017587    0.88   0.5349

RESIDUAL                         0.121298     61    0.00198849
-------------------------------------------------------------------------------
TOTAL (CORRECTED)                1.62565      90
-------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSIONS:  Statistically significant differences in the average particulates
among the fuels, modes, pilot conditions, and some two-way interactions.
```

Means and 95% Tukey HSD Intervals

CONCLUSION: The average particulates at all three pilot conditions are significantly
different from one another.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average particulates for the ALS, CA, and DF-2 fuels are
significantly different from each other and the remaining two fuels. The
average particulates for the ADMM15 and FT-100 fuels are not significantly
different from one another.

Means and 95% Tukey HSD Intervals

CONCLUSION: Modes 10 and 11 are significantly different from one another with
respect to the average particulates.

Multiple Range Tests for PARTIC by COND

Method: 95.0 percent Tukey HSD
COND   Count   LS Mean   Homogeneous Groups

LPP   31   0.216564   X
PilotA   30   0.277749   X
PilotB   30   0.387645   X

Contrast   Difference   +/- Limits

LPP - PilotA   *-0.0611853   0.0274365
LPP - PilotB   *-0.171081   0.0274365
PilotA - PilotB   *-0.109896   0.0276605
----
* denotes a statistically significant difference.

Multiple Range Tests for PARTIC by FUEL

Method: 95.0 percent Tukey HSD
FUEL   Count   LS Mean   Homogeneous Groups

ADMM15   18   0.184316   X
FT-100   18   0.209423   X
ALS   19   0.28249   X
CA   18   0.342372   X
DF-2   18   0.451328   X

Contrast   Difference   +/- Limits

ADMM15 - ALS   *-0.098174   0.041231
ADMM15 - CA   *-0.158056   0.0417844
ADMM15 - DF-2   *-0.267012   0.0417844
ADMM15 - FT-100   -0.0251069   0.0417844
ALS - CA   *-0.0598823   0.041231
ALS - DF-2   *-0.168838   0.041231
ALS - FT-100   *0.0730671   0.041231
CA - DF-2   *-0.108956   0.0417844
CA - FT-100   *0.132949   0.0417844
DF-2 - FT-100   *0.241905   0.0417844
----
* denotes a statistically significant difference.

Multiple Range Tests for PARTIC by MODE

Method: 95.0 percent Tukey HSD
MODE   Count   LS Mean   Homogeneous Groups
----
11   45   0.275402   X
10   46   0.31257   X

Contrast   Difference   +/- Limits
----
10 - 11   *0.0371679   0.0186959
----
* denotes a statistically significant difference.

F-5

Interaction and 95% Tukey HSD Intervals

CONCLUSION: The trend in the average particulates across the pilot conditions for the
DF-2 fuel is significantly different than the trends for the remaining four fuels.
The average particulates for the DF-2 at the Pilot B condition is significantly different
than the other four fuels; however, there is not a significant difference at the LPP
condition.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: There is a significant interaction among the mode and pilot condition
combinations. While the average particulates at mode 11 is significantly different
at the LPP and Pilot A conditions, there is no significant difference at the Pilot B
condition.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average particulates
among the fuel and mode combinations.

```
Multifactor ANOVA - BSNOX (g/kW-hr)
                   Three Pilot Conditions   Modes 10 and 11

Analysis Summary

Dependent variable: BSNOX
Factors:
        COND
        FUEL
        MODE

Number of complete cases: 91
```

Scatterplot by Level Code

Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for BSNOX - Type III Sums of Squares
--------------------------------------------------------------------------------
Source                Sum of Squares   Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:COND                   80.9912       2       40.4956     2053.21     0.0000
 B:FUEL                   3.63542       4      0.908855       46.08     0.0000
 C:MODE                   6.69082       1       6.69082      339.24     0.0000
```

```
INTERACTIONS
 AB                             3.97541      8     0.496927     25.20    0.0000
 AC                            0.761949      2     0.380974     19.32    0.0000
 BC                            0.595608      4     0.148902      7.55    0.0001
 ABC                           0.264499      8    0.0330624      1.68    0.1226

RESIDUAL                        1.2031      61    0.019723
--------------------------------------------------------------------------------
TOTAL (CORRECTED)              98.0747      90
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average BSNOX among the fuels,
modes, pilot conditions, and two-way interactions.
```

Means and 95% Tukey HSD Intervals

CONCLUSION: All three pilot conditions are significantly different from one another with
respect to the average BSNOX.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average BSNOX for the DF-2 fuel is significantly different than the
remaining four fuels. The CA fuel has significantly different average BSNOX than the
ALS and FT-100 fuels. Also, the FT-100, CA, and ADMM15 fuels are not significantly
different from one another.

F-8

Means and 95% Tukey HSD Intervals

CONCLUSION: Modes 10 and 11 are significantly different from one another with respect to the average BSNOX.

Multiple Range Tests for BSNOX by COND

Method: 95.0 percent Tukey HSD

COND	Count	LS Mean	Homogeneous Groups
PilotB	30	1.11171	X
PilotA	30	3.06692	X
LPP	31	3.16761	X

Contrast	Difference	+/- Limits
LPP - PilotA	*0.100688	0.0864081
LPP - PilotB	*2.0559	0.0864081
PilotA - PilotB	*1.95521	0.0871135

----
* denotes a statistically significant difference.

Multiple Range Tests for BSNOX by FUEL

Method: 95.0 percent Tukey HSD

FUEL	Count	LS Mean	Homogeneous Groups
FT-100	18	2.25888	X
ALS	19	2.32239	X
ADMM15	18	2.37957	XX
CA	18	2.45407	X
DF-2	18	2.82881	X

Contrast	Difference	+/- Limits
ADMM15 - ALS	0.0571797	0.129852
ADMM15 - CA	-0.0745012	0.131595
ADMM15 - DF-2	*-0.449242	0.131595
ADMM15 - FT-100	0.120692	0.131595
ALS - CA	*-0.131681	0.129852
ALS - DF-2	*-0.506422	0.129852
ALS - FT-100	0.0635123	0.129852
CA - DF-2	*-0.374741	0.131595
CA - FT-100	*0.195193	0.131595
DF-2 - FT-100	*0.569934	0.131595

----
* denotes a statistically significant difference.

Multiple Range Tests for BSNOX by MODE

```
Method: 95.0 percent Tukey HSD
MODE          Count      LS Mean         Homogeneous Groups
--------------------------------------------------------------------------------
11            45         2.17722         X
10            46         2.72026          X
--------------------------------------------------------------------------------
Contrast                                 Difference        +/-  Limits
--------------------------------------------------------------------------------
10 - 11                                  *0.543039         0.0588805
--------------------------------------------------------------------------------
* denotes a statistically significant difference.
```

Interaction and 95% Tukey HSD Intervals

CONCLUSION: The average BSNOX for the DF-2 fuel is significantly different than
the remaining four fuels at the LPP condition. This trend does not exist at the
Pilot A or Pilot B conditions.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: A significant interaction exists between the pilot condition and the
modes. The difference in the average BSNOX between modes 10 and 11 at the LPP
condition is larger than the difference at the Pilot B condition.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: A significant interaction exists between the mode and fuel levels. The
difference in the average BSNOX between modes 10 and 11 is the largest at the DF-2
fuel and the smallest at the FT-100 fuel.

```
Multifactor ANOVA - BSHC (g/kW-hr)
                  Three Pilot Conditions  Modes 10 and 11

Analysis Summary

Dependent variable: BSHC
Factors:
        COND
        FUEL
        MODE

Number of complete cases: 91
```

Scatterplot by Level Code

Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for BSHC - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares    Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:COND                    1.91308     2       0.956538      41.95     0.0000
```

F-12

```
B:FUEL                      28.1562       4       7.03905     308.73    0.0000
C:MODE                       4.6382       1       4.6382      203.43    0.0000

INTERACTIONS
 AB                          1.41323      8       0.176654      7.75    0.0000
 AC                          0.53378      2       0.26689      11.71    0.0000
 BC                          0.647364     4       0.161841      7.10    0.0001
 ABC                         0.165542     8       0.0206928     0.91    0.5163

RESIDUAL                     1.39082     61       0.0228003
-------------------------------------------------------------------------------
TOTAL (CORRECTED)           38.795       90
-------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average BSHC among the fuels,
modes, pilot conditions, and interactions.
```

Means and 95% Tukey HSD Intervals

CONCLUSION: Average BSHC at the Pilot A and Pilot B conditions are not significantly
different from one another, but both are different from the average BSHC at the LPP
condition.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average BSHC at the FT-100, CA, and DF-2 fuels are all significantly
different from one another. The average BSHC for the ADMM15 and ALS fuels are not
significantly different from one another, but are different from the other 3 fuels.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average BSHC at modes 10 and 11 are significantly different from one another.

Multiple Range Tests for BSHC by COND

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
COND            Count    LS Mean        Homogeneous Groups
--------------------------------------------------------------------------------
LPP              31      1.05976            X
PilotB           30      1.32712             X
PilotA           30      1.39471             X
--------------------------------------------------------------------------------
Contrast                               Difference         +/-  Limits
--------------------------------------------------------------------------------
LPP - PilotA                           *-0.334943          0.0929048
LPP - PilotB                           *-0.267355          0.0929048
PilotA - PilotB                         0.0675875          0.0936632
--------------------------------------------------------------------------------
```
* denotes a statistically significant difference.

Multiple Range Tests for BSHC by FUEL

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
FUEL            Count    LS Mean        Homogeneous Groups
--------------------------------------------------------------------------------
FT-100           18      0.565613           X
ALS              19      0.965014            X
ADMM15           18      0.971421           X
CA               18      1.69051             X
DF-2             18      2.1101               X
--------------------------------------------------------------------------------
Contrast                               Difference         +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                            0.0064071          0.139615
ADMM15 - CA                            *-0.719086          0.141489
ADMM15 - DF-2                          *-1.13868           0.141489
ADMM15 - FT-100                        *0.405808           0.141489
ALS - CA                               *-0.725493          0.139615
ALS - DF-2                             *-1.14508            0.139615
ALS - FT-100                           *0.399401           0.139615
CA - DF-2                              *-0.419591           0.141489
CA - FT-100                            *1.12489             0.141489
DF-2 - FT-100                          *1.54448             0.141489
--------------------------------------------------------------------------------
```
* denotes a statistically significant difference.

Multiple Range Tests for BSHC by MODE

```
--------------------------------------------------------------------------------
```

F-14

```
Method: 95.0 percent Tukey HSD
MODE           Count     LS Mean        Homogeneous Groups
-------------------------------------------------------------------------------
11              45       1.03446        X
10              46       1.4866          X
-------------------------------------------------------------------------------
Contrast                                Difference        +/-  Limits
-------------------------------------------------------------------------------
10 - 11                                 *0.452133         0.0633075
-------------------------------------------------------------------------------
```
* denotes a statistically significant difference.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: The CA and DF-2 fuels have significantly different trends in the average
BSHC at the Pilot B condition than at the other two pilot conditions.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: Mode 11 demonstrates a constant trend with respect to the average BSHC.
However, mode 10 shows significantly different average BSHC at Pilot Conditions A and B
than at the LPP condition.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: A significant interaction exists between the mode and fuel levels. The differences in the average BSHC between modes 10 and 11 are largest at the CA and DF-2 fuels and the smallest at the FT-100 fuel.

```
Multifactor ANOVA - BSCO (g/kW-hr)
                    Three Pilot Conditions   Modes 10 and 11
Analysis Summary

Dependent variable: BSCO
Factors:
        COND
        FUEL
        MODE

Number of complete cases: 91
```

Scatterplot by Level Code

Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for BSCO - Type III Sums of Squares
--------------------------------------------------------------------------------
Source               Sum of Squares   Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:COND                      45.521    2       22.7605      256.44     0.0000
 B:FUEL                     150.552    4       37.6379      424.05     0.0000
 C:MODE                     229.06     1      229.06       2580.74     0.0000

INTERACTIONS
```

AB	13.742	8	1.71774	19.35	0.0000
AC	43.4943	2	21.7471	245.02	0.0000
BC	15.4364	4	3.85911	43.48	0.0000
ABC	3.21386	8	0.401733	4.53	0.0002
RESIDUAL	5.4142	61	0.0887574		

TOTAL (CORRECTED)	504.085	90

All F-ratios are based on the residual mean square error.

CONCLUSION: Statistically significant differences in the average BSCO among the fuels, pilot conditions, modes, two-way interactions, and three-way interaction.

Means and 95% Tukey HSD Intervals

CONCLUSION: All three pilot conditions are significantly different from one another with respect to the average BSCO.

Means and 95% Tukey HSD Intervals

CONCLUSION: All five fuels are significantly different from one another with respect to the average BSCO.

Means and 95% Tukey HSD Intervals

CONCLUSION: Modes 10 and 11 are significantly different from one another with respect to the average BSCO.

F-18

```
Multiple Range Tests for BSCO by COND


--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
COND          Count     LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
LPP           31        4.3539           X
PilotB        30        5.3134            X
PilotA        30        6.08064            X
--------------------------------------------------------------------------------
Contrast                                  Difference        +/-  Limits
--------------------------------------------------------------------------------
LPP - PilotA                              *-1.72674         0.183303
LPP - PilotB                              *-0.959501        0.183303
PilotA - PilotB                           *0.767243         0.1848
--------------------------------------------------------------------------------
* denotes a statistically significant difference.




Multiple Range Tests for BSCO by FUEL


--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
FUEL          Count     LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
FT-100        18        3.19551          X
ALS           19        4.50613           X
ADMM15        18        5.43576            X
CA            18        6.30206             X
DF-2          18        6.8071               X
--------------------------------------------------------------------------------
Contrast                                  Difference        +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                              *0.929626         0.275463
ADMM15 - CA                               *-0.8663          0.279161
ADMM15 - DF-2                             *-1.37134         0.279161
ADMM15 - FT-100                           *2.24025          0.279161
ALS - CA                                  *-1.79593         0.275463
ALS - DF-2                                *-2.30097         0.275463
ALS - FT-100                              *1.31063          0.275463
CA - DF-2                                 *-0.505044        0.279161
CA - FT-100                               *3.10655          0.279161
DF-2 - FT-100                             *3.6116           0.279161
--------------------------------------------------------------------------------
* denotes a statistically significant difference.




Multiple Range Tests for BSCO by MODE


--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
MODE          Count     LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
11            45        3.66063          X
10            46        6.83799           X
--------------------------------------------------------------------------------
Contrast                                  Difference        +/-  Limits
--------------------------------------------------------------------------------
10 - 11                                   *3.17736          0.124907
--------------------------------------------------------------------------------
* denotes a statistically significant difference.
```

F-19

Interaction and 95% Tukey HSD Intervals

CONCLUSION: The trend in the average BSCO for the ADMM15 fuel is significantly different across the pilot conditions than the trends for the remaining four fuels.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: Mode 11 demonstrates a constant trend with respect to the average BSCO. However, mode 10 shows significantly different average BSCO at all three pilot conditions.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: A significant interaction exists between the mode and fuel levels. The difference in the average BSCO between modes 10 and 11 is the largest at fuels CA and DF-2 and the smallest at the FT-100 fuel.

```
Multifactor ANOVA - BSCO2 (g/kW-hr)
                    Three Pilot Conditions   Modes 10 and 11


Analysis Summary

Dependent variable: BSCO2
Factors:
        COND
        FUEL
        MODE

Number of complete cases: 91
```

Scatterplot by Level Code

Pilot Condition

Scatterplot by Level Code

Fuel

Scatterplot by Level Code

Mode

```
Analysis of Variance for BSCO2 - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:COND                  3026.88      2       1513.44       4.93    0.0103
 B:FUEL                  90449.4      4       22612.3      73.73    0.0000
 C:MODE                 601921.0      1      601921.0    1962.53    0.0000
```

```
INTERACTIONS
 AB                              4505.4      8       563.175     1.84    0.0874
 AC                              24.0168     2       12.0084     0.04    0.9616
 BC                              1529.07     4       382.267     1.25    0.3009
 ABC                             5306.95     8       663.369     2.16    0.0430

RESIDUAL                         18709.1     61      306.707
-------------------------------------------------------------------------------
TOTAL (CORRECTED)                722927.0    90
-------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.
```

CONCLUSION: Statistically significant differences in the average BSCO2 among the
fuels, modes, pilot conditions, and three-way interaction.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average BSCO2 for the Pilot B condition is significantly different
than the LPP condition.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average BSCO2 for the FT-100, ALS, and ADMM15 fuels are significantly
different from each other and the remaining two fuels. The average BSCO2 for the CA
and DF-2 fuels are not significantly different from one another.

Means and 95% Tukey HSD Intervals

CONCLUSION: Modes 10 and 11 are significantly different from one another with respect to the average BSCO2.

Multiple Range Tests for BSCO2 by COND

Method: 95.0 percent Tukey HSD
COND   Count   LS Mean   Homogeneous Groups

LPP   31   974.954   X
PilotA   30   982.223   XX
PilotB   30   989.066   X

Contrast   Difference   +/- Limits

LPP - PilotA   -7.26834   10.7753
LPP - PilotB   *-14.112   10.7753
PilotA - PilotB   -6.84368   10.8633
----
* denotes a statistically significant difference.

Multiple Range Tests for BSCO2 by FUEL

Method: 95.0 percent Tukey HSD
FUEL   Count   LS Mean   Homogeneous Groups

FT-100   18   935.124   X
ALS   19   959.404   X
CA   18   988.251   X
DF-2   18   1003.05   X
ADMM15   18   1024.58   X

Contrast   Difference   +/- Limits

ADMM15 - ALS   *65.1737   16.1928
ADMM15 - CA   *36.3268   16.4102
ADMM15 - DF-2   *21.5309   16.4102
ADMM15 - FT-100   *89.4536   16.4102
ALS - CA   *-28.8469   16.1928
ALS - DF-2   *-43.6428   16.1928
ALS - FT-100   *24.2799   16.1928
CA - DF-2   -14.7959   16.4102
CA - FT-100   *53.1268   16.4102
DF-2 - FT-100   *67.9228   16.4102
----
* denotes a statistically significant difference.

Multiple Range Tests for BSCO2 by MODE

Method: 95.0 percent Tukey HSD
MODE   Count   LS Mean   Homogeneous Groups
----
11   45   900.642   X
10   46   1063.52   X

Contrast   Difference   +/- Limits
----
10 - 11   *162.878   7.34254
----
* denotes a statistically significant difference.

F-23

Interaction and 95% Tukey HSD Intervals

CONCLUSION: No significant differences among the fuel and pilot condition
combinations with respect to the average BSCO2.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: No significant differences among the mode and pilot condition
combinations with respect to the average BSCO2.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: No significant differences among the mode and fuel combinations
with respect to the average BSCO2.

```
Multifactor ANOVA - BSSOF (g/kW-hr)
                   Three Pilot Conditions   Modes 10 and 11

Analysis Summary

Dependent variable: bssof
Factors:
        COND
        FUEL
        MODE

Number of complete cases: 90
```

Scatterplot by Level Code

Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for bssof - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares    Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:COND                 0.00848506      2    0.00424253       4.23     0.0191
```

```
 B:FUEL                    0.677894        4        0.169473      169.05     0.0000
 C:MODE                    0.0493254       1        0.0493254      49.20     0.0000

INTERACTIONS
 AB                        0.141082        8        0.0176353      17.59     0.0000
 AC                        0.0174835       2        0.00874174      8.72     0.0005
 BC                        0.0224319       4        0.00560796      5.59     0.0007
 ABC                       0.0221993       8        0.00277492      2.77     0.0113

RESIDUAL                   0.0601491       60       0.00100248
-------------------------------------------------------------------------------
TOTAL (CORRECTED)          0.994981        89
-------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.
```

CONCLUSION: Statistically significant differences in the average BSSOF among the fuels, modes, pilot conditions, all two-factor interactions, and the three-factor interaction between the fuel*mode*pilot condition.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average BSSOF for the Pilot A condition is significantly different from the Pilot B condition.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average BSSOF for the FT-100, CA, and DF-2 fuels are significantly different from one another and the remaining two fuels. The average BSSOF for the ADMM15 and ALS fuels are not significantly different from one another.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average BSSOF for modes 10 and 11 are statistically significant from one another.

Multiple Range Tests for bssof by COND

Method: 95.0 percent Tukey HSD
COND   Count   LS Mean   Homogeneous Groups

PilotB   30   0.160938   X
LPP   30   0.176213   XX
PilotA   30   0.18437   X

Contrast   Difference   +/- Limits

LPP - PilotA   -0.00815713   0.019648
LPP - PilotB   0.0152749   0.019648
PilotA - PilotB   *0.023432   0.019648
----
* denotes a statistically significant difference.

Multiple Range Tests for bssof by FUEL

Method: 95.0 percent Tukey HSD
FUEL   Count   LS Mean   Homogeneous Groups

FT-100   17   0.0776545   X
ALS   19   0.132759   X
ADMM15   18   0.133725   X
CA   18   0.191733   X
DF-2   18   0.333329   X

Contrast   Difference   +/- Limits

ADMM15 - ALS   0.000965815   0.0292901
ADMM15 - CA   *-0.0580086   0.0296832
ADMM15 - DF-2   *-0.199604   0.0296832
ADMM15 - FT-100   *0.0560701   0.0301166
ALS - CA   *-0.0589745   0.0292901
ALS - DF-2   *-0.20057   0.0292901
ALS - FT-100   *0.0551043   0.0297292
CA - DF-2   *-0.141596   0.0296832
CA - FT-100   *0.114079   0.0301166
DF-2 - FT-100   *0.255674   0.0301166
----
* denotes a statistically significant difference.

Multiple Range Tests for bssof by MODE

Method: 95.0 percent Tukey HSD

F-27

```
MODE            Count   LS Mean         Homogeneous Groups
--------------------------------------------------------------------------------
11              44      0.150332        X
10              46      0.197348         X
--------------------------------------------------------------------------------
Contrast                                Difference      +/-  Limits
--------------------------------------------------------------------------------
10 - 11                                 *0.0470161      0.0133552
--------------------------------------------------------------------------------
* denotes a statistically significant difference.
```

Interaction and 95% Tukey HSD Intervals

CONCLUSION: The trend in the average BSSOF across the pilot conditions for the DF-2 fuel
is significantly different than the trends for the remaining four fuels. The average
BSSOF for the DF-2 fuel at the Pilot A and Pilot B conditions are significantly
different than the other four fuels.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: The average BSSOF at the LPP and Pilot A conditions for Mode 10 are
significantly different than those at Mode 11. There is not a significant difference
in the average BSSOF between the two modes at the Pilot B condition.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: The trends in the average BSSOF across the two modes are different
at fuels ADMM15 and CA. There does not appear to be differences in the average
BSSOF for the two modes at the ALS, DF-2 or FT-100 fuels.

```
Multifactor ANOVA - BENZENE (mg/kW-hr)   Toxic Gaseous Emissions
                   Three Pilot Conditions   Modes 10 and 11


Analysis Summary

Dependent variable: BENZENE
Factors:
        COND
        FUEL
        MODE

Number of complete cases: 91
```

Scatterplot by Level Code

Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for BENZENE - Type III Sums of Squares
--------------------------------------------------------------------------------
Source               Sum of Squares   Df   Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:COND                   176.208      2      88.1042      40.24    0.0000
 B:FUEL                   843.208      4      210.802      96.27    0.0000
```

F-30

C:MODE	45.7314	1	45.7314	20.89	0.0000
INTERACTIONS					
AB	123.013	8	15.3766	7.02	0.0000
AC	4.81639	2	2.40819	1.10	0.3394
BC	10.8557	4	2.71392	1.24	0.3037
ABC	4.53938	8	0.567422	0.26	0.9765
RESIDUAL	133.569	61	2.18966		

```
-------------------------------------------------------------------------------
TOTAL (CORRECTED)         1339.93     90
-------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.
```

CONCLUSION: Statistically significant differences in the average benzene among the
fuels, modes, pilot conditions, and the fuel*pilot condition interaction.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average benzene for the Pilot A and Pilot B conditions are not
significantly different from one another, but are significantly different from
the LPP conditions.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average benzene for the ALS, CA, and DF-2 fuels are significantly
different from one another and the remaining two fuels. The average benzene for the
ADMM15 and FT-100 fuels are not significantly different from one another.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average benzene for modes 10 and 11 are significantly different from one another.

Multiple Range Tests for BENZENE by COND

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
COND            Count     LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
LPP             31        5.43508          X
PilotB          30        7.97672           X
PilotA          30        8.66153           X
--------------------------------------------------------------------------------
Contrast                                   Difference       +/-  Limits
--------------------------------------------------------------------------------
LPP - PilotA                               *-3.22645        0.91045
LPP - PilotB                               *-2.54164        0.91045
PilotA - PilotB                            0.684804         0.917883
--------------------------------------------------------------------------------
```
* denotes a statistically significant difference.

Multiple Range Tests for BENZENE by FUEL

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
FUEL            Count     LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
FT-100          18        3.70071          X
ADMM15          18        4.35116          X
ALS             19        7.34001           X
CA              18        9.6714             X
DF-2            18        11.7256             X
--------------------------------------------------------------------------------
Contrast                                   Difference       +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                               *-2.98885        1.3682
ADMM15 - CA                                *-5.32024        1.38657
ADMM15 - DF-2                              *-7.37443        1.38657
ADMM15 - FT-100                            0.65045          1.38657
ALS - CA                                   *-2.33139        1.3682
ALS - DF-2                                 *-4.38558        1.3682
ALS - FT-100                               *3.6393          1.3682
CA - DF-2                                  *-2.05419        1.38657
CA - FT-100                                *5.97069         1.38657
DF-2 - FT-100                              *8.02488         1.38657
--------------------------------------------------------------------------------
```
* denotes a statistically significant difference.

Multiple Range Tests for BENZENE by MODE

```
--------------------------------------------------------------------------------
```

F-32

```
Method: 95.0 percent Tukey HSD
MODE          Count      LS Mean        Homogeneous Groups
----------------------------------------------------------------------------
11            45         6.64792          X
10            46         8.06763           X
----------------------------------------------------------------------------
Contrast                                  Difference      +/-  Limits
----------------------------------------------------------------------------
10 - 11                                   *1.41971        0.620402
----------------------------------------------------------------------------
* denotes a statistically significant difference.
```

Interaction and 95% Tukey HSD Intervals

CONCLUSION: The trend in the average benzene across the pilot conditions for
the DF-2 and CA fuels is significantly different than the trends for the remaining
three fuels. The average benzene for the DF-2 fuel at the Pilot B condition is
significantly different than the other four fuels, but not at the LPP condition.
Also, the Pilot A condition demonstrates that the average benzene for the DF-2 and CA
fuels are not significantly different from one another.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average benzene among the
mode and pilot condition combinations.

F-33

Interaction and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average benzene among the
mode and fuel combinations.

```
Multifactor ANOVA - 1,3 Butadiene (mg/kW-hr)   Toxic Gaseous Emissions
                 Three Pilot Conditions    Modes 10 and 11

Analysis Summary

Dependent variable: BUTAD
Factors:
        COND
        FUEL
        MODE

Number of complete cases: 91
```

Scatterplot by Level Code

Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for BUTAD - Type III Sums of Squares
--------------------------------------------------------------------------------
Source               Sum of Squares   Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:COND                  52.2836        2      26.1418       35.11     0.0000
 B:FUEL                  163.144        4      40.7859       54.78     0.0000
```

F-35

C:MODE	183.857	1	183.857	246.94	0.0000
INTERACTIONS					
AB	100.982	8	12.6227	16.95	0.0000
AC	19.6903	2	9.84514	13.22	0.0000
BC	9.36558	4	2.3414	3.14	0.0204
ABC	9.57871	8	1.19734	1.61	0.1412
RESIDUAL	45.4168	61	0.744538		

```
-------------------------------------------------------------------------------
TOTAL (CORRECTED)       580.649     90
-------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.
```

CONCLUSION: Statistically significant differences in the average 1,3 butadiene
among the fuels, modes, pilot conditions, and two-way interactions.

Means and 95% Tukey HSD Intervals

CONCLUSION: All three pilot conditions are significantly different from one
another with respect to the average 1,3 butadiene.

Means and 95% Tukey HSD Intervals

CONCLUSION: There are several distinct fuel groupings with respect to the average
1,3 butadiene. The average 1,3 butadiene for the DF-2 fuel is significantly different
than the remaining four fuels. The FT-100 fuel is significantly different than the
ADMM15 and CA fuels, but not significantly different than the ALS fuel. Also, the
average
1,3 butadiene for the CA fuel is significantly different than the ALS fuel.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average 1,3 butadiene for mode 10 is significantly different than mode 11.


```
Multiple Range Tests for BUTAD by COND


--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
COND            Count    LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
LPP             31       5.62805          X
PilotA          30       6.70067           X
PilotB          30       7.47402            X
--------------------------------------------------------------------------------
Contrast                                 Difference        +/-  Limits
--------------------------------------------------------------------------------
LPP - PilotA                             *-1.07262         0.530898
LPP - PilotB                             *-1.84597         0.530898
PilotA - PilotB                          *-0.773342        0.535232
--------------------------------------------------------------------------------
* denotes a statistically significant difference.




Multiple Range Tests for BUTAD by FUEL


--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
FUEL            Count    LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
FT-100          18       5.17097          X
ALS             19       5.56048          XX
ADMM15          18       6.29433           XX
CA              18       7.00454            X
DF-2            18       8.97425             X
--------------------------------------------------------------------------------
Contrast                                 Difference        +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                             0.733847          0.79782
ADMM15 - CA                              -0.710209         0.80853
ADMM15 - DF-2                            *-2.67992         0.80853
ADMM15 - FT-100                          *1.12336          0.80853
ALS - CA                                 *-1.44406         0.79782
ALS - DF-2                               *-3.41377         0.79782
ALS - FT-100                             0.389514          0.79782
CA - DF-2                                *-1.96971         0.80853
CA - FT-100                              *1.83357          0.80853
DF-2 - FT-100                            *3.80328          0.80853
--------------------------------------------------------------------------------
* denotes a statistically significant difference.


Multiple Range Tests for BUTAD by MODE


--------------------------------------------------------------------------------
```

```
Method: 95.0 percent Tukey HSD
MODE          Count    LS Mean          Homogeneous Groups
-------------------------------------------------------------------------------
11             45      5.17759              X
10             46      8.02423               X
-------------------------------------------------------------------------------
Contrast                                    Difference        +/-  Limits
-------------------------------------------------------------------------------
10 - 11                                     *2.84664          0.361766
-------------------------------------------------------------------------------
```
* denotes a statistically significant difference.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: The trends in the average 1,3 butadiene across the pilot conditions for
the DF-2 and FT-100 fuels appear similar. However, the ALS fuel demonstrates an
almost constant average 1,3 butadiene across all three pilot conditions while the
CA fuel shows a significant decrease from the Pilot A to Pilot B conditions.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: A significant interaction exists between the pilot condition and the
modes. The difference in the average 1,3 butadiene between the two modes at the LPP
condition is smaller than the differences at the Pilot A and Pilot B conditions.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: A significant interaction exists between the mode and the fuel levels.
The difference in the average 1,3 butadiene between modes 10 and 11 is the
largest at the DF-2 fuel and the smallest at the ALS fuel.

```
Multifactor ANOVA - Formaldehyde (mg/W-hr)   Toxic Gaseous Emissions
                    Three Pilot Conditions    Modes 10 and 11
Analysis Summary

Dependent variable: FORMALD
Factors:
        COND
        FUEL
        MODE

Number of complete cases: 91
```

Scatterplot by Level Code

Formaldehyde vs Pilot Condition (LPP, PilotA, PilotB)

Scatterplot by Level Code

Formaldehyde vs Fuel (ADMM15, ALS, CA, DF-2, FT-100)

Scatterplot by Level Code

Formaldehyde vs Mode (10, 11)

```
Analysis of Variance for FORMALD - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares    Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:COND                  372467.0      2      186234.0       28.61     0.0000
 B:FUEL                  740668.0      4      185167.0       28.44     0.0000
 C:MODE                 1.54489E6      1     1.54489E6      237.29     0.0000
```

F-40

```
INTERACTIONS
 AB                       307919.0       8        38489.8        5.91     0.0000
 AC                       199851.0       2        99925.7       15.35     0.0000
 BC                        76005.8       4        19001.5        2.92     0.0283
 ABC                       55295.1       8        6911.89        1.06     0.4016

RESIDUAL                  397136.0      61        6510.43
-------------------------------------------------------------------------------
TOTAL (CORRECTED)         3.67275E6     90
-------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.
```

CONCLUSION: Statistically significant differences in the average formaldehyde among the fuels, modes, pilot conditions, and two-way interactions.

Means and 95% Tukey HSD Intervals

CONCLUSION: All three pilot conditions are significantly different from one another with respect to the average formaldehyde.

Means and 95% Tukey HSD Intervals

CONCLUSION: There are three distinct fuel groupings with respect to the average formaldehyde. Fuels FT-100 and DF-2 are significantly different from one another and the remaining three fuels. The ADMM15, ALS, and CA fuels are not significantly different from one another, but are significantly different than the other two fuels.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average formaldehyde for mode 10 is significantly different than mode 11.

Multiple Range Tests for FORMALD by COND

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
COND            Count    LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
LPP             31       408.327          X
PilotB          30       493.116           X
PilotA          30       564.674            X
--------------------------------------------------------------------------------
Contrast                                 Difference        +/-  Limits
--------------------------------------------------------------------------------
LPP - PilotA                             *-156.347         49.6447
LPP - PilotB                             *-84.7886         49.6447
PilotA - PilotB                          *71.5582          50.0499
--------------------------------------------------------------------------------
```
* denotes a statistically significant difference.

Multiple Range Tests for FORMALD by FUEL

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
FUEL            Count    LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
FT-100          18       378.998          X
ADMM15          18       458.316           X
ALS             19       472.468           X
CA              18       478.293           X
DF-2            18       655.455            X
--------------------------------------------------------------------------------
Contrast                                 Difference        +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                             -14.1521          74.6048
ADMM15 - CA                              -19.9768          75.6062
ADMM15 - DF-2                            *-197.139         75.6062
ADMM15 - FT-100                          *79.3182          75.6062
ALS - CA                                 -5.82469          74.6048
ALS - DF-2                               *-182.987         74.6048
ALS - FT-100                             *93.4703          74.6048
CA - DF-2                                *-177.163         75.6062
CA - FT-100                              *99.295           75.6062
DF-2 - FT-100                            *276.458          75.6062
--------------------------------------------------------------------------------
```
* denotes a statistically significant difference.

Multiple Range Tests for FORMALD by MODE

```
--------------------------------------------------------------------------------
```

```
Method: 95.0 percent Tukey HSD
MODE          Count     LS Mean         Homogeneous Groups
--------------------------------------------------------------------------------
11             45       358.236            X
10             46       619.175             X
--------------------------------------------------------------------------------
Contrast                                  Difference        +/-  Limits
--------------------------------------------------------------------------------
10 - 11                                   *260.939          33.829
--------------------------------------------------------------------------------
* denotes a statistically significant difference.
```

Interaction and 95% Tukey HSD Intervals

CONCLUSION: The trends in the average formaldehyde across the pilot conditions for
the CA and ALS fuels appear similar. However, the ADMM15 fuel demonstrates an increase
in the average formaldehyde from the Pilot A to the Pilot B conditions, whereas the CA
and ALS fuels showed a decrease.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: A significant interaction exists between the pilot conditions and the modes.
The difference in the average formaldehyde between the two modes at the LPP condition
is smaller than the differences at the Pilot A and Pilot B conditions.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: A significant interaction exists between the mode and the fuel levels.
The difference in the average formaldehyde between modes 10 and 11 is the largest at
the DF-2 fuel and the smallest at the ALS fuel.

F-43

```
Multifactor ANOVA - Acetaldehyde (mg/kW-hr)   Toxic Gaseous Emissions
                    Three Pilot Conditions    Modes 10 and 11

Analysis Summary

Dependent variable: ACETALD
Factors:
        COND
        FUEL
        MODE

Number of complete cases: 91
```

Scatterplot by Level Code

Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for ACETALD - Type III Sums of Squares
--------------------------------------------------------------------------------
Source                Sum of Squares   Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:COND                    34346.8      2        17173.4      20.91     0.0000
 B:FUEL                    92632.3      4        23158.1      28.20     0.0000
 C:MODE                   159403.0      1       159403.0     194.11     0.0000
```

```
INTERACTIONS
 AB                             37491.4       8        4686.43       5.71      0.0000
 AC                             16558.1       2        8279.06      10.08      0.0002
 BC                             5617.49       4        1404.37       1.71      0.1593
 ABC                            7258.13       8        907.266       1.10      0.3727

RESIDUAL                        50093.8      61        821.209
--------------------------------------------------------------------------------
TOTAL (CORRECTED)              401292.0      90
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.
```

CONCLUSION: Statistically significant differences in the average acetaldehyde
among the fuels, modes, pilot conditions, and some two-way interactions.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average acetaldehyde for the LPP and Pilot B conditions are not
significantly different from one another, but are different from the Pilot A condition.

Means and 95% Tukey HSD Intervals

CONCLUSION: There are three distinct fuel groupings with respect to the average
acetaldehyde. The DF-2 fuel is significantly different from the remaining four
fuels. The ADMM15 and FT-100 fuels are not significantly different from one another,
but are different from the other fuels. Also, the CA and ALS fuels are not
significantly different from one another, but are different from the other fuels.

Means and 95% Tukey HSD Intervals

Mode

CONCLUSION: The average acetaldehyde for mode 10 is significantly different than mode 11.

Multiple Range Tests for ACETALD by COND

Method: 95.0 percent Tukey HSD
COND   Count   LS Mean   Homogeneous Groups

LPP   31   151.651   X
PilotB   30   159.56   X
PilotA   30   196.333   X

Contrast   Difference   +/- Limits

LPP - PilotA   *-44.6817   17.6317
LPP - PilotB   -7.9089   17.6317
PilotA - PilotB   *36.7728   17.7757
----
* denotes a statistically significant difference.

Multiple Range Tests for ACETALD by FUEL

Method: 95.0 percent Tukey HSD
FUEL   Count   LS Mean   Homogeneous Groups

ADMM15   18   135.992   X
FT-100   18   139.76   X
CA   18   169.815   X
ALS   19   175.105   X
DF-2   18   225.236   X

Contrast   Difference   +/- Limits

ADMM15 - ALS   *-39.1129   26.4965
ADMM15 - CA   *-33.8224   26.8522
ADMM15 - DF-2   *-89.2434   26.8522
ADMM15 - FT-100   -3.76753   26.8522
ALS - CA   5.29049   26.4965
ALS - DF-2   *-50.1305   26.4965
ALS - FT-100   *35.3454   26.4965
CA - DF-2   *-55.421   26.8522
CA - FT-100   *30.0549   26.8522
DF-2 - FT-100   *85.4759   26.8522
----
* denotes a statistically significant difference.

Multiple Range Tests for ACETALD by MODE

```
Method: 95.0 percent Tukey HSD
MODE           Count     LS Mean         Homogeneous Groups
--------------------------------------------------------------------------------
11              45       127.272              X
10              46       211.091               X
--------------------------------------------------------------------------------
Contrast                                 Difference          +/-  Limits
--------------------------------------------------------------------------------
10 - 11                                  *83.8186            12.0147
--------------------------------------------------------------------------------
* denotes a statistically significant difference.
```


Interaction and 95% Tukey HSD Intervals

CONCLUSION: The trends in the average acetaldehyde across the pilot conditions for
the CA and ALS fuels appear similar. While the ADMM15 fuel demonstrates an increase
in the aveerage acetaldehyde from the Pilot A to Pilot B conditions, the CA and ALS
fuels showed a decrease.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: A significant interaction exists between the pilot condition and the
modes. The difference in the average acetaldehyde between the two modes at the
LPP condition is smaller than the differences at the Pilot A and Pilot B conditions.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average acetaldehyde among the fuel and mode combinations.

```
Multifactor ANOVA - NAPHTHALENE (µg/kW-hr)   Gaseous PAH
                    Three Pilot Conditions   Modes 10 and 11


Analysis Summary


Dependent variable: GNAPHTH
Factors:
        COND
        FUEL
        MODE


Number of complete cases: 91
```

Scatterplot by Level Code

Naphthalene vs Pilot Condition (LPP, PilotA, PilotB)

Scatterplot by Level Code

Naphthalene vs Fuel (ADMM15, ALS, CA, DF-2, FT-100)

Scatterplot by Level Code

Naphthalene vs Mode (10, 11)

```
Analysis of Variance for GNAPHTH - Type III Sums of Squares
--------------------------------------------------------------------------------
Source                Sum of Squares    Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:COND                  1.74687E7        2      8.73433E6     14.33     0.0000
 B:FUEL                  7.55174E8        4      1.88793E8    309.67     0.0000
 C:MODE                  6.71152E6        1      6.71152E6     11.01     0.0015
```

F-49

```
INTERACTIONS
 AB                         1.5257E7       8      1.90713E6       3.13     0.0050
 AC                         664459.0       2       332230.0       0.54     0.5827
 BC                        2.70728E7       4      6.76821E6      11.10     0.0000
 ABC                       6.49723E6       8       812154.0       1.33     0.2451

RESIDUAL                   3.71891E7      61       609658.0
--------------------------------------------------------------------------------
TOTAL (CORRECTED)          8.66535E8      90
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.
```

CONCLUSION: Statistically significant differences in the average naphthalene among the fuels, modes, pilot conditions, the pilot condition*fuel interaction, and the fuel*mode interaction.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average naphthalene for the Pilot A and Pilot B conditions are not significantly different from one another, but are significantly different from the LPP condition.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average naphthalene for the CA and DF-2 fuels are significantly different from one another and the remaining three fuels. The ALS and FT-100 fuels demonstrate significantly different average naphthalene; however, neither one of these fuels was significantly different than the ADMM15 fuel.

F-50

Means and 95% Tukey HSD Intervals

CONCLUSION: The average naphthalene for modes 10 and 11 are significantly
different from one another.

Multiple Range Tests for GNAPHTH by COND

Method: 95.0 percent Tukey HSD
COND   Count   LS Mean   Homogeneous Groups

LPP   31   2458.83   X
PilotB   30   3350.27   X
PilotA   30   3417.32   X

Contrast   Difference   +/- Limits

LPP - PilotA   *-958.492   480.409
LPP - PilotB   *-891.437   480.409
PilotA - PilotB   67.0549   484.33
----
* denotes a statistically significant difference.

Multiple Range Tests for GNAPHTH by FUEL

Method: 95.0 percent Tukey HSD
FUEL   Count   LS Mean   Homogeneous Groups

FT-100   18   323.888   X
ADMM15   18   872.03   XX
ALS   19   1322.76   X
DF-2   18   5046.16   X
CA   18   7812.53   X

Contrast   Difference   +/- Limits

ADMM15 - ALS   -450.729   721.946
ADMM15 - CA   *-6940.5   731.637
ADMM15 - DF-2   *-4174.13   731.637
ADMM15 - FT-100   548.142   731.637
ALS - CA   *-6489.77   721.946
ALS - DF-2   *-3723.4   721.946
ALS - FT-100   *998.871   721.946
CA - DF-2   *2766.36   731.637
CA - FT-100   *7488.64   731.637
DF-2 - FT-100   *4722.28   731.637
----
* denotes a statistically significant difference.

Multiple Range Tests for GNAPHTH by MODE

F-51

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
MODE          Count     LS Mean        Homogeneous Groups
--------------------------------------------------------------------------------
11             45       2803.53             X
10             46       3347.41              X
--------------------------------------------------------------------------------
Contrast                                   Difference        +/-  Limits
--------------------------------------------------------------------------------
10 - 11                                    *543.879          327.362
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: The trend in the average naphthalene across the pilot conditions for
the ADMM15, ALS, and FT-100 fuels is significantly different than the trends for the
CA and DF-2 fuels. Whereas the trends in the ADMM15, ALS, and FT-100 fuels across the
three pilot conditions are relatively constant, the CA and DF-2 fuels show an increase
in the average naphthalene from the LPP to the Pilot A and Pilot B conditions.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average naphthalene among
the mode and pilot condition combinations.

F-52

Interaction and 95% Tukey HSD Intervals

CONCLUSION: A significant interaction exists between the fuels and modes. The
difference in the average naphthalene between the two modes is significant at the
CA fuel. However, the remaining four fuels do not demonstrate a significant difference
between the two modes with respect to the average naphthalene.

```
Multifactor ANOVA - 2-Methylnaphthalene (µg/kW-hr)   Gaseous PAH
                   Three Pilot Conditions   Modes 10 and 11

Analysis Summary

Dependent variable: METHYL2
Factors:
        COND
        FUEL
        MODE

Number of complete cases: 91
```

Scatterplot by Level Code

Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for METHYL2 - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares    Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:COND                  1.30211E7     2      6.51055E6       6.11     0.0038
 B:FUEL                  6.84386E8     4      1.71097E8     160.63     0.0000
 C:MODE                  681627.0      1      681627.0        0.64     0.4268
```

F-54

```
INTERACTIONS
 AB                          2.06216E7       8      2.5777E6     2.42     0.0243
 AC                           164595.0       2      82297.7      0.08     0.9257
 BC                          2.10818E7       4      5.27045E6    4.95     0.0016
 ABC                         8.59668E6       8      1.07459E6    1.01     0.4390

RESIDUAL                     6.49747E7      61      1.06516E6
--------------------------------------------------------------------------------
TOTAL (CORRECTED)            8.13672E8      90
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.
```

CONCLUSION: Statistically significant differences in the average 2-methylnaphthalene
among the pilot conditions, fuels, pilot condition*fuel interaction, and the
fuel*mode interaction.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average 2-methylnaphthalene for the Pilot A and Pilot B conditions
are not significantly different from one another, but are significantly different
from the LPP condition.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average 2-methylnaphthalene for the CA and DF-2 fuels are
significantly different from one another and the remaining three fuels. The
average 2-methylnaphthalene for the ADMM15, ALS, and FT-100 fuels are not
significantly different from one another.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average 2-methylnaphthalene for modes 10 and 11 are not significantly different from one another.

Multiple Range Tests for METHYL2 by COND

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
COND            Count    LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
LPP             31       2072.28          X
PilotA          30       2799.98           X
PilotB          30       2929.34           X
--------------------------------------------------------------------------------
Contrast                                  Difference       +/-  Limits
--------------------------------------------------------------------------------
LPP - PilotA                              *-727.694        635.002
LPP - PilotB                              *-857.061        635.002
PilotA - PilotB                           -129.367         640.186
--------------------------------------------------------------------------------
* denotes a statistically significant difference.
```


Multiple Range Tests for METHYL2 by FUEL

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
FUEL            Count    LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
FT-100          18       84.6176          X
ADMM15          18       376.432          X
ALS             19       802.859          X
CA              18       4868.56           X
DF-2            18       6870.21            X
--------------------------------------------------------------------------------
Contrast                                  Difference       +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                              -426.427         954.265
ADMM15 - CA                               *-4492.13        967.075
ADMM15 - DF-2                             *-6493.78        967.075
ADMM15 - FT-100                           291.815          967.075
ALS - CA                                  *-4065.7         954.265
ALS - DF-2                                *-6067.35        954.265
ALS - FT-100                              718.242          954.265
CA - DF-2                                 *-2001.65        967.075
CA - FT-100                               *4783.94         967.075
DF-2 - FT-100                             *6785.59         967.075
--------------------------------------------------------------------------------
* denotes a statistically significant difference.
```


Multiple Range Tests for METHYL2 by MODE

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
```

```
MODE          Count    LS Mean          Homogeneous Groups
-----------------------------------------------------------------------------
11            45       2513.87          X
10            46       2687.2           X
-----------------------------------------------------------------------------
Contrast                               Difference       +/-  Limits
-----------------------------------------------------------------------------
10 - 11                                173.327          432.705
-----------------------------------------------------------------------------
```
* denotes a statistically significant difference.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: The trend in the average 2-methylnaphthalene across the pilot
conditions for the ADMM15, ALS, and FT-100 fuels is significantly different than
the trends for the CA and DF-2 fuels. Whereas the trends in the ADMM15, ALS, and
FT-100 fuels across the three pilot conditions are relatively constant, the CA
and DF-2 fuels show an increase in the average 2-methylnaphthalene from the LPP
to the Pilot A and Pilot B conditions.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average 2-methylnaphthalene
among the mode and pilot condition combinations.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: A significant interaction exists between the fuels and modes. The
difference in the average 2-methylnaphthalene between the two modes is
significant at the CA fuel. However, the remaining four fuels do not
demonstrate a significant difference between the two modes with respect to
the average 2-methylnaphthalene.

```
Multifactor ANOVA - 1-Methylnaphthalene (µg/kW-hr)   Gaseous PAH
                  Three Pilot Conditions   Modes 10 and 11

Analysis Summary

Dependent variable: METHYL1
Factors:
        COND
        FUEL
        MODE

Number of complete cases: 91
```

Scatterplot by Level Code

Pilot Condition

Scatterplot by Level Code

Fuel

Scatterplot by Level Code

Mode

```
Analysis of Variance for METHYL1 - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares    Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:COND                  7.1201E6      2      3.56005E6       7.02     0.0018
 B:FUEL                  3.2382E8      4      8.0955E7      159.66     0.0000
 C:MODE                  104049.0      1      104049.0        0.21     0.6522
```

F-59

```
INTERACTIONS
 AB                          1.10994E7      8      1.38742E6     2.74    0.0120
 AC                            87299.1      2        43649.5     0.09    0.9176
 BC                          7.60607E6      4      1.90152E6     3.75    0.0086
 ABC                         3.4431E6       8       430387.0     0.85    0.5640

RESIDUAL                     3.09295E7     61       507040.0
--------------------------------------------------------------------------------
TOTAL (CORRECTED)            3.8428E8      90
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.
```

CONCLUSION: Statistically significant differences in the average 1-methylnaphthalene
among the pilot conditions, fuels, pilot condition*fuel interaction, and
fuel*mode interaction.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average 1-methylnaphthalene for the Pilot A and Pilot B
conditions are not significantly different from one another, but are significantly
different from the LPP condition.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average 1-methylnaphthalene for the CA and DF-2 fuels are
significantly different from one another and the remaining three fuels. The
average 1-methylnaphthalene for the ADMM15, ALS, and FT-100 fuels are not
significantly different from one another.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average 1-methylnaphthalene for modes 10 and 11 are not
significantly different from one another.

Multiple Range Tests for METHYL1 by COND

Method: 95.0 percent Tukey HSD
COND   Count   LS Mean   Homogeneous Groups

LPP   31   1296.69   X
PilotA   30   1847.77   X
PilotB   30   1922.05   X

Contrast   Difference   +/- Limits

LPP - PilotA   *-551.08   438.116
LPP - PilotB   *-625.36   438.116
PilotA - PilotB   -74.2805   441.692
----
* denotes a statistically significant difference.

Multiple Range Tests for METHYL1 by FUEL

Method: 95.0 percent Tukey HSD
FUEL   Count   LS Mean   Homogeneous Groups

FT-100   18   53.4942   X
ADMM15   18   185.723   X
ALS   19   468.028   X
CA   18   2868.42   X
DF-2   18   4868.5   X

Contrast   Difference   +/- Limits

ADMM15 - ALS   -282.306   658.39
ADMM15 - CA   *-2682.69   667.228
ADMM15 - DF-2   *-4682.78   667.228
ADMM15 - FT-100   132.229   667.228
ALS - CA   *-2400.39   658.39
ALS - DF-2   *-4400.47   658.39
ALS - FT-100   414.534   658.39
CA - DF-2   *-2000.09   667.228
CA - FT-100   *2814.92   667.228
DF-2 - FT-100   *4815.01   667.228
----
* denotes a statistically significant difference.

Multiple Range Tests for METHYL1 by MODE

F-61

```
Method: 95.0 percent Tukey HSD
MODE          Count     LS Mean        Homogeneous Groups
-------------------------------------------------------------------------------
11             45       1654.97            X
10             46       1722.69            X
-------------------------------------------------------------------------------
Contrast                                 Difference       +/-  Limits
-------------------------------------------------------------------------------
10 - 11                                   67.7191          298.542
-------------------------------------------------------------------------------
* denotes a statistically significant difference.
```

Interaction and 95% Tukey HSD Intervals

CONCLUSION: The trend in the average 1-methylnaphthalene across the pilot
conditions for the ADMM15, ALS, and FT-100 fuels is significantly different than
the trends for the CA and DF-2 fuels. Whereas the trends in the ADMM15, ALS, and
FT-100 fuels across the three pilot conditions are relatively constant, the CA
and DF-2 fuels show an increase in the average 1-methylnaphthalene from the LPP
to the Pilot A and Pilot B conditions.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average 1-methylnapthalene
among the mode and pilot condition combinations.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: A significant interaction exists between the fuels and modes. The difference in the average 1-methylnaphthalene between the two modes is significant at the CA fuel. However, the remaining four fuels do not demonstrate a significant difference between the two modes with respect to the average 1-methylnaphthalene.

```
Multifactor ANOVA - 2,6-Dimethylnaphthalene (µg/kW-hr)   Gaseous PAH
                    Three Pilot Conditions   Modes 10 and 11


Analysis Summary

Dependent variable: DIMETHYL
Factors:
         COND
         FUEL
         MODE

Number of complete cases: 91
```


Scatterplot by Level Code — 2,6-Dimethylnaphthalene vs Pilot Condition (LPP, PilotA, PilotB)

Scatterplot by Level Code — 2,6-Dimethylnaphthalene vs Fuel (ADMM15, ALS, CA, DF-2, FT-100)

Scatterplot by Level Code — 2,6-Dimethylnaphthalene vs Mode (10, 11)

```
Analysis of Variance for DIMETHYL - Type III Sums of Squares
--------------------------------------------------------------------------------
Source                Sum of Squares   Df    Mean Square    F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:COND                   4.46581E6     2      2.23291E6       3.83    0.0270
 B:FUEL                   3.15153E8     4      7.87882E7     135.30    0.0000
```

```
   C:MODE                      106897.0        1       106897.0    0.18     0.6698

INTERACTIONS
   AB                          1.02244E7        8      1.27804E6    2.19     0.0401
   AC                            92309.3        2        46154.7    0.08     0.9239
   BC                          5.23499E6        4      1.30875E6    2.25     0.0743
   ABC                         1.90357E6        8       237947.0    0.41     0.9114

RESIDUAL                       3.55226E7       61       582338.0
--------------------------------------------------------------------------------
TOTAL (CORRECTED)              3.72663E8       90
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.
```

CONCLUSION: Statistically significant differences in the average 2,6-dimethylnaphthalene
among the pilot conditions, fuels, and pilot condition*fuel interaction.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average 2,6-dimethylnaphthalene for the Pilot B condition is
significantly different than the LPP condition.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average 2,6-dimethylnaphthalene for the CA and DF-2 fuels are
significantly different from one another and the remaining three fuels. The average
2,6-dimethylnaphthalene for the ADMM15, ALS, and FT-100 fuels are not
significantly different from one another.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average 2,6-dimethylnaphthalene for modes 10 and 11 are not significantly different from one another.

Multiple Range Tests for DIMETHYL by COND

Method: 95.0 percent Tukey HSD

COND	Count	LS Mean	Homogeneous Groups
LPP	31	1040.88	X
PilotA	30	1404.39	XX
PilotB	30	1570.21	X

Contrast	Difference	+/- Limits
LPP - PilotA	-363.515	469.521
LPP - PilotB	*-529.328	469.521
PilotA - PilotB	-165.813	473.354

----
* denotes a statistically significant difference.

Multiple Range Tests for DIMETHYL by FUEL

Method: 95.0 percent Tukey HSD

FUEL	Count	LS Mean	Homogeneous Groups
FT-100	18	33.1233	X
ADMM15	18	61.705	X
ALS	19	237.558	X
CA	18	1429.7	X
DF-2	18	4930.39	X

Contrast	Difference	+/- Limits
ADMM15 - ALS	-175.853	705.585
ADMM15 - CA	*-1367.99	715.056
ADMM15 - DF-2	*-4868.68	715.056
ADMM15 - FT-100	28.5817	715.056
ALS - CA	*-1192.14	705.585
ALS - DF-2	*-4692.83	705.585
ALS - FT-100	204.435	705.585
CA - DF-2	*-3500.69	715.056
CA - FT-100	*1396.58	715.056
DF-2 - FT-100	*4897.26	715.056

----
* denotes a statistically significant difference.

Multiple Range Tests for DIMETHYL by MODE

```
Method: 95.0 percent Tukey HSD
MODE          Count     LS Mean        Homogeneous Groups
--------------------------------------------------------------------------------
10             46       1304.17            X
11             45       1372.81            X
--------------------------------------------------------------------------------
Contrast                                Difference        +/-  Limits
--------------------------------------------------------------------------------
10 - 11                                 -68.6395          319.943
--------------------------------------------------------------------------------
* denotes a statistically significant difference.
```

Interaction and 95% Tukey HSD Intervals

CONCLUSION: The trend in the average 2,6-dimethylnaphthalene across the pilot
conditions for the ADMM16, ALS, CA, and FT-100 fuels is significantly
different than the trend for the DF-2 fuel. Whereas, the trends in the ADMM15,
ALS, CA, and FT-100 fuels are relatively constant, the DF-2 fuel shows an increase
in the average 2,6-dimethylnaphthalene from the LPP to the Pilot A and Pilot B
conditions.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average
2,6-dimethylnaphthalene among the pilot condition and mode combinations.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average
2,6-dimethylnaphthalene among the fuel and mode combinations.

```
Multifactor ANOVA - Acenaphthylene (µg/kW-hr)   Gaseous PAH
                  Three Pilot Conditions   Modes 10 and 11


Analysis Summary

Dependent variable: GACENAPH
Factors:
        COND
        FUEL
        MODE

Number of complete cases: 91
```

Scatterplot by Level Code

Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for GACENAPH - Type III Sums of Squares
--------------------------------------------------------------------------------
Source                  Sum of Squares    Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:COND                      361412.0      2       180706.0     16.84    0.0000
 B:FUEL                     3.59924E6      4       899810.0     83.86    0.0000
```

F-69

C:MODE	45.4556	1	45.4556	0.00	0.9483
INTERACTIONS					
AB	381971.0	8	47746.4	4.45	0.0003
AC	973.496	2	486.748	0.05	0.9557
BC	41481.9	4	10370.5	0.97	0.4325
ABC	5332.37	8	666.546	0.06	0.9998
RESIDUAL	654523.0	61	10729.9		

| TOTAL (CORRECTED) | 5.04131E6 | 90 | | | |

All F-ratios are based on the residual mean square error.

CONCLUSION: Statistically significant differences in the average acenaphthylene
among the pilot conditions, fuels, and pilot condition*fuel interaction.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average acenaphthylene for the Pilot A and Pilot B conditions
are not significantly different from one another, but are significantly different
from the LPP conditions.

Means and 95% Tukey HSD Intervals

CONCLUSION: There are several distinct fuel groupings with respect to the average
acenaphthalene. The average acenaphthalene for the DF-2 fuel is significantly
different from the remaining four fuels. The CA fuel is significantly different
than the ADMM15 and FT-100 fuels, but not significantly different than the
ALS fuel.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average acenaphthalene for modes 10 and 11 are not
significantly different from one another.

Multiple Range Tests for GACENAPH by COND

Method: 95.0 percent Tukey HSD
COND	Count	LS Mean	Homogeneous Groups

LPP	31	138.991	X
PilotB	30	259.347	X
PilotA	30	282.307	X

Contrast	Difference	+/- Limits

LPP - PilotA	*-143.316	63.7331
LPP - PilotB	*-120.355	63.7331
PilotA - PilotB	22.9605	64.2534
----
* denotes a statistically significant difference.

Multiple Range Tests for GACENAPH by FUEL

Method: 95.0 percent Tukey HSD
FUEL	Count	LS Mean	Homogeneous Groups

FT-100	18	52.0377	X
ADMM15	18	89.6773	X
ALS	19	147.393	XX
CA	18	239.183	X
DF-2	18	606.118	X

Contrast	Difference	+/- Limits

ADMM15 - ALS	-57.7156	95.7766
ADMM15 - CA	*-149.505	97.0622
ADMM15 - DF-2	*-516.441	97.0622
ADMM15 - FT-100	37.6396	97.0622
ALS - CA	-91.7897	95.7766
ALS - DF-2	*-458.725	95.7766
ALS - FT-100	95.3552	95.7766
CA - DF-2	*-366.935	97.0622
CA - FT-100	*187.145	97.0622
DF-2 - FT-100	*554.08	97.0622
----
* denotes a statistically significant difference.

Multiple Range Tests for GACENAPH by MODE

```
Method: 95.0 percent Tukey HSD
MODE            Count      LS Mean          Homogeneous Groups
---------------------------------------------------------------------------
11               45        226.174              X
10               46        227.589              X
---------------------------------------------------------------------------
Contrast                                    Difference        +/-  Limits
---------------------------------------------------------------------------
10 - 11                                      1.41542          43.4292
---------------------------------------------------------------------------
* denotes a statistically significant difference.
```

Interaction and 95% Tukey HSD Intervals

CONCLUSION: The trend in the average acenaphthalene across the pilot conditions
for the ADMM15, ALS, CA, and FT-100 fuels is significantly different than the
trend for the DF-2 fuel. Whereas, the trends in the ADMM15, ALS, CA, and FT-100
fuels are relatively constant, the DF-2 fuel shows an increase in the
average acenaphthalene from the LPP to the Pilot A and Pilot B conditions.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average acenaphthalene
among the pilot condition and mode combinations.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average acenaphthalene
among the fuel and mode combinations.

```
Multifactor ANOVA - Acenaphthene (µg/kW-hr)    Gaseous PAH
                    Three Pilot Conditions    Modes 10 and 11

Analysis Summary

Dependent variable: ACENAPTH
Factors:
        COND
        FUEL
        MODE

Number of complete cases: 91
```

Scatterplot by Level Code

Acenapthene vs Pilot Condition (LPP, PilotA, PilotB)

Scatterplot by Level Code

Acenapthene vs Fuel (ADMM15, ALS, CA, DF-2, FT-100)

Scatterplot by Level Code

Acenapthene vs Mode (10, 11)

```
Analysis of Variance for ACENAPTH - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:COND                  75508.4      2       37754.2      2.40    0.0989
 B:FUEL                  6.6314E6     4      1.65785E6    105.57    0.0000
 C:MODE                  13127.1      1       13127.1      0.84    0.3642
```

F-74

```
INTERACTIONS
 AB                          170019.0       8        21252.3        1.35    0.2353
 AC                          112.754        2        56.3768        0.00    0.9964
 BC                          133598.0       4        33399.5        2.13    0.0883
 ABC                         15184.1        8        1898.01        0.12    0.9982

RESIDUAL                     957924.0       61       15703.7
-------------------------------------------------------------------------------
TOTAL (CORRECTED)            8.00012E6      90
-------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.
```

```
CONCLUSION:  Statistically significant differences in the average acenaphthene
among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average acenaphthene for the three pilot conditions are not
significantly different from one another.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  There are several distinct fuel groupings with respect to the
average acenaphthene.  The average acenaphthene for the DF-2 fuel is significantly
different than the remaining four fuels.  Also, the CA fuel is significantly different
than the FT-100 fuel, but not significantly different than the ADMM15 or ALS fuels.
```

Means and 95% Tukey HSD Intervals

CONCLUSION: The average acenaphthene for modes 10 and 11 are not significantly
different from one another.

Multiple Range Tests for ACENAPTH by COND

Method: 95.0 percent Tukey HSD
COND   Count   LS Mean   Homogeneous Groups

LPP   31   148.117   X
PilotA   30   203.4   X
PilotB   30   213.462   X

Contrast   Difference   +/- Limits

LPP - PilotA   -55.2838   77.1025
LPP - PilotB   -65.3452   77.1025
PilotA - PilotB   -10.0614   77.7319
----
* denotes a statistically significant difference.

Multiple Range Tests for ACENAPTH by FUEL

Method: 95.0 percent Tukey HSD
FUEL   Count   LS Mean   Homogeneous Groups

FT-100   18   7.88772   X
ADMM15   18   24.8077   XX
ALS   19   48.2916   XX
CA   18   137.46   X
DF-2   18   723.184   X

Contrast   Difference   +/- Limits

ADMM15 - ALS   -23.4839   115.868
ADMM15 - CA   -112.653   117.423
ADMM15 - DF-2   *-698.376   117.423
ADMM15 - FT-100   16.9199   117.423
ALS - CA   -89.1687   115.868
ALS - DF-2   *-674.892   115.868
ALS - FT-100   40.4039   115.868
CA - DF-2   *-585.723   117.423
CA - FT-100   *129.573   117.423
DF-2 - FT-100   *715.296   117.423
----
* denotes a statistically significant difference.

Multiple Range Tests for ACENAPTH by MODE

Method: 95.0 percent Tukey HSD

F-76

```
MODE            Count     LS Mean         Homogeneous Groups
-----------------------------------------------------------------------------
10              46        176.3                   X
11              45        200.353                 X
-----------------------------------------------------------------------------
Contrast                                  Difference         +/-  Limits
-----------------------------------------------------------------------------
10 - 11                                   -24.0534           52.5394
-----------------------------------------------------------------------------
```
* denotes a statistically significant difference.

Interactions and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average acenaphthene among the fuel and pilot condition combinations.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average acenaphthene among the mode and pilot condition combinations.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average acenaphthene among the fuel and mode combinations.

F-77

```
Multifactor ANOVA - Fluorene (µg/kW-hr)   Gaseous PAH
                  Three Pilot Conditions   Modes 10 and 11

Analysis Summary

Dependent variable: GFLUOREN
Factors:
        COND
        FUEL
        MODE

Number of complete cases: 91
```

Scatterplot by Level Code

Pilot Condition

Scatterplot by Level Code

Fuel

Scatterplot by Level Code

Mode

```
Analysis of Variance for GFLUOREN - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares   Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:COND                  102193.0     2       51096.4       1.06      0.3515
 B:FUEL                 1.72763E7     4     4.31907E6       89.92      0.0000
 C:MODE                  42733.1      1       42733.1       0.89      0.3493
```

```
INTERACTIONS
 AB                          373258.0        8         46657.3      0.97     0.4668
 AC                            24.422        2          12.211      0.00     0.9997
 BC                          336153.0        4         84038.3      1.75     0.1508
 ABC                          18556.1        8         2319.51      0.05     0.9999

RESIDUAL                     2.93008E6       61         48034.1
------------------------------------------------------------------------------
TOTAL (CORRECTED)            2.10864E7       90
------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.


CONCLUSION:  Statistically significant differences in the average fluorene among the
fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average fluorene for the three pilot conditions are not
significantly different from one another.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average fluorene for the DF-2 fuel is significantly different
than the remaining four fuels.
```

Means and 95% Tukey HSD Intervals

CONCLUSION: The average fluorene for modes 10 and 11 are not significantly
different from one another.

Multiple Range Tests for GFLUOREN by COND

Method: 95.0 percent Tukey HSD
COND   Count   LS Mean   Homogeneous Groups

LPP   31   242.329   X
PilotA   30   292.421   X
PilotB   30   323.542   X

Contrast   Difference   +/- Limits

LPP - PilotA   -50.0916   134.847
LPP - PilotB   -81.2126   134.847
PilotA - PilotB   -31.121   135.948
----
* denotes a statistically significant difference.

Multiple Range Tests for GFLUOREN by FUEL

Method: 95.0 percent Tukey HSD
FUEL   Count   LS Mean   Homogeneous Groups

FT-100   18   14.2477   X
ADMM15   18   21.5123   X
ALS   19   50.0833   X
CA   18   193.028   X
DF-2   18   1151.61   X

Contrast   Difference   +/- Limits

ADMM15 - ALS   -28.5711   202.645
ADMM15 - CA   -171.515   205.366
ADMM15 - DF-2   *-1130.1   205.366
ADMM15 - FT-100   7.26459   205.366
ALS - CA   -142.944   202.645
ALS - DF-2   *-1101.53   202.645
ALS - FT-100   35.8357   202.645
CA - DF-2   *-958.587   205.366
CA - FT-100   178.78   205.366
DF-2 - FT-100   *1137.37   205.366
----
* denotes a statistically significant difference.

Multiple Range Tests for GFLUOREN by MODE

F-80

```
Method: 95.0 percent Tukey HSD
MODE          Count     LS Mean        Homogeneous Groups
-------------------------------------------------------------------------------
10            46        264.398        X
11            45        307.796        X
-------------------------------------------------------------------------------
Contrast                              Difference       +/-  Limits
-------------------------------------------------------------------------------
10 - 11                               -43.3984         91.8882
-------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

Interactions and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average fluorene among
the fuel and pilot condition combinations.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average fluorene among
the pilot condition and mode combinations.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average fluorene among
the fuel and mode combinations.

F-81

```
Multifactor ANOVA - Phenanthrene (micro g/kW-hr)   Gaseous PAH
                    Three Pilot Conditions   Modes 10 and 11
Analysis Summary

Dependent variable: GPHENANT
Factors:
        COND
        FUEL
        MODE

Number of complete cases: 91
```

Scatterplot by Level Code

Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for GPHENANT - Type III Sums of Squares
--------------------------------------------------------------------------------
Source                Sum of Squares   Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:COND                    550944.0     2       275472.0       2.63     0.0801
 B:FUEL                   4.09606E7     4      1.02401E7      97.83     0.0000
 C:MODE                     15030.7     1        15030.7       0.14     0.7061
```

```
INTERACTIONS
  AB                        1.77444E6      8        221804.0    2.12    0.0474
  AC                          22259.4      2         11129.7    0.11    0.8993
  BC                         828870.0      4        207218.0    1.98    0.1089
  ABC                        321701.0      8         40212.6    0.38    0.9250

RESIDUAL                     6.38527E6     61        104676.0
-------------------------------------------------------------------------------
TOTAL (CORRECTED)            5.08462E7     90
-------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.
```

CONCLUSION: Statistically significant differences in the average phenanthrene
among the fuels and pilot condition*fuel interaction.

Means and 95% Tukey HSD Intervals

CONCLUSION: No significant differences in the average phenanthrene among the
three pilot conditions.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average phenanthrene for the DF-2 and CA fuels is significantly
different than the remaining three fuels. The average phenanthrene for the ADMM15,
ALS, and FT-100 fuels are not significantly different from one another.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average phenanthrene for modes 10 and 11 are not significantly
different from one another.

Multiple Range Tests for GPHENANT by COND

Method: 95.0 percent Tukey HSD
COND   Count   LS Mean   Homogeneous Groups

LPP   31   418.379   X
PilotB   30   545.882   X
PilotA   30   604.351   X

Contrast   Difference   +/- Limits

LPP - PilotA   -185.973   199.064
LPP - PilotB   -127.503   199.064
PilotA - PilotB   58.4694   200.689
----
* denotes a statistically significant difference.

Multiple Range Tests for GPHENANT by FUEL

Method: 95.0 percent Tukey HSD
FUEL   Count   LS Mean   Homogeneous Groups

FT-100   18   29.2336   X
ADMM15   18   43.1629   X
ALS   19   169.183   X
CA   18   557.58   X
DF-2   18   1815.19   X

Contrast   Difference   +/- Limits

ADMM15 - ALS   -126.02   299.148
ADMM15 - CA   *-514.417   303.164
ADMM15 - DF-2   *-1772.03   303.164
ADMM15 - FT-100   13.9293   303.164
ALS - CA   *-388.397   299.148
ALS - DF-2   *-1646.01   299.148
ALS - FT-100   139.949   299.148
CA - DF-2   *-1257.61   303.164
CA - FT-100   *528.346   303.164
DF-2 - FT-100   *1785.96   303.164
----
* denotes a statistically significant difference.

Multiple Range Tests for GPHENANT by MODE

Method: 95.0 percent Tukey HSD
MODE   Count   LS Mean   Homogeneous Groups
----
10   46   510.002   X
11   45   535.74   X

Contrast   Difference   +/- Limits
----
10 - 11   -25.7384   135.647
----
* denotes a statistically significant difference.

F-84

Interaction and 95% Tukey HSD Intervals

CONCLUSION: The trend in the average phenanthrene across the pilot conditions
for the ADMM15, ALS, and FT-100 fuels is signficantly different than the trend
for the DF-2 and CA fuels. Whereas, the trends in the ADMM15, ALS, and FT-100
fuels are relatively constant, the DF-2 fuel shows an increase in the average
phenanthrene from the LPP to the Pilot A and Pilot B conditions. Also, the CA
fuel demonstrates an increase in the Pilot A condition.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average phenanthrene
among the pilot conditions and mode combinations.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average phenanthrene
among the fuel and mode combinations.

F-85

```
Multifactor ANOVA - Anthracene (micro g/kW-hr)   Gaseous PAH
                Three Pilot Conditions  Modes 10 and 11

Analysis Summary

Dependent variable: GANTHR
Factors:
        COND
        FUEL
        MODE

Number of complete cases: 91
```

Scatterplot by Level Code

Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for GANTHR - Type III Sums of Squares
--------------------------------------------------------------------------------
Source                Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:COND                   160.338       2        80.1692      0.81    0.4497
 B:FUEL                 38760.6         4      9690.15       97.88    0.0000
 C:MODE                    24.9234      1        24.9234      0.25    0.6176

INTERACTIONS
```

F-86

```
AB                          1755.86      8     219.482     2.22    0.0382
AC                          4.39302      2     2.19651     0.02    0.9781
BC                          209.706      4     52.4265     0.53    0.7144
ABC                         73.6331      8     9.20413     0.09    0.9993

RESIDUAL                    6038.83     61     98.9973
--------------------------------------------------------------------------------
TOTAL (CORRECTED)           47005.4     90
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.
```

CONCLUSION: Statistically significant differences in the average anthracene among
the fuels and pilot condition*fuel interaction.

Means and 95% Tukey HSD Intervals

CONCLUSION: No significant differences in the average anthracene among the three
pilot conditions.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average anthracene for the DF-2 and CA fuels is significantly
different than the remaining three fuels. The average anthracene for the
ADMM15, ALS, and FT-100 fuels are not significantly different from one another.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average anthracene for modes 10 and 11 are not significantly different from one another.

Multiple Range Tests for GANTHR by COND

Method: 95.0 percent Tukey HSD
COND   Count   LS Mean   Homogeneous Groups

LPP   31   14.8053   X
PilotA   30   16.3714   X
PilotB   30   18.054   X

Contrast   Difference   +/- Limits

LPP - PilotA   -1.56609   6.1218
LPP - PilotB   -3.24865   6.1218
PilotA - PilotB   -1.68256   6.17178
----
* denotes a statistically significant difference.

Multiple Range Tests for GANTHR by FUEL

Method: 95.0 percent Tukey HSD
FUEL   Count   LS Mean   Homogeneous Groups

FT-100   18   1.14399   X
ADMM15   18   2.71767   X
ALS   19   4.56641   X
CA   18   17.3941   X
DF-2   18   56.229   X

Contrast   Difference   +/- Limits

ADMM15 - ALS   -1.84874   9.19969
ADMM15 - CA   *-14.6765   9.32318
ADMM15 - DF-2   *-53.5113   9.32318
ADMM15 - FT-100   1.57367   9.32318
ALS - CA   *-12.8277   9.19969
ALS - DF-2   *-51.6626   9.19969
ALS - FT-100   3.42241   9.19969
CA - DF-2   *-38.8348   9.32318
CA - FT-100   *16.2501   9.32318
DF-2 - FT-100   *55.085   9.32318
----
* denotes a statistically significant difference.

Multiple Range Tests for GANTHR by MODE

F-88

```
Method: 95.0 percent Tukey HSD
MODE          Count    LS Mean      Homogeneous Groups
-------------------------------------------------------------------------------
11            45       15.8862          X
10            46       16.9343          X
-------------------------------------------------------------------------------
Contrast                               Difference       +/-  Limits
-------------------------------------------------------------------------------
10 - 11                                1.04808          4.17154
-------------------------------------------------------------------------------
```
* denotes a statistically significant difference.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: The trend in the average anthracene across the pilot conditions
for the ADMM15, ALS, and FT-100 fuels is significantly different than the trend
for the DF-2 and CA fuels. Whereas, the trends in the ADMM15, ALS, and FT-100
fuels are relatively constant, the DF-2 fuel demonstrates a slight increase from
the LPP to the Pilot B condition. Also, the CA fuel shows an increase in the
Pilot A condition.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average anthracene
among the pilot condition and mode combinations.

F-89

Interaction and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average anthracene among the fuel and mode combinations.

```
Multifactor ANOVA - Fluoranthene (μg/kW-hr)    Gaseous PAH
                Three Pilot Conditions    Modes 10 and 11

Analysis Summary

Dependent variable: GFLUORAN
Factors:
        COND
        FUEL
        MODE

Number of complete cases: 91
```

Scatterplot by Level Code

Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for GFLUORAN - Type III Sums of Squares
--------------------------------------------------------------------------------
Source                Sum of Squares    Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:COND                      158.876     2         79.438      15.84     0.0000
```

F-91

```
 B:FUEL                        250.699         4           62.6747       12.50     0.0000
 C:MODE                        6.45211         1           6.45211        1.29     0.2612

INTERACTIONS
 AB                            332.067         8           41.5084        8.28     0.0000
 AC                            3.93472         2           1.96736        0.39     0.6772
 BC                            5.44184         4           1.36046        0.27     0.8954
 ABC                           6.66393         8           0.832991       0.17     0.9946

RESIDUAL                       305.959        61           5.01572
--------------------------------------------------------------------------------
TOTAL (CORRECTED)              1071.07        90
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.
```

CONCLUSION: Statistically significant differences in the average fluoranthene
among the pilot conditions, fuels, and pilot condition*fuel interaction.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average fluoranthene for the Pilot A and Pilot B conditions
are not significantly different from one another, but are significantly different
from the LPP conditions.

Means and 95% Tukey HSD Intervals

CONCLUSION: There are several distinct fuel groupings with respect to the
average fluoranthene. The average fluoranthene for the DF-2 fuel is significantly
different from the remaining four fuels. The CA fuel is significantly different
than the ADMM15 fuel, but not significantly different than the ALS or
FT-100 fuels.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average fluoranthene for modes 10 and 11 are not significantly
different from one another.

Multiple Range Tests for GFLUORAN by COND

Method: 95.0 percent Tukey HSD
COND   Count   LS Mean   Homogeneous Groups

PilotB   30   1.64916   X
PilotA   30   2.45675   X
LPP   31   4.76043   X

Contrast   Difference   +/- Limits

LPP - PilotA   *2.30368   1.37795
LPP - PilotB   *3.11127   1.37795
PilotA - PilotB   0.807583   1.3892
----
* denotes a statistically significant difference.

Multiple Range Tests for GFLUORAN by FUEL

Method: 95.0 percent Tukey HSD
FUEL   Count   LS Mean   Homogeneous Groups

ADMM15   18   1.31817   X
FT-100   18   1.58958   XX
ALS   19   2.34355   XX
CA   18   3.65466   X
DF-2   18   5.87127   X

Contrast   Difference   +/- Limits

ADMM15 - ALS   -1.02538   2.07075
ADMM15 - CA   *-2.33649   2.09855
ADMM15 - DF-2   *-4.55309   2.09855
ADMM15 - FT-100   -0.271407   2.09855
ALS - CA   -1.31111   2.07075
ALS - DF-2   *-3.52771   2.07075
ALS - FT-100   0.753972   2.07075
CA - DF-2   *-2.21661   2.09855
CA - FT-100   2.06508   2.09855
DF-2 - FT-100   *4.28169   2.09855
----
* denotes a statistically significant difference.

Multiple Range Tests for GFLUORAN by MODE

Method: 95.0 percent Tukey HSD

F-93

```
MODE            Count    LS Mean        Homogeneous Groups
------------------------------------------------------------------------------
11              45       2.68881        X
10              46       3.22208        X
------------------------------------------------------------------------------
Contrast                                Difference       +/-  Limits
------------------------------------------------------------------------------
10 - 11                                 0.533264         0.938969
------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: The trend in the average fluoranthene across the pilot conditions
for the ADMM15, ALS, CA, and FT-100 fuels is significantly different than the
trend for the DF-2 fuel. Whereas, the trends in the ADMM15, ALS, CA, and FT-100
fuels are relatively constant, the DF-2 fuel shows an increase in the average
fluoranthene at the LPP condition.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average fluoranthene
among the pilot condition and mode combinations.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average fluoranthene
among the fuel and mode combinations.

```
Multifactor ANOVA - Pyrene (µg/kW-hr)   Gaseous PAH
                    Three Pilot Conditions   Modes 10 and 11

Analysis Summary

Dependent variable: GPYRENE
Factors:
        COND
        FUEL
        MODE

Number of complete cases: 91
```

Scatterplot by Level Code

Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for GPYRENE - Type III Sums of Squares
--------------------------------------------------------------------------------
Source                Sum of Squares    Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:COND                    215.921        2      107.961       12.83     0.0000
 B:FUEL                    522.511        4      130.628       15.52     0.0000
 C:MODE                    1.64188        1      1.64188        0.20     0.6603
```

```
INTERACTIONS
 AB                              635.162       8     79.3952      9.43    0.0000
 AC                              1.44397       2     0.721987     0.09    0.9179
 BC                              7.72609       4     1.93152      0.23    0.9208
 ABC                             3.61495       8     0.451869     0.05    0.9999

RESIDUAL                         513.495      61     8.41795
--------------------------------------------------------------------------------
TOTAL (CORRECTED)                1898.24      90
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.


CONCLUSION:  Statistically significant differences in the average pyrene among the
pilot conditions, fuels, and pilot condition*fuel interaction.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average pyrene for the Pilot A and Pilot B conditions are
not significantly different from one another, but are significantly different
from the LPP condition.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average pyrene for the DF-2 fuel is significantly different
than the other four fuels.  The average pyrene among the ADMM15, ALS, CA, and
FT-100 fuels are not significantly different from one another.
```

Means and 95% Tukey HSD Intervals

CONCLUSION: The average pyrene for modes 10 and 11 are not significantly
different from one another.

Multiple Range Tests for GPYRENE by COND

Method: 95.0 percent Tukey HSD
COND   Count   LS Mean   Homogeneous Groups

PilotB   30   1.6312   X
PilotA   30   2.39782   X
LPP   31   5.20555   X

Contrast   Difference   +/- Limits

LPP - PilotA   *2.80773   1.78513
LPP - PilotB   *3.57434   1.78513
PilotA - PilotB   0.766618   1.79971
----
* denotes a statistically significant difference.

Multiple Range Tests for GPYRENE by FUEL

Method: 95.0 percent Tukey HSD
FUEL   Count   LS Mean   Homogeneous Groups

ADMM15   18   1.08101   X
FT-100   18   1.1652   X
ALS   19   2.17365   X
CA   18   3.37177   X
DF-2   18   7.59931   X

Contrast   Difference   +/- Limits

ADMM15 - ALS   -1.09263   2.68265
ADMM15 - CA   -2.29075   2.71867
ADMM15 - DF-2   *-6.51829   2.71867
ADMM15 - FT-100   -0.0841837   2.71867
ALS - CA   -1.19812   2.68265
ALS - DF-2   *-5.42566   2.68265
ALS - FT-100   1.00845   2.68265
CA - DF-2   *-4.22754   2.71867
CA - FT-100   2.20657   2.71867
DF-2 - FT-100   *6.43411   2.71867
----
* denotes a statistically significant difference.

Multiple Range Tests for GPYRENE by MODE

Method: 95.0 percent Tukey HSD

F-97

```
MODE            Count    LS Mean        Homogeneous Groups
-----------------------------------------------------------------------------
11              45       2.94368        X
10              46       3.21269        X
-----------------------------------------------------------------------------
Contrast                                Difference      +/-  Limits
-----------------------------------------------------------------------------
10 - 11                                 0.269006        1.21643
-----------------------------------------------------------------------------
```
* denotes a statistically significant difference.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: The trend in the average pyrene across the pilot conditions
for the ADMM15, ALS, CA, and FT-100 fuels is significantly different than the
trend for the DF-2 fuel. Whereas, the trends in the ADMM15, ALS, CA, and
FT-100 fuels are relatively constant, the DF-2 fuel shows an increase in the
average pyrene at the LPP condition.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average pyrene
among the pilot condition and mode combinations.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average pyrene among
the fuel and mode combinations.

```
Multifactor ANOVA - Naphthalene (µg/kW-hr)    Soluble PAH
                  Three Pilot Conditions    Modes 10 and 11

Analysis Summary

Dependent variable: naphth
Factors:
        COND
        FUEL
        MODE

Number of complete cases: 91
```

Scatterplot by Level Code

Pilot Condition

Scatterplot by Level Code

Fuel

Scatterplot by Level Code

Mode

```
Analysis of Variance for naphth - Type III Sums of Squares
--------------------------------------------------------------------------------
Source                Sum of Squares    Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:COND                      183.888     2         91.944       0.49     0.6153
 B:FUEL                      4980.21     4        1245.05       6.63     0.0002
 C:MODE                      2252.95     1        2252.95      12.00     0.0010
```

F-99

```
INTERACTIONS
 AB                             2923.31      8        365.414     1.95    0.0691
 AC                             180.828      2        90.4142     0.48    0.6202
 BC                             830.073      4        207.518     1.10    0.3625
 ABC                            1268.55      8        158.569     0.84    0.5678

RESIDUAL                        11456.5      61       187.812
--------------------------------------------------------------------------------
TOTAL (CORRECTED)               24216.7      90
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.
```

CONCLUSION: Statistically significant differences in the average naphthalene
among the fuels and modes.

Means and 95% Tukey HSD Intervals

CONCLUSION: No statistically significant difference in the average naphthalene
across the pilot conditions.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average naphthalene for the CA fuel is significantly different
from the ADMM15, ALS and FT-100 fuels.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average naphthalene for modes 10 and 11 are significantly different
from one another.

Multiple Range Tests for naphth by COND

Method: 95.0 percent Tukey HSD
COND   Count   LS Mean   Homogeneous Groups

PilotB   30   37.731   X
LPP   31   39.5631   X
PilotA   30   41.231   X

Contrast   Difference   +/- Limits

LPP - PilotA   -1.66798   8.43198
LPP - PilotB   1.83203   8.43198
PilotA - PilotB   3.50001   8.50081
----
* denotes a statistically significant difference.

Multiple Range Tests for naphth by FUEL

Method: 95.0 percent Tukey HSD
FUEL   Count   LS Mean   Homogeneous Groups

ADMM15   18   29.574   X
ALS   19   36.6896   X
FT-100   18   37.1125   X
DF-2   18   42.1224   XX
CA   18   52.0434   X

Contrast   Difference   +/- Limits

ADMM15 - ALS   -7.11555   12.6714
ADMM15 - CA   *-22.4693   12.8415
ADMM15 - DF-2   -12.5483   12.8415
ADMM15 - FT-100   -7.53845   12.8415
ALS - CA   *-15.3538   12.6714
ALS - DF-2   -5.4328   12.6714
ALS - FT-100   -0.422909   12.6714
CA - DF-2   9.92098   12.8415
CA - FT-100   *14.9309   12.8415
DF-2 - FT-100   5.00989   12.8415
----
* denotes a statistically significant difference.

Multiple Range Tests for naphth by MODE

Method: 95.0 percent Tukey HSD
MODE   Count   LS Mean   Homogeneous Groups
----
11   45   34.526   X
10   46   44.4908   X

Contrast   Difference   +/- Limits
----
10 - 11   *9.96478   5.74574
----
* denotes a statistically significant difference.

F-101

Interaction and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average naphthalene among the fuel and pilot condition combinations.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average naphthalene among the mode and pilot condition combinations.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average naphthalene among the mode and fuel combinations.

```
Multifactor ANOVA - Acenaphthylene (µg/kW-hr)   Soluble PAH
                   Three Pilot Conditions   Modes 10 and 11

Analysis Summary

Dependent variable: acenaph
Factors:
        COND
        FUEL
        MODE

Number of complete cases: 91
```

Scatterplot by Level Code

Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for acenaph - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares    Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:COND                 10.4983        2       5.24915       28.01     0.0000
 B:FUEL                 4.52142        4       1.13036        6.03     0.0004
 C:MODE                 0.345356       1       0.345356       1.84     0.1796
```

```
INTERACTIONS
 AB                          9.86361       8        1.23295       6.58      0.0000
 AC                          2.57901       2        1.2895        6.88      0.0020
 BC                          4.03223       4        1.00806       5.38      0.0009
 ABC                         4.73901       8        0.592376      3.16      0.0046

RESIDUAL                    11.4328       61        0.187423
-------------------------------------------------------------------------------
TOTAL (CORRECTED)           48.2402       90
-------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.
```

CONCLUSION: Statistically significant differences in the average acenaphthylene
among the pilot conditions, fuels, two-factor interactions, and the three-factor
interaction fuel*mode*pilot condition.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average acenaphthylene for the LPP and Pilot A conditions are
not significantly different from one another, but are significantly different
from the Pilot B condition.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average acenaphthylene for the ADMM15 fuel is significantly
different from the FT-100 fuel. The CA, DF-2, and ALS fuels are not significantly
different from either the ADMM15 or the FT-100 fuels with respect to the
average acenaphthylene.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average acenaphthylene for modes 10 and 11 are not significantly different from one another.


Multiple Range Tests for acenaph by COND


```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
COND            Count     LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
LPP             31        0.709427         X
PilotA          30        0.936941         X
PilotB          30        1.51712           X
--------------------------------------------------------------------------------
Contrast                                   Difference        +/-  Limits
--------------------------------------------------------------------------------
LPP - PilotA                                -0.227514         0.266366
LPP - PilotB                               *-0.807697         0.266366
PilotA - PilotB                            *-0.580183         0.268541
--------------------------------------------------------------------------------
```
* denotes a statistically significant difference.

Multiple Range Tests for acenaph by FUEL


```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
FUEL            Count     LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
ADMM15          18        0.693977         X
CA              18        1.03841          XX
DF-2            18        1.06802          XX
ALS             19        1.07044          XX
FT-100          18        1.40164           X
--------------------------------------------------------------------------------
Contrast                                   Difference        +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                                -0.376466         0.400288
ADMM15 - CA                                 -0.344432         0.405662
ADMM15 - DF-2                               -0.374041         0.405662
ADMM15 - FT-100                            *-0.707664         0.405662
ALS - CA                                     0.0320337        0.400288
ALS - DF-2                                   0.00242547       0.400288
ALS - FT-100                                -0.331198         0.400288
CA - DF-2                                    -0.0296082       0.405662
CA - FT-100                                 -0.363231         0.405662
DF-2 - FT-100                               -0.333623         0.405662
--------------------------------------------------------------------------------
```
* denotes a statistically significant difference.

```
Multiple Range Tests for acenaph by MODE

--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
MODE            Count       LS Mean         Homogeneous Groups
--------------------------------------------------------------------------------
10              46          0.99281         X
11              45          1.11618         X
--------------------------------------------------------------------------------
Contrast                                    Difference          +/-  Limits
--------------------------------------------------------------------------------
10 - 11                                     -0.123374           0.181508
--------------------------------------------------------------------------------
* denotes a statistically significant difference.
```

Interaction and 95% Tukey HSD Intervals

CONCLUSION: The trend in the average acenaphthylene across the pilot conditions
for the FT-100 fuel is significantly different than the trends for the
remaining four fuels. The average acenaphthylene for the FT-100 fuel at the
Pilot B condition is significantly different than the other four fuels, but not at
the LPP or the Pilot A condition.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: The average acenaphthylene at the Pilot B condition for Mode 11
is significantly different than Mode 10. There is no significant difference
in the average acenaphthylene between the two modes at the LPP or Pilot A
conditions.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: The trend in the average acenaphthylene across the two modes
is different at the FT-100 fuel. There does not appear to be differences
in the average acenaphthylene for the two modes at the ADMM15, ALS, CA, or
DF-2 fuels.

```
Multifactor ANOVA - Acenaphthene (µg/kW-hr)    Soluble PAH
                  Three Pilot Conditions    Modees 10 and 11

Analysis Summary

Dependent variable: acenapth
Factors:
        COND
        FUEL
        MODE

Number of complete cases: 91
```

Scatterplot by Level Code

Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for acenapth - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:COND                 26.9198       2       13.4599      3.31     0.0431
 B:FUEL                 53.0297       4       13.2574      3.26     0.0172
 C:MODE                 47.9888       1       47.9888     11.81     0.0011
```

F-108

```
INTERACTIONS
 AB                              89.368        8        11.171      2.75    0.0117
 AC                             4.11053        2       2.05526      0.51    0.6056
 BC                             15.9586        4       3.98965      0.98    0.4243
 ABC                            12.8542        8       1.60677      0.40    0.9189

RESIDUAL                        247.905       61       4.06401
--------------------------------------------------------------------------------
TOTAL (CORRECTED)               498.837       90
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.


CONCLUSION:  Statistically significant differences in the average acenaphthene among
the pilot conditions, fuels, modes, and pilot condition*fuel interaction.
```

Means and 95% Tukey HSD Intervals

CONCLUSION: The average acenaphthene for the LPP condition is significantly different
than the Pilot A condition. The average acenaphthene for the Pilot B condition
is not significantly different from with either the LPP or the Pilot A conditions.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average acenaphthene for the CA fuel is significantly different
from the ADMM15 and the FT-100 fuels.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average acenaphthene for modes 10 and 11 are significantly

F-109

different from one another.

Multiple Range Tests for acenapth by COND


```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
COND            Count      LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
LPP             31         5.03969            X
PilotB          30         5.98379            XX
PilotA          30         6.32198             X
--------------------------------------------------------------------------------
Contrast                                   Difference        +/-  Limits
--------------------------------------------------------------------------------
LPP - PilotA                               *-1.28229          1.24035
LPP - PilotB                               -0.944107          1.24035
PilotA - PilotB                            0.338184           1.25048
--------------------------------------------------------------------------------
```
* denotes a statistically significant difference.

Multiple Range Tests for acenapth by FUEL


```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
FUEL            Count      LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
FT-100          18         4.99828            X
ADMM15          18         5.15909            X
DF-2            18         5.47325            XX
ALS             19         6.20856            XX
CA              18         7.06992             X
--------------------------------------------------------------------------------
Contrast                                   Difference        +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                               -1.04948           1.86397
ADMM15 - CA                                *-1.91083          1.88899
ADMM15 - DF-2                              -0.314163          1.88899
ADMM15 - FT-100                            0.160804           1.88899
ALS - CA                                   -0.86135           1.86397
ALS - DF-2                                 0.735315           1.86397
ALS - FT-100                               1.21028            1.86397
CA - DF-2                                  1.59667            1.88899
CA - FT-100                                *2.07163           1.88899
DF-2 - FT-100                              0.474967           1.88899
--------------------------------------------------------------------------------
```
* denotes a statistically significant difference.

Multiple Range Tests for acenapth by MODE


```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
MODE            Count      LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
11              45         5.05466            X
10              46         6.50898             X
--------------------------------------------------------------------------------
Contrast                                   Difference        +/-  Limits
--------------------------------------------------------------------------------
10 - 11                                    *1.45433           0.845205
--------------------------------------------------------------------------------
```
* denotes a statistically significant difference.

F-110

Interaction and 95% Tukey HSD Intervals

CONCLUSION: The trends in the average acenaphthene for the ALS and CA fuels are significantly different than the DF-2 fuel between the LPP and Pilot A conditions.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average acenaphthene among the pilot condition and mode combinations.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average acenaphthene among the fuel and mode combinations.

F-111

```
Multifactor ANOVA - Fluorene (µg/kW-hr)    Soluble PAH
                   Three Pilot Conditions    Modes 10 and 11

Analysis Summary

Dependent variable: fluorene
Factors:
        COND
        FUEL
        MODE

Number of complete cases: 90
```

Scatterplot by Level Code

X-axis: Pilot Condition (LPP, PilotA, PilotB); Y-axis: Fluorene

Scatterplot by Level Code

X-axis: Fuel (ADMM15, ALS, CA, DF-2, FT-100); Y-axis: Fluorene

Scatterplot by Level Code

X-axis: Mode (10, 11); Y-axis: Fluorene

```
Analysis of Variance for fluorene - Type III Sums of Squares
--------------------------------------------------------------------------------
Source               Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:COND                      55.271    2        27.6355      2.62    0.0808
 B:FUEL                     243.792    4        60.9481      5.79    0.0005
 C:MODE                     101.916    1       101.916       9.68    0.0029
```

F-112

```
INTERACTIONS
 AB                        244.985      8      30.6231     2.91    0.0083
 AC                         13.768      2      6.88402     0.65    0.5237
 BC                        43.3634      4      10.8409     1.03    0.3995
 ABC                       59.6242      8      7.45303     0.71    0.6834

RESIDUAL                   631.743     60      10.5291
-----------------------------------------------------------------------------
TOTAL (CORRECTED)          1426.28     89
-----------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.
```

CONCLUSION: Statistically significant differences in the average fluorene among
the fuels, modes, and pilot condition*fuel interaction.

Means and 95% Tukey HSD Intervals

CONCLUSION: No significant differences in the average fluorene among the pilot
conditions.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average fluorene for the ALS, CA, and DF-2 fuels are significantly
different from the FT-100 fuel, but not significantly different from one another.
Also, the average fluorene for the ALS fuel is signficantly different from the
ADMM15 fuel.

Means and 95% Tukey HSD Intervals

```
CONCLUSION:  The average fluorene for modes 10 and 11 are significantly
different from one another,


Multiple Range Tests for fluorene by COND


-------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
COND            Count      LS Mean          Homogeneous Groups
-------------------------------------------------------------------------------
LPP             30         8.72343          X
PilotA          30         10.2222          X
PilotB          30         10.5328          X
-------------------------------------------------------------------------------
Contrast                                    Difference       +/-  Limits
-------------------------------------------------------------------------------
LPP - PilotA                                -1.4988          2.01361
LPP - PilotB                                -1.8094          2.01361
PilotA - PilotB                             -0.310597        2.01361
-------------------------------------------------------------------------------
* denotes a statistically significant difference.


Multiple Range Tests for fluorene by FUEL


-------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
FUEL            Count      LS Mean          Homogeneous Groups
-------------------------------------------------------------------------------
FT-100          18         7.3756           X
ADMM15          18         8.46579          XX
CA              18         10.6592           XX
DF-2            18         10.7079           XX
ALS             18         11.9224            X
-------------------------------------------------------------------------------
Contrast                                    Difference       +/-  Limits
-------------------------------------------------------------------------------
ADMM15 - ALS                                *-3.45656        3.04205
ADMM15 - CA                                 -2.19339         3.04205
ADMM15 - DF-2                               -2.24208         3.04205
ADMM15 - FT-100                             1.09019          3.04205
ALS - CA                                    1.26317          3.04205
ALS - DF-2                                  1.21448          3.04205
ALS - FT-100                                *4.54675         3.04205
CA - DF-2                                    -0.0486894      3.04205
CA - FT-100                                 *3.28358         3.04205
DF-2 - FT-100                               *3.33227         3.04205
-------------------------------------------------------------------------------
* denotes a statistically significant difference.


Multiple Range Tests for fluorene by MODE


-------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
MODE            Count      LS Mean          Homogeneous Groups
-------------------------------------------------------------------------------
11              44         8.75759          X
10              46         10.8947           X
-------------------------------------------------------------------------------
Contrast                                    Difference       +/-  Limits
-------------------------------------------------------------------------------
10 - 11                                     *2.13714         1.36869
-------------------------------------------------------------------------------
* denotes a statistically significant difference.
```

F-114

Interaction and 95% Tukey HSD Intervals

CONCLUSION: The trend in the average fluorene for the DF-2 fuel is significantly
different than the ALS fuel between the LPP and Pilot A conditions. The CA, ADMM15,
and FT-100 fuels demonstrate similar trends across the pilot conditions with respect
to the average fluorene.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average fluorene among
the pilot condition and mode combinations.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average fluorene among
the fuel and mode combinations.

```
Multifactor ANOVA - Phenanthrene (µg/kW-hr)    Soluble PAH
                  Three Pilot Conditions    Modes 10 and 11

Analysis Summary

Dependent variable: phenanth
Factors:
        COND
        FUEL
        MODE

Number of complete cases: 91
```


Scatterplot by Level Code

Scatterplot by Level Code

Scatterplot by Level Code

```
Analysis of Variance for phenanth - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares    Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:COND                  119680.0      2       59840.1      14.87     0.0000
 B:FUEL                  578014.0      4      144504.0      35.92     0.0000
 C:MODE                  20.9487       1       20.9487       0.01     0.9427
```

F-116

```
INTERACTIONS
 AB                            162582.0         8        20322.8      5.05     0.0001
 AC                            3706.27          2        1853.13      0.46     0.6331
 BC                            10391.8          4        2597.96      0.65     0.6320
 ABC                           7932.45          8        991.556      0.25     0.9799

RESIDUAL                       245398.0        61        4022.92
--------------------------------------------------------------------------------
TOTAL (CORRECTED)              1.13031E6       90
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average phenanthrene
among the pilot conditions, fuels, and pilot condition*fuel interaction.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average phenanthrene for the Pilot A and Pilot B conditions are
not significantly different from one another, but are significantly different from
the LPP condition.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average phenanthrene for the DF-2 fuel is significantly different
than the remaining four fuels.  The average phenanthrene for the ADMM15, FT-100,
Ca, and ALS fuels are not significantly different from one another.
```

F-117

Means and 95% Tukey HSD Intervals

CONCLUSION: There is no significant difference in the average phenanthrene among the two modes.

Multiple Range Tests for phenanth by COND

Method: 95.0 percent Tukey HSD
COND   Count   LS Mean   Homogeneous Groups

LPP   31   58.1416   X
PilotA   30   113.44   X
PilotB   30   145.824   X

Contrast   Difference   +/- Limits

LPP - PilotA   *-55.2985   39.0246
LPP - PilotB   *-87.6821   39.0246
PilotA - PilotB   -32.3835   39.3432
----
* denotes a statistically significant difference.

Multiple Range Tests for phenanth by FUEL

Method: 95.0 percent Tukey HSD
FUEL   Count   LS Mean   Homogeneous Groups

ADMM15   18   46.4785   X
FT-100   18   52.9229   X
CA   18   75.9431   X
ALS   19   90.7957   X
DF-2   18   262.869   X

Contrast   Difference   +/- Limits

ADMM15 - ALS   -44.3172   58.6452
ADMM15 - CA   -29.4646   59.4324
ADMM15 - DF-2   *-216.39   59.4324
ADMM15 - FT-100   -6.44444   59.4324
ALS - CA   14.8526   58.6452
ALS - DF-2   *-172.073   58.6452
ALS - FT-100   37.8727   58.6452
CA - DF-2   *-186.926   59.4324
CA - FT-100   23.0202   59.4324
DF-2 - FT-100   *209.946   59.4324
----
* denotes a statistically significant difference.

Multiple Range Tests for phenanth by MODE

Method: 95.0 percent Tukey HSD

F-118

```
MODE          Count      LS Mean        Homogeneous Groups
---------------------------------------------------------------------
11            45         105.321             X
10            46         106.282             X
---------------------------------------------------------------------
Contrast                                Difference      +/-  Limits
---------------------------------------------------------------------
10 - 11                                 0.960882        26.5923
---------------------------------------------------------------------
* denotes a statistically significant difference.
```

Interaction and 95% Tukey HSD Intervals

CONCLUSION: The trend in the average phenanthrene across the pilot conditions for
the DF-2 fuel is significantly different than the trends for the remaining four
fuels. The average phenanthrene for the DF-2 fuel at the Pilot A and Pilot B
conditions are significantly different than the other four fuels.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average phenanthrene
among the pilot condition and mode combinations.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average phenanthrene
among the fuel and mode combinations.

F-119

```
Multifactor ANOVA - Anthracene (μg/kW-hr)    Soluble PAH
                  Three Pilot Conditions    Modes 10 and 11

Analysis Summary

Dependent variable: anthr
Factors:
        COND
        FUEL
        MODE

Number of complete cases: 91
```

Scatterplot by Level Code

Anthracene vs. Pilot Condition (LPP, PilotA, PilotB)

Scatterplot by Level Code

Anthracene vs. Fuel (ADMM15, ALS, CA, DF-2, FT-100)

Scatterplot by Level Code

Anthracene vs. Mode (10, 11)

```
Analysis of Variance for anthr - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:COND                   194.971     2       97.4855      18.66    0.0000
 B:FUEL                   578.264     4       144.566      27.67    0.0000
 C:MODE                   14.2719     1       14.2719       2.73    0.1035
```

F-120

```
INTERACTIONS
 AB                            292.709       8       36.5887       7.00      0.0000
 AC                            2.55918       2       1.27959       0.24      0.7835
 BC                            89.3981       4       22.3495       4.28      0.0041
 ABC                           102.962       8       12.8702       2.46      0.0221

RESIDUAL                       318.721      61       5.22494
--------------------------------------------------------------------------------
TOTAL (CORRECTED)              1599.78      90
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average anthracene
among the pilot conditions, fuels, pilot condition*fuel interaction,
fuel*mode interaction, and the three-factor interaction.
```


Means and 95% Tukey HSD Intervals

```
CONCLUSION:  The average anthracene for the LPP and Pilot A conditions are
not significantly different from one another, but are significantly different
from the Pilot B condition.
```


Means and 95% Tukey HSD Intervals

```
CONCLUSION:  There are three distinct fuel groupings with respect to the average
anthracene.  The average anthracene for the DF-2 fuel is significantly different
than the remaining four fuels.  The ADMM15 and FT-100 fuels are not significantly
different from one another, but are signficantly different than the remaining three
fuels.  Also, the CA and ALS fuels are not significantly different from one
another, but are significantly different from the remaining fuels.
```

Means and 95% Tukey HSD Intervals

CONCLUSION: There is no significant difference in the average anthracene among
the two modes.

Multiple Range Tests for anthr by COND

Method: 95.0 percent Tukey HSD
COND   Count   LS Mean   Homogeneous Groups

LPP   31   3.02166   X
PilotA   30   3.77928   X
PilotB   30   6.44088   X

Contrast   Difference   +/- Limits

LPP - PilotA   -0.75762   1.4064
LPP - PilotB   *-3.41923   1.4064
PilotA - PilotB   *-2.66161   1.41788
----
* denotes a statistically significant difference.

Multiple Range Tests for anthr by FUEL

Method: 95.0 percent Tukey HSD
FUEL   Count   LS Mean   Homogeneous Groups

ADMM15   18   1.77706   X
FT-100   18   2.04042   X
CA   18   4.50814   X
ALS   19   4.94414   X
DF-2   18   8.79993   X

Contrast   Difference   +/- Limits

ADMM15 - ALS   *-3.16708   2.1135
ADMM15 - CA   *-2.73109   2.14187
ADMM15 - DF-2   *-7.02287   2.14187
ADMM15 - FT-100   -0.263363   2.14187
ALS - CA   0.435995   2.1135
ALS - DF-2   *-3.85579   2.1135
ALS - FT-100   *2.90372   2.1135
CA - DF-2   *-4.29179   2.14187
CA - FT-100   *2.46772   2.14187
DF-2 - FT-100   *6.75951   2.14187
----
* denotes a statistically significant difference.

F-122

```
Multiple Range Tests for anthr by MODE

--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
MODE           Count     LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
11             45        4.01738          X
10             46        4.81049          X
--------------------------------------------------------------------------------
Contrast                                 Difference        +/-  Limits
--------------------------------------------------------------------------------
10 - 11                                  0.793108          0.958353
--------------------------------------------------------------------------------
* denotes a statistically significant difference.
```

Interaction and 95% Tukey HSD Intervals

CONCLUSION: The trends in the average anthracene across the pilot conditions for
the DF-2 and ALS fuels are significantly different than the trends for the
remaining three fuels. The average anthracene for the DF-2 fuel at the Pilot A
and Pilot B conditions are significantly different than the CA, FT-100, and
ADMM15 fuels.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average anthracene
among the pilot condition and mode combinations.

F-123

Interaction and 95% Tukey HSD Intervals

CONCLUSION: The trends in the average anthracene for modes 10 and 11 are
significantly different at the CA fuel. Otherwise, the average anthracene
for the two modes are not significantly different across the remaining
four fuels.

```
Multifactor ANOVA - Fluoranthene (µg/kW-hr)    Soluble PAH
                    Three Pilot Conditions    Modes 10 and 11

Analysis Summary

Dependent variable: fluoran
Factors:
        COND
        FUEL
        MODE

Number of complete cases: 91
```

Scatterplot by Level Code

Fluoranthene vs Pilot Condition (LPP, PilotA, PilotB)

Scatterplot by Level Code

Fluoranthene vs Fuel (ADMM15, ALS, CA, DF-2, FT-100)

Scatterplot by Level Code

Fluoranthene vs Mode (10, 11)

```
Analysis of Variance for fluoran - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares    Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:COND                  2718.83       2       1359.41     14.62    0.0000
 B:FUEL                  14521.4       4       3630.35     39.05    0.0000
 C:MODE                  1346.19       1       1346.19     14.48    0.0003
```

F-125

```
INTERACTIONS
 AB                              3221.95      8         402.744      4.33     0.0004
 AC                              296.078      2         148.039      1.59     0.2118
 BC                              1271.06      4         317.765      3.42     0.0138
 ABC                            1164.98      8         145.623      1.57     0.1539

RESIDUAL                        5671.34     61          92.9727
--------------------------------------------------------------------------------
TOTAL (CORRECTED)              30240.5      90
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.
```

```
CONCLUSION:  Statistically significant differences in the average fluoranthene
among the pilot conditions, fuels, modes, pilot condition*fuel interaction,
and fuel*mode interaction.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average fluoranthene for the Pilot A and Pilot B conditions
are not significantly different from one another, but are significantly different
from the LPP condition.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  There are three distinct fuel groupings with respect to the average
fluoranthene.  The average fluoranthene for the DF-2 fuel is significantly different
than the remaining four fuels.  The ADMM15 and FT-100 fuels are not significantly
different from one another, but are significantly different than the remaining three
fuels.  Also, the CA and ALS fuels are not significantly different from one
another, but are significantly different from the remaining fuels.
```

F-126

Means and 95% Tukey HSD Intervals

CONCLUSION: The average fluoranthene for modes 10 and 11 are significantly
different from one another.

Multiple Range Tests for fluoran by COND

Method: 95.0 percent Tukey HSD

COND	Count	LS Mean	Homogeneous Groups
LPP	31	23.2653	X
PilotB	30	33.6216	X
PilotA	30	35.7437	X

Contrast	Difference	+/- Limits
LPP - PilotA	*-12.4783	5.93261
LPP - PilotB	*-10.3563	5.93261
PilotA - PilotB	2.12207	5.98104

----
* denotes a statistically significant difference.

Multiple Range Tests for fluoran by FUEL

Method: 95.0 percent Tukey HSD

FUEL	Count	LS Mean	Homogeneous Groups
ADMM15	18	18.7128	X
FT-100	18	18.8435	X
ALS	19	29.7554	X
CA	18	33.7345	X
DF-2	18	53.338	X

Contrast	Difference	+/- Limits
ADMM15 - ALS	*-11.0426	8.91537
ADMM15 - CA	*-15.0217	9.03505
ADMM15 - DF-2	*-34.6252	9.03505
ADMM15 - FT-100	-0.130752	9.03505
ALS - CA	-3.97909	8.91537
ALS - DF-2	*-23.5826	8.91537
ALS - FT-100	*10.9119	8.91537
CA - DF-2	*-19.6035	9.03505
CA - FT-100	*14.891	9.03505
DF-2 - FT-100	*34.4944	9.03505

----
* denotes a statistically significant difference.

F-127

```
Multiple Range Tests for fluoran by MODE

--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
MODE            Count      LS Mean            Homogeneous Groups
--------------------------------------------------------------------------------
11              45         27.0255            X
10              46         34.7282             X
--------------------------------------------------------------------------------
Contrast                                      Difference        +/-  Limits
--------------------------------------------------------------------------------
10 - 11                                       *7.70273          4.04262
--------------------------------------------------------------------------------
* denotes a statistically significant difference.
```

Interaction and 95% Tukey HSD Intervals

CONCLUSION: The trend in the average fluoranthene across the pilot conditions
for the DF-2 fuel is significantly different than the trends for the remaining
four fuels. The average fluoranthene for the DF-2 fuel at the LPP condition is
significantly different than the other four fuels.

Interactions and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average fluoranthene
among the pilot condition and mode combinations.

F-128

Interaction and 95% Tukey HSD Intervals

CONCLUSION: The trends in the average fluoranthene for modes 10 and 11 are
significantly different at the CA fuel. Otherwise, the average fluoranthene
for the two modes are not significantly different across the remaining four
fuels.

```
Multifactor ANOVA - Pyrene (mirco g/kW-hr)    Soluble PAH
                     Three Pilot Conditions    Modes 10 and 11

Analysis Summary

Dependent variable: pyrene
Factors:
        COND
        FUEL
        MODE

Number of complete cases: 91
```

Scatterplot by Level Code

Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for pyrene - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:COND                  3128.95      2       1564.47      8.88    0.0004
 B:FUEL                  57792.3      4       14448.1     82.01    0.0000
 C:MODE                  933.572      1       933.572      5.30    0.0248
```

```
INTERACTIONS
 AB                          4706.65      8         588.331     3.34    0.0031
 AC                          375.603      2         187.802     1.07    0.3507
 BC                          1618.66      4         404.665     2.30    0.0692
 ABC                         951.124      8          118.89     0.67    0.7116

RESIDUAL                     10746.4      61        176.171
-------------------------------------------------------------------------------
TOTAL (CORRECTED)            80392.5      90
-------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.
```

```
CONCLUSION:  Statistically significant differences in the average pyrene among the
pilot conditions, fuels, modes, and pilot condition*fuel interaction.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average pyrene for the Pilot A and Pilot B conditions are not
significantly different from one another, but are significantly different from
the LPP condition.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  There are several distinct fuel groupings with respect to the average
pyrene.  The average pyrene for the DF-2 fuel is significantly different than the
remaining four fuels.  The FT-100 fuel is significantly different than the ALS and
CA fuels, but not significantly different than the ADMM15 fuel.
```

F-131

Means and 95% Tukey HSD Intervals

CONCLUSION: The average pyrene for modes 10 and 11 are significantly different
from one another.

Multiple Range Tests for pyrene by COND

Method: 95.0 percent Tukey HSD
COND   Count   LS Mean   Homogeneous Groups

LPP   31   29.6699   X
PilotB   30   41.7887   X
PilotA   30   42.3395   X

Contrast   Difference   +/- Limits

LPP - PilotA   *-12.6696   8.16647
LPP - PilotB   *-12.1188   8.16647
PilotA - PilotB   0.550867   8.23314
----
* denotes a statistically significant difference.

Multiple Range Tests for pyrene by FUEL

Method: 95.0 percent Tukey HSD
FUEL   Count   LS Mean   Homogeneous Groups

FT-100   18   15.0864   X
ADMM15   18   21.6978   XX
ALS   19   32.749   X
CA   18   33.4433   X
DF-2   18   86.6869   X

Contrast   Difference   +/- Limits

ADMM15 - ALS   -11.0512   12.2724
ADMM15 - CA   -11.7455   12.4371
ADMM15 - DF-2   *-64.9892   12.4371
ADMM15 - FT-100   6.61132   12.4371
ALS - CA   -0.694279   12.2724
ALS - DF-2   *-53.9379   12.2724
ALS - FT-100   *17.6626   12.2724
CA - DF-2   *-53.2437   12.4371
CA - FT-100   *18.3568   12.4371
DF-2 - FT-100   *71.6005   12.4371
----
* denotes a statistically significant difference.

Multiple Range Tests for pyrene by MODE

Method: 95.0 percent Tukey HSD

F-132

```
MODE            Count    LS Mean         Homogeneous Groups
-------------------------------------------------------------------------------
11              45       34.7254            X
10              46       41.14               X
-------------------------------------------------------------------------------
Contrast                                 Difference       +/-  Limits
-------------------------------------------------------------------------------
10 - 11                                  *6.41454         5.56482
-------------------------------------------------------------------------------
* denotes a statistically significant difference.
```

Interaction and 95% Tukey HSD Intervals

CONCLUSION: The trend in the average pyrene across the pilot conditions for
the DF-2 fuel is significantly different than the trends for the remaining four
fuels.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average pyrene among
the pilot condition and mode combinations.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average pyrene among the
fuel and mode combinations.

F-133

```
Multifactor ANOVA - Benzo[a]anthracene (µg/kW-hr)    Soluble PAH
                    Three Pilot Conditions    Modes 10 and 11

Analysis Summary

Dependent variable: benzoaan
Factors:
        COND
        FUEL
        MODE

Number of complete cases: 90
```

Scatterplot by Level Code

Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for benzoaan - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:COND                   48.5995     2        24.2997     40.74    0.0000
 B:FUEL                   402.558     4        100.639    168.71    0.0000
 C:MODE                   3.88467     1        3.88467      6.51    0.0133
```

```
INTERACTIONS
 AB                       67.7529      8      8.46911     14.20     0.0000
 AC                       2.79427      2      1.39713      2.34     0.1049
 BC                       4.41053      4      1.10263      1.85     0.1314
 ABC                      4.58466      8      0.573083     0.96     0.4750

RESIDUAL                  35.7914     60      0.596523
--------------------------------------------------------------------------------
TOTAL (CORRECTED)         573.429     89
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.
```

CONCLUSION: Statistically significant differences in the average benzo[a]anthracene among the pilot conditions, fuels, modes, and pilot condition*mode interaction.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average benzo[a]anthracene for the Pilot A and Pilot B conditions are not significantly different from one another, but are significantly different from the LPP condition.

Means and 95% Tukey HSD Intervals

CONCLUSION: There are three distinct fuel groupings with respect to the average benzo[a]anthracene. Fuels DF-2 and CA are significantly different from one another and the remaining three fuels. The FT-100, ADMM15, and ALS fuels are not significantly different from one another, but are significantly different than the other other two fuels.

F-135

Means and 95% Tukey HSD Intervals

CONCLUSION: The average benzo[a]anthracene for mode 10 is significantly different
than mode 11.

Multiple Range Tests for benzoaan by COND

Method: 95.0 percent Tukey HSD
COND   Count   LS Mean   Homogeneous Groups

LPP   30   1.0117   X
PilotB   30   2.48863   X
PilotA   30   2.66345   X

Contrast   Difference   +/- Limits

LPP - PilotA   *-1.65175   0.479284
LPP - PilotB   *-1.47694   0.479284
PilotA - PilotB   0.174814   0.479284
----
* denotes a statistically significant difference.

Multiple Range Tests for benzoaan by FUEL

Method: 95.0 percent Tukey HSD
FUEL   Count   LS Mean   Homogeneous Groups

FT-100   17   0.301925   X
ADMM15   18   0.424917   X
ALS   19   0.966186   X
CA   18   2.61   X
DF-2   18   5.96993   X

Contrast   Difference   +/- Limits

ADMM15 - ALS   -0.541269   0.714488
ADMM15 - CA   *-2.18508   0.724079
ADMM15 - DF-2   *-5.54501   0.724079
ADMM15 - FT-100   0.122992   0.73465
ALS - CA   *-1.64381   0.714488
ALS - DF-2   *-5.00374   0.714488
ALS - FT-100   0.664261   0.725199
CA - DF-2   *-3.35993   0.724079
CA - FT-100   *2.30807   0.73465
DF-2 - FT-100   *5.668   0.73465
----
* denotes a statistically significant difference.

Multiple Range Tests for benzoaan by MODE

Method: 95.0 percent Tukey HSD

F-136

```
MODE            Count    LS Mean         Homogeneous Groups
--------------------------------------------------------------------------------
11              44       1.84597         X
10              46       2.26321          X
--------------------------------------------------------------------------------
Contrast                                 Difference        +/-  Limits
--------------------------------------------------------------------------------
10 - 11                                  *0.417242         0.32578
--------------------------------------------------------------------------------
* denotes a statistically significant difference.
```

Interactions and 95% Tukey HSD Intervals

CONCLUSION: The trends in the average benzo[a]anthracene across the pilot
conditions for the DF-2 and CA fuels are significantly different than the trends
for the remaining three fuels. The average benzo[a]anthracene for the DF-2 and
CA fuels at the Pilot A and Pilot B conditions are significantly different than
the ADMM15, ALS, and FT-100 fuels.

Interactions and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average benzo[a]anthracene
among the pilot condition and mode combinations.

Interactions and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average benzo[a]anthracene
among the fuel and mode combinations.

F-137

```
Multifactor ANOVA - Chrysene (µg/kW-hr)    Soluble PAH
                 Three Pilot Conditions    Modes 10 and 11

Analysis Summary

Dependent variable: chrysene
Factors:
        COND
        FUEL
        MODE

Number of complete cases: 91
```

Scatterplot by Level Code

Scatterplot by Level Code

Scatterplot by Level Code


```
Analysis of Variance for chrysene - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares    Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:COND                 188.566        2       94.2828       35.03     0.0000
 B:FUEL                2128.88         4      532.22        197.75     0.0000
 C:MODE                  14.6927       1       14.6927        5.46     0.0228
```

F-138

```
INTERACTIONS
 AB                            247.004        8        30.8756      11.47     0.0000
 AC                            14.0682        2        7.03408       2.61     0.0815
 BC                            18.4527        4        4.61319       1.71     0.1585
 ABC                           23.1032        8         2.8879       1.07     0.3938

RESIDUAL                       164.177       61        2.69143
-------------------------------------------------------------------------------
TOTAL (CORRECTED)              2790.75       90
-------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.


CONCLUSION:  Statistically significant differences in the average chrysene among
the pilot conditions, fuels, modes, and pilot condition*fuel interaction.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average chrysene for the Pilot A and Pilot B conditions are not
significantly different from one another, but are significantly different from
the LPP condition.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  There are three distinct fuel groupings with respect to the average
chrysene.  Fuels DF-2 and CA are significantly different from one another and
the remaining three fuels.  The FT-100, ADMM15, and ALS fuels are not significantly
different from one another, but are significantly differnt than the other two
fuels.
```

F-139

Means and 95% Tukey HSD Intervals

CONCLUSION: The average chrysene for mode 10 is significantly different than mode 11.

Multiple Range Tests for chrysene by COND

Method: 95.0 percent Tukey HSD
COND   Count   LS Mean   Homogeneous Groups

LPP   31   2.86821   X
PilotB   30   5.53075   X
PilotA   30   6.18938   X

Contrast   Difference   +/- Limits

LPP - PilotA   *-3.32117   1.00939
LPP - PilotB   *-2.66254   1.00939
PilotA - PilotB   0.658631   1.01763
----
* denotes a statistically significant difference.

Multiple Range Tests for chrysene by FUEL

Method: 95.0 percent Tukey HSD
FUEL   Count   LS Mean   Homogeneous Groups

FT-100   18   1.00794   X
ADMM15   18   1.27994   X
ALS   19   2.27269   X
CA   18   5.7963   X
DF-2   18   13.957   X

Contrast   Difference   +/- Limits

ADMM15 - ALS   -0.992748   1.51689
ADMM15 - CA   *-4.51636   1.53725
ADMM15 - DF-2   *-12.6771   1.53725
ADMM15 - FT-100   0.272006   1.53725
ALS - CA   *-3.52361   1.51689
ALS - DF-2   *-11.6843   1.51689
ALS - FT-100   1.26475   1.51689
CA - DF-2   *-8.16073   1.53725
CA - FT-100   *4.78836   1.53725
DF-2 - FT-100   *12.9491   1.53725
----
* denotes a statistically significant difference.

Multiple Range Tests for chrysene by MODE

Method: 95.0 percent Tukey HSD

F-140

```
MODE            Count    LS Mean        Homogeneous Groups
-------------------------------------------------------------------------
11              45       4.46042        X
10              46       5.26514         X
-------------------------------------------------------------------------
Contrast                                Difference          +/-  Limits
-------------------------------------------------------------------------
10 - 11                                 *0.804715           0.687822
-------------------------------------------------------------------------
* denotes a statistically significant difference.
```

Interactions and 95% Tukey HSD Intervals

CONCLUSION: The trends in the average chrysene across the pilot conditions
for the DF-2 and CA fuels are significantly different than the trends for the
remaining three fuels. The average chrysene for the DF-2 and CA fuels at the
Pilot A and Pilot B conditions are significantly different than the ADMM15,
FT-100, and ALS fuels.

Interactions and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average chrysene among the
pilot condition and mode combinations.

Interactions and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average chrysene among
the fuel and mode combinations.

F-141

```
Multifactor ANOVA - Benzo[b]fluoranthene (µg/kW-hr)   Soluble PAH
                  Three Pilot Conditions   Modes 10 and 11

Analysis Summary

Dependent variable: benzobfl
Factors:
        COND
        FUEL
        MODE

Number of complete cases: 90
```

Scatterplot by Level Code

Benzo[b]fluoranthene vs Pilot Condition (LPP, PilotA, PilotB)

Scatterplot by Level Code

Benzo[b]fluoranthene vs Fuel (ADMM15, ALS, CA, DF-2, FT-100)

Scatterplot by Level Code

Benzo[b]fluoranthene vs Mode (10, 11)

```
Analysis of Variance for benzobfl - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares   Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:COND                   33.7923     2        16.8961      61.70     0.0000
 B:FUEL                   187.458     4        46.8646     171.14     0.0000
 C:MODE                   6.52731     1        6.52731      23.84     0.0000
```

F-142

```
INTERACTIONS
 AB                                56.3           8         7.0375        25.70       0.0000
 AC                            5.08814            2         2.54407        9.29       0.0003
 BC                            2.47311            4        0.618277        2.26       0.0734
 ABC                           5.72437            8        0.715547        2.61       0.0160

RESIDUAL                       16.4299           60        0.273831
-----------------------------------------------------------------------------
TOTAL (CORRECTED)              314.118           89
-----------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average benzo[b]fluoranthene
among the pilot conditions, fuels, modes, pilot condition*fuel interaction,
pilot condition*mode interaction, and the three-factor interaction.
```

Means and 95% Tukey HSD Intervals

CONCLUSION: The average benzo[b]fluoranthene for the three pilot conditions
are all significantly different from one another.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average benzo[b]fluoranthene for the ALS, CA, and DF-2 fuels
are significantly different from one another and the remaining two fuels. The
average benzo[b]fluoranthene for the ADMM15 and FT-100 fuels are not
significantly different from one another.

F-143

Means and 95% Tukey HSD Intervals

CONCLUSION: The average benzo[b]fluoranthene for modes 10 and 11 are significantly different from one another.

Multiple Range Tests for benzobfl by COND

Method: 95.0 percent Tukey HSD
COND   Count   LS Mean   Homogeneous Groups

LPP   30   0.974513   X
PilotB   30   1.86744   X
PilotA   30   2.47698   X

Contrast   Difference   +/- Limits

LPP - PilotA   *-1.50247   0.324729
LPP - PilotB   *-0.892926   0.324729
PilotA - PilotB   *0.60954   0.324729
----
* denotes a statistically significant difference.

Multiple Range Tests for benzobfl by FUEL

Method: 95.0 percent Tukey HSD
FUEL   Count   LS Mean   Homogeneous Groups

ADMM15   18   0.440325   X
FT-100   18   0.458957   X
ALS   19   1.18837   X
CA   17   2.55696   X
DF-2   18   4.22027   X

Contrast   Difference   +/- Limits

ADMM15 - ALS   *-0.748046   0.484086
ADMM15 - CA   *-2.11664   0.497747
ADMM15 - DF-2   *-3.77994   0.490584
ADMM15 - FT-100   -0.018632   0.490584
ALS - CA   *-1.36859   0.491343
ALS - DF-2   *-3.0319   0.484086
ALS - FT-100   *0.729414   0.484086
CA - DF-2   *-1.6633   0.497747
CA - FT-100   *2.09801   0.497747
DF-2 - FT-100   *3.76131   0.490584
----
* denotes a statistically significant difference.

Multiple Range Tests for benzobfl by MODE

Method: 95.0 percent Tukey HSD

F-144

```
MODE            Count     LS Mean        Homogeneous Groups
-----------------------------------------------------------------------------
11               44       1.50255        X
10               46       2.0434          X
-----------------------------------------------------------------------------
Contrast                                 Difference        +/-  Limits
-----------------------------------------------------------------------------
10 - 11                                  *0.540852         0.220726
-----------------------------------------------------------------------------
* denotes a statistically significant difference.
```

Interactions and 95% Tukey HSD Intervals

CONCLUSION: The trends in the average benzo[b]fluoranthene across the pilot
conditions for the DF-2 and CA fuels are significantly different than the trends
for the remaining three fuels. The average benzo[b]fluoranthene for the DF-2
and CA fuels at the Pilot A and Pilot B conditions are significantly different
than the ADMM15, FT-100, and ALS fuels.

Interactions and 95% Tukey HSD Intervals

CONCLUSION: The average benzo[b]fluoranthene at the Pilot A condition for Mode 10
is significantly different than Mode 11. There is no significant difference in
the average benzo[b]fluoranthene between the two modes at the LPP or Pilot B
conditions.

F-145

Interactions and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average
benzo[b]fluoranthene among the fuel and mode combinations.

```
Multifactor ANOVA - Benzo[k]fluoranthene (μg/kW-hr)    Soluble PAH
                   Three Pilot Conditions    Modes 10 and 11

Analysis Summary

Dependent variable: benzokfl
Factors:
        COND
        FUEL
        MODE

Number of complete cases: 90
```

Scatterplot by Level Code

Benzo[k]fluoranthene vs Pilot Conditions (LPP, PilotA, PilotB)

Scatterplot by Level Code

Benzo[k]fluoranthene vs Fuel (ADMM15, ALS, CA, DF-2, FT-100)

Scatterplot by Level Code

Benzo[k]fluoranthene vs Mode (10, 11)

```
Analysis of Variance for benzokfl - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:COND                  21.4951      2       10.7475     20.33     0.0000
 B:FUEL                  105.475      4       26.3688     49.89     0.0000
 C:MODE                  7.90494      1       7.90494     14.96     0.0003
```

```
INTERACTIONS
 AB                         8.67666        8       1.08458       2.05     0.0551
 AC                          5.3645        2       2.68225       5.07     0.0092
 BC                         2.33049        4      0.582623       1.10     0.3638
 ABC                        9.53079        8       1.19135       2.25     0.0354

RESIDUAL                    31.7128       60      0.528547
--------------------------------------------------------------------------------
TOTAL (CORRECTED)           192.186       89
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  Statistically significant differences in the average benzo[b]fluoranthene
among the pilot conditions, fuels, modes, pilot condition*mode interaction, and
the three-factor interaction.
```

Means and 95% Tukey HSD Intervals

CONCLUSION: The average benzo[f]fluoranthene for the three pilot conditions are
significantly different from one another.

Means and 95% Tukey HSD Intervals

CONCLUSION: There are several distinct fuel groupings with respect to the average
benzo[k]fluoranthene. The DF-2 fuel is significantly different from the remaining
four fuels. The CA fuel is significantly different than the ADMM15 and the
FT-100 fuels, but not significantly different than the ALS fuel. Also, the ALS
fuel is significantly different than the FT-100 fuel.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average benzo[k]fluoranthene for mode 10 is significantly different than mode 11.

Multiple Range Tests for benzokfl by COND

Method: 95.0 percent Tukey HSD
COND   Count   LS Mean   Homogeneous Groups

LPP   30   1.07438   X
PilotB   30   1.56063   X
PilotA   30   2.27093   X

Contrast   Difference   +/- Limits

LPP - PilotA   *-1.19656   0.45115
LPP - PilotB   *-0.486254   0.45115
PilotA - PilotB   *0.710302   0.45115
----
* denotes a statistically significant difference.

Multiple Range Tests for benzokfl by FUEL

Method: 95.0 percent Tukey HSD
FUEL   Count   LS Mean   Homogeneous Groups

FT-100   18   0.525045   X
ADMM15   18   0.817921   XX
ALS   19   1.4175   XX
CA   17   1.81074   X
DF-2   18   3.60536   X

Contrast   Difference   +/- Limits

ADMM15 - ALS   -0.599576   0.672548
ADMM15 - CA   *-0.992818   0.691526
ADMM15 - DF-2   *-2.78744   0.681575
ADMM15 - FT-100   0.292877   0.681575
ALS - CA   -0.393242   0.68263
ALS - DF-2   *-2.18787   0.672548
ALS - FT-100   *0.892453   0.672548
CA - DF-2   *-1.79462   0.691526
CA - FT-100   *1.28569   0.691526
DF-2 - FT-100   *3.08032   0.681575
----
* denotes a statistically significant difference.

Multiple Range Tests for benzokfl by MODE

Method: 95.0 percent Tukey HSD

F-149

```
MODE           Count    LS Mean        Homogeneous Groups
--------------------------------------------------------------------------------
11             44       1.33772        X
10             46       1.93291         X
--------------------------------------------------------------------------------
Contrast                               Difference       +/-  Limits
--------------------------------------------------------------------------------
10 - 11                                *0.595196        0.306657
--------------------------------------------------------------------------------
```
* denotes a statistically significant difference.

Interactions and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average benzo[k]fluoranthene
among the fuel and pilot condition combinations.

Interactions and 95% Tukey HSD Intervals

CONCLUSION: The average benzo[k]fluoranthene at the Pilot A condition for
Mode 10 is significantly different than Mode 11. There is no significant difference
in the average benzo[k]fluoranthene between the two modes at the LPP or
Pilot B conditions.

Interactions and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average benzo[k]fluoranthene
among the fuel and mode combinations.

```
Multifactor ANOVA - Benzo[e]pyrene  (µg/kW-hr)    Soluble PAH
                    Three Pilot Conditions   Modes 10 and 11

Analysis Summary

Dependent variable: benzoepy
Factors:
        COND
        FUEL
        MODE

Number of complete cases: 91
```

Scatterplot by Level Code

Benzo[e]pyrene vs Pilot Condition (LPP, PilotA, PilotB)

Scatterplot by Level Code

Benzo[e]pyrene vs Fuel (ADMM15, ALS, CA, DF-2, FT-100)

Scatterplot by Level Code

Benzo[e]pyrene vs Mode (10, 11)

```
Analysis of Variance for benzoepy - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares    Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:COND                  19.0613        2        9.53063      74.74     0.0000
 B:FUEL                  61.2053        4       15.3013      119.99     0.0000
 C:MODE                   3.35117       1        3.35117      26.28     0.0000
```

F-151

```
INTERACTIONS
 AB                         15.5695        8       1.94619    15.26    0.0000
 AC                         1.70452        2       0.852262    6.68    0.0024
 BC                         1.17591        4       0.293977    2.31    0.0683
 ABC                        1.62589        8       0.203236    1.59    0.1455

RESIDUAL                    7.7789        61       0.127523
-----------------------------------------------------------------------------
TOTAL (CORRECTED)          111.059        90
-----------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.


CONCLUSION:  Statistically significant differences in the average benzo[e]pyrene
among the pilot conditions, fuels, modes, pilot condition*fuel interaction, and
pilot condition*mode interaction.
```

Means and 95% Tukey HSD Intervals

CONCLUSION: The average benzo[e]pyrene for the three pilot conditions are
significantly different from one another.

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  There are several distinct fuel groupings with respect to the average
benzo[e]pyrene.  The DF-2 and CA fuels are significantly different from the remaining
three fuels.  Also, the ALS fuel is significantly different than the FT-100 fuel.
```

Means and 95% Tukey HSD Intervals

CONCLUSION: The average benzo[e]pyrene for mode 10 is significantly different
than mode 11.

Multiple Range Tests for benzoepy by COND

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
COND            Count    LS Mean         Homogeneous Groups
--------------------------------------------------------------------------------
LPP             31       0.613585        X
PilotB          30       1.3361           X
PilotA          30       1.71474           X
--------------------------------------------------------------------------------
Contrast                                Difference         +/-  Limits
--------------------------------------------------------------------------------
LPP - PilotA                            *-1.10116          0.219716
LPP - PilotB                            *-0.722515         0.219716
PilotA - PilotB                         *0.378641          0.22151
--------------------------------------------------------------------------------
* denotes a statistically significant difference.
```


Multiple Range Tests for benzoepy by FUEL

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
FUEL            Count    LS Mean         Homogeneous Groups
--------------------------------------------------------------------------------
FT-100          18       0.375599        X
ADMM15          18       0.544484        XX
ALS             19       0.874367         X
CA              18       1.73671           X
DF-2            18       2.57622            X
--------------------------------------------------------------------------------
Contrast                                Difference         +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                            -0.329883          0.330184
ADMM15 - CA                             *-1.19223          0.334616
ADMM15 - DF-2                           *-2.03173          0.334616
ADMM15 - FT-100                          0.168886          0.334616
ALS - CA                                *-0.862343         0.330184
ALS - DF-2                              *-1.70185          0.330184
ALS - FT-100                            *0.498769          0.330184
CA - DF-2                               *-0.839507         0.334616
CA - FT-100                             *1.36111           0.334616
DF-2 - FT-100                           *2.20062           0.334616
--------------------------------------------------------------------------------
* denotes a statistically significant difference.
```


Multiple Range Tests for benzoepy by MODE

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
```

F-153

```
MODE          Count    LS Mean         Homogeneous Groups
-------------------------------------------------------------------------------
11            45       1.02932         X
10            46       1.41363          X
-------------------------------------------------------------------------------
Contrast                               Difference       +/-  Limits
-------------------------------------------------------------------------------
10 - 11                                *0.384317        0.14972
-------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

Interactions and 95% Tukey HSD Intervals

CONCLUSION: The trends in the average benzo[e]pyrene across the pilot
conditions for the DF-2 and CA fuels are significantly different than the
trends for the remaining three fuels. The average benzo[e]pyrene for the
DF-2 and CA fuels at the Pilot A and Pilot B conditions are significantly
different than the ADMM15, FT-100, and ALS fuels.

Interactions and 95% Tukey HSD Intervals

CONCLUSION: The average benzo[e]pyrene at the Pilot A condition for Mode 10
is significantly different than Mode 11. There is no significant difference
in the average benzo[e]pyrene between the two modes at the LPP or Pilot B
conditions.

Interactions and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average benzo[e]pyrene
among the fuel and mode combinations.

```
Multifactor ANOVA - Benzo[a]pyrene (µg/kW-hr)    Soluble PAH
                  Three Pilot Conditions    Modes 10 and 11

Analysis Summary

Dependent variable: benzoapy
Factors:
        COND
        FUEL
        MODE

Number of complete cases: 90
```

Scatterplot by Level Code

Benzo[a]pyrene vs Pilot Condition (LPP, PilotA, PilotB)

Scatterplot by Level Code

Benzo[a]pyrene vs Fuel (ADMM15, ALS, CA, DF-2, FT-100)

Scatterplot by Level Code

Benzo[a]pyrene vs Mode (10, 11)

```
Analysis of Variance for benzoapy - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:COND                 13.9325       2       6.96627      70.55    0.0000
 B:FUEL                 28.6525       4       7.16311      72.54    0.0000
```

F-156

C:MODE	1.90042	1	1.90042	19.25	0.0000
INTERACTIONS					
AB	14.7907	8	1.84884	18.72	0.0000
AC	1.26211	2	0.631057	6.39	0.0030
BC	1.38381	4	0.345953	3.50	0.0123
ABC	1.8229	8	0.227863	2.31	0.0315
RESIDUAL	5.92448	60	0.0987413		

TOTAL (CORRECTED)	69.8823	89

All F-ratios are based on the residual mean square error.

CONCLUSION: Statistically significant differences in the average benzo[a]pyrene
among the pilot conditions, fuels, modes, two-factor interactions, and the
three-factor interaction fuel*mode*pilot condition.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average benzo[a]pyrene for the three pilot conditions are
significantly different from one another.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average benzo[a]pyrene for the DF-2, CA, and ALS fuels are
significantly different from one another and the remaining two fuels. The
average benzo[a]pyrene for the ADMM15 and FT-100 fuels are not significantly
different from one another.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average benzo[a]pyrene for mode 10 is significantly different than mode 11.

Multiple Range Tests for benzoapy by COND

Method: 95.0 percent Tukey HSD

COND	Count	LS Mean	Homogeneous Groups		
LPP	31	0.245088	X		
PilotB	30	0.932902		X	
PilotA	29	1.17383			X

Contrast	Difference	+/- Limits
LPP - PilotA	*-0.92874	0.195106
LPP - PilotB	*-0.687815	0.193419
PilotA - PilotB	*0.240925	0.196671

----
* denotes a statistically significant difference.

Multiple Range Tests for benzoapy by FUEL

Method: 95.0 percent Tukey HSD

FUEL	Count	LS Mean	Homogeneous Groups			
FT-100	18	0.160939	X			
ADMM15	17	0.242393	X			
ALS	19	0.639999		X		
CA	18	1.27156			X	
DF-2	18	1.6048				X

Contrast	Difference	+/- Limits
ADMM15 - ALS	*-0.397606	0.295048
ADMM15 - CA	*-1.02917	0.298893
ADMM15 - DF-2	*-1.36241	0.298893
ADMM15 - FT-100	0.0814542	0.298893
ALS - CA	*-0.631563	0.29069
ALS - DF-2	*-0.964804	0.29069
ALS - FT-100	*0.47906	0.29069
CA - DF-2	*-0.33324	0.294593
CA - FT-100	*1.11062	0.294593
DF-2 - FT-100	*1.44386	0.294593

----
* denotes a statistically significant difference.

Multiple Range Tests for benzoapy by MODE

Method: 95.0 percent Tukey HSD

F-158

```
MODE          Count     LS Mean         Homogeneous Groups
-------------------------------------------------------------------------------
11            44        0.638022        X
10            46        0.929856         X
-------------------------------------------------------------------------------
Contrast                                Difference      +/-  Limits
-------------------------------------------------------------------------------
10 - 11                                 *0.291834       0.132544
-------------------------------------------------------------------------------
```
* denotes a statistically significant difference.

Interactions and 95% Tukey HSD Intervals

CONCLUSION: The trends in the average benzo[a]pyrene across the pilot conditions
for the CA and DF-2 fuels are significantly different than the trends for the
remaining three fuels. The average benzo[a]pyrene for the CA and DF-2 fuels at the
Pilot A and Pilot B conditions are significantly different than the ADMM15, FT-100,
and ALS fuels.

Interactions and 95% Tukey HSD Intervals

CONCLUSION: The average benzo[a]pyrene at the Pilot A condition for mode 10
is significantly different than mode 11. There is no significant difference in
the average benzo[a]pyrene between the two modes at the LPP or Pilot B
conditions.

F-159

Interactions and 95% Tukey HSD Intervals

CONCLUSION: The average benzo[a]pyrene for the CA and DF-2 fuels for mode 10
is significantly different than mode 11. There is no significant difference in
the average benzo[a]pyrene between the modes for the ADMM15, ALS, or FT-100 fuels.

```
Multifactor ANOVA - Indeno(1,2,3-cd)pyrene (µg/kW-hr)   Soluble PAH
                 Three Pilot Conditions on Four Fuels     Modes 10 and 11

Analysis Summary

Dependent variable: indeno
Factors:
        COND
        FUEL
        MODE

Number of complete cases: 70
```

Scatterplot by Level Code

Indeno(1,2,3-cd)pyrene vs Pilot Condition (LPP, PilotA, PilotB)

Scatterplot by Level Code

Indeno(1,2,3-cd)pyrene vs Fuel (ADMM15, CA, DF-2, FT-100)

Scatterplot by Level Code

Indeno(1,2,3-cd)pyrene vs Mode (10, 11)

```
Analysis of Variance for indeno - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares   Df   Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:COND                    1.88837    2      0.944186     29.96    0.0000
 B:FUEL                      13.47    3          4.49    142.47    0.0000
 C:MODE                  0.0979782    1     0.0979782      3.11    0.0845
```

```
INTERACTIONS
 AB                          3.30618         6        0.55103     17.48     0.0000
 AC                         0.496114         2       0.248057      7.87     0.0011
 BC                        0.0408507         3      0.0136169      0.43     0.7310
 ABC                       0.815885          6       0.135981      4.31     0.0016

RESIDUAL                    1.44973         46       0.0315159
-------------------------------------------------------------------------------
TOTAL (CORRECTED)          21.8794          69
-------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.
```

```
CONCLUSION:  Statistically significant differences in the average
indeno(1,2,3-cd)pyrene among the pilot conditions, fuels, pilot condition*fuel
interaction, pilot condition*mode interaction, and the three-factor interaction
pilot condition*fuel*mode.
```


Means and 95% Tukey HSD Interval

```
CONCLUSION:  The average indeno(1,2,3-cd)pyrene for the three pilot conditions
are significantly different from one another.
```


Means and 95% Tukey HSD Interval

```
CONCLUSION:  The average indeno(1,2,3-cd)pyrene for the DF-2 and CA fuels are
significantly different from one another and the remaining two fuels.  The average
indeno(1,2,3-cd)pyrene for the FT-100 and ADMM15 fuels are not significantly
different from one another.
```

Means and 95% Tukey HSD Interval

CONCLUSION: There is no significant difference in the average indeno(1,2,3-cd)pyrene
among the two modes.

Multiple Range Tests for indeno by COND

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
COND            Count    LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
LPP             24       0.259249         X
PilotB          24       0.481723          X
PilotA          22       0.666534           X
--------------------------------------------------------------------------------
Contrast                                 Difference       +/-  Limits
--------------------------------------------------------------------------------
LPP - PilotA                             *-0.407284       0.126918
LPP - PilotB                             *-0.222473       0.124128
PilotA - PilotB                          *0.184811        0.126918
--------------------------------------------------------------------------------
* denotes a statistically significant difference.
```


Multiple Range Tests for indeno by FUEL

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
FUEL            Count    LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
FT-100          18       0.0485468        X
ADMM15          16       0.10839          X
CA              18       0.581265          X
DF-2            18       1.13847            X
--------------------------------------------------------------------------------
Contrast                                 Difference       +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - CA                              *-0.472875       0.162599
ADMM15 - DF-2                            *-1.03008        0.162599
ADMM15 - FT-100                           0.0598431       0.162599
CA - DF-2                                *-0.557207       0.157745
CA - FT-100                              *0.532719        0.157745
DF-2 - FT-100                            *1.08993         0.157745
--------------------------------------------------------------------------------
* denotes a statistically significant difference.
```

```
Multifactor ANOVA - indenoMultiple Range Tests for indeno by MODE

--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
MODE            Count       LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
11              35          0.431519         X
10              35          0.506818         X
--------------------------------------------------------------------------------
Contrast                                    Difference        +/-  Limits
--------------------------------------------------------------------------------
10 - 11                                     0.0752996         0.0854216
--------------------------------------------------------------------------------
* denotes a statistically significant difference.
```


Interactions and 95% Tukey HSD Intervals

CONCLUSION: The trends in the average indeno(1,2,3-cd)pyrene across the pilot
conditions for the CA and DF-2 fuels are significantly different than the trends
for the remaining two fuels. The average indeno(1,2,3-cd)pyrene for the CA and
DF-2 fuels at the Pilot A condition are significantly different than the ADMM15
and FT-100 fuels.

Interactions and 95% Tukey HSD Intervals

CONCLUSION: The average indeno(1,2,3-cd)pyrene at the Pilot A condition for
mode 10 is significantly different than mode 11.

Interactions and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average
indeno(1,2,3-cd)pyrene among the fuel and mode combinations.

```
Multifactor ANOVA - Benzo[ghi]perylene (µg/kW-hr)     Soluble PAH
                   Three Pilot Conditions on Four Fuels   Modes 10 and 11

Analysis Summary

Dependent variable: benzogpe
Factors:
        COND
        FUEL
        MODE

Number of complete cases: 71
```

Scatterplot by Level Code

Pilot Condition

Scatterplot by Level Code

Fuel

Scatterplot by Level Code

Mode

```
Analysis of Variance for benzogpe - Type III Sums of Squares
--------------------------------------------------------------------------------
Source            Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:COND              3.76493        2      1.88247       28.05    0.0000
 B:FUEL             29.0105         3      9.67015      144.11    0.0000
 C:MODE              0.320197       1      0.320197       4.77    0.0340
```

F-166

```
INTERACTIONS
 AB                            7.55969        6         1.25995        18.78       0.0000
 AC                           0.850042        2        0.425021         6.33       0.0037
 BC                          0.0839346        3        0.0279782        0.42       0.7416
 ABC                           1.9744         6        0.329066         4.90       0.0006

RESIDUAL                      3.15374        47        0.0671009
-------------------------------------------------------------------------------
TOTAL (CORRECTED)            46.9949         70
-------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.


CONCLUSION:  Statistically significant differences in the average
benzo[ghi]perylene among the pilot conditions, fuels, modes, pilot condition*fuel
interaction, pilot condition*mode interaction, and the three-factor interaction
pilot condition*fuel*mode.
```

Means and 95% Tukey HSD Intervals

Pilot Condition

```
CONCLUSION:  The average benzo[ghi]perylene for the three pilot conditions are
significantly different from one another.
```

Means and 95% Tukey HSD Intervals

Fuel

```
CONCLUSION:  The average benzo[ghi]perylene for the DF-2 and CA fuels are
significantly different from one another and the remaining two fuels.  The average
benzo[ghi]perylene for the FT-100 and ADMM15 fuels are not significantly
different from one another.
```

Means and 95% Tukey HSD Intervals

CONCLUSION: The average benzo[ghi]perylene for mode 10 is significantly
different than mode 11.

Multiple Range Tests for benzogpe by COND

Method: 95.0 percent Tukey HSD
COND   Count   LS Mean   Homogeneous Groups

LPP   24   0.503794   X
PilotB   24   0.800707   X
PilotA   23   1.07206   X

Contrast   Difference   +/- Limits

LPP - PilotA   *-0.568266   0.18295
LPP - PilotB   *-0.296914   0.180993
PilotA - PilotB   *0.271352   0.18295
----
* denotes a statistically significant difference.

Multiple Range Tests for benzogpe by FUEL

Method: 95.0 percent Tukey HSD
FUEL   Count   LS Mean   Homogeneous Groups

FT-100   18   0.148796   X
ADMM15   17   0.248311   X
CA   18   1.0539   X
DF-2   18   1.71774   X

Contrast   Difference   +/- Limits

ADMM15 - CA   *-0.805591   0.233348
ADMM15 - DF-2   *-1.46943   0.233348
ADMM15 - FT-100   0.0995153   0.233348
CA - DF-2   *-0.663836   0.22999
CA - FT-100   *0.905106   0.22999
DF-2 - FT-100   *1.56894   0.22999
----
* denotes a statistically significant difference.

Multiple Range Tests for benzogpe by MODE

Method: 95.0 percent Tukey HSD
MODE   Count   LS Mean   Homogeneous Groups
----
11   35   0.724809   X
10   36   0.859565   X

F-168

```
--------------------------------------------------------------------------------
Contrast                                  Difference        +/-  Limits
--------------------------------------------------------------------------------
10 - 11                                   *0.134757         0.123703
--------------------------------------------------------------------------------
```
* denotes a statistically significant difference.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: The trends in the average benzo[ghi]perylene across the pilot
conditions for the DF-2 and CA fuels are significantly different than the trends
for the remaining two fuels. The average benzo[ghi]perylene for the CA and
DF-2 fuels at the Pilot A condition are significantly different than the ADMM15
and FT-100 fuels.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: The average benzo[ghi]perylene at the Pilot A condition for mode 10
is significantly different than mode 11.

Interaction and 95% Tukey HSD Intervals

CONCLUSION: There is no significant interaction in the average benzo[ghi]perylene
among the fuel and mode combinations.

APPENDIX G

ANOVA for MODE 12

TABLE OF CONTENTS

```
Multifactor ANOVA - Total Particulates (g/kW-hr)
                LPP Only   Mode 12
Analysis Summary

Dependent variable: PARTIC
Factors:
        FUEL
Selection variable: MODE=12

Number of complete cases: 17
```

Scatterplot by Level Code


```
Analysis of Variance for PARTIC - Type III Sums of Squares
--------------------------------------------------------------------------------
Source                Sum of Squares   Df   Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:FUEL                  173.578         4     43.3945      1.50     0.2645

RESIDUAL                 348.132        12     29.011
--------------------------------------------------------------------------------
TOTAL (CORRECTED)        521.71         16
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  No statistically significant differences in the average particulates
among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  No statistically significant differences in the average particulates
among the fuels.


Multiple Range Tests for PARTIC by FUEL

--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
FUEL            Count     LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
ADMM15           3        2.90331          X
FT-100           3        3.54611          X
```

```
DF-2            3           8.41804             X
ALS             4           8.86013             X
CA              4           11.168              X
--------------------------------------------------------------------------
Contrast                                Difference         +/-  Limits
--------------------------------------------------------------------------
ADMM15 - ALS                            -5.95682           13.1343
ADMM15 - CA                             -8.26472           13.1343
ADMM15 - DF-2                           -5.51473           14.0411
ADMM15 - FT-100                         -0.642796          14.0411
ALS - CA                                -2.3079            12.16
ALS - DF-2                              0.44209            13.1343
ALS - FT-100                            5.31402            13.1343
CA - DF-2                               2.74999            13.1343
CA - FT-100                             7.62192            13.1343
DF-2 - FT-100                           4.87193            14.0411
--------------------------------------------------------------------------
```

* denotes a statistically significant difference.

```
Multifactor ANOVA - BSNOX (g/kW-hr)
                 LPP Only   Mode 12
Analysis Summary

Dependent variable: BSNOX
Factors:
        FUEL
Selection variable: MODE=12

Number of complete cases: 17
```

Scatterplot by Level Code

Analysis of Variance for BSNOX - Type III Sums of Squares

Source	Sum of Squares	Df	Mean Square	F-Ratio	P-Value
MAIN EFFECTS					
A:FUEL	19.5585	4	4.88963	0.20	0.9353
RESIDUAL	298.211	12	24.8509		
TOTAL (CORRECTED)	317.769	16			

All F-ratios are based on the residual mean square error.

CONCLUSION: No statistically significant differences in the average BSNOX among the fuels.

Means and 95% Tukey HSD Intervals

CONCLUSION: No statistically significant differences in the average BSNOX among the fuels.

```
Multiple Range Tests for BSNOX by FUEL

--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
FUEL          Count    LS Mean        Homogeneous Groups
--------------------------------------------------------------------------------
CA            4        17.5372        X
```

```
ALS            4        18.714        X
FT-100         3        18.7832       X
DF-2           3        19.3197       X
ADMM15         3        20.8529       X
--------------------------------------------------------------------------------
Contrast                            Difference        +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                        2.13893           12.1561
ADMM15 - CA                         3.31568           12.1561
ADMM15 - DF-2                       1.53323           12.9955
ADMM15 - FT-100                     2.06964           12.9955
ALS - CA                            1.17675           11.2544
ALS - DF-2                          -0.605695         12.1561
ALS - FT-100                        -0.0692861        12.1561
CA - DF-2                           -1.78244          12.1561
CA - FT-100                         -1.24603          12.1561
DF-2 - FT-100                       0.536409          12.9955
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

```
Multifactor ANOVA - BSHC (g/kW-hr)
                  LPP Only   Mode 12
Analysis Summary

Dependent variable: BSHC
Factors:
        FUEL
Selection variable: MODE=12

Number of complete cases: 17
```

Scatterplot by Level Code


```
Analysis of Variance for BSHC - Type III Sums of Squares
--------------------------------------------------------------------------------
Source                 Sum of Squares   Df   Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:FUEL                    1799.42       4      449.854      0.99     0.4499

RESIDUAL                   5456.05      12      454.671
--------------------------------------------------------------------------------
TOTAL (CORRECTED)          7255.47      16
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.
```

```
CONCLUSION:  No statistically significant differences in the average BSHC among
the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  No statistically significant differences in the average BSHC among
the fuels.
```

```
Multiple Range Tests for BSHC by FUEL

--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
FUEL            Count     LS Mean          Homogeneous Groups
```

G-7

```
--------------------------------------------------------------------------------
FT-100          3          28.1695          X
ADMM15          3          36.7632          X
CA              4          52.4152          X
DF-2            3          53.3986          X
ALS             4          54.0764          X
--------------------------------------------------------------------------------
Contrast                                    Difference       +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                                -17.3132         51.9964
ADMM15 - CA                                 -15.652          51.9964
ADMM15 - DF-2                               -16.6354         55.5865
ADMM15 - FT-100                             8.59372          55.5865
ALS - CA                                    1.66119          48.1393
ALS - DF-2                                  0.677775         51.9964
ALS - FT-100                                25.9069          51.9964
CA - DF-2                                   -0.983416        51.9964
CA - FT-100                                 24.2457          51.9964
DF-2 - FT-100                               25.2291          55.5865
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

```
Multifactor ANOVA - BSCO (g/kW-hr)
                  LPP Only   Mode 12
Analysis Summary

Dependent variable: BSCO
Factors:
        FUEL
Selection variable: MODE=12

Number of complete cases: 17
```

Scatterplot by Level Code

Analysis of Variance for BSCO - Type III Sums of Squares

Source	Sum of Squares	Df	Mean Square	F-Ratio	P-Value
MAIN EFFECTS					
A:FUEL	16190.3	4	4047.57	0.86	0.5157
RESIDUAL	56565.5	12	4713.8		
TOTAL (CORRECTED)	72755.8	16			

All F-ratios are based on the residual mean square error.

```
CONCLUSION:  No statistically significant differences in the average BSCO
among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  No statistically significant differences in the average BSCO
among the fuels.


Multiple Range Tests for BSCO by FUEL

--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
```

```
FUEL            Count    LS Mean        Homogeneous Groups
--------------------------------------------------------------------------
FT-100          3        106.035        X
ADMM15          3        159.445        X
CA              4        174.056        X
ALS             4        190.488        X
DF-2            3        195.655        X
--------------------------------------------------------------------------
Contrast                                Difference      +/-  Limits
--------------------------------------------------------------------------
ADMM15 - ALS                            -31.0427        167.421
ADMM15 - CA                             -14.6106        167.421
ADMM15 - DF-2                           -36.2097        178.98
ADMM15 - FT-100                         53.4104         178.98
ALS - CA                                16.4321         155.002
ALS - DF-2                              -5.16696        167.421
ALS - FT-100                            84.4531         167.421
CA - DF-2                               -21.5991        167.421
CA - FT-100                             68.021          167.421
DF-2 - FT-100                           89.62           178.98
--------------------------------------------------------------------------
```

* denotes a statistically significant difference.

```
Multifactor ANOVA - BSCO2 (g/kW-hr)
                  LPP Only   Mode 12

Analysis Summary

Dependent variable: BSCO2
Factors:
        FUEL
Selection variable: MODE=12

Number of complete cases: 17
```

Scatterplot by Level Code


```
Analysis of Variance for BSCO2 - Type III Sums of Squares
--------------------------------------------------------------------------------
Source               Sum of Squares   Df    Mean Square    F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:FUEL                  6.79414E6      4     1.69854E6       0.49     0.7406

RESIDUAL                 4.12673E7     12     3.43894E6
--------------------------------------------------------------------------------
TOTAL (CORRECTED)        4.80614E7     16
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  No statistically significant differences in the average BSCO2
among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  No statistically significant differences in the average BSCO2
among the fuels.

Multiple Range Tests for BSCO2 by FUEL

--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
FUEL           Count     LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
```

```
CA                4          5618.38              X
DF-2              3          5664.79              X
ADMM15            3          6464.75              X
FT-100            3          6754.19              X
ALS               4          7174.0               X
--------------------------------------------------------------------------------
Contrast                                Difference      +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                            -709.244        4522.06
ADMM15 - CA                             846.375         4522.06
ADMM15 - DF-2                           799.964         4834.29
ADMM15 - FT-100                         -289.437        4834.29
ALS - CA                                1555.62         4186.62
ALS - DF-2                              1509.21         4522.06
ALS - FT-100                            419.807         4522.06
CA - DF-2                               -46.4105        4522.06
CA - FT-100                             -1135.81        4522.06
DF-2 - FT-100                           -1089.4         4834.29
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

```
Multifactor ANOVA - BSSOF (g/kW-hr)
                 LPP Only   Mode 12

Analysis Summary

Dependent variable: bssof
Factors:
        fuel
Selection variable: mode=12

Number of complete cases: 16
```

Scatterplot by Level Code


```
Analysis of Variance for bssof - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares    Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                 91.9437        4       22.9859        2.37      0.1165

RESIDUAL               106.826        11        9.71143
--------------------------------------------------------------------------------
TOTAL (CORRECTED)      198.769        15
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  No statistically significant differences in the average BSSOF
among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  No statistically significant differences in the average BSSOF among
the fuels.

Multiple Range Tests for bssof by fuel

--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
fuel            Count     LS Mean          Homogeneous Groups
```

```
--------------------------------------------------------------------------------
ADMM15          3          2.83784              X
FT-100          3          3.16754              X
CA              3          6.36478              X
DF-2            3          7.86606              X
ALS             4          8.60195              X
--------------------------------------------------------------------------------
Contrast                                   Difference        +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                               -5.76411          7.70442
ADMM15 - CA                                -3.52694          8.23638
ADMM15 - DF-2                              -5.02821          8.23638
ADMM15 - FT-100                            -0.329696         8.23638
ALS - CA                                    2.23717          7.70442
ALS - DF-2                                  0.735895         7.70442
ALS - FT-100                                5.43441          7.70442
CA - DF-2                                   -1.50128         8.23638
CA - FT-100                                  3.19724         8.23638
DF-2 - FT-100                                4.69852         8.23638
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

```
Multifactor ANOVA - Benzene (mg/kW-hr)    Toxic Gaseous Emissions
                      LPP Only    Mode 12

Analysis Summary

Dependent variable: BENZENE
Factors:
        FUEL
Selection variable: MODE=12

Number of complete cases: 16
```

Scatterplot by Level Code


```
Analysis of Variance for BENZENE - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:FUEL                  90429.9      4       22607.5      2.31     0.1230

RESIDUAL                107777.0     11        9797.87
--------------------------------------------------------------------------------
TOTAL (CORRECTED)       198206.0     15
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.
```

```
CONCLUSION:  No statistically significant differences in the average benzene
among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  No statistically significant differences in the average benzene among
the fuels.
```

```
Multiple Range Tests for BENZENE by FUEL
```

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
FUEL            Count      LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
FT-100           3         117.955             X
ADMM15           3         178.153             X
DF-2             3         241.471             X
CA               3         249.61              X
ALS              4         333.891             X
--------------------------------------------------------------------------------
Contrast                                   Difference          +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                                -155.738            244.717
ADMM15 - CA                                 -71.4565            261.614
ADMM15 - DF-2                               -63.3182            261.614
ADMM15 - FT-100                             60.198              261.614
ALS - CA                                    84.2815             244.717
ALS - DF-2                                  92.4198             244.717
ALS - FT-100                                215.936             244.717
CA - DF-2                                   8.13835             261.614
CA - FT-100                                 131.654             261.614
DF-2 - FT-100                               123.516             261.614
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

G-16

```
Multifactor ANOVA - 1,3 Butadiene (mg/kW-hr)   Toxic Gaseous Emissions
                     LPP Only   Mode 12

Analysis Summary

Dependent variable: BUTAD
Factors:
        FUEL
Selection variable: MODE=12

Number of complete cases: 16
```

Scatterplot by Level Code


```
Analysis of Variance for BUTAD - Type III Sums of Squares
--------------------------------------------------------------------------------
Source                 Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:FUEL                     169229.0     4       42307.4      2.06     0.1547

RESIDUAL                    225726.0    11       20520.5
--------------------------------------------------------------------------------
TOTAL (CORRECTED)           394955.0    15
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.


CONCLUSION:  No statistically significant differences in the average 1,3 Butadiene
among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  No statistically significant differences in the average 1,3 Butadiene
among the fuels.


Multiple Range Tests for BUTAD by FUEL
```

G-17

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
FUEL             Count      LS Mean         Homogeneous Groups
--------------------------------------------------------------------------------
CA               3          196.865             X
ADMM15           3          216.494             X
DF-2             3          229.33              X
FT-100           3          282.903             X
ALS              4          460.173             X
--------------------------------------------------------------------------------
Contrast                                 Difference          +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                              -243.679           354.155
ADMM15 - CA                                19.6288           378.607
ADMM15 - DF-2                             -12.8365           378.607
ADMM15 - FT-100                           -66.4091           378.607
ALS - CA                                   263.308           354.155
ALS - DF-2                                 230.843           354.155
ALS - FT-100                               177.27            354.155
CA - DF-2                                 -32.4653           378.607
CA - FT-100                               -86.0379           378.607
DF-2 - FT-100                             -53.5726           378.607
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

```
Multifactor ANOVA - Formaldehyde (mg/kW-hr)   Toxic Gaseous Emissions
                    LPP Only   Mode 12

Analysis Summary

Dependent variable: FORMALD
Factors:
        FUEL
Selection variable: MODE=12

Number of complete cases: 16
```

Scatterplot by Level Code


```
Analysis of Variance for FORMALD - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares   Df    Mean Square    F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:FUEL                 4.23523E8      4      1.05881E8      1.38     0.3020

RESIDUAL                8.41735E8     11      7.65213E7
--------------------------------------------------------------------------------
TOTAL (CORRECTED)       1.26526E9     15
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.


CONCLUSION:  No statistically significant differences in the average formaldehyde
among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  No statistically significant differences in the average
formaldehyde among the fuels.


Multiple Range Tests for FORMALD by FUEL
```

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
FUEL            Count     LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
CA              3         18177.0          X
FT-100          3         23723.0          X
ADMM15          3         29186.9          X
DF-2            3         30348.2          X
ALS             4         32241.5          X
--------------------------------------------------------------------------------
Contrast                                   Difference       +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                               -3054.63         21626.7
ADMM15 - CA                                11009.9          23119.9
ADMM15 - DF-2                              -1161.35         23119.9
ADMM15 - FT-100                            5463.88          23119.9
ALS - CA                                   14064.5          21626.7
ALS - DF-2                                 1893.28          21626.7
ALS - FT-100                               8518.5           21626.7
CA - DF-2                                  -12171.2         23119.9
CA - FT-100                                -5545.99         23119.9
DF-2 - FT-100                              6625.22          23119.9
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

```
Multifactor ANOVA - Acetaldehyde (mg/Kw-hr)   Toxic Gaseous Emissions
                    LPP Only   Mode 12

Analysis Summary

Dependent variable: ACETALD
Factors:
        FUEL
Selection variable: MODE=12

Number of complete cases: 16
```

Scatterplot by Level Code


```
Analysis of Variance for ACETALD - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares   Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:FUEL                 2.19352E8     4      5.48381E7       5.37      0.0121

RESIDUAL                1.12414E8    11      1.02195E7
--------------------------------------------------------------------------------
TOTAL (CORRECTED)       3.31766E8    15
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.


CONCLUSION:  Statistically significant differences in the average acetaldehyde
among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average acetaldehyde for the DF-2 fuel is significantly
different than the ALS and CA fuels.


Multiple Range Tests for ACETALD by FUEL

--------------------------------------------------------------------------------
```

```
Method: 95.0 percent Tukey HSD
FUEL            Count    LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
CA                3      2928.49           X
ALS               4      5079.77           X
FT-100            3      8856.78           XX
ADMM15            3      10477.5           XX
DF-2              3      13400.4            X
--------------------------------------------------------------------------------
Contrast                              Difference          +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                           5397.77             7903.37
ADMM15 - CA                            7549.06             8449.06
ADMM15 - DF-2                         -2922.88             8449.06
ADMM15 - FT-100                        1620.77             8449.06
ALS - CA                               2151.28             7903.37
ALS - DF-2                           *-8320.65             7903.37
ALS - FT-100                          -3777.01             7903.37
CA - DF-2                            *-10471.9             8449.06
CA - FT-100                           -5928.29             8449.06
DF-2 - FT-100                          4543.65             8449.06
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

G-22

```
Multifactor ANOVA - Naphthalene (µg/kW-hr)   Gaseous PAH
                    LPP Only    Mode 12

Analysis Summary

Dependent variable: GNAPHTH
Factors:
        FUEL
Selection variable: MODE=12

Number of complete cases: 16
```

Scatterplot by Level Code


```
Analysis of Variance for GNAPHTH - Type III Sums of Squares
--------------------------------------------------------------------------------
Source               Sum of Squares    Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:FUEL                 6.71331E10      4     1.67833E10      25.16     0.0000

RESIDUAL                7.33698E9      11     6.66998E8
--------------------------------------------------------------------------------
TOTAL (CORRECTED)       7.44701E10     15
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.


CONCLUSION:  Statistically significant differences in the average naphthalene
among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  There are two distinct fuel groupings with respect to the average
naphthalene.  The DF-2 and CA fuels are not significantly different from one another
but are significantly different from the remaining three fuels.  The ALS, ADMM15,
and FT-100 fuels are not significantly different from one another, but are
significantly different from the remaining two fuels.
```

G-23

```
Multiple Range Tests for GNAPHTH by FUEL


--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
FUEL            Count    LS Mean           Homogeneous Groups
--------------------------------------------------------------------------------
FT-100          3        6057.98           X
ADMM15          3        23712.5           X
ALS             4        56373.7           X
DF-2            3        130839.0           X
CA              3        182116.0           X
--------------------------------------------------------------------------------
Contrast                                  Difference        +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                               -32661.2         63850.0
ADMM15 - CA                               *-158403.0        68258.5
ADMM15 - DF-2                             *-107126.0        68258.5
ADMM15 - FT-100                            17654.5          68258.5
ALS - CA                                  *-125742.0        63850.0
ALS - DF-2                                *-74465.1         63850.0
ALS - FT-100                               50315.7          63850.0
CA - DF-2                                  51276.7          68258.5
CA - FT-100                               *176058.0         68258.5
DF-2 - FT-100                             *124781.0         68258.5
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

```
Multifactor ANOVA - 2-Methylnaphthalene (µg/kW-hr)   Gaseous PAH
                      LPP Only   Mode 12

Analysis Summary

Dependent variable: METHYL2
Factors:
        FUEL
Selection variable: MODE=12

Number of complete cases: 16
```

Scatterplot by Level Code


```
Analysis of Variance for METHYL2 - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:FUEL               9.06153E10      4     2.26538E10    35.30    0.0000

RESIDUAL              7.05945E9      11      6.41768E8
--------------------------------------------------------------------------------
TOTAL (CORRECTED)    9.76748E10     15
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.


CONCLUSION:  Statistiaclly significant differences in the average 2-methylnaphthalene
among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  There are three distinct fuel groupings with respect to the average
2-methylnaphthalene.  The FT-100, ADMM15, and ALS fuels are not significantly
different from one another, but are significantly different from the remaining
two fuels.  The CA and DF-2 fuels are significantly different from one another and
the remaining three fuels.
```

```
Multiple Range Tests for METHYL2 by FUEL

--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
FUEL          Count    LS Mean           Homogeneous Groups
--------------------------------------------------------------------------------
FT-100         3       2255.56           X
ADMM15         3       17201.2           X
ALS            4       40670.6           X
CA             3       106437.0           X
DF-2           3       212921.0           X
--------------------------------------------------------------------------------
Contrast                                 Difference        +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                              -23469.4         62630.8
ADMM15 - CA                              *-89235.8         66955.1
ADMM15 - DF-2                            *-195719.0        66955.1
ADMM15 - FT-100                           14945.6          66955.1
ALS - CA                                 *-65766.4         62630.8
ALS - DF-2                               *-172250.0        62630.8
ALS - FT-100                              38415.1          62630.8
CA - DF-2                                *-106484.0        66955.1
CA - FT-100                              *104181.0         66955.1
DF-2 - FT-100                            *210665.0         66955.1
--------------------------------------------------------------------------------

* denotes a statistically significant difference.
```

```
Multifactor ANOVA - 1-Methylnaphthalene (µg/kW-hr)  Gaseous PAH
                    LPP Only   Mode 12

Analysis Summary

Dependent variable: METHYL1
Factors:
        FUEL
Selection variable: MODE=12

Number of complete cases: 16
```

Scatterplot by Level Code


```
Analysis of Variance for METHYL1 - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:FUEL                 3.95519E10    4     9.88796E9      49.21    0.0000

RESIDUAL                2.21039E9    11     2.00944E8
--------------------------------------------------------------------------------
TOTAL (CORRECTED)       4.17622E10   15
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.


CONCLUSION:  Statistically significant differences in the average 1-methylnaphthalene
among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  There are three distinct fuel groupings with respect to the average
1-methylnaphthalene.  The FT-100, ADMM15, and ALS fuels are not significantly different
from one another, but are significantly different from the remaining
two fuels.  The CA and DF-2 fuels are significantly different from one another
and the remaining three fuels.
```

```
Multiple Range Tests for METHYL1 by FUEL

--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
FUEL            Count     LS Mean           Homogeneous Groups
--------------------------------------------------------------------------------
FT-100          3         1428.58           X
ADMM15          3         8078.03           X
ALS             4         21017.6           X
CA              3         57939.9            X
DF-2            3         139827.0            X
--------------------------------------------------------------------------------
Contrast                                Difference          +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                             -12939.5           35045.8
ADMM15 - CA                             *-49861.8           37465.6
ADMM15 - DF-2                           *-131749.0          37465.6
ADMM15 - FT-100                          6649.44            37465.6
ALS - CA                                *-36922.3           35045.8
ALS - DF-2                              *-118809.0          35045.8
ALS - FT-100                             19589.0            35045.8
CA - DF-2                               *-81886.7           37465.6
CA - FT-100                             *56511.3            37465.6
DF-2 - FT-100                           *138398.0           37465.6
--------------------------------------------------------------------------------
* denotes a statistically significant difference.
```

```
Multifactor ANOVA - 2,6-Dimethylnaphthalene (µg/kW-hr)   Gaseous PAH
                      LPP Only   Mode 12

Analysis Summary

Dependent variable: DIMETHYL
Factors:
        FUEL
Selection variable: MODE=12

Number of complete cases: 16
```


Scatterplot by Level Code

```
Analysis of Variance for DIMETHYL - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares   Df    Mean Square    F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:FUEL                3.47244E10      4      8.68109E9      82.28    0.0000

RESIDUAL               1.16051E9      11      1.05501E8
--------------------------------------------------------------------------------
TOTAL (CORRECTED)      3.58849E10     15
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.


CONCLUSION:  Statistically significant differences in the average 2,6-dimethylnaphthalene
among the fuels.
```


Means and 95% Tukey HSD Intervals

```
CONCLUSION:  The average 2,6-dimethylnaphthalene for the DF-2 fuel is significantly
different than the remaining four fuels.  The average 2,6-dimethylnaphthalene for
the ADMM15, ALS, CA, and FT-100 fuels are not significantly different from one
another.
```

```
Multiple Range Tests for DIMETHYL by FUEL

--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
FUEL          Count    LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
FT-100        3        1362.24          X
ADMM15        3        2047.66          X
ALS           4        11261.4          X
CA            3        26261.0          X
DF-2          3        127567.0          X
--------------------------------------------------------------------------------
Contrast                              Difference        +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                          -9213.7           25393.8
ADMM15 - CA                           -24213.3          27147.1
ADMM15 - DF-2                         *-125519.0         27147.1
ADMM15 - FT-100                       685.424           27147.1
ALS - CA                              -14999.6          25393.8
ALS - DF-2                            *-116306.0         25393.8
ALS - FT-100                          9899.13           25393.8
CA - DF-2                             *-101306.0         27147.1
CA - FT-100                           24898.8           27147.1
DF-2 - FT-100                         *126205.0          27147.1
--------------------------------------------------------------------------------
* denotes a statistically significant difference.
```

G-30

```
Multifactor ANOVA - Acenaphthylene (µg/kW-hr)   Gaseous PAH
                    LPP Only   Mode 12

Analysis Summary

Dependent variable: GACENAPH
Factors:
        FUEL
Selection variable: MODE=12

Number of complete cases: 16
```

Scatterplot by Level Code


```
Analysis of Variance for GACENAPH - Type III Sums of Squares
-------------------------------------------------------------------------------
Source                 Sum of Squares   Df   Mean Square   F-Ratio   P-Value
-------------------------------------------------------------------------------
MAIN EFFECTS
 A:FUEL                   4.45816E7       4    1.11454E7     18.31    0.0001

RESIDUAL                  6.69741E6      11     608855.0
-------------------------------------------------------------------------------
TOTAL (CORRECTED)         5.1279E7       15
-------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.
```

```
CONCLUSION:  Statistically significant differences in the average acenaphthylene
among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average acenaphthylene for the DF-2 fuel is significantly different
than the remaining four fuels.  The average acenaphthylene for the ADMM15, ALS, CA,
and FT-100 fuels are not significantly different from one another.
```

```
Multiple Range Tests for GACENAPH by FUEL
```

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
FUEL          Count     LS Mean        Homogeneous Groups
--------------------------------------------------------------------------------
FT-100         3        888.181            X
ADMM15         3        953.779            X
CA             3        1925.62            X
ALS            4        2638.22            X
DF-2           3        5591.2              X
--------------------------------------------------------------------------------
Contrast                                 Difference        +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                              -1684.44          1929.1
ADMM15 - CA                               -971.841          2062.3
ADMM15 - DF-2                            *-4637.42          2062.3
ADMM15 - FT-100                           65.5985           2062.3
ALS - CA                                  712.6             1929.1
ALS - DF-2                               *-2952.98          1929.1
ALS - FT-100                              1750.04           1929.1
CA - DF-2                                *-3665.58          2062.3
CA - FT-100                               1037.44           2062.3
DF-2 - FT-100                            *4703.02           2062.3
--------------------------------------------------------------------------------

* denotes a statistically significant difference.
```

```
Multifactor ANOVA - Acenaphthene (µg/kW-hr)   Gaseous PAH
                    LPP Only   Mode 12

Analysis Summary

Dependent variable: ACENAPTH
Factors:
        FUEL
Selection variable: MODE=12

Number of complete cases: 16
```

Scatterplot by Level Code


```
Analysis of Variance for ACENAPTH - Type III Sums of Squares
--------------------------------------------------------------------------------
Source                Sum of Squares    Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:FUEL                  5.40536E8        4     1.35134E8      72.59     0.0000

RESIDUAL                 2.04774E7       11     1.86158E6
--------------------------------------------------------------------------------
TOTAL (CORRECTED)        5.61013E8       15
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.


CONCLUSION:  Statistically significant differences in the average acenaphthene
among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average acenaphthene for the DF-2 fuel is significantly different
than the remaining four fuels.  The average acenaphthene for the FT-100, ADMM15, ALS,
and CA fuels are not significantly different from one another.


Multiple Range Tests for ACENAPTH by FUEL
```

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
FUEL           Count     LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
FT-100           3       195.774             X
ADMM15           3       907.615             X
ALS              4       1706.53             X
CA               3       2385.88             X
DF-2             3       16107.0              X
--------------------------------------------------------------------------------
Contrast                                Difference        +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                             -798.92          3373.18
ADMM15 - CA                              -1478.26         3606.08
ADMM15 - DF-2                           *-15199.4         3606.08
ADMM15 - FT-100                          711.84           3606.08
ALS - CA                                 -679.344         3373.18
ALS - DF-2                              *-14400.5         3373.18
ALS - FT-100                             1510.76          3373.18
CA - DF-2                               *-13721.1         3606.08
CA - FT-100                              2190.1           3606.08
DF-2 - FT-100                           *15911.2          3606.08
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

G-34

```
Multifactor ANOVA - Fluorene (µg/kW-hr)   Gaseous PAH
                    LPP Only    Mode 12

Analysis Summary

Dependent variable: GFLUOREN
Factors:
        FUEL
Selection variable: MODE=12

Number of complete cases: 16
```

Scatterplot by Level Code


```
Analysis of Variance for GFLUOREN - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares   Df    Mean Square    F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:FUEL                 1.25657E9      4      3.14143E8     194.31    0.0000

RESIDUAL                1.77834E7     11      1.61668E6
--------------------------------------------------------------------------------
TOTAL (CORRECTED)       1.27436E9     15
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.


CONCLUSION:  Statistically significant differences in the average fluorene among
the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average fluorene for the DF-2 fuel is significantly different
than the remaining four fuels.  The average fluorene for the ADMM15, ALS, CA, and
FT-100 fuels are not significantly different from one another.


Multiple Range Tests for GFLUOREN by FUEL
```

```
--------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
FUEL            Count     LS Mean        Homogeneous Groups
--------------------------------------------------------------------------
ADMM15            3       296.702            X
FT-100            3       305.082            X
ALS               4       939.148            X
CA                3       2767.23            X
DF-2              3       23660.4             X
--------------------------------------------------------------------------
Contrast                                  Difference        +/-  Limits
--------------------------------------------------------------------------
ADMM15 - ALS                              -642.446          3143.48
ADMM15 - CA                               -2470.53          3360.52
ADMM15 - DF-2                            *-23363.7          3360.52
ADMM15 - FT-100                           -8.3802           3360.52
ALS - CA                                  -1828.08          3143.48
ALS - DF-2                               *-22721.3          3143.48
ALS - FT-100                              634.066           3143.48
CA - DF-2                                *-20893.2          3360.52
CA - FT-100                               2462.15           3360.52
DF-2 - FT-100                            *23355.3           3360.52
--------------------------------------------------------------------------

* denotes a statistically significant difference.
```

```
Multifactor ANOVA - Phenanthrene (µg/kW-hr)    Gaseous PAH
                    LPP Only    Mode 12

Analysis Summary

Dependent variable: GPHENANT
Factors:
        FUEL
Selection variable: MODE=12

Number of complete cases: 16
```

Scatterplot by Level Code


```
Analysis of Variance for GPHENANT - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares    Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:FUEL                1.41708E9       4       3.5427E8      168.73     0.0000

RESIDUAL               2.30963E7      11     2.09967E6
--------------------------------------------------------------------------------
TOTAL (CORRECTED)      1.44018E9      15
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.


CONCLUSION:  Statistically significant differences in the average phenanthrene
among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average phenanthrene for the DF-2 fuel is significantly different
than the remaining four fuels.  The average phenanthrene for the ADMM15, ALS,
CA, and FT-100 fuels are not significantly different from one another.


Multiple Range Tests for GPHENANT by FUEL
```

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
FUEL           Count    LS Mean           Homogeneous Groups
--------------------------------------------------------------------------------
ADMM15         3        457.248           X
FT-100         3        699.826           X
ALS            4        1891.43           X
CA             3        2267.23           X
DF-2           3        25421.1            X
--------------------------------------------------------------------------------
Contrast                                 Difference        +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                             -1434.18          3582.4
ADMM15 - CA                              -1809.99          3829.74
ADMM15 - DF-2                            *-24963.9         3829.74
ADMM15 - FT-100                          -242.578          3829.74
ALS - CA                                 -375.802          3582.4
ALS - DF-2                               *-23529.7         3582.4
ALS - FT-100                             1191.6            3582.4
CA - DF-2                                *-23153.9         3829.74
CA - FT-100                              1567.41           3829.74
DF-2 - FT-100                            *24721.3          3829.74
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

```
Multifactor ANOVA - Anthracene (µg/kW-hr)    Gaseous PAH
                    LPP Only    Mode 12

Analysis Summary

Dependent variable: GANTHR
Factors:
        FUEL
Selection variable: MODE=12

Number of complete cases: 16
```

Scatterplot by Level Code


```
Analysis of Variance for GANTHR - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:FUEL                 570491.0      4       142623.0     26.36    0.0000

RESIDUAL                 59515.0     11         5410.46
--------------------------------------------------------------------------------
TOTAL (CORRECTED)       630006.0     15
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.


CONCLUSION:  Statistically significant differences in the average anthracene
among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average anthracene for the DF-2 fuel is significantly different
than the remaining four fuels.  The average anthracene for the ADMM15, ALS, CA,
and FT-100 fuels are not significantly different from one another.


Multiple Range Tests for GANTHR by FUEL
```

G-39

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
FUEL            Count     LS Mean        Homogeneous Groups
--------------------------------------------------------------------------------
ADMM15          3         22.3976            X
FT-100          3         29.4149            X
ALS             4         54.2201            X
CA              3         129.708            X
DF-2            3         533.053             X
--------------------------------------------------------------------------------
Contrast                                  Difference         +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                               -31.8225          181.851
ADMM15 - CA                                -107.311          194.407
ADMM15 - DF-2                             *-510.655          194.407
ADMM15 - FT-100                            -7.01737          194.407
ALS - CA                                   -75.4884          181.851
ALS - DF-2                                *-478.833          181.851
ALS - FT-100                               24.8052           181.851
CA - DF-2                                 *-403.344          194.407
CA - FT-100                                100.294           194.407
DF-2 - FT-100                             *503.638           194.407
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

G-40

```
Multifactor ANOVA - Fluoranthene (μg/kW-hr)   Gaseous PAH
                    LPP Only   Mode 12

Analysis Summary

Dependent variable: GFLUORAN
Factors:
        FUEL
Selection variable: MODE=12

Number of complete cases: 15
```

Scatterplot by Level Code

Analysis of Variance for GFLUORAN - Type III Sums of Squares

Source	Sum of Squares	Df	Mean Square	F-Ratio	P-Value
MAIN EFFECTS					
A:FUEL	1489.76	4	372.439	2.57	0.1028
RESIDUAL	1447.56	10	144.756		
TOTAL (CORRECTED)	2937.32	14			

All F-ratios are based on the residual mean square error.

```
CONCLUSION:  No statistically significant differences in the average fluoranthene
among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  No statistically significant differences in the average fluoranthene
among the fuels.


Multiple Range Tests for GFLUORAN by FUEL

--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
```

```
FUEL           Count    LS Mean        Homogeneous Groups
--------------------------------------------------------------------------
ADMM15         3        14.0387        X
FT-100         3        27.4609        X
DF-2           2        29.9511        X
ALS            4        39.9585        X
CA             3        40.4149        X
--------------------------------------------------------------------------
Contrast                               Difference        +/-  Limits
--------------------------------------------------------------------------
ADMM15 - ALS                           -25.9198          30.245
ADMM15 - CA                            -26.3762          32.3333
ADMM15 - DF-2                          -15.9124          36.1497
ADMM15 - FT-100                        -13.4222          32.3333
ALS - CA                               -0.45635          30.245
ALS - DF-2                             10.0074           34.2946
ALS - FT-100                           12.4976           30.245
CA - DF-2                              10.4638           36.1497
CA - FT-100                            12.9539           32.3333
DF-2 - FT-100                          2.49016           36.1497
--------------------------------------------------------------------------
```

* denotes a statistically significant difference.

G-42

```
Multifactor ANOVA - Pyrene (μg/kW-hr)   Gaseous PAH
                    LPP Only   Mode 12

Analysis Summary

Dependent variable: GPYRENE
Factors:
        FUEL
Selection variable: MODE=12

Number of complete cases: 16
```

Scatterplot by Level Code


```
Analysis of Variance for GPYRENE - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares    Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:FUEL                 2271.39        4       567.846       3.61      0.0409

RESIDUAL                1728.66       11       157.15
--------------------------------------------------------------------------------
TOTAL (CORRECTED)       4000.04       15
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.


CONCLUSION:  Statistically significant differences in the average pyrene among the
fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average pyrene for the DF-2 fuel is significantly different
than the ADMM15 fuel.


Multiple Range Tests for GPYRENE by FUEL
```

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
FUEL            Count    LS Mean         Homogeneous Groups
--------------------------------------------------------------------------------
ADMM15          3        12.7041         X
FT-100          3        21.803          XX
CA              3        33.2915         XX
ALS             4        39.4763         XX
DF-2            3        46.4006          X
--------------------------------------------------------------------------------
Contrast                                 Difference        +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                             -26.7722          30.9925
ADMM15 - CA                              -20.5875          33.1324
ADMM15 - DF-2                            *-33.6965         33.1324
ADMM15 - FT-100                          -9.09893          33.1324
ALS - CA                                 6.18478           30.9925
ALS - DF-2                               -6.92426          30.9925
ALS - FT-100                             17.6733           30.9925
CA - DF-2                                -13.109           33.1324
CA - FT-100                              11.4885           33.1324
DF-2 - FT-100                            24.5976           33.1324
--------------------------------------------------------------------------------

* denotes a statistically significant difference.
```

```
Multifactor ANOVA - Naphthalene (µg/kW-hr)    Soluble PAH
                       LPP Only    Mode 12

Analysis Summary

Dependent variable: naphth
Factors:
        fuel
Selection variable: mode=12

Number of complete cases: 16
```

Scatterplot by Level Code


```
Analysis of Variance for naphth - Type III Sums of Squares
--------------------------------------------------------------------------------
Source                Sum of Squares    Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                     834111.0     4       208528.0       2.44     0.1094

RESIDUAL                    941727.0    11        85611.6
--------------------------------------------------------------------------------
TOTAL (CORRECTED)          1.77584E6    15
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  No statistically significant differences in the average naphthalene
among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  No statistically significant differnces in the average naphthalene
among the fuels.


Multiple Range Tests for naphth by fuel

--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
```

```
fuel            Count    LS Mean         Homogeneous Groups
--------------------------------------------------------------------------------
ALS             4        192.221         X
CA              3        541.585         X
ADMM15          3        553.687         X
DF-2            3        732.529         X
FT-100          3        822.211         X
--------------------------------------------------------------------------------
Contrast                                 Difference        +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                             361.466           723.377
ADMM15 - CA                              12.1018           773.323
ADMM15 - DF-2                            -178.842          773.323
ADMM15 - FT-100                          -268.524          773.323
ALS - CA                                 -349.364          723.377
ALS - DF-2                               -540.308          723.377
ALS - FT-100                             -629.99           723.377
CA - DF-2                                -190.943          773.323
CA - FT-100                              -280.625          773.323
DF-2 - FT-100                            -89.682           773.323
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

```
Multifactor ANOVA - Acenaphthylene (µg/kW-hr)   Soluble PAH
                   LPP Only   Mode 12

Analysis Summary

Dependent variable: acenaph
Factors:
        fuel
Selection variable: mode=12

Number of complete cases: 16
```

Scatterplot by Level Code


```
Analysis of Variance for acenaph - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                4687.94        4       1171.98      11.34    0.0007

RESIDUAL               1136.45       11       103.314
--------------------------------------------------------------------------------
TOTAL (CORRECTED)      5824.39       15
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.
```

CONCLUSION: Statistically significant differences in the average acenaphthylene among the fuels.

Means and 95% Tukey HSD Intervals

CONCLUSION: The average acenaphthylene for the DF-2 fuel is significantly different than the remaining four fuels. The average acenaphthylene for the ADMM15, ALS, CA, and FT-100 fuels are not significantly different.

```
Multiple Range Tests for acenaph by fuel

--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
```

```
fuel          Count    LS Mean        Homogeneous Groups
--------------------------------------------------------------------------------
ADMM15        3        10.2537        X
FT-100        3        10.5474        X
ALS           4        11.3751        X
CA            3        23.1257        X
DF-2          3        55.8058         X
--------------------------------------------------------------------------------
Contrast                              Difference        +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                          -1.12136          25.1292
ADMM15 - CA                           -12.872           26.8642
ADMM15 - DF-2                         *-45.5521         26.8642
ADMM15 - FT-100                       -0.293675         26.8642
ALS - CA                              -11.7506          25.1292
ALS - DF-2                            *-44.4307         25.1292
ALS - FT-100                          0.827684          25.1292
CA - DF-2                             *-32.6801         26.8642
CA - FT-100                           12.5783           26.8642
DF-2 - FT-100                         *45.2584          26.8642
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

```
Multifactor ANOVA - Acenaphthene (µg/kW-hr)   Soluble PAH
                    LPP Only   Mode 12

Analysis Summary

Dependent variable: acenapth
Factors:
        fuel
Selection variable: mode=12

Number of complete cases: 16
```

Scatterplot by Level Code


```
Analysis of Variance for acenapth - Type III Sums of Squares
--------------------------------------------------------------------------------
Source               Sum of Squares    Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                   16485.5       4        4121.37       2.36     0.1170

RESIDUAL                  19189.6      11        1744.51
--------------------------------------------------------------------------------
TOTAL (CORRECTED)         35675.1      15
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.

CONCLUSION:  No statistically significant differences in the average acenaphthene
among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  No statistically significant differences in the average acenaphthene
among the fuels.


Multiple Range Tests for acenapth by fuel

--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
```

```
fuel            Count   LS Mean         Homogeneous Groups
--------------------------------------------------------------------------
ALS             4       29.8938         X
ADMM15          3       78.0651         X
CA              3       94.6604         X
FT-100          3       98.0092         X
DF-2            3       120.096         X
--------------------------------------------------------------------------
Contrast                                Difference      +/-  Limits
--------------------------------------------------------------------------
ADMM15 - ALS                            48.1713         103.261
ADMM15 - CA                             -16.5953        110.39
ADMM15 - DF-2                           -42.0307        110.39
ADMM15 - FT-100                         -19.9441        110.39
ALS - CA                                -64.7666        103.261
ALS - DF-2                              -90.2021        103.261
ALS - FT-100                            -68.1155        103.261
CA - DF-2                               -25.4354        110.39
CA - FT-100                             -3.34881        110.39
DF-2 - FT-100                           22.0866         110.39
--------------------------------------------------------------------------
```

* denotes a statistically significant difference.

```
Multifactor ANOVA - Fluorene (µg/kW-hr)    Soluble PAH
                    LPP Only    Mode 12

Analysis Summary

Dependent variable: fluorene
Factors:
        fuel
Selection variable: mode=12

Number of complete cases: 16
```

Scatterplot by Level Code


```
Analysis of Variance for fluorene - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                 151451.0      4       37862.7      4.26     0.0254

RESIDUAL                 97880.1     11       8898.19
--------------------------------------------------------------------------------
TOTAL (CORRECTED)       249331.0     15
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.


CONCLUSION:  Statistically signficant differences in the average fluorene among
the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average fluorene for the DF-2 fuel is significantly different
than the ALS fuel.


Multiple Range Tests for fluorene by fuel

--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
```

```
fuel            Count   LS Mean         Homogeneous Groups
------------------------------------------------------------------------
ALS             4       59.0582         X
ADMM15          3       118.419         XX
FT-100          3       126.625         XX
CA              3       219.753         XX
DF-2            3       334.938          X
------------------------------------------------------------------------
Contrast                                Difference      +/-  Limits
------------------------------------------------------------------------
ADMM15 - ALS                            59.3603         233.211
ADMM15 - CA                             -101.334        249.313
ADMM15 - DF-2                           -216.519        249.313
ADMM15 - FT-100                         -8.20674        249.313
ALS - CA                                -160.695        233.211
ALS - DF-2                              *-275.879       233.211
ALS - FT-100                            -67.5671        233.211
CA - DF-2                               -115.185        249.313
CA - FT-100                             93.1275         249.313
DF-2 - FT-100                           208.312         249.313
------------------------------------------------------------------------
```

* denotes a statistically significant difference.

```
Multifactor ANOVA - Phenanthrene (µg/kW-hr)   Soluble PAH
                    LPP Only   Mode 12

Analysis Summary

Dependent variable: phenanth
Factors:
        fuel
Selection variable: mode=12

Number of complete cases: 16
```

Scatterplot by Level Code


```
Analysis of Variance for phenanth - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares   Df    Mean Square    F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                2.62026E8      4     6.55064E7      44.22     0.0000

RESIDUAL               1.62965E7     11     1.4815E6
--------------------------------------------------------------------------------
TOTAL (CORRECTED)      2.78322E8     15
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.
```

```
CONCLUSION:  Statistically significant differences in the average phenanthrene
among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average phenanthrene for the DF-2 fuel is significantly different
than the remaining four fuels.  The average phenanthrene for the ADMM15, FT-100,
ALS, and CA fuels are not significantly different from one another.
```

```
Multiple Range Tests for phenanth by fuel
```

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
fuel          Count    LS Mean        Homogeneous Groups
--------------------------------------------------------------------------------
ADMM15          3      459.058            X
FT-100          3      572.378            X
ALS             4      736.461            X
CA              3      2331.39            X
DF-2            3      11230.9             X
--------------------------------------------------------------------------------
Contrast                                  Difference        +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                               -277.403          3009.19
ADMM15 - CA                                -1872.33          3216.96
ADMM15 - DF-2                             *-10771.8          3216.96
ADMM15 - FT-100                            -113.32           3216.96
ALS - CA                                   -1594.93          3009.19
ALS - DF-2                                *-10494.4          3009.19
ALS - FT-100                                164.083          3009.19
CA - DF-2                                 *-8899.49          3216.96
CA - FT-100                                1759.01           3216.96
DF-2 - FT-100                             *10658.5           3216.96
--------------------------------------------------------------------------------

* denotes a statistically significant difference.
```

```
Multifactor ANOVA - Anthracene (µg/kW-hr)   Soluble PAH
                    LPP Only   Mode 12

Analysis Summary

Dependent variable: anthr
Factors:
        fuel
Selection variable: mode=12

Number of complete cases: 16
```

Scatterplot by Level Code


```
Analysis of Variance for anthr - Type III Sums of Squares
--------------------------------------------------------------------------------
Source               Sum of Squares   Df   Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                  180940.0      4      45234.9      30.26    0.0000

RESIDUAL                  16443.1     11       1494.83
--------------------------------------------------------------------------------
TOTAL (CORRECTED)        197383.0     15
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.
```

```
CONCLUSION:  Statistically significant differences in the average anthracene
among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average anthracene for the DF-2 fuel is significantly different
than the remaining four fuels.  The average anthracene for the ADMM15, ALS, CA,
and FT-100 fuels are not significantly different from one another.
```

```
Multiple Range Tests for anthr by fuel

--------------------------------------------------------------------------------
```

```
Method: 95.0 percent Tukey HSD
fuel            Count    LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
ALS              4       25.7452          X
ADMM15           3       37.8165          X
FT-100           3       46.7152          X
CA               3       66.3094          X
DF-2             3       312.962           X
--------------------------------------------------------------------------------
Contrast                                  Difference        +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                              12.0713           95.5861
ADMM15 - CA                               -28.493           102.186
ADMM15 - DF-2                             *-275.145         102.186
ADMM15 - FT-100                           -8.89873          102.186
ALS - CA                                  -40.5643          95.5861
ALS - DF-2                                *-287.217         95.5861
ALS - FT-100                              -20.97            95.5861
CA - DF-2                                 *-246.652         102.186
CA - FT-100                               19.5943           102.186
DF-2 - FT-100                             *266.247          102.186
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

G-56

```
Multifactor ANOVA - Fluoranthene (µg/kW-hr)    Soluble PAH
                     LPP Only   Mode 12

Analysis Summary

Dependent variable: fluoran
Factors:
        fuel
Selection variable: mode=12

Number of complete cases: 16
```

Scatterplot by Level Code


```
Analysis of Variance for fluoran - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares    Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                 3.96106E6      4       990264.0      50.53     0.0000

RESIDUAL                215558.0      11        19596.2
--------------------------------------------------------------------------------
TOTAL (CORRECTED)      4.17661E6      15
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.
```

```
CONCLUSION:  Statistically significant differences in the average fluoranthene
among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average fluoranthene for the DF-2 fuel is significantly different
than the remaining four fuels.  The average fluoranthene for the ADMM15, ALS, CA,
 and FT-100 fuels are not significantly different from one another.
```

```
Multiple Range Tests for fluoran by fuel
```

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
fuel            Count     LS Mean        Homogeneous Groups
--------------------------------------------------------------------------------
ADMM15          3         98.2249        X
FT-100          3         144.586        X
ALS             4         205.029        X
CA              3         375.497        X
DF-2            3         1459.07         X
--------------------------------------------------------------------------------
Contrast                                 Difference         +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                             -106.804           346.086
ADMM15 - CA                              -277.272           369.982
ADMM15 - DF-2                            *-1360.84          369.982
ADMM15 - FT-100                          -46.3612           369.982
ALS - CA                                 -170.468           346.086
ALS - DF-2                               *-1254.04          346.086
ALS - FT-100                             60.4428            346.086
CA - DF-2                                *-1083.57          369.982
CA - FT-100                              230.911            369.982
DF-2 - FT-100                            *1314.48           369.982
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

```
Multifactor ANOVA - Pyrene (µg/kW-hr)    Soluble PAH
                    LPP Only   Mode 12

Analysis Summary

Dependent variable: pyrene
Factors:
        fuel
Selection variable: mode=12

Number of complete cases: 16
```

Scatterplot by Level Code


```
Analysis of Variance for pyrene - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares    Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                 3.49509E7       4      8.73773E6     185.73     0.0000

RESIDUAL                517496.0       11       47045.1
--------------------------------------------------------------------------------
TOTAL (CORRECTED)      3.54684E7       15
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.


CONCLUSION:  Statistically significant differences in the average pyrene
among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average pyrene for the DF-2 fuel is significantly different
than the remaining four fuels.  The average pyrene for the ADMM15, ALS, CA,
and FT-100 fuels are not significantly different from one another.


Multiple Range Tests for pyrene by fuel
```

```
--------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
fuel          Count    LS Mean         Homogeneous Groups
--------------------------------------------------------------------------
FT-100         3       112.589          X
ADMM15         3       122.261          X
ALS            4       306.989          X
CA             3       317.881          X
DF-2           3       4002.05           X
--------------------------------------------------------------------------
Contrast                             Difference        +/-  Limits
--------------------------------------------------------------------------
ADMM15 - ALS                          -184.728         536.236
ADMM15 - CA                           -195.62          573.26
ADMM15 - DF-2                         *-3879.79         573.26
ADMM15 - FT-100                        9.67186          573.26
ALS - CA                              -10.8921          536.236
ALS - DF-2                            *-3695.06         536.236
ALS - FT-100                           194.4            536.236
CA - DF-2                             *-3684.17         573.26
CA - FT-100                            205.292          573.26
DF-2 - FT-100                         *3889.46          573.26
--------------------------------------------------------------------------

* denotes a statistically significant difference.
```

```
Multifactor ANOVA - Benzo[a]anthracene (µg/kW-hr)    Soluble PAH
                    LPP Only    Mode 12

Analysis Summary

Dependent variable: benzoaan
Factors:
        fuel
Selection variable: mode=12

Number of complete cases: 16
```

Scatterplot by Level Code


```
Analysis of Variance for benzoaan - Type III Sums of Squares
--------------------------------------------------------------------------------
Source            Sum of Squares    Df    Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel               25507.2        4        6376.8       35.98     0.0000

RESIDUAL              1949.28       11        177.207
--------------------------------------------------------------------------------
TOTAL (CORRECTED)    27456.5       15
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.


CONCLUSION:  Statistically significant differences in the average
benzo[a]anthracene among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average benzo[a]anthracene for the DF-2 fuel is significantly
different than the remaining four fuels.  The average benzo[a]anthracene
for the ADMM15, ALS, CA, and FT-100 fuels are not significantly different
from one another.


Multiple Range Tests for benzoaan by fuel
```

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
fuel          Count     LS Mean         Homogeneous Groups
--------------------------------------------------------------------------------
ADMM15          3       2.81296            X
FT-100          3       4.49021            X
ALS             4       11.4693            X
CA              3       26.9346            X
DF-2            3       111.52              X
--------------------------------------------------------------------------------
Contrast                                  Difference       +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                              -8.65633         32.9109
ADMM15 - CA                               -24.1216         35.1832
ADMM15 - DF-2                             *-108.707        35.1832
ADMM15 - FT-100                           -1.67725         35.1832
ALS - CA                                  -15.4653         32.9109
ALS - DF-2                                *-100.05         32.9109
ALS - FT-100                              6.97908          32.9109
CA - DF-2                                 *-84.5852        35.1832
CA - FT-100                               22.4444          35.1832
DF-2 - FT-100                             *107.03          35.1832
--------------------------------------------------------------------------------

* denotes a statistically significant difference.
```

```
Multifactor ANOVA - Chrysene (µg/kW-hr)    Soluble PAH
                      LPP Only    Mode 12

Analysis Summary

Dependent variable: chrysene
Factors:
        fuel
Selection variable: mode=12

Number of complete cases: 16
```

Scatterplot by Level Code

Analysis of Variance for chrysene - Type III Sums of Squares

Source	Sum of Squares	Df	Mean Square	F-Ratio	P-Value
MAIN EFFECTS					
A:fuel	200207.0	4	50051.8	70.98	0.0000
RESIDUAL	7756.57	11	705.143		
TOTAL (CORRECTED)	207964.0	15			

All F-ratios are based on the residual mean square error.

```
CONCLUSION:  Statistically signficant differences in the average chrysene
among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average chrysene for the DF-2 fuel is significantly different
than the remaining four fuels.  The average chrysene for the ADMM15, ALS, CA,
and FT-100 fuels are not significantly different from one another.


Multiple Range Tests for chrysene by fuel
```

```
--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
fuel            Count       LS Mean         Homogeneous Groups
--------------------------------------------------------------------------------
ADMM15          3           8.13341             X
FT-100          3           15.3873             X
ALS             4           25.5521             X
CA              3           57.3427             X
DF-2            3           310.066              X
--------------------------------------------------------------------------------
Contrast                                 Difference          +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                             -17.4186            65.6504
ADMM15 - CA                              -49.2093            70.1832
ADMM15 - DF-2                            *-301.933           70.1832
ADMM15 - FT-100                          -7.25384            70.1832
ALS - CA                                 -31.7906            65.6504
ALS - DF-2                               *-284.514           65.6504
ALS - FT-100                             10.1648             65.6504
CA - DF-2                                *-252.724           70.1832
CA - FT-100                              41.9554             70.1832
DF-2 - FT-100                            *294.679            70.1832
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

G-64

```
Multifactor ANOVA - Benzo[b]fluoranthene (µg/kW-hr)   Soluble PAH
                   LPP Only   Mode 12

Analysis Summary

Dependent variable: benzobfl
Factors:
        fuel
Selection variable: mode=12

Number of complete cases: 16
```

Scatterplot by Level Code


```
Analysis of Variance for benzobfl - Type III Sums of Squares
--------------------------------------------------------------------------------
Source                Sum of Squares   Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                    3639.5       4       909.874       9.84     0.0012

RESIDUAL                   1017.54     11        92.5037
--------------------------------------------------------------------------------
TOTAL (CORRECTED)          4657.04     15
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.
```

```
CONCLUSION:  Statistically significant differences in the average benzo[b]fluoranthene
among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average benzo[b]fluoranthene for the DF-2 fuel is significantly
different than the remaining four fuels.  The average benzo[b]fluoranthene
for the ADMM15, ALS, CA, and FT-100 fuels are not significantly different from
one another.
```

```
Multiple Range Tests for benzobfl by fuel

--------------------------------------------------------------------------------
```

G-65

```
Method: 95.0 percent Tukey HSD
fuel            Count    LS Mean        Homogeneous Groups
--------------------------------------------------------------------------------
ADMM15           3       4.11655          X
FT-100           3      10.4925           X
ALS              4      16.872            X
CA               3      21.7637           X
DF-2             3      49.2356            X
--------------------------------------------------------------------------------
Contrast                                Difference        +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                             -12.7554         23.7781
ADMM15 - CA                              -17.6472         25.4199
ADMM15 - DF-2                           *-45.119          25.4199
ADMM15 - FT-100                          -6.37593         25.4199
ALS - CA                                 -4.89179         23.7781
ALS - DF-2                              *-32.3636         23.7781
ALS - FT-100                             6.37947          23.7781
CA - DF-2                               *-27.4718         25.4199
CA - FT-100                              11.2713          25.4199
DF-2 - FT-100                           *38.7431          25.4199
--------------------------------------------------------------------------------
```

* denotes a statistically significant difference.

G-66

```
Multifactor ANOVA - Benzo[k]fluoranthene (µg/kW-hr)    Soluble PAH
                     LPP Only    Mode 12

Analysis Summary

Dependent variable: benzokfl
Factors:
        fuel
Selection variable: mode=12

Number of complete cases: 16
```

Scatterplot by Level Code


```
Analysis of Variance for benzokfl - Type III Sums of Squares
--------------------------------------------------------------------------------
Source                Sum of Squares    Df    Mean Square   F-Ratio   P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                    1697.42       4       424.355      12.26    0.0005

RESIDUAL                    380.707      11       34.6097
--------------------------------------------------------------------------------
TOTAL (CORRECTED)          2078.13       15
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.


CONCLUSION:  Statistically significant differences in the average
benzo[k]fluoranthene among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average benzo[k]fluoranthene for the DF-2 fuel is significantly
different than the remaining four fuels.  The average benzo[k]fluoranthene
for the ADMM15, ALS, CA, and FT-100 fuels are not significantly different from
one another.
```

```
Multiple Range Tests for benzokfl by fuel

--------------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
fuel          Count     LS Mean          Homogeneous Groups
--------------------------------------------------------------------------------
ADMM15        3         5.01499          X
FT-100        3         8.63606          X
ALS           4         12.614           X
CA            3         15.2594          X
DF-2          3         35.4502           X
--------------------------------------------------------------------------------
Contrast                                 Difference        +/-  Limits
--------------------------------------------------------------------------------
ADMM15 - ALS                             -7.59898          14.5445
ADMM15 - CA                              -10.2444          15.5487
ADMM15 - DF-2                            *-30.4352         15.5487
ADMM15 - FT-100                          -3.62108          15.5487
ALS - CA                                 -2.6454           14.5445
ALS - DF-2                               *-22.8362         14.5445
ALS - FT-100                             3.9779            14.5445
CA - DF-2                                *-20.1908         15.5487
CA - FT-100                              6.6233            15.5487
DF-2 - FT-100                            *26.8141          15.5487
--------------------------------------------------------------------------------
* denotes a statistically significant difference.
```

```
Multifactor ANOVA - Benzo[e]pyrene (µg/kW-hr)   Soluble PAH
                    LPP Only   Mode 12

Analysis Summary

Dependent variable: benzoepy
Factors:
        fuel
Selection variable: mode=12

Number of complete cases: 16
```

Scatterplot by Level Code


```
Analysis of Variance for benzoepy - Type III Sums of Squares
--------------------------------------------------------------------------------
Source              Sum of Squares    Df     Mean Square    F-Ratio    P-Value
--------------------------------------------------------------------------------
MAIN EFFECTS
 A:fuel                 1581.98        4       395.494        14.93     0.0002

RESIDUAL                291.333       11        26.4848
--------------------------------------------------------------------------------
TOTAL (CORRECTED)      1873.31        15
--------------------------------------------------------------------------------
All F-ratios are based on the residual mean square error.
```

```
CONCLUSION:  Statistically significant differences in the average benzo[e]pyrene
among the fuels.
```

Means and 95% Tukey HSD Intervals


```
CONCLUSION:  The average benzo[e]pyrene for the DF-2 fuel is significantly
different than the remaining four fuels.  The average benzo[e]pyrene for the
ADMM15, ALS, CA, and FT-100 fuels are not significantly different from one
another.
```

```
Multiple Range Tests for benzoepy by fuel
```

```
--------------------------------------------------------------------------
Method: 95.0 percent Tukey HSD
fuel          Count    LS Mean          Homogeneous Groups
--------------------------------------------------------------------------
ADMM15        3        3.53663          X
FT-100        3        9.77367          X
ALS           4        10.2791          X
CA            3        14.118           X
DF-2          3        33.5322           X
--------------------------------------------------------------------------
Contrast                                Difference          +/-  Limits
--------------------------------------------------------------------------
ADMM15 - ALS                            -6.74243            12.7232
ADMM15 - CA                             -10.5813            13.6017
ADMM15 - DF-2                           *-29.9956           13.6017
ADMM15 - FT-100                         -6.23704            13.6017
ALS - CA                                -3.83891            12.7232
ALS - DF-2                              *-23.2531           12.7232
ALS - FT-100                            0.505398            12.7232
CA - DF-2                               *-19.4142           13.6017
CA - FT-100                             4.34431             13.6017
DF-2 - FT-100                           *23.7585            13.6017
--------------------------------------------------------------------------
```

* denotes a statistically significant difference.

G-70